

Package ‘diggitdata’

May 16, 2024

Type Package

Title Example data for the diggit package

Version 1.37.0

Date 2014-08-29

Author Mariano Javier Alvarez

Maintainer Mariano Javier Alvarez <reef103@gmail.com>

Description This package provides expression profile and CNV data for glioblastoma from TCGA, and transcriptional and post-translational regulatory networks assembled with the ARACNe and MINDy algorithms, respectively.

License GPL (>=2)

Depends R(>= 2.14.0), Biobase, methods

Imports viper

LazyLoad yes

biocViews ExperimentData, Cancer

git_url <https://git.bioconductor.org/packages/diggitdata>

git_branch devel

git_last_commit 6bb3a58

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-05-16

Contents

diggitdata-package	2
gbm.aracne	2
gbm.cnv	3
gbm.cnv.normal	3
gbm.expression	4
gbm.mindy	4
Index	5

diggitdata-package *Datasets and network models required for the examples in the diggit package*

Description

This package contains a human glioblastoma mRNA expression dataset, a human glioblastoma copy number variation (CNV) dataset, a glioblastoma context-specific transcriptional network, and a glioblastoma context-specific post-translational network.

Details

Package: diggitdata
Type: Package
Version: 0.99.0
Date: 2014-08-29
License: GPL (>=2)
LazyLoad: yes

Author(s)

Mariano Javier Alvarez

Maintainer: Mariano Javier Alvarez <reef103@gmail.com>

gbm.aracne *Transcriptional regulatory network for human glioblastoma*

Description

Human glioblastoma transcriptional regulatory network assembled by the ARACNE algorithm from TCGA expression data. The data is stored in a S3 class 'regulon' object.

Usage

```
data(gbm.aracne)
```

References

Margolin,A.A. et al. (2006) ARACNE: an algorithm for the reconstruction of gene regulatory networks in a mammalian cellular context. BMC Bioinformatics, 7 Suppl 1, S7.

Examples

```
data(gbm.aracne)
print(gbmTFregulon)
```

`gbm.cnv`*Human glioblastoma TCGA copy number variation (CNV) dataset*

Description

Normalized CNV data, summarized at the gene level, for 230 samples from TCGA profiled by Agilent HG-CGH-244A arrays. The CNV data is in a matrix format, with samples in columns and genes in rows.

Usage

```
data(gbm.cnv)
```

Examples

```
data(gbm.cnv)
print(gbmCNV[1:5, 1:5])
```

`gbm.cnv.normal`*Human normal blood TCGA copy number variation (CNV) dataset*

Description

Normalized CNV data, summarized at the gene level, for 33 blood samples from TCGA profiled by Agilent HG-CGH-244A arrays. The CNV data is in a matrix format, with samples in columns and genes in rows.

Usage

```
data(gbm.cnv.normal)
```

Examples

```
data(gbm.cnv.normal)
print(gbmCNVnormal[1:5, 1:5])
```

gbm.expression *Human glioblastoma mRNA expression dataset from TCGA*

Description

ExpressionSet object containing cleaner summarized and mas5 normalized mRNA expression data from 250 human glioblastoma samples profiled by TCGA on HT-HGU133A arrays.

Usage

```
data(gbm.expression)
```

References

Alvarez,M.J. et al. (2009) Correlating measurements across samples improves accuracy of large-scale expression profile experiments. *Genome Biol.*, 10, R143.

Examples

```
data(gbm.expression)
print(gbmExprs)
```

gbm.mindy *Post-translational regulatory network for human glioblastoma*

Description

Human glioblastoma post-translational regulatory network assembled by the MINDy algorithm from TCGA expression data. The data is stored in a S3 class 'regulon' object.

Usage

```
data(gbm.mindy)
```

References

Wang,K. et al. (2009) Genome-wide identification of post-translational modulators of transcription factor activity in human B cells. *Nat. Biotechnol.*, 27, 829-39.

Examples

```
data(gbm.mindy)
print(gbmMindy)
```

Index

* datasets

- gbm.aracne, [2](#)
- gbm.cnv, [3](#)
- gbm.cnv.normal, [3](#)
- gbm.expression, [4](#)
- gbm.mindy, [4](#)

[diggitdata \(diggitdata-package\), 2](#)
[diggitdata-package, 2](#)

[gbm.aracne, 2](#)
[gbm.cnv, 3](#)
[gbm.cnv.normal, 3](#)
[gbm.expression, 4](#)
[gbm.mindy, 4](#)
[gbmCNV \(gbm.cnv\), 3](#)
[gbmCNVnormal \(gbm.cnv.normal\), 3](#)
[gbmExprs \(gbm.expression\), 4](#)
[gbmMindy \(gbm.mindy\), 4](#)
[gbmTFregulon \(gbm.aracne\), 2](#)