

Package ‘RNAinteract’

May 6, 2024

Type Package

Title Estimate Pairwise Interactions from multidimensional features

Version 1.52.0

Description RNAinteract estimates genetic interactions from multi-dimensional read-outs like features extracted from images. The screen is assumed to be performed in multi-well plates or similar designs. Starting from a list of features (e.g. cell number, area, fluorescence intensity) per well, genetic interactions are estimated. The packages provides functions for reporting interacting gene pairs, plotting heatmaps and double RNAi plots. An HTML report can be written for quality control and analysis.

License Artistic-2.0

LazyLoad yes

Imports RColorBrewer, ICS, ICSNP, cellHTS2, geneplotter, gplots, grid, hwriter, lattice, latticeExtra, limma, methods, splots (>= 1.13.12), abind, locfit, Biobase

Depends R (>= 2.12.0),

biocViews ImmunoOncology, CellBasedAssays, QualityControl, Preprocessing, Visualization

git_url <https://git.bioconductor.org/packages/RNAinteract>

git_branch RELEASE_3_19

git_last_commit c0f681c

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-05

Author Bernd Fischer [aut],
Wolfgang Huber [ctb],
Mike Smith [cre]

Maintainer Mike Smith <mike.smith@embl.de>

Contents

RNAinteract-package	2
bindscreens	4
computePI	5
computePValues	6
createCellHTSFromFiles	7
createRNAinteract	8
createRNAinteractFromFiles	9
embedPCA	10
estimateMainEffect	11
getData	12
getMain	14
getReplicateData	16
getScale	17
getScreenNames	18
grid.doublePerturbation	18
grid.sgiHeatmap	20
normalizeMainEffectQuery	21
normalizeMainEffectTemplate	22
normalizePlateEffect	23
plotDoublePerturbation	24
plotHeatmap	26
reportAnnotation	27
RNAinteract-class	29
sgi	31
sgisubset	31
sgisubsetQueryDesign	32
startReport	33
summarizeScreens	34
swaptree	35
Index	36

RNAinteract-package *Analysis of Pairwise Interaction Screens.*

Description

The package contains functions to organize the data from (single- and multi-parametric) genetic interaction screens. Methods to estimate main effects (single perturbation effects) and pairwise interactions. p-values are computed. Furthermore a comprehensive html-report is generated.

Details

See vignette("RNAinteract") for details.

Package content

Class RNAinteract (Documentation: [RNAinteract-class](#))

Data input and creating of an object of class RNAinteract.

- [createCellHTSFromFiles](#)
- [createRNAinteract](#), [createRNAinteractFromFiles](#)

Data access

- [getData](#) Primary data access function for multiple types of screen data.
- [getMain](#), [getMainNeg](#) access to main effects.
- [getReplicateData](#), [getIndDesignData](#) Comparing replicate data.
- [getChannelNames](#), [getScreenNames](#), [getScale](#)

Subsetting, summarizing, and binding screens

- [sgisubset](#), [sgisubsetQueryDesign](#)
- [bindscreens](#)
- [summarizeScreens](#)

Main effects and pairwise interactions

- [estimateMainEffect](#)
- [normalizeMainEffectQuery](#), [normalizeMainEffectTemplate](#), [normalizePlateEffect](#)
- [computePI](#), [computePValues](#)
- [embedPCA](#)

Plotting

- [plotDoublePerturbation](#), [plotHeatmap](#) standard plot functions
- [doublePerturbationGrob](#), [grid.doublePerturbation](#), [grid.sgiHeatmap](#) specialized grid plotting functions for experts

HTML report

- [startReport](#), [endReport](#) starting and finalizing a report
- [reportAnnotation](#), [reportStatistics](#) global reports
- [reportDoublePerturbation](#), [reportGeneLists](#), [reportHeatmap](#), [reportMainEffects](#), [reportNetworks](#), [reportScreenData](#) reports specific for each screen and each channel

Author(s)

Bernd Fischer

Maintainer: Bernd Fischer <bernd.fischer@embl.de>

References

T. Horn, T. Sandmann, B. Fischer, W. Huber, M. Boutros. Mapping of Signalling Networks through Synthetic Genetic Interaction Analysis by RNAi. Nature Methods, 2011.

bindscreens

bind RNAinteract objects along screens

Description

Bind two RNAinteract objects along screens.

Usage

```
bindscreens(sgi1, sgi2)
```

Arguments

sgi1 An object of class [RNAinteract](#).
sgi2 An object of class [RNAinteract](#).

Details

This function binds two double interaction screens along screens.

Value

An object of class [RNAinteract](#) with all screens in sgi1 and sgi2.

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi
sginew <- summarizeScreens(sgi, screens=c("1","2"), newscreenname = "m")
sginew
sgibind <- bindscreens(sgi, sginew)
sgibind
```

computePI	<i>compute pairwise interaction</i>
-----------	-------------------------------------

Description

Compute the pairwise interaction term for each single experiments.

Usage

```
computePI(sgi)
```

Arguments

`sgi` An object of class [RNAinteract](#).

Details

Computes the pairwise interaction term for each single experiment. Multiple values for each gene pair are not yet summarized.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi <- computePI(sgi)
PI <- getData(sgi, type="pi", format="targetMatrix")
```

computePValues	<i>compute p-values</i>
----------------	-------------------------

Description

Compute p-values for genetic interactions terms. Assess if genetic interaction term is different from zero.

Usage

```
computePValues(sgi,
               method = "pooled.ttest",
               mixTemplateQuery = TRUE,
               p.adjust.function = function(x) { p.adjust(x, method = "BH")},
               verbose = 0)
```

Arguments

sgi	An object of class RNAinteract .
method	The method used to compute p-values. One of "pooled.ttest", "ttest", "limma", "HotellingT2". For "ttest" a Student t-test is applied for each gene pair. The variance is estimated locally for each gene pair. For "pooled.ttest", a pooled variance is estimated from all gene pairs. The variance applied for each gene pair is the maximum of the pooled and the local variance estimate. This method obtains conservative p-values. For "limma" mediates between the local and the global variance estimation in a Bayesian framework. The limma-package is applied to compute the p-values. For "HotellingT2" Hotelling-T ² statistics is computed jointly for all dimensions. It results in a single p-value summarizing all channels. For simplification the p-values are stored in a matrix of dimension genes x genes x screens x channels and the p-values are repeated for each channel. The same holds for q-values.
mixTemplateQuery	If a gene-pair is measured twice as template-query and as query-template, a single p-value is computed by combining all measurements, if mixTemplateQuery = TRUE. Else a p-value is computed independently for both cases.
p.adjust.function	A function that corrects the p-values for multiple testing. Default method is the Benjamini-Hochberg method.
verbose	Either 0 (default, no output), 1 (minimum output), or 2 (outout)

Details

Computes p-values from a t-test, using the bioconductor package limma, or with a multidimensional Hotelling T² test.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi <- computePValues(sgi, method = "HotellingT2")
# Hotelling T^2 test will provide one p-value for all channels, PV will be the same
# for all channels in this case
PV <- getData(sgi, type="p.value", format="targetMatrix", channel="nrCells")
```

createCellHTSFromFiles

create cellHTS2 object from text files

Description

A cellHTS2 object is created from a set of text files.

Usage

```
createCellHTSFromFiles(filePlatelist = "Platelist.txt",
                        name = "anonymous",
                        path = ".", pdim = NULL)
```

Arguments

filePlatelist	The platelist (See vignette("RNAinteract"))
name	A (arbitrary) string providing the name for the screen
path	The path were the data files are located
pdim	Giving the plate dimensions, e.g. pdim=c(8,12) or pdim=c(16,24).

Details

See vignette("RNAinteract") for an example how to create an RNAinteract object.

Value

An object of class [cellHTS2](#).

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#), [createRNAinteractFromFiles](#), [createRNAinteract](#)

createRNAinteract *create a RNAinteract object*

Description

Creates a RNAinteract object given data matrices, annotation, query and template design.

Usage

```
createRNAinteract(data, well, plate, pdim,
                  Reagents, Targets,
                  TemplateDesign, QueryDesign,
                  Transformation = NULL)
```

Arguments

data	An array with dimensions features x screens x channels.
well	A vector of length #features with well names.
plate	A vector of length #features with plate numbers.
pdim	A vector of length 2 with plate dimensions (e.g. pdim=c(12,8)).
Reagents	A data.frame describing the reagents.
Targets	A data.frame describing the targets.
TemplateDesign	A data.frame with the layout of the template plates.
QueryDesign	A data.frame with the layout of the query plates.
Transformation	A Transformation that is applied to the data. If NULL the data is log2 transformed.

Details

See vignette("RNAinteract") for an example how to create an RNAinteract object.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#), [createRNAinteractFromFiles](#), [createCellHTSFromFiles](#)

createRNAinteractFromFiles

create an RNAinteract object from text files

Description

Reads text files with annotation, query and template design, and data. Creates a RNAinteract object.

Usage

```
createRNAinteractFromFiles(name = "anonymous",
  filePlatelist = "Platelist.txt",
  fileReagents = "Reagents.txt",
  fileTargets = "Targets.txt",
  fileTemplateDesign = "TemplateDesign.txt",
  fileQueryDesign = "QueryDesign.txt",
  path = ".",
  pdim = NULL,
  Transformation = "log2")
```

Arguments

name	A name for the screen.
filePlatelist	The filename of the text file containing the plate list.
fileReagents	The filename of the text file containing the reagent annotation.
fileTargets	The filename of the text file containing the target annotation.
fileTemplateDesign	The filename of the text file containing the template design.
fileQueryDesign	The filename of the text file containing the query design.

path	The system directory where the textfiles filePlatelist, fileReagents, fileTargets, fileTemplateDesign, and fileQueryDesign are located.
pdim	The dimensions of the multi-well plates (e.g. pdim = c(nrow=24, ncol=16)). if pdim = NULL (default), the plate dimension will be estimated from the input data.
Transformation	The transformation that is applied to the data. All calculations are done on additive scale.

Details

See vignette("RNAinteract") for an example how to create an RNAinteract object.

Value

An object of class `RNAinteract`.

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#), [createRNAinteract](#), [createCellHTSFromFiles](#)

embedPCA

Computes a PCA for a pairwise interaction matrix.

Description

A principal component analysis is performed for a pairwise interaction matrix. The low-dimensional embedding is returned.

Usage

```
embedPCA(sgi, screen, channel,  
         dim = 4, embed = "template",  
         withoutgroups = c())
```

Arguments

sgi	An object of class RNAinteract
screen	The screen name whose interaction matrix will be embedded.
channel	The channel name whose interaction matrix will be embedded.
dim	The embedding dimension.
embed	Either "template" (default) or "query" denotes if the embedding is done for rows or columns.
withoutgroups	Genes annotated with these groupnames are not considered for embedding.

Value

Returns a matrix with dimensions genes x dim.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
X <- embedPCA(sgi, screen="1", channel="nrCells", dim=2)
plot(X[,1], X[,2], pch=20, cex=0.01)
text(X[,1], X[,2], row.names(X))
```

estimateMainEffect *estimate main effect*

Description

estimates the main effects in an additive model.

Usage

```
estimateMainEffect(sgi, use.query = NULL)
```

Arguments

sgi	An object of class RNAinteract .
use.query	A list of reagent identifiers as annotated in the RID field of the reagent list. For the estimation of the template main effects only these queries are used.

Details

The main effect is the single RNAi knockdown effect. When `use.query` is not specified, the main effect is estimated by minimizing the L1 distance from the non-interacting model to the double RNAi measurements. The implemented non-interacting model is the additive model (sum of single main effects). If the screen does not contain a lot of query genes with no or very small main effect, it is recommended to estimate the template main effects only by using selected query genes. This can be obtained by specifying `use.query`. To estimate main effects in a multiplicative model define `Transformation="log2"` when creating the `RNAinteract` object (See [createRNAinteractFromFiles](#)), which is already the default.

Value

An object of class `RNAinteract`.

Author(s)

Bernd Fischer

References

~put references to the literature/web site here ~

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi <- estimateMainEffect(sgi)
getMain(sgi)
```

getData

Primary access function for all screen data.

Description

This function is the primary access function for a wide range of data from the screen. It does perform normalization, transformation, and reshaping if specified.

Usage

```
getData(sgi, type = "data", format = "plain",
  design = "template", mixTemplateQuery = TRUE,
  screen = NULL, channel = NULL,
  do.trafo = TRUE, do.inv.trafo = FALSE,
  normalized = FALSE, withoutgroups = c(),
  drop = TRUE)
```

Arguments

sgi	An object of class RNAinteract
type	Specifies which data is returned. Possible values are: <ul style="list-style-type: none"> • "p.value", "q.value": returns the p-value or q-value as computed by computePValues. • "data": returns the input data. • "pi": returns the pairwise interaction score. • "plateeffect": returns the plate effect estimated by normalizePlateEffect. • "ni.model" returns the non-interacting model as estimated by estimateMainEffect. • "main": returns the main effects. • "mainsderr": returns the std error of the main effects. • "mainsd": returns the std deviation of the main effects. • "maintime": returns the estimated time effect as estimated by normalizeMainEffectQuery • "mainspatial": returns the estimated spatial effect as estimated by normalizePlateEffect
format	The output format. Possible values: <ul style="list-style-type: none"> • "plain": The data can be returned as a plain vector • "platelist": a list of plate matrices that can be passed to plotScreen • "reagentMatrix": All values for the same reagent pair are summarized in a matrix of dimension reagents x reagents • "targetMatrix": All values for the same gene pair are summarized in a matrix of dimension genes x genes
design	If type is one of the main effect types, the design can be specified to state if the "template" or "query" main effect is returned.
mixTemplateQuery	If TRUE, The template-query and query-template entries in the matrix are symmetrized.
screen	The screen names of which data should be returned.
channel	The channel names of which data should be returned.
do.trafo	Only effective, if type is "data". If TRUE, the data is transformed.
do.inv.trafo	Not effective if type is "data", "p.value", or "q.value". If TRUE, the values are back-transformed to the original scale.
normalized	If TRUE, the normalization data is returned.
withoutgroups	The genes from the specified groups are not returned in the data.
drop	If FALSE, the returned array is reduced in dimensions, whenever there is a dimension 1.

Value

An array containing the specified values is returned. In the case, the format is chosen to be "platelist", a list of matrices is returned.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")

# get the original data, as plain file, reshaped in plate layout,
# reshaped and summarized as target matrix
D <- getData(sgi, type="data", do.inv.trafo = TRUE)
Dplatelayout <- getData(sgi, type="data",
  format="platelist", do.inv.trafo = TRUE)
splots::plotScreen(Dplatelayout[["1"]][["nrCells"]],
  nx=sgi@pdim[2], ny=sgi@pdim[1], ncol=3)
Dmatrix <- getData(sgi, type="data",
  format="targetMatrix", do.inv.trafo = TRUE)

# get main effects as plate layout with specified transformation
# (usually log-transformed)
Mplatelayout <- getData(sgi, type="main", design="template",
  screen="1", channel="nrCells", format="platelist")
splots::plotScreen(Mplatelayout, nx=sgi@pdim[2], ny=sgi@pdim[1],
  ncol=3)

# get non-interacting model and pairwise interaction scores as matrix
NImatrix <- getData(sgi, type="ni.model", format="targetMatrix")
PImatrix <- getData(sgi, type="pi", format="targetMatrix")
PIplatelayout <- getData(sgi, type="main", design="query",
  screen="1", channel="nrCells", format="platelist")
splots::plotScreen(PIplatelayout, nx=sgi@pdim[2], ny=sgi@pdim[1],
  ncol=3)

# get p-values and q-values
PVmatrix <- getData(sgi, type="p.value", format="targetMatrix")
QVmatrix <- getData(sgi, type="q.value", format="targetMatrix")
```

getMain

get main effects

Description

Returns the main effects.

Usage

```
getMain(sgi, type = "main", design = "template", summary = "none",
  QueryNr = NULL, TemplatePlate = NULL,
  do.inv.trafo = FALSE, format = "plain", withoutgroups = c(),
  screen = NULL, channel = NULL, normalized = TRUE, drop = TRUE)
```

```
getMainNeg(sgi, type = "all", do.inv.trafo = FALSE,  
screen = NULL, channel = NULL, drop = TRUE)
```

Arguments

sgi	An object of class RNAinteract
type	always "main"
design	Either "template" or "query" defining if template or query main effects are returned.
summary	If summary is "targets" the main effects are summarized per target gene.
QueryNr, TemplatePlate	Only main effects of one query nr or one template plate are returned.
format	targetmatrix
withoutgroups	The genes within this group are not shown in the heatmap. It is convenient to hide screen controls.
do.inv.trafo	If TRUE, the data will be back-transformed for original scale of data. In the case of log-transformed data, the main effects are returned as factors, otherwise the main effects are returned as log values.
screen	The screen from which the main effects should be returned.
channel	The channel from which the main effects should be returned.
drop	Does return a drop array dimensions, even if only one screen or one channel is selected.
normalized	If true the normalized main effects are returned.

Value

An array containing the main effects.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")  
getMain(sgi)  
getMainNeg(sgi)
```

getReplicateData *Extract replicates measurements from the screen.*

Description

A genetic interaction screen can contain within screen replicates, if some reagent pairs are measured at least twice. Usually this appears when measuring reagent pairs once as template-query and once as query-template. `getReplicateData` returns a list of these technical replicates.

If multiple reagents are used to target the same gene, different reagent pairs that target the same gene pair are extracted from the screen. These pairs are returned by `getIndDesignData`.

Usage

```
getReplicateData(sgi, screen, channel,
                 type = "data", design = "template",
                 do.trafo = TRUE, do.inv.trafo = FALSE,
                 normalized = FALSE)
getIndDesignData(sgi, screen, channel,
                 type = "data", design = "template",
                 do.trafo = TRUE, do.inv.trafo = FALSE,
                 normalized = FALSE)
```

Arguments

`sgi` An object of class [RNAinteract](#).

`screen` The screen name from which the replicates will be extracted.

`channel` The channel name from which the replicates will be extracted.

`type` The type of data that is extracted. It is the type argument of the [getData](#) function.

`design, do.trafo, do.inv.trafo, normalized`
See the [getData](#) documentation for details.

Value

Returns a `data.frame` with columns `x` and `y`.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
res <- getIndDesignData(sgi, screen="1", channel="nrCells", type = "data")
plot(res$x, res$y)
```

getScale

get scale information for a channel.

Description

Returns a character string with the scale of each channel.

Usage

```
getScale(sgi, channel)
```

Arguments

sgi A [RNAinteract](#)
object.

channel A channel name.

Value

Returns a character string with scale information for each channel.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
getScale(sgi, channel="nrCells")
```

getScreenNames *get names of screens and channels*

Description

Returns the names of all screens or all channels.

Usage

```
getScreenNames(sgi)
getChannelNames(sgi)
```

Arguments

sgi [RNAinteract](#)

Value

A vector of screen or channel names.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
getScreenNames(sgi)
getChannelNames(sgi)
```

grid.doublePerturbation

Double Perturbation Plot Grob

Description

These functions create a double perturbation grob for interaction screens. All interactions of one gene are displayed in one panel. The double perturbation readout level is plotted against the single perturbation level.

Usage

```
doublePerturbationGrob( mainEffect, dpEffect, mainEffectTarget,
  range=NULL, main=NULL, xlab=NULL, ylab=NULL,
  text=NULL, avoid.overlap=TRUE,
  axisOnOrigin = FALSE,
  drawBox = TRUE,
  pch = 21, size=unit(1, "char"), fill = NULL,
  gpMain = gpar(lty="dashed", lwd=3, col="cyan"),
  gpNI = gpar(lty="dashed", lwd=3, col="orange"),
  gpPoints = gpar(pch=21),
  gpText = NULL,
  gpAxis = NULL,
  gpWTLines=NULL,
  name=NULL, gp=NULL, vp=NULL )
grid.doublePerturbation(..., draw = TRUE)

# a helper function for doublePerturbationGrob:
postDrawDetails.doublePerturbation(x, recording)
```

Arguments

mainEffect	A numeric vector of main effects.
dpEffect	A numeric vector of double perturbation effects.
mainEffectTarget	The main effect of the target gene (A single numeric value).
range	The range of the plot. Equals the xlim, ylim arguments of plot .
main	An overall title of the plot.
xlab	A title of the x-axis.
ylab	A title of the y-axis.
text	A character vector of text. Has to have the same length as mainEffect.
avoid.overlap	If TRUE (default) the text labels are moved such that the text is not overlapping.
axisOnOrigin	If TRUE, the x- and y-axis are draw on the origin of the data. If FALSE (default), the axis are drawn on the left and on the bottom.
drawBox	If TRUE (default), a box is drawn around the plot.
pch	Either an integer specifying a symbol or a single character to be used in plotting points. See points for possible values.
size	A unit object specifying the size of the plotting symbols.
fill	A list containing (some of) the following elements: col defines a fill color for the points. Either a single value or a vector of the same length as mainEffect. If col is defined, all other elements of fill have no effect. values is a numeric vector of the same length as mainEffect that contains values that are mapped to colors. at is a numeric vector indicating breakpoints along the values. If not specified will be equally spaced on the range of the values. colors defines a set of colors from which a colramp is created. colramp defines a colramp directly. colramp has no effect, if colors is defined.

gp	An object of class <code>gpar</code> , typically the output from a call to the function <code>gpar</code> . This is basically a list of graphical parameter settings. Overall settings for the plot are set in <code>gp</code> .
gpMain, gpNI	An object of class <code>gpar</code> (See <code>gp</code>). <code>gpMain</code> and <code>gpNI</code> indicate the graphics parameter for the main effect lines and the non-interacting line.
gpPoints, gpText, gpAxis, gpWTLines	An object of class <code>gpar</code> (See <code>gp</code>). These arguments define graphical parameters for single compartments of the plot.
name	A character identifier.
vp	A Grid viewport object (or <code>NULL</code>).
draw	If <code>TRUE</code> the grob is drawn on the current device.
...	Further arguments passed to <code>doublePerturbationGrob</code> .
x, recording	Internal usage only.

Details

This function creates a grob for a double perturbation plot. It is probably more convenient to use the function `plotDoublePerturbation`.

Value

A grob is returned.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#), [plotDoublePerturbation](#), [reportDoublePerturbation](#)

grid.sgiHeatmap	<i>A heatmap grob</i>
-----------------	-----------------------

Description

A grob is created and printed for a matrix `PI` which is intended to represent pairwise interaction scores.

Usage

```
grid.sgiHeatmap(PI, pi.max = NULL, main = expression(paste(pi, "--score")),
  hc.row = NULL, hc.col = NULL)
```

Arguments

PI	A matrix of pairwise interactions.
pi.max	The interaction score at the top end of the colorbar. pairwise interaction score larger than this value can not be distinguished anymore.
main	A title for the plot.
hc.row	An hierarchical clustering as produced by hclust of the rows.
hc.col	Clustering of the columns.

Details

A heatmap is plotted with positive interaction represented in yellow and negative interactions represented in blue. A colorbar is plotted on the left and dendrograms are added. This function can be used to integrate the plot in other grid objects. It is recommended to use the function [plotHeatmap](#) to plot heatmaps of an [RNAinteract](#) object.

Value

A grob is returned.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
PI = getData(sgi, type="pi", format="targetMatrix", screen="1", channel="nrCells")
grid.sgiHeatmap(PI)
```

normalizeMainEffectQuery

normalize query main effect

Description

Normalize for a time effect of the query genes.

Usage

```
normalizeMainEffectQuery(sgi, batch = NULL, time = NULL)
```

Arguments

sgi	An object of class RNAinteract .
batch	batch is a vector of integers with length equal to the number of queries. It assigns each query to a batch. Within each batch a linear regression is estimated assuming a linear effect between the order of queries and the main effects.
time	batch is a vector of numbers. A linear regression is estimated fitting the main effect as a function of the time.

Details

Normalizing the query main effect does not influence the estimation of the pairwise interaction term.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi <- normalizeMainEffectQuery(sgi)
```

```
normalizeMainEffectTemplate
normalize template main effect
```

Description

Normalize for a spatial main effect of the template genes.

Usage

```
normalizeMainEffectTemplate(sgi, screen = NULL, channel = NULL)
```

Arguments

sgi	An object of class RNAinteract .
screen	The name of the screen in which the normalization should be applied. If screen = NULL, the normalization is applied on all screens.
channel	The name of the channel in which the normalization should be applied. If channel = NULL, the normalization is applied on all channels.

Details

Normalizing the query main effect does not influence the estimation of the pairwise interaction term.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi <- normalizeMainEffectTemplate(sgi)
```

normalizePlateEffect *Normalization of plate effects*

Description

Normalization of plate effects in the screen.

Usage

```
normalizePlateEffect(sgi, type = "Bscore", maxit = 20, verbose = 0)
```

Arguments

sgi	An object of class RNAinteract
type	If type is "Bscore" (default) a Bscore-normalization is performed. If type is "spatial", a locfit regression is estimated that accounts for spatial effects.
maxit	Maximum number of iterations for locfit.
verbose	Either 0 (default, no output), 1 (minimum output), or 2 (outout).

Details

The Bscore normalization estimates row and column effects for each plate. It returns the residuals to the sum of row and column effects. The spatial normalization estimates a non-linear 2D regression for each plate and returns the residuals.

Value

An object of class `RNAinteract`. The returned object contains the normalization information.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
normalizePlateEffect(sgi)
```

plotDoublePerturbation

Double Perturbation Plot

Description

This function draws a double perturbation plot for interaction screens. All interactions of one gene are displayed in one panel. The double perturbation readout level is plotted against the single perturbation level.

Usage

```
plotDoublePerturbation( sgi, screen, channel, target,
                        withoutgroups = c("neg", "pos"), design,
                        main, xlab, ylab, range,
                        show.labels = "none", label.par, label,
                        avoid.overlap, col, fill,
                        D , MT, MQ, PV, QV, PI, ...)
```

Arguments

<code>sgi</code>	An object of class <code>RNAinteract</code> .
<code>target</code>	A character name of the target gene.
<code>screen</code>	The character name of the screen to display. If not specified, the first screen is used. Does not have to be specified, if <code>sgi</code> contains only one screen.
<code>channel</code>	The character name of the channel to display. If not specified, the first channel is used. Does not have to be specified, if <code>sgi</code> contains only one channel.
<code>withoutgroups</code>	Interactions to genes from these groups (as specified in the reagent or target annotation) are excluded from the plot, e.g. positive and negative controls.

design	The Either "template" (default) or "query". The single perturbation effects are either the template main effects or the query main effects.
main	An overall title of the plot.
xlab	A title of the x-axis.
ylab	A title of the y-axis.
range	A numeric vector of length two. range equals the xlim, ylim argument in plot .
show.labels	Automatically select text labels for the points. 'all' shows a text label for all genes, "q.value" and "p.value" show a text label for all genes with a q.value (p.value) larger than label.par, "none" does not show any text label. This argument has no effect, if label is specified.
label.par	Cut-off value for q.value or p.value for displaying text labels (See show.labels).
label	Either a character vector with gene names, or a named vector of text labels. The names of the vector represent the gene names.
avoid.overlap	If TRUE (default), text is moved such that text labels are not overlapping.
col	A named vector with colors. The names of col define which points are colored (See also fill).
fill	A list up to four values. colors defines a set of colors from which a colramp is created. If colramp is specified, colors has no effect. colramp directly specifies the colramp. values define the values that are color coded. If values is not specified, the pairwise interaction term is used instead. at is a numeric vector defining the breakpoints along the values. If not specified, breakpoints are selected to range three times the standard deviation of the values around zero. fill has no effect, if col is specified.
D, MT, MQ, PV, QV, PI	Internal usage.
...	Further argument passed to grid.doublePerturbation or doublePerturbationGrob .

Details

Plots a double perturbation plot. It shows the interaction profile for one (query) gene.

Value

A grob is returned.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#), [grid.doublePerturbation](#), [reportDoublePerturbation](#)

Examples

```
data("sgi")
plotDoublePerturbation( sgi, screen="1", channel="nrCells", target="r1", show.labels="p.value")
```

plotHeatmap *plots a heatmap for an interaction screen.*

Description

A heatmap of an interaction screen is plotted.

Usage

```
plotHeatmap(sgi, screen, channel, pi.max = NULL,
             main = expression(paste(pi, "-score")),
             hc.row = NULL, hc.col = NULL,
             withoutgroups = c("neg", "pos"))
```

Arguments

sgi	An object of class RNAinteract
screen	The screen name of which the interaction matrix is plotted.
channel	The channel name of which the interaction matrix is plotted.
pi.max	The pairwise interaction score that is represented at the top of the color scale. All interaction scores above this value can not be distinguished any more.
main	The title of the plot.
hc.row	A hierarchical clustering (hclust) for the rows.
hc.col	A hierarchical clustering (hclust) for the columns.
withoutgroups	The genes within this group are not shown in the heatmap. It is convinient to hide screen controls in the heatmap.

Details

A heatmap for one screen and one channel is plotted. Positive interactions are marked blue, negative ones are marked yellow. A colorbar is shown on the left hand side.

Value

Returns a grob.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
plotHeatmap(sgi, screen="1", channel="nrCells")
```

reportAnnotation	<i>Specialized report functions</i>
------------------	-------------------------------------

Description

Functions that provide a html report of genetic interactions screens for specific topics.

Usage

```
reportAnnotation      (sgi, verbose = 0, path = ".", dir = "annotation",
                      prefix = "annotation", report = NULL)
reportStatistics      (sgi, verbose = 0, path = ".", dir = "stats",
                      prefix = "stat", report = NULL)
reportGeneLists       (sgi, verbose = 0, path = ".", dir = "hitlist",
                      prefix = "hitlist", report = NULL)
reportNetworks        (sgi, verbose = 0, path = ".", dir = "networks",
                      prefix = "networks", Networks, qv = 0.05,
                      withoutgroups = c("pos", "neg"), report = NULL)
reportScreenData      (sgi, type = "data", design = "template",
                      do.trafo = TRUE, do.inv.trafo = FALSE, verbose = 0,
                      path = ".", dir = "screenplots", prefix = "screenplot",
                      png.args = list(width = 960, height = 960),
                      pdf.args = list(width = 7, height = 7),
                      plotScreen.args = list(ncol = 6L, do.legend = TRUE,
                                              fill = c("red", "white", "blue")),
                      png.scatter.args = list(width = 400, height = 400),
                      pdf.scatter.args = list(width = 7, height = 7), report = NULL)
reportDoublePerturbation(sgi, verbose = 0, path = ".", dir = "doublePerturbations",
                        prefix = "doublePerturbationPlots", report = NULL,
                        withoutgroups = c("neg", "pos"),
                        png.args = list(width = 500, height = 500),
                        pdf.args = list(width = 7, height = 7), ...)
reportMainEffects     (sgi, verbose = 0, path = ".", dir = "maineffects",
                      prefix = "maineffects",
                      png.args = list(width = 500, height = 500),
                      pdf.args = list(width = 7, height = 7),
                      plot.args = list(), report = NULL)
reportHeatmap         (sgi, verbose = 0, path = ".", dir = "heatmap",
                      prefix = "heatmap",
                      png.args = list(width = 1000, height = 1000),
                      pdf.args = list(width = 15, height = 15),
                      report = NULL, withoutgroups = c("neg", "pos"))
```

Arguments

sgi	An object of class RNAinteract .
verbose	Either 0 (default, no output), 1 (minimum output), or 2 (outout)
path	The main path to the HTML report directory.
dir	A subdirectory where the report is written to.
prefix	A prefix for each file written in the subdirectory. Using different prefixes, one can write multiple reports in the same directory.
report	A report object as generated by startReport .
Networks	A boolean array with edges from interaction graphs.
qv	A cut-off value for the q-values.
withoutgroups	Genes annotated with these groups are not plotted in this report.
type	Any "type" that can be passed to getData .
design	Either "template" (default) or "query"
do.trafo, do.inv.trafo	Apply the (inverse) transformation before plotting.
png.args	A list with entries width and height specifying the width and height of the generated png images.
pdf.args	A list with entries width and height specifying the width and height of the generated of files.
plotScreen.args	Arguments for the screen plots
png.scatter.args, pdf.scatter.args, plot.args	Arguments for the scatter plots
...	Parameters passed to the plotting functions.

Details

Each of these function generates a HTML report. It is added to a HTML frame.

The report object has to be created with [startReport](#) beforehand. Multiple report functions can be called afterwards. When all reports are written, the report is finalized and closed by [endReport](#).

Value

All functions return a report object as returned by [startReport](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#), [startReport](#), [endReport](#)

Examples

```

data("sgi")
report = startReport("report")
reportAnnotation(sgi, report = report)
endReport(report)
# browseURL(file.path("report", "index.html"))

```

RNAinteract-class *Class "RNAinteract"*

Description

A class for double perturbation experiments (genetic interaction screens, drug-drug interaction screens). There are functions for creation, analysis, and display of interaction screens.

Objects from the Class

Objects can be created by calls of [createRNAinteractFromFiles](#). See `vignette("RNAinteract")` for an example of creating an RNAinteract object.

Slots

data: Object of class "array" with dimension `sgi@F` x `sgi@S` x `sgi@C`. The raw data of the screen.

screenNames: Object of class "character" with length `sgi@S`.

channelNames: Object of class "character" with length `sgi@C`.

well: Object of class "character" with length `sgi@F`. Well name (e.g. F04) for each measurement.

plate: Object of class "integer" with length `sgi@F`. Number of the plate for each measurement

pdim: Object of class "integer" of length 2. Plate dimensions.

NT: Object of class "integer" of length 1. Number of template reagents.

NQ: Object of class "integer" of length 1. Number of query reagents.

C: Object of class "integer" of length 1. Number of readout channels.

S: Object of class "integer" of length 1. Number of screens.

F: Object of class "integer" of length 1. Number of measurements or single experiments per screen.

reagents: Object of class "data.frame" describing each reagents. Obligatory columns: RID and TID.

targets: Object of class "data.frame" describing each target gene. Obligatory columns: TID, Symbol, group, GID.

templateDesign: Object of class "data.frame" with `sgi@NT` rows describing the template design. Obligatory columns: TemplatePlate, Well, RID, QueryNr.

queryDesign: Object of class "data.frame" with `sgi@NQ` rows describing the query design. Obligatory columns: Plate, TemplatePlate, QueryNr, RID.

transformation: Object of class "character" of length $sg_i@C$. The transformation applied to the input data.

mainTemplate: Object of class "array" with dimension $sg_i@NT \times sg_i@S \times sg_i@C$. The main effect of the template reagents.

mainQuery: Object of class "array" with dimension $sg_i@NQ \times sg_i@S \times sg_i@C$. The main effect of the query reagents.

mainSderrTemplate: Object of class "array" with dimension $sg_i@NT \times sg_i@S \times sg_i@C$. The standard error of the main effect of the template reagents.

mainSderrQuery: Object of class "array" with dimension $sg_i@NQ \times sg_i@S \times sg_i@C$. The standard error of the main effect of the query reagents.

mainSdTemplate: Object of class "array" with dimension $sg_i@NQ \times sg_i@S \times sg_i@C$. The standard deviation of the main effect of the query reagents.

mainSdQuery: Object of class "array" with dimension $sg_i@NQ \times sg_i@S \times sg_i@C$. The standard deviation of the main effect of the query reagents.

mainTimeEffect: Object of class "array" with dimension $sg_i@NQ \times sg_i@S \times sg_i@C$. The systematic changes of the query main effects, e.g. decreasing cell number over time.

mainSpatialEffect: Object of class "array" with dimension $sg_i@F \times sg_i@S \times sg_i@C$. The systematic spatial plate effects.

mainSpatialEffectRow: Object of class "array". Spatial effects per row (as computed by Bscore).

mainSpatialEffectCol: Object of class "array". Spatial effects per column (as computed by Bscore).

mainNeg: Object of class "array" with dimension $sg_i@S \times sg_i@C$. The main effect of the negative control.

mainNegTemplate: Object of class "array" with dimension $sg_i@S \times sg_i@C$. The template main effect of the negative control.

mainNegQuery: Object of class "array" with dimension $sg_i@S \times sg_i@C$. The query main effect of the negative control.

data2mainTemplate: Object of class "integer" with dimension $sg_i@F$. Mapping of single experiments to template reagents.

data2mainQuery: Object of class "integer" with dimension $sg_i@F$. Mapping of single experiments to query reagents.

ni.model: Object of class "array" with dimension $sg_i@F \times sg_i@S \times sg_i@C$. The expected values of the non-interacting model.

pi: Object of class "array" with dimension $sg_i@F \times sg_i@S \times sg_i@C$. The pairwise interaction score.

plateeffect: Object of class "array".

p.value: Object of class "array" with dimension $sg_i@NT \times sg_i@NQ \times sg_i@S \times sg_i@C$ describing the p.values.

q.value: Object of class "array" with dimension $sg_i@NT \times sg_i@NQ \times sg_i@S \times sg_i@C$ describing the q.values.

Methods

show signature(object = "RNAinteract"): ...

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
showClass("RNAinteract")
```

sgi	<i>Dataset of class 'RNAinteract'</i>
-----	---------------------------------------

Description

Sample object of class [RNAinteract](#). The data are real but anonymized. The object contains two replicate screens with three readout channels.

Usage

```
data(sgi)
```

Format

The data contains two screens with three readout channels. The screen is performed on multiwell plates with 8 x 12 wells.

Examples

```
data(sgi)
sgi
```

sgisubset	<i>subset of an RNAinteract object.</i>
-----------	---

Description

A new object of class [RNAinteract](#) is created that contains a subset of screens and channels.

Usage

```
sgisubset(sgi, screen = getScreenNames(sgi), channel = getChannelNames(sgi))
```

Arguments

sgi	An object of class RNAinteract .
screen	Names of the selected screens.
channel	Names of the selected channels.

Details

This function returns a [RNAinteract](#) object that only contains the selected screens and channels.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi
sgi1 <- sgisubset(sgi, screen = "1")
sgi1
sgi2 <- sgisubset(sgi, channel = "nrCells")
sgi2
```

sgisubsetQueryDesign *Subsetting query genes in a RNAinteract object.*

Description

A [RNAinteract](#) object with a subset of query genes is returned.

Usage

```
sgisubsetQueryDesign(sgi, query.targets = NULL, query.reagents = NULL)
```

Arguments

sgi	An RNAinteract object.
query.targets	The query target ids to be selected.
query.reagents	The query reagent ids to be selected.

Value

Returns an object of class [RNAinteract](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

startReport	<i>start and end a RNAinteract report</i>
-------------	---

Description

startReport will open a html page and starts writing an html report for a RNAinteract screen. endReport finishes the report and closes the html-file.

Usage

```
startReport(outputpath)
endReport(report)
```

Arguments

outputpath	the path to the output directory where the report is written to.
report	An report object as returned by startReport or any report... function.

Details

~~ details ~~

Value

startReport returns an report object. It is handed over to each report-function.

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#), [reportAnnotation](#), [reportStatistics](#), [reportGeneLists](#), [reportNetworks](#), [reportScreenData](#), [reportDoublePerturbation](#), [reportMainEffects](#)

Examples

```
data("sgi")
report <- startReport("report")
reportAnnotation(sgi, report = report)
endReport(report)
# browseURL(file.path("report", "index.html"))
```

summarizeScreens	<i>summarize screens</i>
------------------	--------------------------

Description

Creates a new object of class [RNAinteract](#) with one screen. The new screen is the mean of all screens in the input object.

Usage

```
summarizeScreens(sgi, screens, newscreenname = "mean")
```

Arguments

sgi	An object of class RNAinteract .
screens	The screen names to be summarized.
newscreenname	The name of the new summary screen.

Details

If multiple screens with the same layout are stored in the same [RNAinteract](#) object, then these screens are summarized by averaging to a new screen. The returned object contains one screen.

Value

An object of class [RNAinteract](#).

Author(s)

Bernd Fischer

See Also

[RNAinteract-package](#)

Examples

```
data("sgi")
sgi
sginew <- summarizeScreens(sgi, screens=c("1","2"), newscreenname = "m")
sginew
```

swaptree	<i>Swaps a branch of a hclust object.</i>
----------	---

Description

Swaps the left and right branch at a specified level of a dendrogram.

Usage

```
swaptree(hc, level)
```

Arguments

hc	An hierarchical clustering object as produced by hclust.
level	The level to be swapped.

Value

Returns an hclust object.

Author(s)

Bernd Fischer

Index

- * **attribute**
 - getData, [12](#)
 - getMain, [14](#)
 - getReplicateData, [16](#)
 - getScale, [17](#)
 - getScreenNames, [18](#)
- * **classes**
 - RNAinteract-class, [29](#)
- * **datasets**
 - sgi, [31](#)
- * **hplot**
 - grid.doublePerturbation, [18](#)
 - grid.sgiHeatmap, [20](#)
 - plotDoublePerturbation, [24](#)
 - plotHeatmap, [26](#)
- * **htest**
 - computePValues, [6](#)
- * **manip**
 - bindscreens, [4](#)
 - computePI, [5](#)
 - computePValues, [6](#)
 - createCellHTSFromFiles, [7](#)
 - createRNAinteract, [8](#)
 - createRNAinteractFromFiles, [9](#)
 - embedPCA, [10](#)
 - estimateMainEffect, [11](#)
 - normalizeMainEffectQuery, [21](#)
 - normalizeMainEffectTemplate, [22](#)
 - normalizePlateEffect, [23](#)
 - sgisubset, [31](#)
 - sgisubsetQueryDesign, [32](#)
 - summarizeScreens, [34](#)
- * **multivariate**
 - computePValues, [6](#)
- * **package**
 - RNAinteract-package, [2](#)
- * **print**
 - reportAnnotation, [27](#)
 - startReport, [33](#)
- bindscreens, [3, 4](#)
- cellHTS2, [8](#)
- computePI, [3, 5](#)
- computePValues, [3, 6, 13](#)
- createCellHTSFromFiles, [3, 7, 9, 10](#)
- createRNAinteract, [3, 8, 8, 10](#)
- createRNAinteractFromFiles, [3, 8, 9, 9, 12, 29](#)
- doublePerturbationGrob, [3, 20, 25](#)
- doublePerturbationGrob
(grid.doublePerturbation), [18](#)
- embedPCA, [3, 10](#)
- endReport, [3, 28](#)
- endReport (startReport), [33](#)
- estimateMainEffect, [3, 11, 13](#)
- getChannelNames, [3](#)
- getChannelNames (getScreenNames), [18](#)
- getData, [3, 12, 16, 28](#)
- getIndDesignData, [3](#)
- getIndDesignData (getReplicateData), [16](#)
- getMain, [3, 14](#)
- getMainNeg, [3](#)
- getMainNeg (getMain), [14](#)
- getReplicateData, [3, 16](#)
- getScale, [3, 17](#)
- getScreenNames, [3, 18](#)
- gpar, [20](#)
- grid.doublePerturbation, [3, 18, 25](#)
- grid.sgiHeatmap, [3, 20](#)
- limma-package, [6](#)
- normalizeMainEffectQuery, [3, 13, 21](#)
- normalizeMainEffectTemplate, [3, 22](#)
- normalizePlateEffect, [3, 13, 23](#)
- plot, [19, 25](#)

plotDoublePerturbation, [3](#), [20](#), [24](#)
plotHeatmap, [3](#), [21](#), [26](#)
plotScreen, [13](#)
points, [19](#)
postDrawDetails.doublePerturbation
 (grid.doublePerturbation), [18](#)

reportAnnotation, [3](#), [27](#), [33](#)
reportDoublePerturbation, [3](#), [20](#), [25](#), [33](#)
reportDoublePerturbation
 (reportAnnotation), [27](#)
reportGeneLists, [3](#), [33](#)
reportGeneLists (reportAnnotation), [27](#)
reportHeatmap, [3](#)
reportHeatmap (reportAnnotation), [27](#)
reportMainEffects, [3](#), [33](#)
reportMainEffects (reportAnnotation), [27](#)
reportNetworks, [3](#), [33](#)
reportNetworks (reportAnnotation), [27](#)
reportScreenData, [3](#), [33](#)
reportScreenData (reportAnnotation), [27](#)
reportStatistics, [3](#), [33](#)
reportStatistics (reportAnnotation), [27](#)
RNAinteract, [4–7](#), [9–13](#), [15–18](#), [21–24](#), [26](#),
 [28](#), [31–34](#)
RNAinteract (RNAinteract-package), [2](#)
RNAinteract-class, [29](#)
RNAinteract-package, [2](#)

sgi, [31](#)
sgisubset, [3](#), [31](#)
sgisubsetQueryDesign, [3](#), [32](#)
show, RNAinteract-method
 (RNAinteract-class), [29](#)
startReport, [3](#), [28](#), [33](#)
summarizeScreens, [3](#), [34](#)
swaptree, [35](#)