

# Package ‘phantasusLite’

May 6, 2024

**Type** Package

**Title** Loading and annotation RNA-seq counts matrices

**Version** 1.2.0

**Description** PhantasusLite – a lightweight package with helper functions of general interest extracted from phantasus package. In particular it simplifies working with public RNA-seq datasets from GEO by providing access to the remote HSDS repository with the precomputed gene counts from ARCHS4 and DEE2 projects.

**Depends** R (>= 4.2)

**Imports** data.table, rhdf5client(>= 1.25.1), httr, stringr, stats, utils, Biobase, methods

**biocViews** GeneExpression, Transcriptomics, RNASeq

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.3.1

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown, BiocStyle, rhdf5, GEOquery

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**URL** <https://github.com/ctlab/phantasusLite/>

**BugReports** <https://github.com/ctlab/phantasusLite/issues>

**git\_url** <https://git.bioconductor.org/packages/phantasusLite>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** c542b29

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-05

**Author** Rita Sablina [aut],  
 Maxim Kleverov [aut],  
 Alexey Sergushichev [aut, cre]

**Maintainer** Alexey Sergushichev <alsergbox@gmail.com>

## Contents

createH5 . . . . .	2
createIndexH5 . . . . .	3
createIndexH5Remote . . . . .	3
createMetaH5 . . . . .	4
createPriorityH5 . . . . .	4
getCountsMetaPart . . . . .	5
getHSDSFileList . . . . .	5
getIndexRemote . . . . .	6
gsmToChunk . . . . .	6
inferCondition . . . . .	7
inferConditionImpl . . . . .	7
loadCountsFromH5FileHSDS . . . . .	8
loadCountsFromHSDS . . . . .	8
readGct . . . . .	9
removeRepeatWords . . . . .	10
updateARCHS4meta . . . . .	10
updateDEE2meta . . . . .	11
updateIndexH5 . . . . .	11
validateCountsCollection . . . . .	12
writeGct . . . . .	12
<b>Index</b>	<b>13</b>

---

createH5	<i>Creates metafiles for HDF5-files</i>
----------	---

---

### Description

Creates metafiles for HDF5-files

### Usage

```
createH5(data, file, dataset_name)
```

### Arguments

data	contains metadata
file	contains file name
dataset_name	contains dataset name

**Value**

Returns NULL

---

createIndexH5	<i>Writes indexes to the file</i>
---------------	-----------------------------------

---

**Description**

Writes indexes to the file

**Usage**

```
createIndexH5(data, file)
```

**Arguments**

data	contains metadata
file	contains the file name

**Value**

Returns NULL

---

createIndexH5Remote	<i>Creates HDF5-file with indexes</i>
---------------------	---------------------------------------

---

**Description**

Creates HDF5-file with indexes

**Usage**

```
createIndexH5Remote(
  url,
  collections = c("archs4", "dee2"),
  destfile = "index.h5"
)
```

**Arguments**

url	contains URL to the root of counts files
collections	vector of collection names to process
destfile	where to put resulting index file

**Value**

Returns NULL

---

createMetaH5	<i>Converts collection meta.txt files to meta.h5, putting them to the respective collection folders</i>
--------------	---

---

**Description**

Converts collection meta.txt files to meta.h5, putting them to the respective collection folders

**Usage**

```
createMetaH5(counts_dir)
```

**Arguments**

counts_dir	contains directory name
------------	-------------------------

**Value**

Returns NULL

---

createPriorityH5	<i>Creates HDF5-File with priority</i>
------------------	--

---

**Description**

Creates HDF5-File with priority

**Usage**

```
createPriorityH5(counts_dir, force = FALSE, verbose = FALSE)
```

**Arguments**

counts_dir	contains counts directory
force	logical value which lets function replace existing priority file
verbose	logical value which determines a content of the output.

**Value**

Returns NULL

---

getCountsMetaPart	<i>Gets list with metadata</i>
-------------------	--------------------------------

---

**Description**

Gets list with metadata

**Usage**

```
getCountsMetaPart(counts_dir, collection_name, verbose)
```

**Arguments**

counts_dir	contains counts directory
collection_name	contains name of the collection
verbose	logical value which determines a content of the output.

**Value**

list with metadata

---

getHSDSFileList	<i>Returns list of all HDF5-files on HSDS-server</i>
-----------------	--

---

**Description**

Returns list of all HDF5-files on HSDS-server

**Usage**

```
getHSDSFileList(  
  url = "https://alserglab.wustl.edu/hsds/?domain=/counts",  
  directory = NULL  
)
```

**Arguments**

url	containing url of the server and root domain.
directory	containing name of the directory

**Value**

List of all HDF5-files on the server or all files of the collection

**Examples**

```
url <- 'https://alserglab.wustl.edu/hsds/?domain=/counts'
getHSDSFileList(url)
```

---

getIndexRemote	<i>Creates a data table with indexes and chunks of samples in remote HDF5-files</i>
----------------	---

---

**Description**

Creates a data table with indexes and chunks of samples in remote HDF5-files

**Usage**

```
getIndexRemote(url, collections)
```

**Arguments**

url	contains url to the root of counts files
collections	contains names of the collections

**Value**

table with samples, indexes and chunks in all HDF5-files

---

gsmToChunk	<i>Gets chunk from GSE identifiers.</i>
------------	---

---

**Description**

Gets chunk from GSE identifiers.

**Usage**

```
gsmToChunk(samples)
```

**Arguments**

samples	containing a list of samples
---------	------------------------------

**Value**

list of chunks

---

inferCondition	<i>Adds condition to the annotation.</i>
----------------	--

---

**Description**

Adds condition to the annotation.

**Usage**

```
inferCondition(es)
```

**Arguments**

es                    contains ExpressionSet object

**Value**

Annotated ExpressionSet with conditions and replicates

**Examples**

```
ess <- GEOquery::getGEO("GSE143903")
es <- ess[[1]]
es <- inferCondition(es)
es$condition # contains inferred groups
es$replicate # contains inferred replicate numbers
```

---

inferConditionImpl	<i>Creates condition from the samples titles</i>
--------------------	--

---

**Description**

Creates condition from the samples titles

**Usage**

```
inferConditionImpl(gse_titles)
```

**Arguments**

gse\_titles            contains titles

**Value**

List of conditions and replicates

---

`loadCountsFromH5FileHSDS`*Load count matrix from remote HDF5-file*

---

**Description**

Load count matrix from remote HDF5-file

**Usage**

```
loadCountsFromH5FileHSDS(  
  es,  
  url = "https://alserglab.wustl.edu/hsds/?domain=/counts",  
  file,  
  sampleIndexes = NULL  
)
```

**Arguments**

<code>es</code>	containing ExpressionSet loaded from GEO. Contains empty expression matrix.
<code>url</code>	containing url of the server and root domain.
<code>file</code>	containing name of the file (relative to the root domain)
<code>sampleIndexes</code>	containing sample indexes list

**Value**

ExpressionSet object with loaded count matrix

**Examples**

```
ess <- GEOquery::getGEO("GSE53053")  
es <- ess[[1]]  
url <- 'https://alserglab.wustl.edu/hsds/?domain=/counts'  
file <- "/dee2/mmusculus_star_matrix_20240409.h5"  
es <- loadCountsFromH5FileHSDS(es, url, file)
```

---

`loadCountsFromHSDS`*Load count matrix from HDF5-files.*

---

**Description**

Load count matrix from HDF5-files.



**Usage**

```
loadCountsFromHSDS(  
  es,  
  url = "https://alserglab.wustl.edu/hsds/?domain=/counts"  
)
```

**Arguments**

es                   containing ExpressionSet loaded from GEO. Contains empty expression matrix.  
url                   containing url of the server and root domain.

**Value**

ExpressionSet with loaded count matrix

**Examples**

```
ess <- GEOquery::getGEO("GSE85653")  
es <- ess[[1]]  
url <- 'https://alserglab.wustl.edu/hsds/?domain=/counts'  
es <- loadCountsFromHSDS(es, url)
```

---

readGct	<i>Reads ExpressionSet from a GCT file.</i>
---------	---

---

**Description**

Only versions 1.2 and 1.3 are supported.

**Usage**

```
readGct(gct)
```

**Arguments**

gct                   Path to gct file

**Value**

ExpressionSet object

**Examples**

```
es <- readGct(system.file("extdata/testdata/gct/test.gct", package="phantasusLite"))
```

---

removeRepeatWords	<i>Removes repeated words from conditions</i>
-------------------	---

---

**Description**

Removes repeated words from conditions

**Usage**

```
removeRepeatWords(titles)
```

**Arguments**

titles	contains titles
--------	-----------------

**Value**

titles without repeated words

---

updateARCHS4meta	<i>Creates meta.txt file, which describes typical archs4 and archs4Zoo files.</i>
------------------	---

---

**Description**

Creates meta.txt file, which describes typical archs4 and archs4Zoo files.

**Usage**

```
updateARCHS4meta(  
  archDir = file.path(getOption("phantasusCacheDir"), "counts/archs4")  
)
```

**Arguments**

archDir	path to directory with arch4 .h5 files.
---------	---

**Value**

Returns NULL

---

updateDEE2meta	<i>Creates meta.txt file, which describes typical dee2 files.</i>
----------------	---

---

**Description**

Creates meta.txt file, which describes typical dee2 files.

**Usage**

```
updateDEE2meta(  
  destDir = file.path(getOption("phantasusCacheDir"), "counts/dee2")  
)
```

**Arguments**

destDir            path to directory with DEE2 .h5 files.

**Value**

Returns NULL

---

updateIndexH5	<i>Updates indexes from HDF5-files</i>
---------------	--

---

**Description**

Updates indexes from HDF5-files

**Usage**

```
updateIndexH5(counts_dir, force = FALSE, verbose = FALSE)
```

**Arguments**

counts\_dir        contains counts directory  
force             logical value which lets function replace existing index file  
verbose           logical value which determines a content of the output.

**Value**

Returns NULL

---

validateCountsCollection  
*Validates counts collection*

---

**Description**

Validates counts collection

**Usage**

```
validateCountsCollection(collectionDir, verbose = FALSE)
```

**Arguments**

collectionDir contains directory name  
verbose logical value which determines a content of the output.

**Value**

false if collection is not valid

---

writeGct *Saves ExpressionSet to a GCT file (version 1.3).*

---

**Description**

Saves ExpressionSet to a GCT file (version 1.3).

**Usage**

```
writeGct(es, file, gzip = FALSE)
```

**Arguments**

es ExpressionSet object to save  
file Path to output gct file  
gzip Whether to gzip apply gzip-compression for the output file#'

**Value**

Result of the closing file (as in 'close()' function')

**Examples**

```
es <- readGct(system.file("extdata/testdata/gct/test.gct", package="phantasusLite"))
out <- tempfile(fileext = ".gct.gz")
writeGct(es, out, gzip=TRUE)
```

# Index

## \* **internal**

- createH5, [2](#)
- createIndexH5, [3](#)
- createIndexH5Remote, [3](#)
- createMetaH5, [4](#)
- createPriorityH5, [4](#)
- getCountsMetaPart, [5](#)
- getIndexRemote, [6](#)
- gsmToChunk, [6](#)
- inferConditionImpl, [7](#)
- removeRepeatWords, [10](#)
- updateARCHS4meta, [10](#)
- updateDEE2meta, [11](#)
- updateIndexH5, [11](#)
- validateCountsCollection, [12](#)

- createH5, [2](#)
- createIndexH5, [3](#)
- createIndexH5Remote, [3](#)
- createMetaH5, [4](#)
- createPriorityH5, [4](#)

- getCountsMetaPart, [5](#)
- getHSDSFileList, [5](#)
- getIndexRemote, [6](#)
- gsmToChunk, [6](#)

- inferCondition, [7](#)
- inferConditionImpl, [7](#)

- loadCountsFromH5FileHSDS, [8](#)
- loadCountsFromHSDS, [8](#)

- readGct, [9](#)
- removeRepeatWords, [10](#)

- updateARCHS4meta, [10](#)
- updateDEE2meta, [11](#)
- updateIndexH5, [11](#)

- validateCountsCollection, [12](#)

- writeGct, [12](#)