

# Package ‘alabaster.sce’

May 1, 2024

**Title** Load and Save SingleCellExperiment from File

**Version** 1.4.0

**Date** 2023-12-29

**License** MIT + file LICENSE

**Description** Save SingleCellExperiment into file artifacts, and load them back into memory.

This is a more portable alternative to serialization of such objects into RDS files.

Each artifact is associated with metadata for further interpretation;

downstream applications can enrich this metadata with context-specific properties.

**Depends** SingleCellExperiment, alabaster.base

**Imports** methods, alabaster.se, jsonlite

**Suggests** knitr, testthat, BiocStyle, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 7.2.3

**biocViews** DataImport, DataRepresentation

**git\_url** <https://git.bioconductor.org/packages/alabaster.sce>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 5d6e1fa

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-01

**Author** Aaron Lun [aut, cre]

**Maintainer** Aaron Lun <[infinite.monkeys.with.keyboards@gmail.com](mailto:infinite.monkeys.with.keyboards@gmail.com)>

## Contents

readSingleCellExperiment	2
saveSingleCellExperiment	3
<b>Index</b>	<b>5</b>

readSingleCellExperiment

*Read a SingleCellExperiment from disk*

---

## Description

Read a [SingleCellExperiment](#) object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

## Usage

```
readSingleCellExperiment(path, metadata, ...)
```

## Arguments

path	String containing a path to a directory, itself created using the <a href="#">saveObject</a> method for <a href="#">SingleCellExperiment</a> objects.
metadata	Named list of metadata for this object, see <a href="#">readObjectFile</a> for details.
...	Further arguments passed to <a href="#">readRangedSummarizedExperiment</a> and internal <a href="#">altReadObject</a> calls.

## Value

A [SingleCellExperiment](#) object.

## Author(s)

Aaron Lun

## See Also

"[saveObject,SingleCellExperiment-method](#)", to save the [SingleCellExperiment](#) to disk.

## Examples

```
# Mocking up an SCE:
mat <- matrix(rpois(10000, 10), ncol=10)
colnames(mat) <- letters[1:10]
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))

se <- SingleCellExperiment(list(counts=mat))
se$stuff <- LETTERS[1:10]
se$blah <- runif(10)
reducedDims(se) <- list(
  PCA=matrix(rnorm(ncol(se)*10), ncol=10),
  TSNE=matrix(rnorm(ncol(se)*2), ncol=2)
)
altExps(se) <- list(spikes=SummarizedExperiment(list(counts=mat[1:2,])))
```

```
# Staging it:
tmp <- tempfile()
saveObject(se, tmp)
readObject(tmp)
```

---

saveSingleCellExperiment

*Save a SingleCellExperiment to disk*

---

## Description

Save a [SingleCellExperiment](#) to its on-disk representation.

## Usage

```
## S4 method for signature 'SingleCellExperiment'
saveObject(x, path, ...)
```

## Arguments

x	A <a href="#">SingleCellExperiment</a> object or one of its subclasses.
path	String containing the path to a directory in which to save x.
...	Further arguments to pass to the <code>RangedSummarizedExperiment</code> method.

## Value

x is saved into path and NULL is invisibly returned.

## Author(s)

Aaron Lun

## See Also

[readSingleCellExperiment](#), to read the `SingleCellExperiment` back into the R session.

## Examples

```
# Mocking up an SCE:
mat <- matrix(rpois(10000, 10), ncol=10)
colnames(mat) <- letters[1:10]
rownames(mat) <- sprintf("GENE_%i", seq_len(nrow(mat)))

se <- SingleCellExperiment(list(counts=mat))
se$stuff <- LETTERS[1:10]
se$blah <- runif(10)
```

```
reducedDims(se) <- list(  
  PCA=matrix(rnorm(ncol(se)*10), ncol=10),  
  TSNE=matrix(rnorm(ncol(se)*2), ncol=2)  
)  
altExps(se) <- list(spikes=SummarizedExperiment(list(counts=mat[1:2,])))  
  
# Staging it:  
tmp <- tempfile()  
saveObject(se, tmp)  
list.files(tmp, recursive=TRUE)
```

# Index

altReadObject, [2](#)

loadSingleCellExperiment  
    (readSingleCellExperiment), [2](#)

readObject, [2](#)  
readObjectFile, [2](#)  
readRangedSummarizedExperiment, [2](#)  
readSingleCellExperiment, [2](#), [3](#)

saveObject, [2](#)  
saveObject, SingleCellExperiment-method  
    (saveSingleCellExperiment), [3](#)  
saveSingleCellExperiment, [3](#)  
SingleCellExperiment, [2](#), [3](#)  
stageObject, SingleCellExperiment-method  
    (saveSingleCellExperiment), [3](#)