Package 'spqnData'

May 14, 2024

17149 1 1, 2021
Version 1.16.0
Title Data for the spqn package
Description Bulk RNA-seq from GTEx on 4,000 randomly selected, expressed genes. Data has been processed for co-expression analysis.
Depends R (>= 4.0), SummarizedExperiment
License Artistic-2.0
LazyData FALSE
biocViews Homo_sapiens_Data, ExpressionData, Tissue, RNASeqData
git_url https://git.bioconductor.org/packages/spqnData
git_branch RELEASE_3_19
git_last_commit 8f3ef94
git_last_commit_date 2024-04-30
Repository Bioconductor 3.19
Date/Publication 2024-05-14
Author Yi Wang [cre, aut], Kasper Daniel Hansen [aut]
Maintainer Yi Wang <pre></pre>
Contents
gtex.4k
Index 3

2 gtex.4k

gtex.4k

Example data for the spqn package.

Description

A random sample of 4,000 expressed genes (protein-coding or lincRNAs) from GTEx v6p. The tissue is Adipose Subcutaneous.

Usage

```
data("gtex.4k")
```

Format

An object of class SummarizedExperiment.

Details

Data is 350 samples from GTEx v6p. The tissue is Adipose Subcutanous.

We first selected protein-coding or lincRNAs based on the supplied annotation files. Next we kept genes with a median log2(RPKM) expression greater than zero. This resulted in a data matrix with 12,267 genes of which 11,911 are protein-coding. We stored the mean expression value per gene in rowData(gtex.4k)\$ave_logrpkm.

We next mean centered and variance scaled the expression values so all genes have zero mean and variance 1. We then removed 4 principal components from this data matrix using the removePrincipalComponents function from the WGCNA package.

Finally, we randomly selected 4,000 genes.

Additional information on the genes are present in the rowData. The type of gene (lincRNA or protein-coding) is present in the gene_type column. The average expression of each gene on the log2(RPKM)-scale, prior to removing principal components, are present in the ave_logrpkm column.

Source

Original data from gtexportal.org. A script for downloading and processing the paper is included in scripts/gtex.Rmd.

Examples

```
data(gtex.4k)
```

Index

* datasets gtex.4k,2 gtex.4k,2