

Package ‘BioNAR’

April 23, 2024

Title Biological Network Analysis in R

Version 1.5.5

Description the R package BioNAR, developed to step by step analysis of PPI network. The aim is to quantify and rank each protein’s simultaneous impact into multiple complexes based on network topology and clustering. Package also enables estimating of co-occurrence of diseases across the network and specific clusters pointing towards shared/common mechanisms.

License Artistic-2.0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Depends R (>= 3.5.0), igraph (>= 2.0.1.1), poweRlaw, latex2exp, RSpectra, Rdpack

Imports stringr, viridis, clusterCons, fgsea, grid, methods, AnnotationDbi, dplyr, GO.db, org.Hs.eg.db, rSpectral, WGCNA, ggplot2, ggrepel, minpack.lm, cowplot, data.table, scales, stats, Matrix

RdMacros Rdpack

Suggests knitr, BiocStyle, magick, rmarkdown, igraphdata, testthat (>= 3.0.0), vdiff, devtools, pander, plotly, randomcoloR

Config/testthat/edition 3

VignetteBuilder knitr

BugReports <https://github.com/lptolik/BioNAR/issues/>

biocViews Software, GraphAndNetwork, Network

LazyData true

git_url <https://git.bioconductor.org/packages/BioNAR>

git_branch devel

git_last_commit d85809e

git_last_commit_date 2024-04-22

Repository Bioconductor 3.19

Date/Publication 2024-04-23

Author Colin Mclean [aut],
 Anatoly Sorokin [aut, cre],
 Oksana Sorokina [aut],
 J. Douglas Armstrong [aut, fnd],
 T. Ian Simpson [ctb, fnd]

Maintainer Anatoly Sorokin <lptolik@gmail.com>

Contents

| | |
|---|----|
| addEdgeAtts | 4 |
| annotateGeneNames | 4 |
| annotateGoBP | 5 |
| annotateGoCC | 6 |
| annotateGoMF | 7 |
| annotateGOont | 8 |
| annotateInterpro | 9 |
| annotatePresynaptic | 9 |
| annotateSCHanno | 10 |
| annotateTopOntoOVG | 11 |
| annotateVertex | 12 |
| applpMatrixToGraph | 13 |
| BioNAR | 14 |
| buildConsensusMatrix | 15 |
| buildNetwork | 15 |
| calcAllClustering | 16 |
| calcBridgeness | 17 |
| calcCentrality | 18 |
| calcCentralityExternalDistances | 19 |
| calcCentralityInternalDistances | 20 |
| calcClustering | 21 |
| calcDiseasePairs | 22 |
| calcEntropy | 23 |
| calcMembership | 24 |
| calcReclusterMatrix | 25 |
| calcSparsness | 26 |
| clusteringSummary | 27 |
| clusterORA | 28 |
| degreeBinnedGDAs | 29 |
| diseasome | 30 |
| escapeAnnotation | 31 |
| evalCentralitySignificance | 32 |
| findLCC | 33 |
| fitDegree | 33 |
| fitSigmoid | 35 |
| flatfile.go.BP.csv | 36 |

| | |
|---------------------------------------|----|
| flatfile.go.CC.csv | 36 |
| flatfile.go.MF.csv | 36 |
| flatfile_human_gene2HDO.csv | 37 |
| getAnnotationList | 37 |
| getAnnotationVertexList | 38 |
| getBridgeness | 39 |
| getCentralityMatrix | 40 |
| getClustering | 41 |
| getClusterSubgraphByID | 42 |
| getCommunityGraph | 43 |
| getDiseases | 43 |
| getDType | 44 |
| getDYNAMO | 45 |
| getEntropy | 46 |
| getEntropyRate | 47 |
| getGNP | 48 |
| getGraphCentralityECDF | 49 |
| getIDs | 49 |
| getPA | 50 |
| getRandomGraphCentrality | 51 |
| getRobustness | 52 |
| gofs | 53 |
| law-class | 54 |
| layoutByCluster | 54 |
| layoutByRecluster | 55 |
| makeConsensusMatrix | 55 |
| metlMatrix | 57 |
| normModularity | 57 |
| permute | 59 |
| plotBridgeness | 59 |
| plotEntropy | 61 |
| plotRatio | 62 |
| plotSigmoid | 63 |
| PPI_Presynaptic.csv | 63 |
| PPI_Presynaptic.gml | 64 |
| prepareGDA | 64 |
| PresynAn.csv | 65 |
| recluster | 65 |
| removeVertexTerm | 66 |
| runPermDisease | 67 |
| sampleDegBinnedGDA | 68 |
| sampleGraphClust | 69 |
| SCH_flatfile.csv | 70 |
| summaryStats | 70 |
| unescapeAnnotation | 71 |
| zeroNA | 71 |

| | |
|-------------|---|
| addEdgeAtts | <i>Copy edge attributes from one graph to another</i> |
|-------------|---|

Description

Copy edge attributes from one graph to another

Usage

```
addEdgeAtts(GG, gg)
```

Arguments

| | |
|----|-------------------------------------|
| GG | igraph object, source of attributes |
| gg | igraph object, attributes recipient |

Value

annotated version of gg igraph object

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
GG <- igraph::read_graph(file, format="gml")
gg<-findLCC(GG)
gg <- addEdgeAtts(GG, gg)
edge_attr_names(gg)
```

| | |
|-------------------|----------------------------------|
| annotateGeneNames | <i>Annotate Human Gene Names</i> |
|-------------------|----------------------------------|

Description

For the protein-protein interaction (PPI) or disease gene interaction (DGN) graphs that have EntrezID as a vertex name this function extract standard name from [org.Hs.eg.db](#) and annotate vertices.

Usage

```
annotateGeneNames(gg, orgDB = org.Hs.eg.db, keytype = "ENTREZID")
```

Arguments

| | |
|---------|--|
| gg | igraph object to annotate |
| orgDB | ordDB object, by default human is assumed from org.Hs.eg.db |
| keytype | type of IDs stored in the name vertex attribute, by default ENTREZID is assumed. |

Details

If vertex name attribute stores not EntrezID or network is build not from human genes, other `OrgDb-class` object could be provided in `orgDB` and one of `keytypes` from that object that correspond to the nature of the vertex name attribute could be provided in the `keytype` attribute.

If for some vertices name attribute does not match `keys` with particular `keytypes` in the `orgDB` object, empty string is added as `GeneName`.

Value

igraph object with new vertex attribute `GeneName`

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
```

annotateGoBP

Add GO BP annotation to the graph vertices

Description

The function loads an annotation data matrix called `annoF`, which contains three columns; the first containing gene Entrez IDs, the second gene GO BP ID terms, the third gene GO BP description terms. The function then performs a many-to-one mapping of each matrix row to a network vertex using matching Entrez IDs, filling the vertices attributes `GO_BP_ID` and `GO_BP`.

Usage

```
annotateGoBP(gg, annoF, idatt = "name")
```

Arguments

| | |
|--------------------|--|
| <code>gg</code> | graph to update |
| <code>annoF</code> | annotation matrix in Pair form |
| <code>idatt</code> | optional name of the vertex attribute to map to the annotation data.frame first column |

Value

annotated igraph object

See Also

`getAnnotationVertexList`

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
sfile<-system.file("extdata", "flatfile.go.BP.csv", package = "BioNAR")
goBP <- read.table(sfile, sep="\t", skip=1, header=FALSE,
strip.white=TRUE, quote="")
sgg <- annotateGoBP(gg, goBP)
```

annotateGoCC

Add GO CC annotation to the graph vertices

Description

The function loads an annotation data matrix called annoF, which contains three columns; the first containing gene Entrez IDs, the second gene GO ID terms, the third gene GO CC description terms. The function then performs a many-to-one mapping of each matrix row to a network vertex using matching Entrez IDs, filling the vertices attributes GO_CC_ID and GO_CC.

Usage

```
annotateGoCC(gg, annoF, idatt = "name")
```

Arguments

| | |
|-------|--|
| gg | graph to update |
| annoF | annotation matrix in Pair form |
| idatt | optional name of the vertex attribute to map to the annotation data.frame first column |

Value

annotated igraph object

See Also

getAnnotationVertexList

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
sfile<-system.file("extdata", "flatfile.go.CC.csv", package = "BioNAR")
goCC <- read.table(sfile, sep="\t", skip=1, header=FALSE,
strip.white=TRUE, quote="")
sgg <- annotateGoCC(gg, goCC)
```

| | |
|--------------|---|
| annotateGoMF | <i>Add GO MF annotation to the graph vertices</i> |
|--------------|---|

Description

The function loads an annotation data matrix called annoF, which contains three columns; the first containing gene Entrez IDs, the second gene GO MF ID terms, the third gene GO MF description terms. The function then performs a many-to-one mapping of each matrix row to a network vertex using matching Entrez IDs, filling the vertices attributes GO_MF_ID and GO_MF.

Usage

```
annotateGoMF(gg, annoF, idatt = "name")
```

Arguments

| | |
|-------|--|
| gg | graph to update |
| annoF | annotation matrix in Pair form |
| idatt | optional name of the vertex attribute to map to the annotation data.frame first column |

Value

annotated igraph object

See Also

getAnnotationVertexList

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
sfile<-system.file("extdata", "flatfile.go.MF.csv", package = "BioNAR")
goMF <- read.table(sfile, sep="\t", skip=1, header=FALSE,
strip.white=TRUE, quote="")
sgg <- annotateGoMF(gg, goMF)
```

| | |
|---------------|-------------------------------------|
| annotateGOont | <i>Annotate nodes with GO terms</i> |
|---------------|-------------------------------------|

Description

For the protein-protein interaction (PPI) or disease gene interaction (DGN) graphs that have EntrezID as a vertex name this function extract GeneOntology annotation from orgDB, which should be [OrgDb-class](#), split them into three ontology group (MF,BP,CC) and annotate vertices with .

Usage

```
annotateGOont(gg, orgDB = org.Hs.eg.db, keytype = "ENTREZID", idatt = "name")
```

Arguments

| | |
|---------|--|
| gg | igraph object to annotate |
| orgDB | ordDB object, by default human is assumed from org.Hs.eg.db |
| keytype | type of IDs stored in the name vertex attribute, by default ENTREZID is assumed. |
| idatt | optional name of the vertex attributes that contains IDs matching the keytype |

Details

If vertex name attribute stores not EntrezID or network is build not from human genes, other [OrgDb-class](#) object could be provided in orgDB and one of [keytypes](#) from that object that correspond to the nature of the vertex name attribute could be provided in the keytype attribute.

If for some vertices name attribute does not match [keys](#) with particular [keytypes](#) in the orgDB object, empty string is added as GeneName.

Value

igraph object with new vertex attribute GeneName

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
ggGO <- annotateGOont(gg)
```

| | |
|------------------|--|
| annotateInterpro | <i>Add InterPro Family and Domain annotation to the graph vertices</i> |
|------------------|--|

Description

Function takes data from annoF matrix and add them to attributes InterPro_Family for term and InterPro_Family_ID for IDs.

Usage

```
annotateInterpro(gg, annoF, annoD, idatt = "name")
```

Arguments

| | |
|-------|---|
| gg | graph to update |
| annoF | family annotation matrix in Pair form |
| annoD | domain annotation matrix in Pair form |
| idatt | optional name of the vertex attributes that contains Entrez IDs |

Details

Function takes data from annoD matrix and add them to attributes InterPro_Domain for term and InterPro_Domain_ID for IDs.

Value

annotated igraph object

See Also

getAnnotationVertexList

| | |
|---------------------|--|
| annotatePresynaptic | <i>Add presynaptic functional groups</i> |
|---------------------|--|

Description

Function takes from anno matrix manually curated presynaptic genes functional annotation derived from Boyken et al. (2013) [doi:10.1016/j.neuron.2013.02.027](https://doi.org/10.1016/j.neuron.2013.02.027) and add them to attributes PRESYNAPTIC.

Usage

```
annotatePresynaptic(gg, anno, idatt = "name")
```

Arguments

| | |
|-------|---|
| gg | graph to update |
| anno | annotation matrix in Pair form |
| idatt | optional name of the vertex attributes that contains Entrez IDs |

Value

annotated igraph object

See Also

getAnnotationVertexList

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
sfile<-system.file("extdata", "PresynAn.csv", package = "BioNAR")
pres <- read.csv(sfile,skip=1,header=FALSE,strip.white=TRUE,quote="")
gg <- annotatePresynaptic(gg, pres)
```

annotateSCHanno

Add SCHanno synaptic functional groups

Description

The function loads an annotation data matrix of functional groups for schizopherina risk genes (1) called anno, which contains three columns; the first containing gene Entrez IDs, the second gene functional group ID terms, the third gene functional group description terms. The function then performs a many-to-one mapping of each matrix row to a network vertex using matching Entrez IDs, filling the SCHanno vertices attribute.

Usage

```
annotateSCHanno(gg, anno, idatt = "name")
```

Arguments

| | |
|-------|---|
| gg | igraph object to annotate |
| anno | annotation matrix in Pairs form |
| idatt | optional name of the vertex attributes that contains Entrez IDs |

Details

References:

1. Lips E, Cornelisse L, Toonen R, Min J, Hultman C, the International Schizophrenia Consortium, Holmans P, Donovan M, Purcell S, Smit A, Verhage M, Sullivan P, Visscher P, D P: Functional gene group analysis identifies synaptic gene groups as risk factor for schizophrenia. *Molecular Psychiatry* 2012,17:996–1006.

Value

annotated igraph object

See Also

getAnnotationVertexList

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
afile<-system.file("extdata", "SCH_flatfile.csv", package = "BioNAR")
dis <- read.table(afile, sep="\t", skip=1, header=FALSE,
strip.white=TRUE, quote="")
agg<-annotateSCHanno(gg, dis)
```

| | |
|--------------------|--|
| annotateTopOntoOVG | <i>Annotate graph with disease terms</i> |
|--------------------|--|

Description

The function loads a human disease annotation matrix called `dis`, which contains three columns; the first containing gene Entrez IDs, the second gene Human Disease Ontology (HDO) ID terms, the third gene HDO description terms. For human protein-protein interaction (PPI) or disease-gene networks (DGN) that have human Entrez IDs for the igraph vertex name attribute. The function then performs a many-to-one mapping of each matrix row to a network vertex using matching Entrez IDs, filling the vertices attributes `TopOnto_OVG_HDO_ID` and `TopOnto_OVG`.

Usage

```
annotateTopOntoOVG(gg, dis, idatt = "name")
```

Arguments

| | |
|--------------------|---|
| <code>gg</code> | igraph object to annotate |
| <code>dis</code> | annotation matrix in Pairs form |
| <code>idatt</code> | optional name of the vertex attributes that contains Entrez IDs |

Value

annotated igraph object

See Also

getAnnotationVertexList

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
# read HD0 data extracted from hxin/topOnto.HD0.db for synaptic network
afile<-system.file("extdata", "flatfile_human_gene2HD0.csv",
package = "BioNAR")
dis <- read.table(afile, sep="\t", skip=1, header=FALSE,
strip.white=TRUE, quote="")
agg<-annotateTopOntoOVG(gg, dis)
```

annotateVertex

Generic annotation function

Description

Function to build and fill a vertex attribute given an igraph object. Where parameter 'name' is the new vertex attribute name and values are filled from a two column data.frame supplied to 'value' attribute. The first first containing vertex name IDs, and the second the vertex annotation value.

Usage

```
annotateVertex(gg, name, values, idatt = "name")
```

Arguments

| | |
|--------|--|
| gg | igraph object to annotate |
| name | name of the attribute |
| values | annotation data.frame |
| idatt | optional name of the vertex attribute to map to the annotation data.frame first column |

Details

As a first step all attributes with provided names will be removed.

Value

igraph object where vertex attribute name contains annotation terms separated by semicolon.

See Also

getAnnotationVertexList

Examples

```
g1 <- make_star(10, mode="undirected")
V(g1)$name <- letters[1:10]
m<-rbind(data.frame(ID=letters[1:10], terms=letters[1:10]),
data.frame(ID=letters[1:10], terms=LETTERS[1:10]))
g2<-annotateVertex(g1, name='cap', values=m)
V(g2)$cap
```

| | |
|-------------------|--------------------------------------|
| aplpMatrixToGraph | <i>Add attributes to the vertex.</i> |
|-------------------|--------------------------------------|

Description

This function suits more for updating calculated vertex properties rather than node annotation. For the later case use [annotateVertex](#).

Usage

```
aplpMatrixToGraph(gg, m)
```

Arguments

| | |
|----|---|
| gg | igraph object |
| m | matrix of values to be applied as vertex attributes. matrix should contains column "ID" to map value to the vertex. |

Details

Unlike [annotateVertex](#), which is able to collapse multiple annotation terms, this function assume that vertex ID values are unique in the `m` matrix and corresponds to the name vertex attribute. If graph has no name vertex attribute error will be raised.

Value

modified igraph object

See Also

[annotateVertex](#)

Examples

```
g1 <- make_star(10, mode="undirected")
V(g1)$name <- letters[1:10]
m<-cbind(ID=letters[1:10],capital=LETTERS[1:10])
g1<-BioNAR::aplpMatrixToGraph(g1,m)
V(g1)$capital
```

BioNAR

BioNAR: Biological Network Analysis in R

Description

The R package BioNAR, developed to step by step analysis of PPI network. The aim is to quantify and rank each protein's simultaneous impact into multiple complexes based on network topology and clustering. Package also enables estimating of co-occurrence of diseases across the network and specific clusters pointing towards shared/common mechanisms.

Author(s)

Maintainer: Anatoly Sorokin <lptolik@gmail.com>

Authors:

- Colin Mclean <Colin.D.Mclean@ed.ac.uk>
- Oksana Sorokina <oksana.sorokina@ed.ac.uk>
- J. Douglas Armstrong <Douglas.Armstrong@ed.ac.uk> [funder]

Other contributors:

- T. Ian Simpson <Ian.Simpson@ed.ac.uk> [contributor, funder]

See Also

Useful links:

- Report bugs at <https://github.com/lptolik/BioNAR/issues/>

| | |
|----------------------|---|
| buildConsensusMatrix | <i>Build a consensus matrix from list of resampled clustering matrices outputted from the function sampleGraphClust</i> |
|----------------------|---|

Description

Build a consensus matrix from list of resampled clustering matrices outputted from the function [sampleGraphClust](#)

Usage

```
buildConsensusMatrix(lcc)
```

Arguments

lcc list of membership matrices obtained from the [sampleGraphClust](#)

Details

Function build a consensus matrix from list of membership matrices, which are a three column matrix: the first column contains the vertex IDs of input network; the second column the vertex IDs of the subsampled network, or -1 if the vertex has been masked; the third column the cluster membership of subsampled network, or -1 if vertex has been masked. The randomised resampled membership matrices could be obtained from the function [sampleGraphClust](#).

Value

consensus matrix of Nvert X Nvert

| | |
|--------------|--------------------------------------|
| buildNetwork | <i>Build network from data.table</i> |
|--------------|--------------------------------------|

Description

Wrapper for [graph_from_data_frame](#) function which will always return the largest connect component for a given network ff. The function will also annotated the edges in ff with PubMed data from kw if provided.

Usage

```
buildNetwork(ff, kw = NA, LCC = TRUE, simplify = TRUE)
```

Arguments

| | |
|----------|---|
| ff | network structure data.frame with first two columns defining the network edge nodes |
| kw | pmid keyword annotation data.frame. If NA no annotation will be added |
| LCC | if TRUE only largest connected component is returned |
| simplify | if TRUE loops and multiple edges will be removed |

Value

igraph object of the largest connected component

Examples

```
f<-data.frame(A=c('A', 'A', 'B', 'D'), B=c('B', 'C', 'C', 'E'))
gg<-buildNetwork(f)
V(gg)$name
```

| | |
|-------------------|--|
| calcAllClustering | <i>Calculate memberships for all clustering algorithms and store them on the graph vertices.</i> |
|-------------------|--|

Description

This function will call [calcClustering](#) for each clustering algorithm given in our predefined list. In the event no clustering could be performed, warnings will be issued and no new vertex attribute added to the graph.

Usage

```
calcAllClustering(gg, weights = NULL)
```

Arguments

| | |
|---------|---|
| gg | graph for analysis |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

Value

new graph object with all membership results stored as a vertex attribute.

See Also

calcClustering

Examples

```
g1 <- make_star(10, mode="undirected")
V(g1)$name <- letters[1:10]
g1<-calcAllClustering(g1)
clusteringSummary(g1)
```

| | |
|----------------|--|
| calcBridgeness | <i>Helper function that uses getBridgeness to calculate graph node bridgeness values for selected algorithm and consensus matrix and save them as a graph attribute BRIDGENESS.<alg> with <alg> replaced by the selected algorithm name.</i> |
|----------------|--|

Description

Helper function that uses [getBridgeness](#) to calculate graph node bridgeness values for selected algorithm and consensus matrix and save them as a graph attribute BRIDGENESS.<alg> with <alg> replaced by the selected algorithm name.

Usage

```
calcBridgeness(gg, alg, conmat)
```

Arguments

| | |
|--------|---|
| gg | igraph object |
| alg | clustering algorithm |
| conmat | consensus matrix calculated with that algorithm |

Value

graph with additional attributes to store Bridgeness value

See Also

[getBridgeness](#)

Examples

```
library(BioNAR)
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
set.seed(100)
gg <- calcClustering(karate, 'louvain')
cnmat <- makeConsensusMatrix(gg, N=10, alg = 'louvain', type = 2, mask = 10)
gg<-calcBridgeness(gg, alg = 'louvain', cnmat)
hist(V(gg)$BRIDGENESS.louvain)
```

calcCentrality

*Calculate the vertex centrality measures***Description**

Calculate the vertex centrality measures (degree, betweenness, closeness, semi-local, etc....) for each graph vertex and store each result as new vertex attribute in the graph.

Usage

```
calcCentrality(gg, weights = NULL)
```

Arguments

| | |
|---------|--|
| gg | igraph object |
| weights | Possibly a numeric vector giving edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). |

Details

A wrapper function that first calls [getCentralityMatrix](#), to calculate all vertex centrality measures, and then [applsMatrixToGraph](#) to store each centrality result as a new vertex attribute in the graph. The use of weights explained in details in [getCentralityMatrix](#).

Value

modified igraph object

See Also

[getCentralityMatrix\(\)](#)

Examples

```
data(karate,package='igraphdata')
ggm<-calcCentrality(karate)
V(ggm)$DEG
```

`calcCentralityExternalDistances`

Function to calculate a distance matrix between a list of permuted vertex centrality matrices and a unperturbed reference matrix.

Description

Function to calculate a distance matrix between a list of permuted vertex centrality matrices and a unperturbed reference matrix.

Usage

```
calcCentralityExternalDistances(m, l, keepOrder = FALSE, dist = "euclidean")
```

Arguments

| | |
|------------------------|---|
| <code>m</code> | reference matrix, for example centrality obtained by invocation getCentralityMatrix |
| <code>l</code> | list of permuted matrix, for example centrality obtained by invocation getRandomGraphCentrality |
| <code>keepOrder</code> | if FALSE values will be sorted |
| <code>dist</code> | methods available from dist function |

Value

matrix with seven columns containing distances between each element of `l` and reference matrix `m`

See Also

[getRandomGraphCentrality](#)
[getCentralityMatrix](#)
[calcCentralityInternalDistances](#)

Examples

```
data(karate, package='igraphdata')
m<-getCentralityMatrix(karate)
gnp<-list()
for(i in 1:10){
  gnp[[i]]<-getRandomGraphCentrality(karate, type = 'gnp')
}
gnpEDist<-calcCentralityExternalDistances(m,gnp)
summary(gnpEDist)
```

calcCentralityInternalDistances

Function calculates a set of distance metrics between each vertex pair given a list of vertex centrality matrices

Description

Function calculates a set of distance metrics between each vertex pair given a list of vertex centrality matrices

Usage

```
calcCentralityInternalDistances(l, keepOrder = FALSE, dist = "euclidean")
```

Arguments

| | |
|------------------------|--|
| <code>l</code> | list of matrices, for example centrality obtained by invocation getRandomGraphCentrality |
| <code>keepOrder</code> | if FALSE values will be sorted before distance calculations |
| <code>dist</code> | methods available from dist function |

Value

matrix with seven columns containing distances between all pairs of `l` elements.

See Also

[getRandomGraphCentrality](#)
[getCentralityMatrix](#)
[calcCentralityExternalDistances](#)

Examples

```
data(karate, package='igraphdata')
m<-getCentralityMatrix(karate)
gnp<-list()
for(i in 1:10){
  gnp[[i]]<-getRandomGraphCentrality(karate, type = 'gnp')
}
gnpIDist<-calcCentralityInternalDistances(gnp)
summary(gnpIDist)
```

| | |
|----------------|--|
| calcClustering | <i>Calculate community membership for given clustering algorithm and store the results as new vertex attributes in the graph..</i> |
|----------------|--|

Description

When applying resampling the clustering results of a clustering algorithm applied to a graph can differ due to the stochastic nature of the resampling algorithm. To allow reproducible downstream analysis clustering results are stored as vertex attributes in the graph. This function call [getClustering](#) and stores community membership as new vertex attribute in the graph, and Modularity as a new graph attribute prefix with the alg name.

Usage

```
calcClustering(gg, alg, weights = NULL)
```

Arguments

| | |
|---------|---|
| gg | igraph object to cluster |
| alg | algorithm to apply |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

Details

NOTE: [getClustering](#) verifies algorithm names with [match.arg](#) so correct membership will be calculated, but name of the attribute is taken from alg argument, so it is possible that vertex attribute name won't exactly match name of the algorithm from `link{getClustering}`.

Value

modified igraph object with calculated membership stored as a vertex attribute and modularity as a graph attribute

See Also

[getClustering](#)

Examples

```
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
g<-calcClustering(karate, 'louvain')
vertex_attr_names(g)
graph_attr(g, 'louvain')
```

| | |
|------------------|---|
| calcDiseasePairs | <i>Calculate each disease-disease pair overlap given a list of disease terms.</i> |
|------------------|---|

Description

Calculate each disease-disease pair overlap (or separation) on a given PPI network model, based on analysis described in Menche et al. 2015

Usage

```
calcDiseasePairs(
  gg,
  name,
  diseases = NULL,
  permute = c("none", "random", "binned")
)
```

Arguments

| | |
|----------|--|
| gg | interactome network as igraph object |
| name | name of the attribute that stores disease annotation |
| diseases | list of diseases to match |
| permute | type of permutations. none – no permutation is applied, random – annotation is randomly shuffled, binned – annotation is shuffled in a way to preserve node degree-annotation relationship by degreeBinnedGDAs . |

Value

list with three matrices:

- disease_separation – Ndisease X Ndisease matrix of separations
- gene_disease_separation – Ngenes X Ndisease+2 matrix of gene-disease separation
- disease_localisation – matrix with diseases in rows and number of genes (N), average and standard deviation of gene-disease separation in columns

References

Menche, J. et al. Uncovering disease-disease relationships through the incomplete interactome. Science, 347, (6224):1257601 (2015).

See Also

degreeBinnedGDAs
sampleDegBinnedGDA

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
p <- calcDiseasePairs(
  agg,
  name = "TopOntoOVGHDOID",
  diseases = c("DOID:10652", "DOID:3312", "DOID:12849"),
  permute = "n"
)
p$disease_separation
```

| | |
|-------------|---|
| calcEntropy | <i>Calculate the graph entropy for each perturbed vertex, and save the results as new vertex attributes in the graph.</i> |
|-------------|---|

Description

This function calculate the graph entropy for each perturbed vertex by calling [getEntropy](#), and save the results as new vertex attributes SR_UP and SR_DOWN in the graph.

Usage

```
calcEntropy(gg, maxSr = NULL, exVal = NULL)
```

Arguments

| | |
|-------|--|
| gg | igraph object |
| maxSr | the maximum entropy rate <i>maxSR</i> , if NULL getEntropyRate will be called. |
| exVal | expression values boundaries. Two columns are expected: xx and lambda. If NULL default values c(2,14) and c(-14,14) will be used for xx and lambda respectively. |

Details

According to Teschendorf et al., 2010, network entropy measure quantifies the degree of randomness in the local pattern information flux around single genes. For instance, in metastatic cancer this measure was found significantly higher than in non-metastatic and helped to identify genes and entire pathways involved on metastasis. However, for the assessment of scale-free structure we do not actually require gene expression data as it based solely on the network topology.

Value

graph with SR_UP and SR_DOWN vertex attributes storing the graph entropy values with over- or under-expressing each vertex.

See Also

[getEntropy\(\)](#)

Other Entropy Functions: [getEntropy\(\)](#), [getEntropyRate\(\)](#), [plotEntropy\(\)](#)

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
gg<-annotateGeneNames(gg)
gg<- calcEntropy(gg)
```

calcMembership

Calculate cluster memberships for the graph.

Description

Calculates the clustering membership for each of the 10 clustering algorithms defined in function [getClustering](#)

Usage

```
calcMembership(
  gg,
  alg = c("lec", "wt", "fc", "infomap", "louvain", "sgG1", "sgG2", "sgG5", "spectral"),
  weights = NULL
)
```

Arguments

| | |
|---------|---|
| gg | igraph object to cluster |
| alg | algorithm name |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a ‘weight’ edge attribute, then that attribute will be used. If it is NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph has a ‘weight’ edge attribute, but you don’t want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

Value

data.frame with columns names and membership

See Also

getClustering

Examples

```
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
m<-calcMembership(karate, 'lec')
head(m)
```

calcReclusterMatrix *Hierarchical graph clustering*

Description

This function takes in a gg and initial vertex community membership values mem as returned by calcMembership, and then performs a reclustering of the graph given the clustering algorithm alg to those clusters of size greater than CnMAX

Usage

```
calcReclusterMatrix(
  gg,
  mem,
  alg,
  CnMAX = 10,
  weights = NULL,
  keepSplit = FALSE
)
```

Arguments

| | |
|---------|---|
| gg | graph to cluster |
| mem | data.frame with previous level clustering results |
| alg | algorithm to apply |
| CnMAX | maximus size of the cluster in mem that will not be processed |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a ‘weight’ edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a ‘weight’ edge attribute, but you don’t want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

keepSplit logical, wether to keep previous membership in the output matrix

Value

remembership matrix, that contains vertex ID membership and result of reclustering

Examples

```
data(karate,package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate,alg = alg)
remem<-calcReclusterMatrix(karate,mem,alg,10)
```

| | |
|---------------|--|
| calcSparsness | <i>Calculate sparsness of the graph.</i> |
|---------------|--|

Description

For a simple unweighted, undirected graph $G(N,E)$. Network sparseness is defined as the ratio of the actual number of graph edges (E) to the maximum number of edges possible in a graph with same number of vertices (N): $E/\text{binom}(N,2)$

Usage

```
calcSparsness(gg)
```

Arguments

gg graph to evaluate

Value

sparsness value

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
calcSparsness(gg)
```

| | |
|-------------------|--|
| clusteringSummary | <i>Matrix of cluster characteristics</i> |
|-------------------|--|

Description

Function to calculate basic summary statistics after apply clustering algorithm:

- N – number of vertices in the graph `vcount`
- mod – clustering modularity `modularity`, the ratio of edges found within communities to the number of edges found between communities, relative to a randomised model
- C – number of clusters
- Cn1 – number of singletons (clusters of size 1)
- Cn100 – number of clusters containing more than 100 nodes
- mu – the ratio of edges found within communities to the number of edges found between communities
- Min. C – minimum of the cluster size
- 1st Qu. C – first quartile of the cluster size
- Median C – median of the cluster size
- Mean C – average cluster size
- 3rd Qu. C – third quartile of the cluster size
- Max. C – maximum of the cluster size

Usage

```
clusteringSummary(  
  gg,  
  att = c("lec", "wt", "fc", "infomap", "louvain", "sgG1", "sgG2", "sgG5", "spectral")  
)
```

Arguments

| | |
|------------------|---|
| <code>gg</code> | graph to analyse |
| <code>att</code> | vector of attribute names that contains membership data |

Value

matrix of clustering characteristics

Examples

```
data(karate, package='igraphdata')  
g<-calcAllClustering(karate)  
clusteringSummary(g)
```

clusterORA

*Calculate annotation enrichment for clusters in the graph***Description**

Calculate the cluster enrichment of a graph given a clustering algorithm *alg* and vertex annotation attribute 'name'. Function generates an enrichment table, one row for each cluster, containing: size of the cluster (C_n), number of annotated vertices in the graph F_n (F_n), number of annotated vertices in the cluster μ (μ), odds ratio (OR) and its 95% Confidence interval [CI_l , CI_u] (CI_l and CI_u), two fold enrichment values F_e (F_e) and F_c (F_c). We also provide the list of vertices from the cluster that contribute to the annotation term, p.value of enrichment (*pval*) and depletion (*palt*) using the Hypergeometric test, adjusted p.values using Benjamini and Yekutieli correction (BY).

Usage

```
clusterORA(g, alg, name, vid = "name", alpha = 1, col = COLLAPSE)
```

Arguments

| | |
|--------------|---|
| <i>g</i> | graph to get annotation from |
| <i>alg</i> | cluster algorithm and membership attribute name |
| <i>name</i> | annotation attribute name |
| <i>vid</i> | attribute to be used as a vertex ID |
| <i>alpha</i> | probability threshold |
| <i>col</i> | list separation character in attribute, by default is ; |

Details

Given the enrichment results, we can calculate the log of the Odds Ratio (OR) as:

$$\ln(OR) = \ln\left(\frac{\mu(N - F_n + \mu - C_n)}{(C_n - \mu)(F_n - \mu)}\right)$$

and it's upper and lower 95% Confidence Interval:

$$CI(\ln(OR)) = \ln(OR) \pm 1.96 \sqrt{\frac{1}{\mu} + \frac{1}{C_n - \mu} + \frac{1}{F_n - \mu} + \frac{1}{N - F_n + \mu - C_n}}$$

Using the odds ratio allows us to distinguish functionally enriched communities relative to functionally depleted communities.

Two types of fold enrichment values calculated as follow:

$$F_e = \frac{\left(\frac{\mu}{F_n}\right)}{\left(\frac{C_n}{N}\right)}$$

$$F_c = \frac{\left(\frac{\mu}{C_n}\right)}{\left(\frac{C_n}{N}\right)}$$

Value

A table with overrepresentation results. Each row corresponds to a tested annotation in particular cluster. The columns are the following:

- alg – name of the clustering algorithm;
- cl – cluster ID;
- Fl – name of the enriched term;
- N – number vertices in the network;
- Fn – number of vertices in the graph annotated by term Fl (F_n);
- Cu – size of the cluster;
- Mu – number of vertices in the cluster annotated by term Fl (μ);
- OR – odds ratio ;
- CIl – odds ratio 95% confidence interval lower bound (CI_l);
- CIu – odds ratio 95% confidence interval upper bound(CI_u);
- Fe – fold enrichment F_e ;
- Fc – fold enrichment F_c ;
- pval – an enrichment p-value from hypergeometric test;
- padj – a BY-adjusted p-value;
- palt – an depletion p-value from hypergeometric test;
- paltadj – a BY-adjusted depletion p-value;
- overlapGenes – vector with overlapping genes.

Examples

```
options("show.error.messages"=TRUE)
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
g <- igraph::read_graph(file, format="gml")
anL<-getAnnotationVertexList(g, 'TopOntoOVGHDOID')
res<-clusterORA(g, alg='louvain', name='TopOntoOVGHDOID', vid='name')
andf<-unique(data.frame(ID=vertex_attr(g, 'TopOntoOVGHDOID'),
Term=vertex_attr(g, 'TopOntoOVG')))
rr<-merge(andf, res, by.y='FL', by.x='ID')
rr[order(rr$cl), ]
```

degreeBinnedGDAs

Prepare mapping for degree-aware annotation shuffling.

Description

Function to randomly shuffle vertex annotation terms, whilst preserving the vertex degree originally found with that annotation term.

Usage

```
degreeBinnedGDAs(gg, GDA, dtype)
```

Arguments

| | |
|-------|---|
| gg | graph to analyse |
| GDA | vertex annotations returned by prepareGDA |
| dtype | list of unique annotation terms to analyze |

Value

mapping matrix between vertices, vertex-degree groups and annotation terms.

See Also

- [prepareGDA](#)
- [getAnnotationList](#)
- [sampleDegBinnedGDA](#)

Examples

```
options("show.error.messages"=TRUE)
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
gda<-prepareGDA(agg, 'TopOntoOVGHDOID')
m<-degreeBinnedGDAs(agg, gda, getAnnotationList(gda))
c(dim(m), vcount(agg), length(getAnnotationList(gda)))
head(m)
```

| | |
|-----------|-------------------------------------|
| diseasome | <i>Barabasi's Diseasome Network</i> |
|-----------|-------------------------------------|

Description

In the paper Goh.t al. (2007) doi:10.1073/pnas.0701361104 Barabasi with colleagues published Diseasome: a network of disorders and disease genes linked by known disorder–gene associations. We extract definition of the genes, disorders and interactions from papers supplementary materials and store it as [graph](#) object.

Usage

```
diseasome
```

Format

A bipartite graph as `graph` object.

Vertex attributes: 'name' for the node ID, 'Name' for the human readable node name, 'Disorder.class', 'Type' for the human readable node type, 'label' and 'shape' for plotting the graph, 'type' the node type for bipartite `graph` representation.

Details

Diseasome is a bipartite graph that have nodes of two types gene and disease and links are allowed only between nodes of different types. It could be projected to Human Disease Network (HDN) and Disease Gene Network (DGN).

Source

Goh, K.-I. et al. The human disease network. Proc. Natl. Acad. Sci. U.S.A. 104, 8685–8690 (2007). <https://pnas.org/doi/full/10.1073/pnas.0701361104>

| | |
|------------------|--|
| escapeAnnotation | <i>Escapes elements of list in annotation.</i> |
|------------------|--|

Description

In situations when a given list of annotation ID terms may not be well formatted, and therefore not be interoperated as unique. For example, given a list of HDO IDs: HDO:14, HDO:143, HDO:1433, and HDO:14330, a grep for the term HDO:14 could return: HDO:143, HDO:1433, HDO:14330. To avoid this all terms should be enclosed in escape characters, which unlikely to find within annotation itself.

Usage

```
escapeAnnotation(annVec, col = COLLAPSE, esc = ESC)
```

Arguments

| | |
|--------|-------------------------------|
| annVec | vector of annotation strings |
| col | term list separator character |
| esc | escape character |

Details

NOTE: spaces are treated as regular characters, no trimming is applied before or after escaping.

Value

vector of annotation strings with elements escaped

See Also

unescapeAnnotation

Examples

```
annVec<-apply(matrix(letters, ncol=13), 2, paste, collapse=';')
cbind(annVec, escapeAnnotation(annVec, ';', '|'))
```

evalCentralitySignificance

Compare distance distributions of internal and external distances

Description

Function to compare two distance distributions using the Kolmogorov-Smirnov test. Where the first distance distribution is generated internally and calculates the distance between random graph centralities. The second distance distribution is generated externally, and measures the distance between random and the original graph centralities.

Usage

```
evalCentralitySignificance(dmi, dme)
```

Arguments

| | |
|-----|---|
| dmi | distribution of internal distances between random graph centralities |
| dme | distribution of external distances between random and original graph centralities |

Value

list of lists for each centrality value in the input matrix three element list is created where ks contains Kolmogorov-Smirnov test result from class ks.test; pval contains Kolmogorov-Smirnov test pvalue; and dt contains input distribution.

See Also

ks.test

Examples

```
data(karate, package='igraphdata')
m<-getCentralityMatrix(karate)
gnp<-list()
for(i in 1:10){
  gnp[[i]]<-getRandomGraphCentrality(karate, type = 'gnp')
}
gnpIDist<-calcCentralityInternalDistances(gnp)
gnpEDist<-calcCentralityExternalDistances(m, gnp)
```



```
simSig<-evalCentralitySignificance(gnpIDist,gnpEDist)
sapply(simSig,function(.x).x$ks$p.value)
```

findLCC

Find Largest Connected Component of the graph

Description

Find Largest Connected Component of the graph

Usage

```
findLCC(GG)
```

Arguments

GG igraph object to analyze

Value

igraph representation LCC

Examples

```
g1 <- make_star(10, mode="undirected") %du% make_ring(7) %du% make_ring(5)
lcc<-findLCC(g1)
summary(lcc)
```

fitDegree

Fit Power Law to degree distribution.

Description

Fit a Powerlaw distribution to graph's degree distribution using the R "PoweRlaw" package (version 0.50.0) (Gillespie, 2015)

Usage

```
fitDegree(
  DEG,
  Nsim = 100,
  plot = FALSE,
  DATAleg = "Fit power-law",
  threads = 4,
  WIDTH = 480,
  HEIGHT = 480,
  legpos = "bottomleft",
  showErr = TRUE
)
```

Arguments

| | |
|---------|---|
| DEG | degree distribution |
| Nsim | number of bootstrap iterations |
| plot | logical, do you want plot to be drawn |
| DATAleg | legend string for degree data |
| threads | number of parallel computational threads |
| WIDTH | width of the plot in ptx |
| HEIGHT | height of the plot in ptx |
| legpos | position of the legend @seealsolegend |
| showErr | logical, do you want error on the plot legend |

Value

an object of class `law-class` with results of fitting

Examples

```
##No: of bootstrap iterations use nsim > 100 for reliable result
nsim <- 10

##Legend Titles
Legend <- "Presynaptic PPI"

file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
pFit <- fitDegree( as.vector(igraph::degree(graph=gg)),
  DATAleg=Legend, threads=1, Nsim=nsim)
```

fitSigmoid*Fit Fold-enrichment distribution to sigmoid function*

Description

This function calculates fit of the Fold-Enrichment distribution to the sigmoid function with the levels of noise specified in SDV for all clustering algorithms, which have non-zero SUM3\$`Psig&ORsig` in the enrichment table summary results. The function returns the list in which each element contains result for one of the noise level.

Usage

```
fitSigmoid(stat, SDv = c(0, 0.05, 0.1, 0.5))
```

Arguments

| | |
|------|---|
| stat | enrichment results obtained from summaryStats |
| SDv | vector of noise SD values |

Details

Results are repersented as a list with five elements:

- gridplot that allow comparison of fitting for different clustering algorithms;
- plots the list of individual plots from gridplot;
- fitInfo the data.frame that contains results of fitting, such as message, number of iterations and exit code;
- parInfo values and standard deviations for all sigmoid parameters;
- ks table of Kolmogorov-Smirnov test p-values.

Grid plot is designed in a way to be viewed in the device at least 12 inches in width and 12 inches in height.

Value

list of fitted functions tables and plots

See Also

[summaryStats\(\)](#)

| | |
|--------------------|---|
| flatfile.go.BP.csv | <i>Annotation from Gene Ontology Biological Process (GO_BP)</i> |
|--------------------|---|

Description

Annotation, downloaded from Gene Ontology for Biological Process domain. The table has columns: the first containing gene functional group ID terms, the second gene functional group description terms, the third - Human gene Entrez IDs; in csv format

See Also

[annotateGoBP](#)

| | |
|--------------------|---|
| flatfile.go.CC.csv | <i>Annotation from Gene Ontology Cellular Compartment (GO_CC)</i> |
|--------------------|---|

Description

Annotation, downloaded from Gene Ontology for Cellular Compartment domain. The table has columns: the first containing gene functional group ID terms, the second gene functional group description terms, the third - Human gene Entrez IDs; in csv format

See Also

[annotateGoCC](#)

| | |
|--------------------|---|
| flatfile.go.MF.csv | <i>Annotation from Gene Ontology Molecular Function (GO_MF)</i> |
|--------------------|---|

Description

Annotation, downloaded from Gene Ontology for Molecular Function domain. The table has columns: the first containing gene functional group ID terms, the second gene functional group description terms, the third - Human gene Entrez IDs; in csv format

See Also

[annotateGoMF](#)

`flatfile_human_gene2HDO.csv`*Human Gene Disease Associations (GDA)*

Description

Annotation derived from Human Disease Ontology database (HDO). The table contains three columns; the first containing gene Entrez IDs, the second gene Human Disease Ontology (HDO) ID terms, the third gene HDO description terms; in csv format

See Also[annotateTopOnto0VG](#)

`getAnnotationList`*Extract unique values from annotations.*

Description

It is not uncommon to find both duplicated vertex annotation terms, and vertices annotated with multiple terms, in a given annotation list. This function creates a vector of unique annotation terms for each vertex given an input annotation list.

Usage

```
getAnnotationList(  
  annVec,  
  col = COLLAPSE,  
  sort = c("none", "string", "frequency")  
)
```

Arguments

| | |
|---------------------|------------------------------|
| <code>annVec</code> | vector of annotation strings |
| <code>col</code> | list separator character |
| <code>sort</code> | how to sort the result list |

Value

vector of unique annotation terms

See Also[getAnnotationVertexList](#)

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
annVec<-V(gg)$TopOntoOVG
al<-getAnnotationList(annVec)
al
```

getAnnotationVertexList

Return vertex list for each term in annotation attribute

Description

For different purposes annotation of graph vertices could be represented in three forms:

Pairs dataframe with vertex ID and annotation terms

Vertex Annotation list named with vertex ID and containing terms annotating each vertex

Annotation Vertices list named with term and containing vertex IDs

Usage

```
getAnnotationVertexList(g, name, vid = "name", col = COLLAPSE)
```

Arguments

| | |
|------|---|
| g | graph to get annotation from |
| name | annotation attribute name |
| vid | attribute to be used as a vertex ID |
| col | list separation character in attribute, by default is ; |

Details

This function takes Vertex Annotation from vertex attribute and convert it to Annotation Vertices form.

Value

named list with annotation in Annotation Vertices form

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
avl<-getAnnotationVertexList(gg, 'TopOntoOVGHDOID')
head(avl)
```

| | |
|---------------|---|
| getBridgeness | <i>Calculate bridginess from consensus matrix</i> |
|---------------|---|

Description

Bridginess takes into account a vertices shared community membership together with its local neighbourhood. It was proposed in Nepusz et al., 2008 [doi:10.1103/PhysRevE.77.016107](https://doi.org/10.1103/PhysRevE.77.016107).

Usage

```
getBridgeness(gg, alg, conmat)
```

Arguments

| | |
|--------|---|
| gg | igraph object |
| alg | clustering algorithm |
| conmat | consensus matrix calculated with that algorithm |

Details

Function assumes clustering already been performed by the clustering algorithm, and its membership values stored in vertex attributes. If clustering algorithm vertex `alg` attribute is not found an error will be issued.

Value

data.frame with first column contains vertex ID, if `GeneName` attribute assigned to the vertices its value will be stored as a second column, the last column contains bridginess values for the

Examples

```
library(BioNAR)
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
gg <- calcClustering(karate, 'louvain')
cnmat <- makeConsensusMatrix(gg, N=10, alg = 'louvain', type = 2, mask = 10)
br<-getBridgeness(gg, alg = 'louvain', cnmat)
```

getCentralityMatrix *Calculate centrality measures for graph nodes.*

Description

Calculate centrality measures for graph nodes.

Usage

```
getCentralityMatrix(gg, weights = NULL)
```

Arguments

| | |
|---------|--|
| gg | igraph object |
| weights | Possibly a numeric vector giving edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). |

Details

The edge attribute weights treated differently by different functions calculating centrality measures. For example, [betweenness](#) use weights as an edge length, while in [page_rank](#) "an edge with a larger weight is more likely to be selected by the surfer", which infer the opposite meaning. Taking into account that all methods in [getClustering](#) treat edge weights in the same way as [page_rank](#), we calculate the distance=1/weights as edge weights for BET, dBET, mnSP, and sdSP values. So we treat weights in the package consistently as the strength and closiness of vertices, rather the distance between them.

Value

data.frame with following columns:

- ID - vertex ID
- DEG - degree
- iDEG - in-degree (directed graph only)
- oDEG - out-degree (directed graph only)
- BET - betweenness for undirected graph
- dBET - betweenness when directionality is taken into account (directed graph only)
- CC - clustering coefficient
- SL - semilocal centrality
- mnSP - mean shortest path
- PR - page rank for undirected graph
- dPR - page rank when directionality is taken into account (directed graph only)
- sdSP - standard deviation of the shortest path

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
m<-getCentralityMatrix(gg)
```

getClustering

Get clustering results for the graph.

Description

Wrapper function for calculation of clustering for predefined set of ten algorithms:

- lec – leading eigenvector community (version of [cluster_leading_eigen](#)), directed graph will be converted to undirected by [as.undirected](#) with mode collapse;
- wt – walktrap community [cluster_walktrap](#);
- fc – fastgreedy community [cluster_fast_greedy](#), directed graph will be converted to undirected by [as.undirected](#) with mode collapse;
- infomap – infomap community [cluster_infomap](#);
- louvain – cluster_louvain [cluster_louvain](#), directed graph will be converted to undirected by [as.undirected](#) with mode collapse;
- sgG1 – spin-glass model and simulated annealing clustering (version of [cluster_spinglass](#) with spins=500 and gamma=1);
- sgG2 – spin-glass model and simulated annealing clustering (version of [cluster_spinglass](#) with spins=500 and gamma=2);
- sgG5 – spin-glass model and simulated annealing clustering (version of [cluster_spinglass](#) with spins=500 and gamma=7);
- spectral – spectral modularity clustering [spectral_igraph_communities](#);

Usage

```
getClustering(
  gg,
  alg = c("lec", "wt", "fc", "infomap", "louvain", "sgG1", "sgG2", "sgG5", "spectral"),
  weights = NULL
)
```

Arguments

| | |
|-----|---------------------------|
| gg | igraph object to cluster |
| alg | clustering algorithm name |

weights The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering.

Details

graph suppose to be undirected. If algorithm failed warning will be issued and function returned NULL.

Algorithm names are verified with match.arg.

Value

[communities](#) object or NULL if algorithm failed.

Examples

```
data(karate,package='igraphdata')
c<-getClustering(karate,'lec')
c$modularity
```

getClusterSubgraphByID

Return induced subgraph for cluster

Description

Function reads in a graph gg, vertex cluster membership vector mem, and returns an induced subgraph given a cluster membership number 'clID'.

Usage

```
getClusterSubgraphByID(clID, gg, mem)
```

Arguments

| | |
|------|------------------------|
| clID | cluster ID to extracte |
| gg | graph to analyze |
| mem | membership vector |

Value

induced subgraph as igraph object

Examples

```
data(karate, package='igraphdata')
alg<-'louvain'
c<-getClustering(karate, alg = alg)
gc3<-getClusterSubgraphByID(3, karate, membership(c))
#plot(gc3, vertex.label=V(gc3)$name)
```

| | |
|-------------------|---|
| getCommunityGraph | Create new graph with communities as a nodes. |
|-------------------|---|

Description

The idea based upon [this StackOverflow answer](#)

Usage

```
getCommunityGraph(gg, membership)
```

Arguments

| | |
|------------|----------------------------------|
| gg | graph to convert |
| membership | participation list for new graph |

Value

community graph

Examples

```
data(karate, package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate, alg = alg)
cg<-getCommunityGraph(karate, mem$membership)
```

| | |
|-------------|---------------------|
| getDiseases | Get HDO disease IDs |
|-------------|---------------------|

Description

Return vector of HDO disease IDs for synaptic PPI analysis.

Usage

```
getDiseases()
```

Value

vector of disease IDs of interest

See Also

getDType

Examples

```
getDiseases()
```

getDType

Get DiseaseTypes

Description

Return vector of disease abbreviations for synaptic PPI analysis.

Usage

```
getDType()
```

Value

vector of disease abbreviations for synaptic PPI analysis.

See Also

getDiseases

Examples

```
getDType()
```

| | |
|-----------|---|
| getDYNAMO | <i>Calculate DYNAMO sensitivity matrix.</i> |
|-----------|---|

Description

This function calculates sensitivity matrix that represents perturbation patterns defined by topology and edge weights of the network. If weights are signed value sensitivity matrix is able to reproduce not only activation but inhibition relationships in the network.

Usage

```
getDYNAMO(g, attr = NULL, vid = "name", alpha = 0.9)
```

Arguments

| | |
|--------------------|--|
| <code>g</code> | igraph object |
| <code>attr</code> | NULL or the name of edge attribute containing numerical weight values |
| <code>vid</code> | name of the vertex attribute to be used as row and column names |
| <code>alpha</code> | parameter characterizing the propagation strength, default value 0.9 taken from Santolini paper. |

Details

Algorithm proposed in:

Santolini,M. and Barabasi,A.-L. (2018) Predicting perturbation patterns from the topology of biological networks. Proc Natl Acad Sci USA, 169, 201720589.

Value

sparse sensitivity matrix defined by the network topology and edge values

Examples

```
data(karate, package='igraphdata')
upgrade_graph(karate)
d<-getDYNAMO(karate,attr='weight')
df<-metlMatrix(d)
head(df)
```

| | |
|------------|--|
| getEntropy | <i>Calculates vertex perturbation graph entropy.</i> |
|------------|--|

Description

According to Teschendorf et al., 2010, network entropy measure quantifies the degree of randomness in the local pattern information flux around single genes. For instance, in metastatic cancer this measure was found significantly higher than in non-metastatic and helped to identify genes and entire pathways involved on metastasis. However, for the assessment of scale-free structure we do not actually require gene expression data as it based solely on the network topology.

Usage

```
getEntropy(gg, maxSr = NULL, exVal = NULL)
```

Arguments

| | |
|-------|--|
| gg | igraph object |
| maxSr | the maximum entropy rate <i>maxSR</i> , if NULL getEntropyRate will be called. |
| exVal | expression values boundaries. Two columns are expected: xx and lambda. If NULL default values c(2, 14) and c(-14, 14) will be used for xx and lambda respectively. |

Details

In this function, following procedure described in (Teschendorff et al., 2015), all vertexes are artificially assigned a uniform weight then sequentially perturbed with the global entropy rate (SR) after each protein's perturbation being calculated and plotted against the log of the protein's degree. In case of scale-free or approximate scale-free topologies, we see a clear bi-modal response between over-weighted vertices and their degree and an opposing bi-phasic response in under-weighted vertices and their degrees.

Value

matrix containing for each Gene:

- Entrez ID,
- Name,
- Degree,
- UP – Graph Entropy values when gene is expressed up,
- DOWN – Graph Entropy values when gene is expressed down.

Note

Entropy is calculated with respect to GeneName property, if there is no such vertex attribute in the graph vertex name will be copied to the GeneName attribute. If any NA is found in GeneNames error will be thrown.

See Also

Other Entropy Functions: [calcEntropy\(\)](#), [getEntropyRate\(\)](#), [plotEntropy\(\)](#)

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
gg<-annotateGeneNames(gg)
any(is.na(V(gg)$GeneName))
# due to error in org.Hs.eg.db we have to manually annotate one node
idx <- which(V(gg)$name == '80273')
V(gg)$GeneName[idx]<-'GRPEL1'
e<- getEntropy(gg)
```

getEntropyRate

Calculate the maximum entropy rate and initial entropy rate .

Description

This function calculates the maximum entropy rate $maxSR$ (maxSr) and initial entropy rate SR_0 (SRo) given a connected network.

Usage

```
getEntropyRate(gg)
```

Arguments

gg igraph object

Details

The maximum entropy rate being calculated from the network's adjacency matrix:

$$maxSR = \sum_{i,j} p_{ij} = \frac{A_{ij}\nu_j}{\lambda\nu_i}$$

where ν and λ are the leading eigenvector and eigenvalue of the network adjacency matrix A respectively.

The initial configuration occurs when the entropy for each node is maximal. This can be calculated by setting the expression value for each gene/node in the network to be the same, and thus the maximal node entropy is dependent only on the node's degree k :

$$SR_0 = \frac{1}{N\bar{k}} \sum_j k_j \log k_i$$

where N here is the number of nodes and \bar{k} the average node degree found in the network.

Value

list with values of maxSr and SRO

See Also

Other Entropy Functions: [calcEntropy\(\)](#), [getEntropy\(\)](#), [plotEntropy\(\)](#)

Examples

```
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
ent <- getEntropyRate(karate)
```

getGNP

Generate random graph from reference

Description

Function generates random $G(n,p)$ Erdos-Renyi graph ([sample_gnp](#)) with the same number of vertices and edges as in in the reference graph gg.

Usage

```
getGNP(gg, ...)
```

Arguments

| | |
|-----|---|
| gg | reference graph |
| ... | additional arguments to be passed to sample_gnp |

Value

new instance of the random graph.

Examples

```
data(karate,package='igraphdata')
vcount(karate)
ecount(karate)
rg<- getGNP(karate)
vcount(rg)
ecount(rg)
```

getGraphCentralityECDF

Convert centrality matrix into ECDF

Description

Convert centrality matrix into ECDF

Usage

```
getGraphCentralityECDF(m)
```

Arguments

m centrality matrix from [getCentralityMatrix](#) invocation.

Value

list of several ecdf objects, corresponding to values in centrality matrix from [getCentralityMatrix](#) invocation.

See Also

[getCentralityMatrix](#)

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
m<-getCentralityMatrix(gg)
ecdfL<-getGraphCentralityECDF(m)
```

getIDs

Utility function to get vertex ids from vertex attributes The function obtain attribute values and check duplicates in it. It fails if any duplicate found.

Description

Utility function to get vertex ids from vertex attributes The function obtain attribute values and check duplicates in it. It fails if any duplicate found.

Usage

```
getIDs(gg, idatt)
```

Arguments

| | |
|--------------------|----------------|
| <code>gg</code> | graph |
| <code>idatt</code> | attribute name |

Value

`idatt` attribute values

| | |
|--------------------|---|
| <code>getPA</code> | <i>Generate random graph from reference</i> |
|--------------------|---|

Description

The function generates random Barabasi-Albert graph ([sample_pa](#)) with the same vertex number as in the reference graph `gg` and the power specified by parameter `pwr`. If `pwr` is missing, we are trying to estimate `pwr` from the reference graph `gg`.

Usage

```
getPA(gg, pwr, ...)
```

Arguments

| | |
|------------------|---|
| <code>gg</code> | reference graph |
| <code>pwr</code> | the power parameter for the sample_pa |
| <code>...</code> | additional parameters to be passed to the sample_pa |

Value

new instance of the random graph.

Examples

```
data(karate, package='igraphdata')
vcount(karate)
ecount(karate)
rg<- getPA(karate, pwr=1.25)
vcount(rg)
ecount(rg)
```

getRandomGraphCentrality

Centrality measures for random graphs induced by input one

Description

Generate a random graph that mimics the properties of the input graph and calls [getCentralityMatrix](#) to calculate all available vertex centrality measures. There are four different types of random graph to generate

Usage

```
getRandomGraphCentrality(
  gg,
  type = c("gnp", "pa", "cgnp", "rw"),
  power = NULL,
  weights = NULL,
  ...
)
```

Arguments

| | |
|---------|---|
| gg | template graph to mimic |
| type | type of random graph to generate: <ul style="list-style-type: none"> • gnp – $G(n,p)$ Erdos-Renyi model (sample_gnp) • pa – Barabasi-Albert model (sample_pa) • cgnp – new random graph from a given graph by randomly adding/removing edges (sample_correlated_gnp) • rw – new random graph from a given graph by rewiring 25% of edges preserving the degree distribution sample_gnp, sample_correlated_gnp, and sample_pa |
| power | optional argument of the power of the preferential attachment to be passed to sample_pa . If power is NULL the power of the preferential attachment will be estimated from fitDegree function. |
| weights | Possibly a numeric vector giving edge weights. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used (even if the graph has a weight attribute). |
| ... | other parameters passed to random graph generation functions |

Value

matrix of random graph vertices centrality measure.

See Also

[getCentralityMatrix\(\)](#) for explanation of the use of weights.

Examples

```
data(karate,package='igraphdata')
m<-getRandomGraphCentrality(karate,'pa',threads=1)
# to avoid repetitive costly computation of PowerLaw fit
# power parameter could be send explicitly:
pFit <- fitDegree( as.vector(igraph::degree(graph=karate)),
  Nsim=10, plot=FALSE,threads=1)
pwr <- slot(pFit,'alpha')
m<-getRandomGraphCentrality(karate,'pa',power=pwr)
lpa<-lapply(1:5,getRandomGraphCentrality,gg=karate,type='pa',
  power=pwr,weights = NULL)
```

getRobustness

Calculate cluster robustness from consensus matrix

Description

This function takes as argument a network (gg), the name of a clustering algorithm (alg) which can be found in the network, and a consensus matrix (conmat) generated from the clustering network. The function uses the consensus matrix to generate a measure of cluster robustness C_{rob} (Crob) for each cluster (C) using the R function [clrob](#). Briefly, this is done by summing elements of the consensus matrix that are found in the same cluster, and dividing this by the total number of entries in the matrix:

$$C_{rob} = \frac{2}{C_n(C_n - 1)} \sum_{\substack{i,j \in I_C \\ i \leq j}} conmat_{i,j}$$

where I_C – indices of vertices of the cluster C , C_n is the number of nodes found inside the cluster C .

Usage

```
getRobustness(gg, alg, conmat)
```

Arguments

| | |
|--------|----------------------|
| gg | igraph object |
| alg | clustering algorithm |
| conmat | consensus matrix |

Value

data.frame that for each cluster C shows

- its size C_n (Cn),
- robustness C_{rob} (Crob) and
- robustness scaled to range between 0 and 1 (CrobScaled).

See Also

Other Robustness functions: [makeConsensusMatrix\(\)](#)

Examples

```
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
alg<-'louvain'
gg<-calcClustering(karate, alg = alg)
conmat<-makeConsensusMatrix(gg, N=100, mask = 10, alg = alg, type = 2)
clob<-getRobustness(gg, alg = alg, conmat)
clob
```

gofs

Goodnes of fit KS test

Description

This is internal function and do not suppose to be called by user.

Usage

```
gofs(x, rate, model, sigma2 = NULL, countDATA = TRUE)
```

Arguments

| | |
|-----------|-----------------------------|
| x | steps along the Fe |
| rate | parameters of the sigmoid |
| model | fitted model |
| sigma2 | noise strength |
| countDATA | should points to be counted |

Value

list of [ks.test](#) values for each value in rate

| | |
|-----------|-------------------------------|
| law-class | <i>Result of PowerLaw fit</i> |
|-----------|-------------------------------|

Description

Result of PowerLaw fit

Slots

- fit [displ-class](#) result of power law fit.
- p numeric.
- alpha numeric degree of power-law.
- SDxmin numeric bootstrap sd of Xmin.
- SDalpha numeric bootstrap sd of alpha.

| | |
|-----------------|---|
| layoutByCluster | <i>Calculate layout based upon membership</i> |
|-----------------|---|

Description

Function to split graph into clusters and layout each cluster independently..

Usage

```
layoutByCluster(gg, mem, layout = layout_with_kk)
```

Arguments

- gg graph to layout
- mem membership data.frame from [calcMembership](#)
- layout algorithm to use for layout

Value

Layout in a form of 2D matrix.

See Also

[igraph::layout_](#)

Examples

```
data(karate,package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate,alg = alg)
lay<-layoutByCluster(karate,mem)
#plot(karate,layout=lay)
```

| | |
|-------------------|---|
| layoutByRecluster | <i>Calculate two-level layout from recluster matrix</i> |
|-------------------|---|

Description

Takes results of recluster and apply layoutByCluster to each

Usage

```
layoutByRecluster(gg, remem, layout = layout_with_kk)
```

Arguments

| | |
|--------|--|
| gg | graph to layout |
| remem | recluster result obtained by <code>calcReclusterMatrix</code> invocation |
| layout | one of the layout algorithms from <code>layout_</code> |

Value

Layout in a form of 2D matrix.

Examples

```
data(karate, package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate, alg = alg)
remem<-calcReclusterMatrix(karate, mem, alg, 10)
lay<-layoutByRecluster(karate, remem)
#plot(karate, layout=lay)
```

| | |
|---------------------|--|
| makeConsensusMatrix | <i>Function to make random resampling consensus matrix in memory</i> |
|---------------------|--|

Description

Function to make random resampling consensus matrix in memory

Usage

```
makeConsensusMatrix(
  gg,
  N = 500,
  mask = 20,
  alg,
  type,
  weights = NULL,
```

```

    reclust = FALSE,
    Cnmax = 10
  )

```

Arguments

| | |
|---------|---|
| gg | graph to perturb |
| N | number of perturbation steps |
| mask | percentage of elements to perturb |
| alg | clustering alg. |
| type | edges (1) or nodes (2) to mask |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |
| reclust | logical to decide whether to invoke reclustering via recluster |
| Cnmax | maximum size of the cluster in mem that will not be processed if reclustering is invoked |

Details

Function to assess the robustness of network clustering. A randomisation study is performed apply the same clustering algorithm to N perturbed networks, and which returns the consensus matrix where each vertex pair is assigned the probability of belong to the same cluster. The inputted network is perturbed by randomly removing a mask percentage of edges (type=1) or vertices (type=2) from the network before clustering.

Value

consensus matrix of Nvert X Nvert

See Also

Other Robustness functions: [getRobustness\(\)](#)

Examples

```

karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
alg<-'louvain'
gg<-calcClustering(karate, alg = alg)
conmat<-makeConsensusMatrix(gg, N=100, mask = 10, alg = alg, type = 2)
dim(conmat)

```

| | |
|------------|---|
| metlMatrix | <i>Convert sparse matrix into triplet data.frame.</i> |
|------------|---|

Description

For very large graphs handling adjacency-like matrices is difficult due to its sparse nature. This function convert sparse matrix into triplet data.frame with row and column indices and names, and cell value.

Usage

```
metlMatrix(sparseM)
```

Arguments

sparseM sparse matrix to convert into triplet data.frame

Value

data.frame with three columns:

- i – row index;
- j – column index;
- x – cell value;
- Rname – i-th row name;
- Cname – j-th column name.

Examples

```
data(karate, package='igraphdata')
upgrade_graph(karate)
Ws <- as_adjacency_matrix(karate,type='both',attr='weight',sparse = TRUE)
mdf<-metlMatrix(Ws)
head(mdf)
```

| | |
|----------------|--|
| normModularity | <i>Calculates the normalised network modularity value.</i> |
|----------------|--|

Description

Function to compare network Modularity of input network with networks of different size and connectivity.

Usage

```
normModularity(
  gg,
  alg = c("lec", "wt", "fc", "infomap", "louvain", "sgG1", "sgG2", "sgG5"),
  Nint = 1000,
  weights = NULL
)
```

Arguments

| | |
|----------------------|---|
| <code>gg</code> | graph object to analyze |
| <code>alg</code> | clustering algorithm |
| <code>Nint</code> | number of iterations |
| <code>weights</code> | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

Details

Used the normalised network modularity value Q_m based on the previous studies by Parter et al., 2007, Takemoto, 2012, Takemoto, 2013, Takemoto and Borjigin, 2011, which was defined as:

$$Q_m = \frac{Q_{real} - Q_{rand}}{Q_{max} - Q_{rand}}$$

Where Q_{real} is the network modularity of a real-world signalling network and, Q_{rand} is the average network modularity value obtained from 10,000 randomised networks constructed from its real-world network. Q_{max} was estimated as: $1 - 1/M$, where M is the number of modules in the real network.

Randomised networks were generated from a real-world network using the edge-rewiring algorithm (Maslov and Sneppen, 2002).

Value

normalized modularity value

References

Takemoto, K. & Kihara, K. Modular organization of cancer signaling networks is associated with patient survivability. *Biosystems* 113, 149–154 (2013).

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)

nm<-normModularity(gg, alg='louvain',Nint=10)
```

permute

*Randomly shuffle annotations***Description**

This function is a convinience wrapper to [sample](#) with replace= FALSE

Usage

```
permute(GNS, N)
```

Arguments

| | |
|-----|-----------------------------------|
| GNS | annotation list to take data from |
| N | size of the sample |

Value

random list of GNS values

Examples

```
permute(LETTERS, 15)
```

plotBridgeness

*Plot Bridgeness values***Description**

Semi-local centrality measure (Chen et al., 2011) lies between 0 and 1 indicating whether protein is important globally or locally. By plotting Bridgeness against semi-local centrality we can categorises the influence each protein found in our network has on the overall network structure:

- Region 1, proteins having a 'global' rather than 'local' influence in the network (also been called bottle-neck bridges, connector or kinless hubs ($0 < Sl < 0.5$; $0.5 < Br < 1$).
- Region 2, proteins having 'global' and 'local' influence ($0.5 < Sl < 1$, $0.5 < Br < 1$).
- Region 3, proteins centred within the community they belong to, but also communicating with a few other specific communities ($0 < Sl < 0.5$; $0.1 < Br < 0.5$).
- Region 4, proteins with 'local' impact , primarily within one or two communities (local or party hubs, $0.5 < Sl < 1$, $0 < Br < 0.5$).

Usage

```
plotBridgeness(
  gg,
  alg,
  VIPs,
  Xatt = "SL",
  Xlab = "Semilocal Centrality (SL)",
  Ylab = "Bridgeness (B)",
  bsize = 3,
  spsize = 7,
  MainDivSize = 0.8,
  xmin = 0,
  xmax = 1,
  ymin = 0,
  ymax = 1,
  baseColor = "royalblue2",
  SPColor = "royalblue2"
)
```

Arguments

| | |
|-------------|---|
| gg | igraph object with bridgeness values stored as attributes, after call to calcBridgeness |
| alg | clustering algorithm that was used to calculate bridgeness values |
| VIPs | list of 'specical' genes to be marked on the plot |
| Xatt | name of the attribute that stores values to be used as X-axis values. By default SL for semi-local centrality |
| Xlab | label for the X-axis |
| Ylab | label for the Y-axis |
| bsize | point size for genes |
| spsize | point size for 'specical' genes |
| MainDivSize | size of the line for the region separation lines |
| xmin | low limit for X-axis |
| xmax | upper limit for X-axis |
| ymin | low limit for Y-axis |
| ymax | upper limit for Y-axis |
| baseColor | basic color for genes |
| SPColor | colour highlighting any 'specical' genes |

Value

[ggplot](#) object with plot

Examples

```
karate <- make_graph("Zachary")
# We need vertex ID in the 'name' attribute of the vertex
V(karate)$name<-c(LETTERS,letters)[1:vcount(karate)]
set.seed(100)
gg <- calcClustering(karate, 'louvain')
gg <- calcCentrality(gg)
cnmat <- makeConsensusMatrix(gg, N=10, alg = 'louvain', type = 2, mask = 10)
gg<-calcBridgeness(gg, alg = 'louvain', cnmat)
plotBridgeness(gg,alg = 'louvain',VIPs=c("Mr Hi","John A"))
```

| | |
|-------------|--|
| plotEntropy | <i>Plot graph entropy values versus vertex degree for each perturbed vertex value.</i> |
|-------------|--|

Description

Following procedure described in (Teschendorff et al., 2015), all vertexes are artificially assigned a uniform weight then sequentially perturbed with the global entropy rate (SRprime) after each protein's perturbation being calculated by [getEntropy](#) function.

Usage

```
plotEntropy(SRprime, subTIT = "Entropy", SRo = NULL, maxSr = NULL)
```

Arguments

| | |
|---------|---|
| SRprime | results of getEntropy invocation |
| subTIT | entropy axis label |
| SRo | initial entropy rate SR_0 , results of getEntropyRate invocation |
| maxSr | the maximum entropy rate $maxSR$, results of getEntropyRate invocation |

Details

This function plot SRprime against the log of the protein's degree. In case of scale-free or approximate scale-free topologies, we see a clear bi-modal response between over-weighted vertices and their degree and an opposing bi-phasic response in under-weighted vertices and their degrees.

If maxSr or SRo is set to their default value NULL [getEntropyRate](#) will be called and returned values will be used in the following calculations. As maxSr is required for SRprime calculation by [getEntropy](#) using explicit values could save some time in the case of large network.

Value

ggplot2 object with diagram

See Also

[getEntropy\(\)](#)
Other Entropy Functions: [calcEntropy\(\)](#), [getEntropy\(\)](#), [getEntropyRate\(\)](#)

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.csv", package = "BioNAR")
tbl <- read.csv(file, sep="\t")
gg <- buildNetwork(tbl)
gg<-annotateGeneNames(gg)
ent <- getEntropyRate(gg)
SRprime <- getEntropy(gg, maxSr = NULL)
plotEntropy(SRprime, subTIT = "Entropy", SRo = ent$SRo, maxSr = ent$maxSr)
```

| | |
|-----------|--|
| plotRatio | <i>Plot fraction of enriched communities</i> |
|-----------|--|

Description

Plot fraction of enriched communities

Usage

```
plotRatio(
  x,
  desc = "",
  anno = "",
  LEGtextSize = 1.5,
  LEGlineSize = 4,
  type = NULL
)
```

Arguments

| | |
|-------------|-------------------------|
| x | enrichment statistics |
| desc | plot subtitle |
| anno | name of annotation used |
| LEGtextSize | size of the text |
| LEGlineSize | width of the line |
| type | type of the plot |

Value

ggplot object

| | |
|-------------|--|
| plotSigmoid | <i>Plot results of the sigmoid fit</i> |
|-------------|--|

Description

Plot results of the sigmoid fit

Usage

```
plotSigmoid(x, rates, model, alg = "", pv = 0)
```

Arguments

| | |
|-------|-----------------------------------|
| x | steps along the Fe |
| rates | parameters of the sigmoid |
| model | fitted model |
| alg | name of the clustering algorithm |
| pv | Kolmogorov-Smirnov test's p-value |

Value

[ggplot](#) object with sigmoid fit plot

| | |
|---------------------|--|
| PPI_Presynaptic.csv | <i>Table of protein protein interactions for presynaptic compartment</i> |
|---------------------|--|

Description

Protein-protein interactions (PPIS) for presynaptic compartment, extracted from Synaptome.db, in a csv form. Columns A and B correspond to Entrez IDs for interacting proteins A and B (node names); column We contains the edge weights, if available.

See Also

[buildNetwork](#)

| | |
|---------------------|--|
| PPI_Presynaptic.gml | <i>PPI graph for presynaptic compartment</i> |
|---------------------|--|

Description

Protein-protein interactions (PPIS) for presynaptic compartment, extracted from Synaptome.db, and saved in a graph format. Graph contains node attributes, such as names (Entrez IDs), Gene Names, disease association (TopOntoOVG, TopOntoOVGHDOID), annotation with schizophrenia-related genes (Schanno (v/c), function annotation from GO (GOBPID, GOBP, GOMFID, GOMF, GOC-CID, GOCC), centrality measures (DEG - degree, BET - betweenness, CC - clustering coefficient, SL - semilocal centrality, mnSP - mean shortest path, PR - page rank, sdSP - standard deviation of the shortest path), and clustering memberships for 8 clustering algorithms (lec, wt, fc, infomap, louvain, sgG1, sgG2, sgG5)

| | |
|------------|--|
| prepareGDA | <i>Function to return vertex annotation from a graph in the Vertex Annotation form and format it for further analysis.</i> |
|------------|--|

Description

Function to return vertex annotation from a graph in the Vertex Annotation form and format it for further analysis.

Usage

prepareGDA(gg, name)

Arguments

- | | |
|------|---|
| gg | igraph object to take annotation from |
| name | name of the vertex attribute that contains annotation. If graph has no such vertex attribute an error is thrown.. |

Value

escaped annotation in Vertex Annotation form

See Also

- getAnnotationVertexList
- escapeAnnotation

Examples

```
file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
gda<-prepareGDA(agg, 'TopOntoOVGHDOID')
gda<-prepareGDA(agg, 'TopOntoOVGHDOID')
head(gda)
```

PresynAn.csv

*Presynaptic genes specific functional annotation***Description**

Presynaptic genes functional annotation derived from Boyken et al. (2013) [doi:10.1016/j.neuron.2013.02.027](https://doi.org/10.1016/j.neuron.2013.02.027). The table has columns: the first containing functional group ID terms, the second - gene functional group description terms, third - gene Human Entrez Ids; in csv format

See Also

[annotatePresynaptic](#)

recluster

*Hierarchical graph clustering***Description**

Function reads in a graph GG with cluster membership stored in vertex attribute ALGN, and reapplies the clustering algorithm ALGN to all clusters larger than CnMAX

Usage

```
recluster(GG, ALGN, CnMAX, weights = NULL)
```

Arguments

| | |
|---------|---|
| GG | graph to cluster |
| ALGN | algorithm to apply |
| CnMAX | maximum size of the cluster in mem that will not be processed |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |

Value

remembership matrix, that contains vertex ID membership and result of reclustering

Examples

```
data(karate,package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate,alg = alg)
remem<-calcReclusterMatrix(karate,mem,alg,10)
```

| | |
|------------------|--------------------------------|
| removeVertexTerm | <i>Remove vertex property.</i> |
|------------------|--------------------------------|

Description

Remove vertex property.

Usage

```
removeVertexTerm(GG, NAME)
```

Arguments

| | |
|------|---------------------------------------|
| GG | igraph object |
| NAME | name of the vertex property to remove |

Value

igraph object with attribute removed

Examples

```
data(karate, package='igraphdata')
upgrade_graph(karate)
vertex_attr_names(karate)
m<-removeVertexTerm(karate, 'color')
vertex_attr_names(m)
```

| | |
|----------------|---|
| runPermDisease | <i>Calculate disease-disease pair overlaps on permuted network to estimate its statistical significance</i> |
|----------------|---|

Description

Function to calculate the disease-pair overlap characteristics of an inputted network, before applying Nperm permutations on the disease annotations of # type "random" or "binned" permute. From the permuted networks the function estimates the significance of disease overlap: p-value, Bonferoni-adjusted p-value, and q-value in the Disease_overlap_sig. The function also compares the average disease separation between inputted and permuted networks, and calculates its significance using the Wilcox test and store. Significance of disease-pair overlap and disease separation results are stored in the matrix Disease_location_sig.

Usage

```
runPermDisease(
  gg,
  name,
  diseases = NULL,
  Nperm = 100,
  permute = c("random", "binned"),
  alpha = c(0.05, 0.01, 0.001)
)
```

Arguments

| | |
|----------|--|
| gg | interactome network as igraph object |
| name | name of the attribute that stores disease annotation |
| diseases | list of diseases to match |
| Nperm | number of permutations to apply |
| permute | type of permutations. random – annotation is randomly shuffled, binned – annotation is shuffled in a way to preserve node degree-annotation relationship by degreeBinnedGDAs . |
| alpha | statistical significance levels |

Details

Run with care, as large number of permutations could require a lot of memory and be timeconsuming.

Value

list of two matrices: Disease_overlap_sig gives s tatistics for each pair of disease, and Disease_location_sig gives intra-disease statistics

Examples

```

file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
r <- runPermDisease(
  agg,
  name = "TopOntoOVGHDOID",
  diseases = c("DOID:10652", "DOID:3312", "DOID:12849", "DOID:1826"),
  Nperm = 10,
  alpha = c(0.05, 0.01, 0.001))
r$Disease_location_sig

```

| | |
|--------------------|---|
| sampleDegBinnedGDA | <i>Function to randomly shuffle vertex annotation terms, whilst preserving the vertex degree originally found with that annotation term..</i> |
|--------------------|---|

Description

Function to randomly shuffle vertex annotation terms, whilst preserving the vertex degree originally found with that annotation term..

Usage

```
sampleDegBinnedGDA(org.map, term)
```

Arguments

| | |
|---------|--|
| org.map | degree-annotation mapping returned by degreeBinnedGDAs |
| term | annotation term to shuffle |

Value

vertex IDs to assign term in shuffled annotation

See Also

[degreeBinnedGDAs](#)

Examples

```

file <- system.file("extdata", "PPI_Presynaptic.gml", package = "BioNAR")
gg <- igraph::read_graph(file, format="gml")
agg<-annotateGeneNames(gg)
gda<-prepareGDA(agg, 'TopOntoOVGHDOID')
diseases<-getAnnotationList(gda)
m<-degreeBinnedGDAs(agg, gda, diseases)
sampleDegBinnedGDA(m, diseases[1])

```

| | |
|------------------|--|
| sampleGraphClust | <i>Perturbe graph and calculate its clustering</i> |
|------------------|--|

Description

Function will mask a percentage of edges (type=1) or vertices (type=2) from the network, find the largest connected component of the masked network and cluster it. The clustering results are stored in a three column matrix: the first column contains the vertex IDs of input network; the second column the vertex IDs of the subsampled network, or -1 if the vertex has been masked; the third column the cluster membership of subsampled network, or -1 if vertex has been masked.

Usage

```
sampleGraphClust(
  gg,
  mask = 20,
  alg,
  type,
  weights = NULL,
  reclust = FALSE,
  Cnmax = 10
)
```

Arguments

| | |
|---------|---|
| gg | graph |
| mask | percentage of elements to perturb |
| alg | clustering alg. |
| type | edges=>1 or nodes=>2 to mask |
| weights | The weights of the edges. It must be a positive numeric vector, NULL or NA. If it is NULL and the input graph has a 'weight' edge attribute, then that attribute will be used. If NULL and no such attribute is present, then the edges will have equal weights. Set this to NA if the graph was a 'weight' edge attribute, but you don't want to use it for community detection. A larger edge weight means a stronger connection for this function. The weights value is ignored for the spectral clustering. |
| reclust | logical to decide whether to invoke reclustering via recluster |
| Cnmax | maximum size of the cluster in mem that will not be processed if reclustering is invoked |

Details

This is internal function and not supposed to be called by end user.

Value

list of Nx3 matrices

Examples

```
data(karate,package='igraphdata')
alg<-'louvain'
mem<-calcMembership(karate,alg = alg)
smp1<-BioNAR:::sampleGraphClust(karate,mask=10,alg,type=2)
```

| | |
|------------------|---|
| SCH_flatfile.csv | <i>Schizopherina related synaptic gene functional annotation.</i> |
|------------------|---|

Description

Annotation, manually curated from an external file: Lips et al., (2012) doi:10.1038/mp.2011.117.The table has columns: the first containing gene Human Entrez IDs, the second gene functional group ID terms, the third gene functional group description terms; in csv format

See Also

[annotateSCHanno](#)

| | |
|--------------|---|
| summaryStats | <i>Calculate summary statistics from enrichment table</i> |
|--------------|---|

Description

Calculate summary statistics from enrichment table

Usage

```
summaryStats(RES, ALPHA, usePadj = FALSE, FeMAX = 0, FcMAX = 0)
```

Arguments

| | |
|---------|--|
| RES | enrichment results data.frame |
| ALPHA | p-value cut-off |
| usePadj | logical, wether to use plain or adjusted p-value |
| FeMAX | max of the FE |
| FcMAX | max of the FC |

Value

list of data.frame

| | |
|--------------------|------------------------------------|
| unescapeAnnotation | <i>Unescape annotation strings</i> |
|--------------------|------------------------------------|

Description

Function to remove all escape characters from annotation strings (opposite to escapeAnnotation).

Usage

```
unescapeAnnotation(annVec, col = COLLAPSE, esc = ESC)
```

Arguments

| | |
|--------|---|
| annVec | vector of annotation strings |
| col | list separator character within annotation string |
| esc | escape character |

Details

NOTE: spaces are treated as regular characters, no trimming is applied before or after escaping.

Value

vector of annotation strings with removed escape characters

See Also

escapeAnnotation

Examples

```
annVec<-apply(matrix(letters, ncol=13), 2, paste, collapse=';')
escVec<-escapeAnnotation(annVec, ';', '|')
cbind(annVec, escVec, unescapeAnnotation(escVec, ';', '|'))
```

| | |
|--------|--|
| zeroNA | <i>Auxiliary function to replace NAs with zeros.</i> |
|--------|--|

Description

Auxiliary function to replace NAs with zeros.

Usage

```
zeroNA(x)
```

Arguments

`x` matrix or vector to process

Value

matrix or vector with NAs replaced by zero.

Examples

```
x<-matrix(NA,nrow = 3,ncol = 3)
zeroNA(x)
```


Index

- * **diseasome**
 - diseasome, [30](#)
- * **file**
 - flatfile.go.BP.csv, [36](#)
 - flatfile.go.CC.csv, [36](#)
 - flatfile.go.MF.csv, [36](#)
 - flatfile_human_gene2HDO.csv, [37](#)
 - PPI_Presynaptic.csv, [63](#)
 - PPI_Presynaptic.gml, [64](#)
 - PresynAn.csv, [65](#)
 - SCH_flatfile.csv, [70](#)
- * **graphs**
 - diseasome, [30](#)
- * **internal**
 - buildConsensusMatrix, [15](#)
- * **list(Entropy Functions)**
 - calcEntropy, [23](#)
 - getEntropy, [46](#)
 - getEntropyRate, [47](#)
 - plotEntropy, [61](#)
- * **list(Robustness functions)**
 - getRobustness, [52](#)
 - makeConsensusMatrix, [55](#)
- addEdgeAtts, [4](#)
- annotateGeneNames, [4](#)
- annotateGoBP, [5](#), [36](#)
- annotateGoCC, [6](#), [36](#)
- annotateGoMF, [7](#), [36](#)
- annotateGOont, [8](#)
- annotateInterpro, [9](#)
- annotatePresynaptic, [9](#), [65](#)
- annotateSCHanno, [10](#), [70](#)
- annotateTopOntoOVG, [11](#), [37](#)
- annotateVertex, [12](#), [13](#)
- applMatrixToGraph, [13](#), [18](#)
- as.undirected, [41](#)
- betweenness, [40](#)
- BioNAR, [14](#)
- BioNAR-package (BioNAR), [14](#)
- buildConsensusMatrix, [15](#)
- buildNetwork, [15](#), [63](#)
- calcAllClustering, [16](#)
- calcBridgeness, [17](#), [60](#)
- calcCentrality, [18](#)
- calcCentralityExternalDistances, [19](#)
- calcCentralityInternalDistances, [20](#)
- calcClustering, [16](#), [21](#)
- calcDiseasePairs, [22](#)
- calcEntropy, [23](#), [47](#), [48](#), [62](#)
- calcMembership, [24](#), [54](#)
- calcReclusterMatrix, [25](#), [55](#)
- calcSparsness, [26](#)
- clrob, [52](#)
- cluster_fast_greedy, [41](#)
- cluster_infomap, [41](#)
- cluster_leading_eigen, [41](#)
- cluster_louvain, [41](#)
- cluster_spinglass, [41](#)
- cluster_walktrap, [41](#)
- clusteringSummary, [27](#)
- clusterORA, [28](#)
- communities, [42](#)
- degreeBinnedGDAs, [22](#), [29](#), [67](#), [68](#)
- diseasome, [30](#)
- dist, [20](#)
- escapeAnnotation, [31](#)
- evalCentralitySignificance, [32](#)
- findLCC, [33](#)
- fitDegree, [33](#), [51](#)
- fitSigmoid, [35](#)
- flatfile.go.BP.csv, [36](#)
- flatfile.go.CC.csv, [36](#)
- flatfile.go.MF.csv, [36](#)
- flatfile_human_gene2HDO.csv, [37](#)

getAnnotationList, [37](#)
getAnnotationVertexList, [38](#)
getBridgeness, [17](#), [39](#)
getCentralityMatrix, [18](#), [19](#), [40](#), [49](#), [51](#)
getCentralityMatrix(), [18](#), [51](#)
getClustering, [21](#), [24](#), [40](#), [41](#)
getClusterSubgraphByID, [42](#)
getCommunityGraph, [43](#)
getDiseases, [43](#)
getDType, [44](#)
getDYNAMO, [45](#)
getEntropy, [23](#), [24](#), [46](#), [48](#), [61](#), [62](#)
getEntropy(), [24](#), [62](#)
getEntropyRate, [24](#), [47](#), [47](#), [61](#), [62](#)
getGNP, [48](#)
getGraphCentralityECDF, [49](#)
getIDs, [49](#)
getPA, [50](#)
getRandomGraphCentrality, [19](#), [20](#), [51](#)
getRobustness, [52](#), [56](#)
ggplot, [60](#), [63](#)
gofs, [53](#)
graph, [30](#), [31](#)
graph_from_data_frame, [15](#)

keys, [5](#), [8](#)
keytypes, [5](#), [8](#)
ks.test, [53](#)

law-class, [54](#)
layout_, [55](#)
layoutByCluster, [54](#)
layoutByRecluster, [55](#)

makeConsensusMatrix, [53](#), [55](#)
match.arg, [21](#), [42](#)
metlMatrix, [57](#)
modularity, [27](#)

normModularity, [57](#)

org.Hs.eg.db, [4](#), [8](#)

page_rank, [40](#)
permute, [59](#)
plotBridgeness, [59](#)
plotEntropy, [24](#), [47](#), [48](#), [61](#)
plotRatio, [62](#)
plotSigmoid, [63](#)
PPI_Presynaptic.csv, [63](#)

PPI_Presynaptic.gml, [64](#)
prepareGDA, [30](#), [64](#)
PresynAn.csv, [65](#)

recluster, [56](#), [65](#), [69](#)
removeVertexTerm, [66](#)
runPermDisease, [67](#)

sample, [59](#)
sample_correlated_gnp, [51](#)
sample_gnp, [48](#), [51](#)
sample_pa, [50](#), [51](#)
sampleDegBinnedGDA, [68](#)
sampleGraphClust, [15](#), [69](#)
SCH_flatfile.csv, [70](#)
spectral_igraph_communities, [41](#)
summaryStats, [35](#), [70](#)
summaryStats(), [35](#)

unescapeAnnotation, [71](#)

vcount, [27](#)

zeroNA, [71](#)