

Package ‘FRASER’

January 26, 2023

Type Package

Title Find RAre Splicing Events in RNA-Seq Data

Version 1.11.0

Date 2021-04-05

Description Detection of rare aberrant splicing events in transcriptome profiles. Read count ratio expectations are modeled by an autoencoder to control for confounding factors in the data. Given these expectations, the ratios are assumed to follow a beta-binomial distribution with a junction specific dispersion. Outlier events are then identified as read-count ratios that deviate significantly from this distribution. FRASER is able to detect alternative splicing, but also intron retention. The package aims to support diagnostics in the field of rare diseases where RNA-seq is performed to identify aberrant splicing defects.

biocViews RNASeq, AlternativeSplicing, Sequencing, Software, Genetics, Coverage

License MIT + file LICENSE

URL <https://github.com/gagneurlab/FRASER>

BugRepots <https://github.com/gagneurlab/FRASER/issues>

RoxygenNote 7.1.2

Encoding UTF-8

VignetteBuilder knitr

Depends BiocParallel, data.table, Rsamtools, SummarizedExperiment

Imports AnnotationDbi, BBmisc, Biobase, BiocGenerics, biomaRt, BSgenome, cowplot, DelayedArray (>= 0.5.11), DelayedMatrixStats, extraDistr, generics, GenomeInfoDb, GenomicAlignments, GenomicFeatures, GenomicRanges, IRanges, grDevices, ggplot2, ggrepel, HDF5Array, matrixStats, methods, OUTRIDER, pcaMethods, pheatmap, plotly, PRROC, RColorBrewer, rhdf5, Rsubread, R.utils, S4Vectors, stats, tibble, tools, utils, VGAM

Suggests BiocStyle, knitr, rmarkdown, testthat, covr, TxDb.Hsapiens.UCSC.hg19.knownGene, org.Hs.eg.db,

LinkingTo Rcpp, RcppArmadillo

Collate variables.R getNSetterFuns.R FRASER-package.R
 FraserDataSet-class.R AllGenerics-definitions.R AllGenerics.R
 Fraser-pipeline.R annotationOfRanges.R beta-binomial-testing.R
 calculatePSIValue.R countRNAseqData.R example_functions.R
 filterExpression.R find_encoding_dimensions.R getURLs.R
 helper-functions.R mergeExternalData.R saveHDF5Objects.R
 RcppExports.R autoencoder.R updateD.R updateE.R updateRho.R
 pvalsNzscore.R makeSimulatedDataset.R fitCorrectionMethods.R
 plotMethods.R zzz.R

git_url <https://git.bioconductor.org/packages/FRASER>

git_branch master

git_last_commit ab699ed

git_last_commit_date 2022-11-01

Date/Publication 2023-01-26

Author Christian Mertes [aut, cre],
 Ines Scheller [aut],
 Vicente Yopez [ctb],
 Julien Gagneur [aut]

Maintainer Christian Mertes <mertes@in.tum.de>

R topics documented:

annotateRanges	3
assayNames,FraserDataSet-method	4
assays,FraserDataSet-method	5
calculatePSIValues	6
countRNA	7
createTestFraserSettings	11
filtering	12
fit	14
FRASER	15
FraserDataSet	18
FraserDataSet-class	19
getter_setter_functions	19
injectOutliers	22
K	23
length,FraserDataSet-method	24
loadFraserDataSet	25
makeSimulatedFraserDataSet	26
mergeExternalData	27
optimHyperParams	28
plotFunctions	29
psiTypes	35
results,FraserDataSet-method	36

annotateRanges 3

samples 38
subset.FRASER 41

Index 43

annotateRanges *Annotates the given FraserDataSet with the HGNC symbol with biomaRt*

Description

Annotates the given *FraserDataSet* with the HGNC symbol with *biomaRt*

Usage

```
annotateRanges(  
  fds,  
  feature = "hgnc_symbol",  
  featureName = feature,  
  biotype = list("protein_coding"),  
  ensembl = NULL,  
  GRCh = 37  
)
```

```
annotateRangesWithTxDb(  
  fds,  
  feature = "SYMBOL",  
  featureName = "hgnc_symbol",  
  keytype = "ENTREZID",  
  txdb = NULL,  
  orgDb = NULL  
)
```

Arguments

<code>fds</code>	<i>FraserDataSet</i>
<code>feature</code>	Defines which feature (default is HGNC symbol) should be annotated. Has to be the <i>biomaRt</i> feature name or a column name in <i>orgDb</i> .
<code>featureName</code>	The column name of the feature in the <i>FraserDataSet</i> <i>mcols</i> .
<code>biotype</code>	The biotype for <i>biomaRt</i> .
<code>ensembl</code>	The <i>ensembl</i> that should be used. If <code>NULL</code> , the default one is used (<i>hsapi-ens_gene_ensembl</i> , <i>GRCh37</i>).
<code>GRCh</code>	<i>GRCh</i> version to connect to. If this is <code>NULL</code> , then the current <i>GRCh38</i> is used. Otherwise, this can only be 37 (default) at the moment (see useEnsembl).
<code>keytype</code>	The keytype or column name of gene IDs in the <i>TxDb</i> object (see keytypes for a list of available ID types).

txdb	A TxDb object. If this is NULL, then the default one is used, currently this is TxDb.Hsapiens.UCSC.hg19.knownGene.
orgDb	An orgDb object or a data table to map the feature names. If this is NULL, then org.Hs.eg.db is used as the default.

Value

FraserDataSet

Examples

```

fds <- createTestFraserDataSet()

### Two ways to annotage ranges with gene names:
# either using biomart with GRCh38
try({
  fds <- annotateRanges(fds, GRCh=38)
  rowRanges(fds, type="psi5")[c("hgnc_symbol")]
})

# either using biomart with GRCh37
try({
  fds <- annotateRanges(fds, featureName="hgnc_symbol_37", GRCh=37)
  rowRanges(fds, type="psi5")[c("hgnc_symbol_37")]
})

# or with a provided TxDb object
require(TxDb.Hsapiens.UCSC.hg19.knownGene)
txdb <- TxDb.Hsapiens.UCSC.hg19.knownGene
require(org.Hs.eg.db)
orgDb <- org.Hs.eg.db
fds <- annotateRangesWithTxDb(fds, txdb=txdb, orgDb=orgDb)
rowRanges(fds, type="psi5")[,"hgnc_symbol"]

```

 assayNames,FraserDataSet-method

Returns the assayNames of FRASER

Description

Returns the assayNames of FRASER

Usage

```

## S4 method for signature 'FraserDataSet'
assayNames(x)

```

Arguments

x FraserDataSet

Value

Character vector

assays,FraserDataSet-method

Returns the assay for the given name/index of the FraserDataSet

Description

Returns the assay for the given name/index of the FraserDataSet

Usage

```
## S4 method for signature 'FraserDataSet'
assays(x, withDimnames = TRUE, ...)

## S4 replacement method for signature 'FraserDataSet,SimpleList'
assays(x, withDimnames = TRUE, HDF5 = TRUE, type = NULL, ...) <- value

## S4 replacement method for signature 'FraserDataSet,list'
assays(x, withDimnames = TRUE, HDF5 = TRUE, type = NULL, ...) <- value

## S4 replacement method for signature 'FraserDataSet,DelayedMatrix'
assays(x, withDimnames = TRUE, HDF5 = TRUE, type = NULL, ...) <- value
```

Arguments

x FraserDataSet

withDimnames Passed on to SummarizedExperiment::assays()

... Parameters passed on to SummarizedExperiment::assays()

HDF5 Logical value indicating whether the assay should be stored as a HDF5 file.

type The psi type.

value The new value to which the assay should be set.

Value

(Delayed) matrix.

calculatePSIValues *PSI value calculation*

Description

This function calculates the PSI values for each junction and splice site based on the FraserDataSet object

Usage

```
calculatePSIValues(  
  fds,  
  types = psiTypes,  
  overwriteCts = FALSE,  
  BPPARAM = bpparam()  
)
```

Arguments

fds	A FraserDataSet object
types	A vector with the psi types which should be calculated. Default is all of psi5, psi3 and theta.
overwriteCts	FALSE or TRUE (the default) the total counts (aka N) will be recalculated based on the existing junction counts (aka K)
BPPARAM	the BiocParallel parameters for the parallelization

Value

FraserDataSet

Examples

```
fds <- createTestFraserDataSet()  
fds <- calculatePSIValues(fds, types="psi5")  
  
### usually one would run this function for all psi types by using:  
# fds <- calculatePSIValues(fds)
```

countRNA	<i>Count RNA-seq data</i>
----------	---------------------------

Description

The FRASER package provides multiple functions to extract and count both split and non-spliced reads from bam files. See Detail and Functions for more information.

Usage

```
countRNAData(  
  fds,  
  NcpuPerSample = 1,  
  minAnchor = 5,  
  recount = FALSE,  
  BPPARAM = bpparam(),  
  genome = NULL,  
  junctionMap = NULL,  
  filter = TRUE,  
  minExpressionInOneSample = 20,  
  keepNonStandardChromosomes = TRUE,  
  countDir = file.path(workingDir(fds), "savedObjects", nameNoSpace(name(fds))),  
  ...  
)  
  
getSplitReadCountsForAllSamples(  
  fds,  
  NcpuPerSample = 1,  
  junctionMap = NULL,  
  recount = FALSE,  
  BPPARAM = bpparam(),  
  genome = NULL,  
  countFiles = NULL,  
  keepNonStandardChromosomes = TRUE,  
  outDir = file.path(workingDir(fds), "savedObjects", nameNoSpace(name(fds)),  
    "splitCounts")  
)  
  
getNonSplitReadCountsForAllSamples(  
  fds,  
  splitCountRanges,  
  NcpuPerSample = 1,  
  minAnchor = 5,  
  recount = FALSE,  
  BPPARAM = bpparam(),  
  longRead = FALSE,  
  outDir = file.path(workingDir(fds), "savedObjects", nameNoSpace(name(fds)),
```

```

    "nonSplitCounts")
)

addCountsToFraserDataSet(fds, splitCounts, nonSplitCounts)

countSplitReads(
  sampleID,
  fds,
  NcpuPerSample = 1,
  genome = NULL,
  recount = FALSE,
  keepNonStandardChromosomes = TRUE,
  bamfile = bamFile(fds[, sampleID]),
  pairedend = pairedEnd(fds[, sampleID]),
  strandmode = strandSpecific(fds),
  cacheFile = getSplitCountCacheFile(sampleID, fds),
  scanbamparam = scanBamParam(fds),
  coldata = colData(fds)
)

mergeCounts(
  countList,
  fds,
  junctionMap = NULL,
  assumeEqual = FALSE,
  spliceSiteCoords = NULL,
  BPPARAM = SerialParam()
)

countNonSplicedReads(
  sampleID,
  splitCountRanges,
  fds,
  NcpuPerSample = 1,
  minAnchor = 5,
  recount = FALSE,
  spliceSiteCoords = NULL,
  longRead = FALSE
)

```

Arguments

fds	A FraserDataSet object
NcpuPerSample	A BiocParallel param object or a positive integer to configure the parallel back-end of the internal loop per sample
minAnchor	Minimum overlap around the Donor/Acceptor for non spliced reads. Default to 5
recount	if TRUE the cache is ignored and the bam file is recounted.

BPPARAM	the BiocParallel parameters for the parallelization
genome	NULL (default) or a character vector specifying the names of the reference genomes that were used to align the reads for each sample. The names have to be in a way accepted by the <code>getBSgenome</code> function. Available genomes can be listed using the <code>available.genomes</code> function from the BSgenome package. If genome is of length 1, the same reference genome will be used for all samples. If genome is supplied and <code>strandSpecific(fds) == 0L</code> (unstranded), then the strand information will be estimated by checking the dinucleotides found at the intron boundaries (see <code>summarizeJunctions</code> in GenomicAlignments package for details). This can e.g. help to avoid ambiguities when adding gene names from a gene annotation to the introns in a later step.
junctionMap	A object or file containing a map of all junctions of interest across all samples
filter	If TRUE, splice sites of introns with low read support in all samples are not considered when calculating the non-split reads. This helps to speed up the subsequent steps.
minExpressionInOneSample	The minimal split read count in at least one sample that is required for an intron to pass the filter.
keepNonStandardChromosomes	Logical value indicating if non standard chromosomes should also be counted. Defaults to TRUE.
countDir	The directory in which the tsv containing the position and counts of the junctions should be placed.
...	Further parameters passed on to <code>Rsubread::featureCounts</code> .
countFiles	If specified, the split read counts for all samples are read from the specified files. Should be a vector of paths to files containing the split read counts for the individual samples. Reading from files is only supported for <code>tsv(.gz)</code> or RDS files containing <code>GRranges</code> objects. The order of the individual sample files should correspond to the order of the samples in the <code>fds</code> .
outDir	The full path to the output folder containing the merged counts. If the given folder already exists and stores a <code>SummarizedExperiment</code> object, the counts from this folder will be read in and used in the following (i.e. the reads are not recounted), unless the option <code>recount=TRUE</code> is used. If this folder doesn't exist or if <code>recount=TRUE</code> , then it will be created after counting has finished.
splitCountRanges	The merged <code>GRanges</code> object containing the positions of all the introns in the dataset over all samples.
longRead	If TRUE, then the <code>isLongRead</code> option of <code>Rsubread::featureCounts</code> is used when counting the non spliced reads overlapping splice sites.
splitCounts	The <code>SummarizedExperiment</code> object containing the position and counts of all the introns in the dataset for all samples.
nonSplitCounts	The <code>SummarizedExperiment</code> object containing the position and non split read counts of all splice sites present in the dataset for all samples.
sampleID	The ID of the sample to be counted.

bamfile	The BAM file to be used to extract the counts. Defaults to the BAM file defined in the FraserDataSet object.
pairedend	TRUE or FALSE if the BAM file is paired end. Defaults to the value specified in the FraserDataSet object.
strandmode	0 (no, default), 1 (stranded), or 2 (revers) to specify the used protocol for the RNA-seq experiment.
cacheFile	File path to the cache, where counts are stored.
scanbamparam	The ScanBamParam object which is used for loading the reads from the BAM file before counting. Defaults to the params stored in the FraserDataSet object.
coldata	The colData as given by the FraserDataSet object.
countList	A list of GRanges objects containing the counts that should be merged into one object.
assumeEqual	Logical indicating whether all objects in countList can be assumed to contain counts for the same ranges. If FALSE, merging of the ranges is performed.
spliceSiteCoords	A GRanges object containing the positions of the splice sites. If it is NULL, then splice sites coordinates are calculated first based on the positions of the junctions defined from the split reads.

Details

The functions described in this file extract and count both the split and the non-spliced reads from bam files.

[countRNAData](#) is the main function that takes care of all counting steps and returns a [FraserDataSet](#) containing the counts for all samples in the `fds`.

[getSplitReadCountsForAllSamples](#) counts split reads for all samples and [getNonSplitReadCountsForAllSamples](#) counts non split reads overlapping splice sites for all samples. [addCountsToFraserDataSet](#) adds these counts to an existing `fds`.

[countSplitReads](#) calculates the split read counts for a single sample. [countNonSplicedReads](#) counts the non split reads overlapping with splice sites for a single sample.

[mergeCounts](#) merges the counts from different samples into a single count object, where the counts for junctions that are not present in a sample are set to zero.

Value

[countRNAData](#) returns a [FraserDataSet](#).

[getSplitReadCountsForAllSamples](#) returns a [GRanges](#) object.

[getNonSplitReadCountsForAllSamples](#) returns a [GRanges](#) object.

[addCountsToFraserDataSet](#) returns a [FraserDataSet](#).

[countSplitReads](#) returns a [GRanges](#) object.

[mergeCounts](#) returns a [SummarizedExperiment](#) object.

[countNonSplicedReads](#) returns a [GRanges](#) object.

Functions

- `countRNAData`: This method extracts and counts the split reads and non spliced reads from RNA bam files.
- `getSplitReadCountsForAllSamples`: This method creates a `GRanges` object containing the split read counts from all specified samples.
- `getNonSplitReadCountsForAllSamples`: This method creates a `GRanges` object containing the non split read counts at the exon-intron boundaries inferred from the `GRanges` object containing the positions of all the introns in this dataset.
- `addCountsToFraserDataSet`: This method adds the split read and non split read counts to a existing `FraserDataSet` containing the settings.
- `countSplitReads`: This method counts all split reads in a bam file for a single sample.
- `mergeCounts`: This method merges counts for multiple samples into one `SummarizedExperiment` object.
- `countNonSplicedReads`: This method counts non spliced reads based on the given target (acceptor/donor) regions for a single sample.

Examples

```
# On Windows SNOW is the default for the parallele backend, which can be
# very slow for many but small tasks. Therefore, we will use
# for the example the SerialParam() backend.
if(.Platform$OS.type != "unix") {
  register(SerialParam())
}

fds <- countRNAData(createTestFraserSettings())
```

`createTestFraserSettings`

Create a test dataset

Description

Create a test case dataset based on the test sample annotation to be used in the vignette and to explore the functionality of the FRASER package. Dependent on the request only the sample annotation or a full fitted model is returned.

Usage

```
createTestFraserSettings(workingDir = "FRASER_output")
```

```
createTestFraserDataSet(workingDir = "FRASER_output", rerun = FALSE)
```

Arguments

`workingDir` Directory where to store HDF5 and RDS files. Defaults to `FRASER_output` in the current working directory.

`rerun` Defaults to `FALSE`. If set to `TRUE` it reruns the full fit of the model.

Value

A `FraserDataSet` object that contains a test case

Examples

```
fds <- createTestFraserSettings()
fds

fds <- createTestFraserDataSet()
fds
```

 filtering

Filtering FraserDataSets

Description

This method can be used to filter out introns that are not reliably detected and to remove introns with no variability between samples.

Usage

```
filterExpressionAndVariability(
  object,
  minExpressionInOneSample = 20,
  quantile = 0.95,
  quantileMinExpression = 10,
  minDeltaPsi = 0.05,
  filter = TRUE,
  delayed = ifelse(ncol(object) <= 300, FALSE, TRUE),
  BPPARAM = bpparam()
)

## S4 method for signature 'FraserDataSet'
filterExpression(
  object,
  minExpressionInOneSample = 20,
  quantile = 0.95,
  quantileMinExpression = 10,
  filter = TRUE,
  delayed = ifelse(ncol(object) <= 300, FALSE, TRUE),
```

```

    BPPARAM = bpparam()
  )

  filterVariability(
    object,
    minDeltaPsi = 0.05,
    filter = TRUE,
    delayed = ifelse(ncol(object) <= 300, FALSE, TRUE),
    BPPARAM = bpparam()
  )

```

Arguments

object	A FraserDataSet object
minExpressionInOneSample	The minimal read count in at least one sample that is required for an intron to pass the filter.
quantile	Defines which quantile should be considered for the filter.
quantileMinExpression	The minimum read count an intron needs to have at the specified quantile to pass the filter.
minDeltaPsi	Only introns for which the maximal difference in the psi value of a sample to the mean psi of the intron is larger than this value pass the filter.
filter	If TRUE, a subsetting of introns containing only those that passed all filters is returned. If FALSE, no subsetting is done and the information of whether an intron passed the filters is only stored in the mcols.
delayed	If FALSE, count matrices will be loaded into memory, otherwise the function works on the delayedMatrix representations. The default value depends on the number of samples in the fds-object.
BPPARAM	the BiocParallel parameters for the parallelization

Value

A [FraserDataSet](#) with information about which junctions passed the filters. If filter=TRUE, the filtered [FraserDataSet](#) is returned.

Functions

- `filterExpressionAndVariability`: This function filters out both introns with low read support and introns that are not variable across samples.
- `filterExpression,FraserDataSet-method`: This function filters out introns and corresponding splice sites that have low read support in all samples.
- `filterVariability`: This function filters out introns and corresponding splice sites which do not show variability across samples.

Examples

```

fds <- createTestFraserDataSet()
fds <- filterExpressionAndVariability(fds, minDeltaPsi=0.1, filter=FALSE)
mcols(fds, type="psi5")[, c(
  "maxCount", "passedExpression", "maxDPsi3", "passedVariability")]

plotFilterExpression(fds)
plotFilterVariability(fds)

```

fit

Fitting the denoising autoencoder

Description

This method corrects for confounders in the data and fits a beta-binomial distribution to the introns/splice sites.

For more details please see [FRASER](#).

Usage

```

## S3 method for class 'FraserDataSet'
fit(
  object,
  implementation = c("PCA", "PCA-BB-Decoder", "AE", "AE-weighted", "PCA-BB-full",
    "fullAE", "PCA-regression", "PCA-reg-full", "PCA-BB-Decoder-no-weights", "BB"),
  q,
  type = "psi3",
  rhoRange = c(1e-08, 1 - 1e-08),
  weighted = FALSE,
  noiseAlpha = 1,
  convergence = 1e-05,
  iterations = 15,
  initialize = TRUE,
  control = list(),
  BPPARAM = bpparam(),
  nSubset = 15000,
  minDeltaPsi = 0.1,
  ...
)

```

Arguments

object A [FraserDataSet](#) object

implementation The method that should be used to correct for confounders.

q	The encoding dimensions to be used during the fitting procedure. Should be fitted using <code>optimHyperParams</code> if unknown. If a named vector is provided it is used for the different splicing types.
type	The type of PSI (psi5, psi3 or theta for theta/splicing efficiency)
rhoRange	Defines the range of values that rho parameter from the beta-binomial distribution is allowed to take. For very small values of rho, the loss can be unstable, so it is not recommended to allow $\rho < 1e-8$.
weighted	If TRUE, the weighted implementation of the autoencoder is used
noiseAlpha	Controls the amount of noise that is added for the denoising autoencoder.
convergence	The fit is considered to have converged if the difference between the previous and the current loss is smaller than this threshold.
iterations	The maximal number of iterations. When the autoencoder has not yet converged after these number of iterations, the fit stops anyway.
initialize	If FALSE and a fit has been previously run, the values from the previous fit will be used as initial values. If TRUE, (re-)initialization will be done.
control	List of control parameters passed on to <code>optim()</code> .
BPPARAM	the BiocParallel parameters for the parallelization
nSubset	The size of the subset to be used in fitting if subsetting is used.
minDeltaPsi	Minimal delta psi of an intron to be considered a variable intron.
...	Currently not used

Value

[FraserDataSet](#)

See Also

[FRASER](#)

FRASER

FRASER: Find RAre Splicing Events in RNA-seq data

Description

This help page describes the FRASER function which can be used run the default FRASER pipeline. This pipeline combines the beta-binomial fit, the computation of Z scores and p values as well as the computation of delta-PSI values.

Usage

```
FRASER(
  fds,
  q,
  implementation = c("PCA", "PCA-BB-Decoder", "AE-weighted", "AE", "BB"),
  iterations = 15,
  BPPARAM = bpparam(),
  correction,
  ...
)
```

```
calculateZscore(fds, type = currentType(fds), logit = TRUE)
```

```
calculatePvalues(
  fds,
  type = currentType(fds),
  implementation = "PCA",
  BPPARAM = bpparam(),
  distributions = c("betabinomial"),
  capN = 5 * 1e+05
)
```

```
calculatePadjValues(fds, type = currentType(fds), method = "BY")
```

Arguments

<code>fds</code>	A FraserDataSet object
<code>q</code>	The encoding dimensions to be used during the fitting procedure. Should be fitted using optimHyperParams if unknown. If a named vector is provided it is used for the different splicing types.
<code>implementation</code>	The method that should be used to correct for confounders.
<code>iterations</code>	The maximal number of iterations. When the autoencoder has not yet converged after these number of iterations, the fit stops anyway.
<code>BPPARAM</code>	A BiocParallel object to run the computation in parallel
<code>correction</code>	Deprecated. The name changed to <code>implementation</code> .
<code>...</code>	Additional parameters passed on to the internal fit function
<code>type</code>	The type of PSI (psi5, psi3 or theta for theta/splicing efficiency)
<code>logit</code>	Indicates if z scores are computed on the logit scale (default) or in the natural (psi) scale.
<code>distributions</code>	The distribution based on which the p-values are calculated. Possible are beta-binomial, binomial and normal.
<code>capN</code>	Counts are capped at this value to speed up the p-value calculation
<code>method</code>	The p.adjust method that should be used.

Details

All computed values are returned as an `FraserDataSet` object. To have more control over each analysis step, one can call each function separately.

- `fit` to control for confounding effects and fit the beta binomial model parameters
- `calculatePvalues` to calculate the nominal p values
- `calculatePadjValues` to calculate adjusted p values (per sample)
- `calculateZscore` to calculate the Z scores

Available methods to correct for the confounders are currently: a denoising autoencoder with a BB loss ("AE" and "AE-weighted"), PCA ("PCA"), a hybrid approach where PCA is used to fit the latent space and then the decoder of the autoencoder is fit using the BB loss ("PCA-BB-Decoder"). Although not recommended, it is also possible to directly fit the BB distribution to the raw counts ("BB").

Value

`FraserDataSet`

Functions

- `FRASER`: This function runs the default FRASER pipeline combining the beta-binomial fit, the computation of Z scores and p values as well as the computation of delta-PSI values.
- `calculateZscore`: This function calculates z-scores based on the observed and expected logit psi.
- `calculatePvalues`: This function calculates two-sided p-values based on the beta-binomial distribution (or binomial or normal if desired). The returned p values are already adjusted with Holm's method per donor or acceptor site, respectively.
- `calculatePadjValues`: This function adjusts the previously calculated p-values per sample for multiple testing.

Author(s)

Christian Mertes <mertes@in.tum.de>

Ines Scheller <scheller@in.tum.de>

See Also

[fit](#)

Examples

```
# set default parallel backend
register(SerialParam())

# preprocessing
fds <- createTestFraserDataSet()
```

```

# filtering not expressed introns
fds <- calculatePSIValues(fds)
fds <- filterExpressionAndVariability(fds)

# Run the full analysis pipeline: fits distribution and computes p values
fds <- FRASER(fds, q=2, implementation="PCA")

# afterwards, the fitted fds-object can be saved and results can
# be extracted and visualized, see ?saveFraserDataSet, ?results and
# ?plotVolcano

# The functions run inside the FRASER function can also be directly
# run themselves.
# To directly run the fit function:
fds <- fit(fds, implementation="PCA", q=2, type="psi5")

# To directly run the nomial and adjusted p value and z score
# calculation, the following functions can be used:
fds <- calculatePvalues(fds, type="psi5")
head(pVals(fds, type="psi5"))
fds <- calculatePadjValues(fds, type="psi5", method="BY")
head(padjVals(fds, type="psi5"))
fds <- calculateZscore(fds, type="psi5")
head(zScores(fds, type="psi5"))

```

FraserDataSet

The FRASER dataset object

Description

Constructs an FRASER object based on the given input. It can take only the annotation (colData) or count tables (junctions/spliceSites).

Usage

```
FraserDataSet(colData = NULL, junctions = NULL, spliceSites = NULL, ...)
```

Arguments

colData	A DataFrame containing the annotation of the samples
junctions, spliceSites	A data.frame like object containing the raw counts for each junction or splice site. It requires the columns startID and endID for the junctions and spliceSiteID and type for the splice sites. Those columns identifies the corresponding splice site for the given junction and map to the splice site. For each sample the counts are saved in a corresponding column with the same name. It can also be a GRRange object.
...	Any parameters corresponding to the slots and their possible values. See Fraser-DataSet

Value

A FraserDataSet object.

Author(s)

Christian Mertes <mertes@in.tum.de>

Examples

```
fraser <- FraserDataSet()

# example sample annoation
sampleTable <- fread(system.file("extdata",
  "sampleTable_countTable.tsv", package="FRASER", mustWork=TRUE))

# get raw counts
junctionCts <- fread(system.file("extdata",
  "raw_junction_counts.tsv.gz", package="FRASER", mustWork=TRUE))
spliceSiteCts <- fread(system.file("extdata",
  "raw_site_counts.tsv.gz", package="FRASER", mustWork=TRUE))

# create FRASER object
fds <- FraserDataSet(colData=sampleTable, junctions=junctionCts,
  spliceSites=spliceSiteCts, name="Example Dataset")
```

FraserDataSet-class *FraserDataSet*

Description

This class is designed to store the whole FRASER data set needed for an analysis of a disease cohort

Author(s)

Christian Mertes <mertes@in.tum.de>

getter_setter_functions
Getter/Setter functions

Description

This is a collection of small accessor/setter functions for easy access to the values within the FRASER model.

Usage

```

featureExclusionMask(fds, type = currentType(fds))

featureExclusionMask(fds, type = currentType(fds)) <- value

rho(fds, type = currentType(fds))

zScores(fds, type = currentType(fds), byGroup = FALSE, ...)

pVals(fds, type = currentType(fds), level = "site", dist = "BetaBinomial", ...)

padjVals(fds, type = currentType(fds), dist = c("BetaBinomial"), ...)

predictedMeans(fds, type = currentType(fds))

deltaPsiValue(fds, type = currentType(fds))

currentType(fds)

currentType(fds) <- value

pseudocount(value = NULL)

hyperParams(fds, type = currentType(fds), all = FALSE)

bestQ(fds, type = currentType(fds))

dontWriteHDF5(fds)

dontWriteHDF5(fds) <- value

verbose(fds)

verbose(fds) <- value

```

Arguments

<code>fds</code>	An <code>FraserDataSet</code> object.
<code>type</code>	The type of psi (psi5, psi3 or theta)
<code>value</code>	The new value to be assigned.
<code>byGroup</code>	If TRUE, aggregation by donor/acceptor site will be done.
<code>...</code>	Internally used parameteres.
<code>level</code>	Indicates if the retrieved p values should be adjusted on the donor/acceptor site-level (default) or if unadjusted junction-level p values should be returned.
<code>dist</code>	Distribution for which the p-values should be extracted.

`all` Logical value indicating whether `hyperParams(fds)` should return the results of all evaluated parameter combinations or only for the optimal parameter combination.

Value

A (delayed) matrix or vector dependent on the type of data retrieved.

Functions

- `featureExclusionMask`: Retrieves a logical vector indicating for each junction whether it is included or excluded during the fitting procedure.
- `featureExclusionMask<-`: To remove certain junctions from being used in the train step of the encoding dimension we can set the `featureExclusion` vector to `FALSE`. This can be helpful if we have local linkage between features which we do not want to model by the autoencoder.
- `rho`: Returns the fitted rho values for the beta-binomial distribution
- `zScores`: This returns the calculated z-scores.
- `pVals`: This returns the calculated p-values.
- `padjVals`: This returns the adjusted p-values.
- `predictedMeans`: This returns the fitted mu (i.e. psi) values.
- `deltaPsiValue`: Returns the difference between the observed and the fitted psi values.
- `currentType`: Returns the psi type that is used within several methods in the FRASER package.
- `currentType<-`: Sets the psi type that is to be used within several methods in the FRASER package.
- `pseudocount`: Sets and returns the pseudo count used within the FRASER fitting procedure.
- `hyperParams`: This returns the results of the hyperparameter optimization `NULL` if the hyperparameter optimization was not run yet.
- `bestQ`: This returns the optimal size of the latent space according to the hyperparameter optimization or a simple estimate of about a tenth of the number of samples if the hyperparameter optimization was not run yet.
- `dontWriteHDF5`: Gets the current value of whether the assays should be stored as hdf5 files.
- `dontWriteHDF5<-`: Sets whether the assays should be stored as hdf5 files.
- `verbose`: Dependend on the level of verbosity the algorithm reports more or less to the user. 0 means being quiet and 10 means everything.
- `verbose<-`: Sets the verbosity level to a value between 0 and 10. 0 means being quiet and 10 means reporting everything.

Examples

```
fds <- createTestFraserDataSet()
# should assays be saved as hdf5?
```

```

dontWriteHDF5(fds)
dontWriteHDF5 <- TRUE

# get/set the splice metric for which results should be retrieved
currentType(fds) <- "psi5"
currentType(fds)

# get fitted parameters
bestQ(fds)
predictedMeans(fds)
rho(fds)

# get statistics
pVals(fds)
padjVals(fds)
zScores(fds)

# set and get pseudocount
pseudocount(4L)
pseudocount()

# retrieve or set a mask to exclude certain junctions in the fitting step
featureExclusionMask(fds, type="theta") <- sample(
  c(FALSE, TRUE), nrow(mcols(fds, type="theta")), replace=TRUE)
featureExclusionMask(fds, type="theta")

# controlling the verbosity level of the output of some algorithms
verbose(fds) <- 2
verbose(fds)

```

injectOutliers

Inject artificial outliers in an existing fds

Description

Inject artificial outliers in an existing fds

Usage

```

injectOutliers(
  fds,
  type = c("psi5", "psi3", "theta"),
  freq = 0.001,
  minDpsi = 0.2,
  minCoverage = 2,
  deltaDistr = "uniformDistr",
  verbose = FALSE,
  method = c("samplePSI", "meanPSI", "simulatedPSI"),
  BPPARAM = bpparam()
)

```

Arguments

fds	FraserDataSet
type	The psi type
freq	The injection frequency.
minDpsi	The minimal delta psi with which outliers will be injected.
minCoverage	The minimal total coverage (i.e. N) required for a junction to be considered for injection of an outlier.
deltaDistr	The distribution from which the delta psi value of the injections is drawn (default: uniform distribution).
verbose	Should additional information be printed during computation?
method	Defines by which method the new psi of injections is computed, i.e. to which value the delta psi of the injection is added: "meanPSI" for adding to the mean psi of the junction over all samples or "samplePSI" to add to the psi value of the junction in the specific sample. "simulatedPSI" is only possible if a simulated dataset is used.
BPPARAM	A BiocParallel object to run the computation in parallel

Value

FraserDataSet

Examples

```
# A generic dataset
fds <- makeSimulatedFraserDataSet()
fds <- injectOutliers(fds, minDpsi=0.2, freq=1E-3)
```

K

Getter/setter for count data

Description

Getter/setter for count data
 setter for count data

Usage

```
K(fds, type = currentType(fds))

N(fds, type = currentType(fds))

## S4 method for signature 'FraserDataSet'
counts(object, type = NULL, side = c("ofInterest", "otherSide"))

## S4 replacement method for signature 'FraserDataSet,ANY'
counts(object, type = NULL, side = c("ofInterest", "otherSide"), ...) <- value
```

Arguments

<code>fds, object</code>	FraserDataSet
<code>type</code>	The psi type.
<code>side</code>	"ofInterest" for junction counts, "other" for sum of counts of all other junctions at the same donor site (psi5) or acceptor site (psi3), respectively.
<code>...</code>	Further parameters that are passed to <code>assays(object,...)</code>
<code>value</code>	An integer matrix containing the counts.

Value

FraserDataSet

Examples

```
fds <- createTestFraserDataSet()

counts(fds, type="psi5", side="ofInterest")
counts(fds, type="psi5", side="other")
head(K(fds, type="psi3"))
head(N(fds, type="theta"))
```

`length,FraserDataSet-method`

retrieve the length of the object (aka number of junctions)

Description

retrieve the length of the object (aka number of junctions)

Usage

```
## S4 method for signature 'FraserDataSet'
length(x)
```

Arguments

<code>x</code>	FraserDataSet
----------------	---------------

Value

Length of the object.

loadFraserDataSet *Loading/Saving FraserDataSets*

Description

This is a convenient function to load and save a FraserDataSet object. It loads and saves the FraserDataSet objects and HDF5 files on disk under the given working dir. Internally it uses HDF5 files for all assays.

Usage

```
loadFraserDataSet(dir, name = NULL, file = NULL, upgrade = FALSE)
```

```
saveFraserDataSet(fds, dir = NULL, name = NULL, rewrite = FALSE)
```

Arguments

dir	A path where to save the objects (replaces the working directory)
name	The analysis name of the project (saved within the 'dir')
file	The file path to the fds-object.RDS file that should be loaded.
upgrade	Should the version of the loaded object be updated?
fds	A FraserDataSet object to be saved
rewrite	logical if the object should be rewritten. This makes sense if you have filtered or subsetted the object and want to save only the subsetted version

Value

FraserDataSet

Examples

```
fds <- createTestFraserSettings()
name(fds) <- "saveing_test"

# make sure the object is saved to disc
dontWriteHDF5(fds) <- FALSE
fdsSaved <- saveFraserDataSet(fds)
fdsSaved

# load object from disc
fdsLoaded <- loadFraserDataSet(dir=workingDir(fds), name=name(fds))
fdsLoaded

all.equal(fdsSaved, fdsLoaded)
```

`makeSimulatedFraserDataSet`*Create an simulated example data set for FRASER*

Description

Simulates a data set based on random counts following a beta binomial (or Dirichlet-Multinomial) distribution.

Usage

```
makeSimulatedFraserDataSet(  
  m = 100,  
  j = 500,  
  q = 10,  
  distribution = c("BB", "DM"),  
  ...  
)
```

Arguments

<code>m</code>	Number of simulated samples
<code>j</code>	Number of simulated junctions
<code>q</code>	number of simulated latent variables.
<code>distribution</code>	Either "BB" for a beta-binomial simulation or "DM" for a dirichlet-multinomial simulation.
<code>...</code>	Further arguments used to construct the FraserDataSet.

Value

An FraserDataSet containing an example dataset based on simulated data

Examples

```
# A generic dataset  
fds1 <- makeSimulatedFraserDataSet()  
fds1  
  
# A generic dataset with specified sample size and injection method  
fds2 <- makeSimulatedFraserDataSet(m=10, j=100, q=3)  
fds2
```

mergeExternalData	<i>Merge external data</i>
-------------------	----------------------------

Description

To boost its own sequencing data, one can download existing and precounted data. This function merges the existing FraserDataSet with external count data.

Usage

```
mergeExternalData(fds, countFiles, sampleIDs, annotation = NULL)
```

Arguments

fds	A FraserDataSet
countFiles	A character vector of file names pointing to the external count data. The vector has to be names or the files have to start with k_j, k_theta, n_psi3, n_psi5, n_theta.
sampleIDs	The samples to be merged from the external data.
annotation	A sample annotation of the external data (optional).

Details

For more details on existing datasets have a look at: <<https://github.com/gagneurlab/drop#datasets>>
Since FRASER can not hand NA values, the merge will return only the intersecting regions and will drop any non overlapping features. This has to be kept in mind when analysing rare disease samples.

Value

Merged FraserDataSet object.

Examples

```
anno <- fread(system.file("extdata", "externalCounts",  
  "annotation.tsv.gz", package="FRASER"))  
ctsFiles <- list.files(full.names = TRUE, pattern="counts",  
  system.file("extdata", "externalCounts", package="FRASER"))  
  
fds <- createTestFraserDataSet()  
fds_merged <- mergeExternalData(fds, ctsFiles, anno[,sampleID], anno)  
  
K(fds, "psi5")  
K(fds_merged, "psi5")
```

optimHyperParams *Find optimal encoding dimension*

Description

Finds the optimal encoding dimension by injecting artificial splicing outlier ratios while maximizing the precision-recall curve.

Usage

```
optimHyperParams(
  fds,
  type,
  implementation = "PCA",
  q_param = seq(2, min(40, ncol(fds)), by = 3),
  noise_param = 0,
  minDeltaPsi = 0.1,
  iterations = 5,
  setSubset = 50000,
  injectFreq = 0.01,
  BPPARAM = bpparam(),
  internalThreads = 1,
  plot = TRUE,
  delayed = ifelse(ncol(fds) <= 300, FALSE, TRUE),
  ...
)
```

Arguments

fds	A FraserDataSet object
type	The type of PSI (psi5, psi3 or theta for theta/splicing efficiency)
implementation	The method that should be used to correct for confounders.
q_param	Vector specifying which values of q should be tested
noise_param	Vector specifying which noise levels should be tested.
minDeltaPsi	Minimal delta psi of an intron to be considered a variable intron.
iterations	The maximal number of iterations. When the autoencoder has not yet converged after these number of iterations, the fit stops anyway.
setSubset	The size of the subset of the most variable introns that should be used for the hyperparameter optimization.
injectFreq	The frequency with which outliers are injected into the data.
BPPARAM	the BiocParallel parameters for the parallelization
internalThreads	The number of threads used internally.

plot	If TRUE, a plot of the area under the curve and the model loss for each evaluated parameter combination will be displayed after the hyperparameter optimization finishes.
delayed	If FALSE, count matrices will be loaded into memory (faster calculations), otherwise the function works on the delayedMatrix representations (more memory efficient). The default value depends on the number of samples in the fds-object.
...	Additional parameters passed to injectOutliers.

Value

FraserDataSet

See Also[FRASER](#)**Examples**

```
# generate data
fds <- makeSimulatedFraserDataSet(m=15, j=20)

# run hyperparameter optimization
fds <- optimHyperParams(fds, type="psi5", q_param=c(2, 5))

# get estimated optimal dimension of the latent space
bestQ(fds, type="psi5")
hyperParams(fds, type="psi5")
```

plotFunctions

*Visualization functions for FRASER***Description**

The FRASER package provides multiple functions to visualize the data and the results of a full data set analysis.

Plots the p values over the delta psi values, known as volcano plot. Visualizes per sample the outliers. By type and aggregate by gene if requested.

Plot the number of aberrant events per samples

Plots the observed split reads of the junction of interest over all reads coming from the given donor/acceptor.

Plots the expected psi value over the observed psi value of the given junction.

Plots the quantile-quantile plot

Histogram of the geometric mean per junction based on the filter status

Histogram of minimal delta psi per junction

Count correlation heatmap function

Usage

```
## S4 method for signature 'FraserDataSet'
plotVolcano(
  object,
  sampleID,
  type = c("psi3", "psi5", "theta"),
  basePlot = TRUE,
  aggregate = FALSE,
  main = NULL,
  label = NULL,
  deltaPsiCutoff = 0.3,
  padjCutoff = 0.1,
  ...
)

## S4 method for signature 'FraserDataSet'
plotAberrantPerSample(
  object,
  main,
  type = c("psi3", "psi5", "theta"),
  padjCutoff = 0.1,
  zScoreCutoff = NA,
  deltaPsiCutoff = 0.3,
  aggregate = TRUE,
  BPPARAM = bpparam(),
  ...
)

plotExpression(
  fds,
  type = c("psi5", "psi3", "theta"),
  site = NULL,
  result = NULL,
  colGroup = NULL,
  basePlot = TRUE,
  main = NULL,
  label = "aberrant",
  ...
)

plotExpectedVsObservedPsi(
  fds,
  type = c("psi5", "psi3", "theta"),
  idx = NULL,
  result = NULL,
  colGroup = NULL,
  main = NULL,
  basePlot = TRUE,
```

```
    label = "aberrant",
    ...
)

## S4 method for signature 'FraserDataSet'
plotQQ(
  object,
  type = NULL,
  idx = NULL,
  result = NULL,
  aggregate = FALSE,
  global = FALSE,
  main = NULL,
  conf.alpha = 0.05,
  samplingPrecision = 3,
  basePlot = TRUE,
  label = "aberrant",
  Ncpus = min(3, getDTthreads()),
  ...
)

## S4 method for signature 'FraserDataSet'
plotEncDimSearch(
  object,
  type = c("psi3", "psi5", "theta"),
  plotType = c("auc", "loss")
)

plotFilterExpression(
  fds,
  bins = 200,
  legend.position = c(0.8, 0.8),
  onlyVariableIntrons = FALSE
)

plotFilterVariability(
  fds,
  bins = 200,
  legend.position = c(0.8, 0.8),
  onlyExpressedIntrons = FALSE
)

## S4 method for signature 'FraserDataSet'
plotCountCorHeatmap(
  object,
  type = c("psi5", "psi3", "theta"),
  logit = FALSE,
  topN = 50000,
```

```

topJ = 5000,
minMedian = 1,
minCount = 10,
main = NULL,
normalized = FALSE,
show_rownames = FALSE,
show_colnames = FALSE,
minDeltaPsi = 0.1,
annotation_col = NA,
annotation_row = NA,
border_color = NA,
nClust = 5,
plotType = c("sampleCorrelation", "junctionSample"),
sampleClustering = NULL,
plotMeanPsi = TRUE,
plotCov = TRUE,
...
)

```

Arguments

object, fds	An FraserDataSet object.
sampleID	A sample ID which should be plotted. Can also be a vector. Integers are treated as indices.
type	The psi type: either psi5, psi3 or theta (for SE).
basePlot	if TRUE (default), use the R base plot version, else use the plotly framework.
aggregate	If TRUE, the pvalues are aggregated by gene (default), otherwise junction level pvalues are used (default for Q-Q plot).
main	Title for the plot, if missing a default title will be used.
label	Indicates the genes or samples that will be labelled in the plot (only for basePlot=TRUE). Setting label="aberrant" will label all aberrant genes or samples. Labelling can be turned off by setting label=NULL. The user can also provide a custom list of gene symbols or sampleIDs.
padjCutoff, zScoreCutoff, deltaPsiCutoff	Significance, Z-score or delta psi cutoff to mark outliers
...	Additional parameters passed to plot() or plot_ly() if not stated otherwise in the details for each plot function
BPPARAM	BiocParallel parameter to use.
result	The result table to be used by the method.
colGroup	Group of samples that should be colored.
idx, site	A junction site ID or gene ID or one of both, which should be plotted. Can also be a vector. Integers are treated as indices.
global	Flag to plot a global Q-Q plot, default FALSE
conf.alpha	If set, a confidence interval is plotted, defaults to 0.05

samplingPrecision	Plot only non overlapping points in Q-Q plot to reduce number of points to plot. Defines the digits to round to.
Ncpus	Number of cores to use.
plotType	The type of plot that should be shown as character string. For plotEncDimSearch, it has to be either "auc" for a plot of the area under the curve (AUC) or "loss" for the model loss. For the correlation heatmap, it can be either "sampleCorrelation" for a sample-sample correlation heatmap or "junctionSample" for a junction-sample correlation heatmap.
bins	Set the number of bins to be used in the histogram.
legend.position	Set legend position (x and y coordinate), defaults to the top right corner.
onlyVariableIntrons	Logical value indicating whether to show only introns that also pass the variability filter. Defaults to FALSE.
onlyExpressedIntrons	Logical value indicating whether to show only introns that also pass the expression filter. Defaults to FALSE.
logit	If TRUE, the default, psi values are plotted in logit space.
topN	Top x most variable junctions that should be used for the calculation of sample x sample correlations.
topJ	Top x most variable junctions that should be displayed in the junction-sample correlation heatmap. Only applies if plotType is "junctionSample".
minMedian, minCount, minDeltaPsi	Minimal median ($m \geq 1$), delta psi ($ \Delta\psi > 0.1$), read count ($n \geq 10$) value of a junction to be considered for the correlation heatmap.
normalized	If TRUE, the normalized psi values are used, the default, otherwise the raw psi values
show_rownames, show_colnames	Logical value indicating whether to show row or column names on the heatmap axes.
annotation_col, annotation_row	Row or column annotations that should be plotted on the heatmap.
border_color	Sets the border color of the heatmap
nClust	Number of clusters to show in the row and column dendrograms.
sampleClustering	A clustering of the samples that should be used as an annotation of the heatmap.
plotMeanPsi, plotCov	If TRUE, then the heatmap is annotated with the mean psi values or the junction coverage.

Details

This is the list of all plotting function provided by FRASER:

- `plotAberrantPerSample()`
- `plotVolcano()`
- `plotExpression()`
- `plotQQ()`
- `plotExpectedVsObservedPsi()`
- `plotCountCorHeatmap()`
- `plotFilterExpression()`
- `plotFilterVariability()`
- `plotEncDimSearch()`

For a detailed description of each plot function please see the details. Most of the functions share the same parameters.

`plotAberrantPerSample`: The number of aberrant events per sample are plotted sorted by rank. The ... parameters are passed on to the `aberrant` function.

`plotVolcano`: the volcano plot is sample-centric. It plots for a given sample and psi type the negative log10 nominal P-values against the delta psi values for all splice sites or aggregates by gene if requested.

`plotExpression`: This function plots for a given site the read count at this site (i.e. K) against the total coverage (i.e. N) for the given psi type ($\psi_5, \psi_3, or \theta$ (SE)) for all samples.

`plotQQ`: the quantile-quantile plot for a given gene or if `global` is set to TRUE over the full data set. Here the observed P-values are plotted against the expected ones in the negative log10 space.

`plotExpectedVsObservedPsi`: A scatter plot of the observed psi against the predicted psi for a given site.

`plotCountCorHeatmap`: The correlation heatmap of the count data either of the full data set (i.e. sample-sample correlations) or of the top x most variable junctions (i.e. junction-sample correlations). By default the values are log transformed and row centered. The ... arguments are passed to the `pheatmap` function.

`plotFilterExpression`: The distribution of FPKM values. If the `FraserDataSet` object contains the `passedFilter` column, it will plot both FPKM distributions for the expressed introns and for the filtered introns.

`plotFilterVariability`: The distribution of maximal delta Psi values. If the `FraserDataSet` object contains the `passedFilter` column, it will plot both maximal delta Psi distributions for the variable introns and for the filtered (i.e. non-variable) introns.

`plotEncDimSearch`: Visualization of the hyperparameter optimization. It plots the encoding dimension against the achieved loss (area under the precision-recall curve). From this plot the optimum should be chosen for the q in fitting process.

Value

If base R graphics are used nothing is returned else the plotly or the gplot object is returned.

Examples

```

# create full FRASER object
fds <- makeSimulatedFraserDataSet(m=40, j=200)
fds <- calculatePSIValues(fds)
fds <- filterExpressionAndVariability(fds, filter=FALSE)
# this step should be done for all splicing metrics and more dimensions
fds <- optimHyperParams(fds, "psi5", q_param=c(2,5,10,25))
fds <- FRASER(fds)

# QC plotting
plotFilterExpression(fds)
plotFilterVariability(fds)
plotCountCorHeatmap(fds, "theta")
plotCountCorHeatmap(fds, "theta", normalized=TRUE)
plotEncDimSearch(fds, type="psi5")

# extract results
plotAberrantPerSample(fds, aggregate=FALSE)
plotVolcano(fds, "sample1", "psi5")

# dive into gene/sample level results
res <- results(fds)
res
plotExpression(fds, result=res[1])
plotQQ(fds, result=res[1])
plotExpectedVsObservedPsi(fds, type="psi5", res=res[1])

```

psiTypes

Available psi types

Description

Available psi types

Usage

```
psiTypes
```

Format

An object of class character of length 3.

Examples

```

# to show available psi types:
psiTypes

```

 results,FraserDataSet-method

Extracting results and aberrant splicing events

Description

The result function extracts the results from the given analysis object based on the given options and cutoffs. The aberrant function extracts aberrant splicing events based on the given cutoffs.

Usage

```
## S4 method for signature 'FraserDataSet'
results(
  object,
  sampleIDs = samples(object),
  padjCutoff = 0.05,
  zScoreCutoff = NA,
  deltaPsiCutoff = 0.3,
  minCount = 5,
  psiType = c("psi3", "psi5", "theta"),
  additionalColumns = NULL,
  BPPARAM = bpparam(),
  ...
)

resultsByGenes(res, geneColumn = "hgncSymbol", method = "BY")

## S4 method for signature 'FraserDataSet'
aberrant(
  object,
  type = currentType(object),
  padjCutoff = 0.05,
  deltaPsiCutoff = 0.3,
  zScoreCutoff = NA,
  minCount = 5,
  by = c("none", "sample", "feature"),
  aggregate = FALSE,
  ...
)
```

Arguments

object	A FraserDataSet object
sampleIDs	A vector of sample IDs for which results should be retrieved
padjCutoff	The FDR cutoff to be applied or NA if not requested.
zScoreCutoff	The z-score cutoff to be applied or NA if not requested.

deltaPsiCutoff	The cutoff on delta psi or NA if not requested.
minCount	The minimum count value of the total coverage of an intron to be considered as significant. result
psiType	The psi types for which the results should be retrieved.
additionalColumns	Character vector containing the names of additional columns from mcols(fds) that should appear in the result table (e.g. ensembl_gene_id). Default is NULL, so no additional columns are included.
BPPARAM	The BiocParallel parameter.
...	Further arguments can be passed to the method. If "zscores", "pajVals" or "dPsi" is given, the values of those arguments are used to define the aberrant events.
res	Result as created with results()
geneColumn	The name of the column in mcols(res) that contains the gene symbols.
method	The p.adjust method that is being used to adjust p values per sample.
type	Splicing type (psi5, psi3 or theta)
by	By default none which means no grouping. But if sample or feature is specified the sum by sample or feature is returned
aggregate	If TRUE the returned object is based on the grouped features

Value

For results: GRanges object containing significant results. For aberrant: Either a of logical values of size introns/genes x samples if "by" is NA or a vector with the number of aberrant events per sample or feature depending on the vaule of "by"

Examples

```
# get data, fit and compute p-values and z-scores
fds <- createTestFraserDataSet()

# extract results: for this example dataset, z score cutoff of 2 is used to
# get at least one result and show the output
res <- results(fds, padjCutoff=NA, zScoreCutoff=3, deltaPsiCutoff=0.05)
res

# aggregate the results by genes (gene symbols need to be annotated first
# using annotateRanges() function)
resultsByGenes(res)

# get aberrant events per sample: on the example data, nothing is aberrant
# based on the adjusted p-value
aberrant(fds, type="psi5", by="sample")

# get aberrant events per gene (first annotate gene symbols)
fds <- annotateRangesWithTxDb(fds)
aberrant(fds, type="psi5", by="feature", zScoreCutoff=2, padjCutoff=NA,
```

```

        aggregate=TRUE)

# find aberrant junctions/splice sites
aberrant(fds, type="psi5")

```

samples	<i>Getter/Setter methods for the FraserDataSet The following methods are getter and setter methods to extract or set certain values of a FraserDataSet object. samples sets or gets the sample IDs; condition ; nonSplicedReads return a RangedSummarizedExperiment object containing the counts for the non spliced reads overlapping splice sites in the fds.</i>
---------	---

Description

Getter/Setter methods for the FraserDataSet

The following methods are getter and setter methods to extract or set certain values of a FraserDataSet object.

samples sets or gets the sample IDs; condition ; nonSplicedReads return a RangedSummarizedExperiment object containing the counts for the non spliced reads overlapping splice sites in the fds.

Mapping of chromosome names

Usage

```

samples(object)

samples(object) <- value

condition(object)

condition(object) <- value

bamFile(object)

bamFile(object) <- value

name(object)

name(object) <- value

strandSpecific(object)

strandSpecific(object) <- value

pairedEnd(object)

```

```
pairedEnd(object) <- value
workingDir(object)
workingDir(object) <- value
scanBamParam(object)
scanBamParam(object) <- value
nonSplicedReads(object)
nonSplicedReads(object) <- value
## S4 method for signature 'FraserDataSet'
samples(object)
## S4 replacement method for signature 'FraserDataSet'
samples(object) <- value
## S4 method for signature 'FraserDataSet'
condition(object)
## S4 replacement method for signature 'FraserDataSet'
condition(object) <- value
## S4 method for signature 'FraserDataSet'
bamFile(object)
## S4 replacement method for signature 'FraserDataSet'
bamFile(object) <- value
## S4 method for signature 'FraserDataSet'
name(object)
## S4 replacement method for signature 'FraserDataSet'
name(object) <- value
## S4 method for signature 'FraserDataSet'
workingDir(object)
## S4 replacement method for signature 'FraserDataSet'
workingDir(object) <- value
## S4 method for signature 'FraserDataSet'
strandSpecific(object)
```

```

## S4 replacement method for signature 'FraserDataSet'
strandSpecific(object) <- value

## S4 method for signature 'FraserDataSet'
pairedEnd(object)

## S4 replacement method for signature 'FraserDataSet'
pairedEnd(object) <- value

## S4 method for signature 'FraserDataSet'
scanBamParam(object)

## S4 replacement method for signature 'FraserDataSet'
scanBamParam(object) <- value

## S4 method for signature 'FraserDataSet'
nonSplicedReads(object)

## S4 replacement method for signature 'FraserDataSet'
nonSplicedReads(object) <- value

FRASER.mcols.get(x, type = NULL, ...)

FRASER.rowRanges.get(x, type = NULL, ...)

mapSeqlevels(fds, style = "UCSC", ...)

```

Arguments

object	A FraserDataSet object.
value	The new value that should replace the current one.
x	A FraserDataSet object.
type	The psi type (psi3, psi5 or theta)
...	Further parameters. For mapSeqLevels: further parameters passed to Genome-InfoDb::mapSeqlevels().
fds	FraserDataSet
style	The style of the chromosome names.

Value

Getter method return the respective current value.

Author(s)

Christian Mertes <mertes@in.tum.de>
 Ines Scheller <scheller@in.tum.de>

Examples

```

fds <- createTestFraserDataSet()
samples(fds)
samples(fds) <- 1:dim(fds)[2]
condition(fds)
condition(fds) <- 1:dim(fds)[2]
bamFile(fds) # file.paths or objects of class BamFile
bamFile(fds) <- file.path("bamfiles", samples(fds), "rna-seq.bam")
name(fds)
name(fds) <- "My Analysis"
workingDir(fds)
workingDir(fds) <- tempdir()
strandSpecific(fds)
strandSpecific(fds) <- TRUE
strandSpecific(fds) <- "reverse"
strandSpecific(fds)
scanBamParam(fds)
scanBamParam(fds) <- ScanBamParam(mapqFilter=30)
nonSplicedReads(fds)
rowRanges(fds)
rowRanges(fds, type="theta")
mcols(fds, type="psi5")
mcols(fds, type="theta")
seqlevels(fds)
seqlevels(mapSeqlevels(fds, style="UCSC"))
seqlevels(mapSeqlevels(fds, style="Ensembl"))
seqlevels(mapSeqlevels(fds, style="dbSNP"))

```

subset.FRASER

*Subsetting by indices for junctions***Description**

Providing subsetting by indices through the single-bracket operator

Usage

```

## S3 method for class 'FRASER'
subset(x, i, j, by = c("j", "ss"))

## S4 method for signature 'FraserDataSet,ANY,ANY,ANY'
x[i, j, by = c("j", "ss")]

```

Arguments

x	A FraserDataSet object
i	A integer vector to subset the rows/ranges
j	A integer vector to subset the columns/samples
by	a character (j or ss) defining if we subset by junctions or splice sites

Value

A subsetted FraserDataSet object

Examples

```
fds <- createTestFraserDataSet()
fds[1:10,2:3]
fds[,samples(fds) %in% c("sample1", "sample2")]
fds[1:10,by="ss"]
```

Index

- * **datasets**
 - psiTypes, [35](#)
- [,FraserDataSet,ANY,ANY,ANY-method
 - (subset.FRASER), [41](#)
- 'featureExclusionMask<-'
 - (getter_setter_functions), [19](#)
- aberrant, [34](#)
- aberrant,FraserDataSet-method
 - (results,FraserDataSet-method), [36](#)
- addCountsToFraserDataSet, [10](#)
- addCountsToFraserDataSet (countRNA), [7](#)
- annotateRanges, [3](#)
- annotateRangesWithTxDb
 - (annotateRanges), [3](#)
- assayNames,FraserDataSet-method, [4](#)
- assays,FraserDataSet-method, [5](#)
- assays<- ,FraserDataSet,DelayedMatrix-method
 - (assays,FraserDataSet-method), [5](#)
- assays<- ,FraserDataSet,list-method
 - (assays,FraserDataSet-method), [5](#)
- assays<- ,FraserDataSet,SimpleList-method
 - (assays,FraserDataSet-method), [5](#)
- available.genomes, [9](#)
- bamFile (samples), [38](#)
- bamFile,FraserDataSet-method (samples), [38](#)
- bamFile<- (samples), [38](#)
- bamFile<- ,FraserDataSet-method (samples), [38](#)
- bestQ (getter_setter_functions), [19](#)
- calculatePadjValues (FRASER), [15](#)
- calculatePSIValues, [6](#)
- calculatePvalues (FRASER), [15](#)
- calculateZscore (FRASER), [15](#)
- condition (samples), [38](#)
- condition,FraserDataSet-method (samples), [38](#)
- condition<- (samples), [38](#)
- condition<- ,FraserDataSet-method (samples), [38](#)
- countNonSplicedReads, [10](#)
- countNonSplicedReads (countRNA), [7](#)
- countRNA, [7](#)
- countRNAData, [10](#)
- countRNAData (countRNA), [7](#)
- counts,FraserDataSet-method (K), [23](#)
- counts<- ,FraserDataSet,ANY-method (K), [23](#)
- countSplitReads, [10](#)
- countSplitReads (countRNA), [7](#)
- createTestFraserDataSet
 - (createTestFraserSettings), [11](#)
- createTestFraserSettings, [11](#)
- currentType (getter_setter_functions), [19](#)
- currentType<- (getter_setter_functions), [19](#)
- deltaPsiValue
 - (getter_setter_functions), [19](#)
- dontWriteHDF5
 - (getter_setter_functions), [19](#)
- dontWriteHDF5<- (getter_setter_functions), [19](#)
- fds-methods (samples), [38](#)
- featureExclusionMask
 - (getter_setter_functions), [19](#)
- featureExclusionMask,
 - (getter_setter_functions), [19](#)
- featureExclusionMask<- (getter_setter_functions), [19](#)

- filterExpression, FraserDataSet-method (filtering), 12
- filterExpressionAndVariability (filtering), 12
- filtering, 12
- filterVariability (filtering), 12
- fit, 14, 17
- FRASER, 14, 15, 15, 29
- FRASER.mcols.get (samples), 38
- FRASER.rowRanges.get (samples), 38
- FraserDataSet, 6, 8, 10, 13–16, 18, 18, 28, 32, 36
- FraserDataSet-class, 19
- getBSgenome, 9
- getNonSplitReadCountsForAllSamples, 10
- getNonSplitReadCountsForAllSamples (countRNA), 7
- getSplitReadCountsForAllSamples, 10
- getSplitReadCountsForAllSamples (countRNA), 7
- getter_setter_functions, 19
- hyperParams (getter_setter_functions), 19
- injectOutliers, 22
- K, 23
- keytypes, 3
- length, FraserDataSet-method, 24
- loadFraserDataSet, 25
- makeSimulatedFraserDataSet, 26
- mapSeqlevels (samples), 38
- mergeCounts, 10
- mergeCounts (countRNA), 7
- mergeExternalData, 27
- N (K), 23
- name (samples), 38
- name, FraserDataSet-method (samples), 38
- name<- (samples), 38
- name<-, FraserDataSet-method (samples), 38
- nonSplicedReads (samples), 38
- nonSplicedReads, FraserDataSet-method (samples), 38
- nonSplicedReads<- (samples), 38
- nonSplicedReads<-, FraserDataSet-method (samples), 38
- optimHyperParams, 15, 16, 28
- padjVals (getter_setter_functions), 19
- padjVals, (getter_setter_functions), 19
- pairedEnd (samples), 38
- pairedEnd, FraserDataSet-method (samples), 38
- pairedEnd<- (samples), 38
- pairedEnd<-, FraserDataSet-method (samples), 38
- pheatmap, 34
- plotAberrantPerSample (plotFunctions), 29
- plotAberrantPerSample, FraserDataSet-method (plotFunctions), 29
- plotCountCorHeatmap (plotFunctions), 29
- plotCountCorHeatmap, FraserDataSet-method (plotFunctions), 29
- plotEncDimSearch (plotFunctions), 29
- plotEncDimSearch, FraserDataSet-method (plotFunctions), 29
- plotExpectedVsObservedPsi (plotFunctions), 29
- plotExpression (plotFunctions), 29
- plotFilterExpression (plotFunctions), 29
- plotFilterVariability (plotFunctions), 29
- plotFunctions, 29
- plotQQ (plotFunctions), 29
- plotQQ, FraserDataSet-method (plotFunctions), 29
- plotVolcano (plotFunctions), 29
- plotVolcano, FraserDataSet-method (plotFunctions), 29
- predictedMeans (getter_setter_functions), 19
- pseudocount (getter_setter_functions), 19
- psiTypes, 35
- pVals (getter_setter_functions), 19
- pVals, (getter_setter_functions), 19
- results, FraserDataSet-method, 36
- resultsByGenes (results, FraserDataSet-method), 36

rho (getter_setter_functions), 19
rho, (getter_setter_functions), 19

samples, 38
samples,FraserDataSet-method (samples),
38
samples<- (samples), 38
samples<- ,FraserDataSet-method
(samples), 38
saveFraserDataSet (loadFraserDataSet),
25
scanBamParam (samples), 38
scanBamParam,FraserDataSet-method
(samples), 38
scanBamParam<- (samples), 38
scanBamParam<- ,FraserDataSet-method
(samples), 38
strandSpecific (samples), 38
strandSpecific,FraserDataSet-method
(samples), 38
strandSpecific<- (samples), 38
strandSpecific<- ,FraserDataSet-method
(samples), 38
subset.FRASER, 41
summarizeJunctions, 9

useEnsembl, 3

verbose (getter_setter_functions), 19
verbose<- (getter_setter_functions), 19

workingDir (samples), 38
workingDir,FraserDataSet-method
(samples), 38
workingDir<- (samples), 38
workingDir<- ,FraserDataSet-method
(samples), 38

zScore, (getter_setter_functions), 19
zScores (getter_setter_functions), 19