

BufferedMatrixMethods

April 12, 2012

`BufferedMatrix.read.probematrix`

Read CEL file data into PM or MM BufferedMatrix

Description

Read CEL data into [BufferedMatrix](#) objects.

Usage

```
BufferedMatrix.read.probematrix(..., filenames = character(0), celfile.path=NULL, rm.mask = FALSE,
```

Arguments

<code>...</code>	file names separated by comma.
<code>filenames</code>	file names in a character vector.
<code>celfile.path</code>	path where CEL files are located
<code>rm.mask</code>	should the spots marked as 'MASKS' set to NA ?
<code>rm.outliers</code>	should the spots marked as 'OUTLIERS' set to NA
<code>rm.extra</code>	if TRUE, overrides what is in <code>rm.mask</code> and <code>rm.outliers</code>
<code>verbose</code>	verbosity flag
<code>which</code>	should be either "pm", "mm" or "both"
<code>cdfname</code>	Used to specify the name of an alternative cdf package. If set to NULL, the usual cdf package based on Affymetrix' mappings will be used.

Value

A list of one or two [BufferedMatrix](#) objects. Each [BufferedMatrix](#) objects is either PM or MM data. No [AffyBatch](#) is created.

Author(s)

Ben Bolstad <bmb@bmbolstad.com>

See Also

[AffyBatch](#), [read.affybatch](#)

BufferedMatrix.justRMA

Use BufferedMatrix objects to facilitate RMA computation with low memory overhead

Description

Read CEL data into [BufferedMatrix](#) objects.

Usage

```
BufferedMatrix.justRMA(..., filenames=character(0), celfile.path=NULL,
                        phenoData=new("AnnotatedDataFrame"),
                        description=NULL,
                        notes="",
                        verbose=FALSE, background=TRUE, normalize=TRUE,
                        cdfname = NULL)
```

Arguments

...	file names separated by comma.
filenames	file names in a character vector.
celfile.path	path where CEL files are located
phenoData	a AnnotatedDataFrame object
description	a MIAME object
notes	notes
verbose	verbosity flag
normalize	logical value. If TRUE normalize data using quantile normalization
background	logical value. If TRUE background correct using RMA background correction
cdfname	Used to specify the name of an alternative cdf package. If set to NULL, the usual cdf package based on Affymetrix' mappings will be used.

Value

An ExpressionSet object, containing expression values identical to what one would get from running [rma](#) on an [AffyBatch](#).

Author(s)

Ben Bolstad <bmb@bmbolstad.com>

See Also

[BufferedMatrix](#), [BufferedMatrix.read.probematrix](#)

`BufferedMatrix.read.celfiles`*Read CEL file data into PM or MM BufferedMatrix*

Description

Read CEL data into [BufferedMatrix](#) objects.

Usage

```
BufferedMatrix.read.celfiles(..., filenames = character(0), celfile.path=NULL)
```

Arguments

<code>...</code>	file names separated by comma.
<code>filenames</code>	file names in a character vector.
<code>celfile.path</code>	path where CEL files are located

Value

A [BufferedMatrix](#) object containing the CEL file intensities.

Author(s)

Ben Bolstad <bmb@bmbolstad.com>

See Also

[BufferedMatrix](#), [BufferedMatrix.read.probematrix](#)

`RMA preprocess BufferedMatrix`*RMA preprocessing functions that work on BufferedMatrix objects*

Description

This group of functions can be used to apply the RMA background correction, Quantile normalization and Median polish summarization to data stored in a [BufferedMatrix](#) object.

Usage

```
bg.correct.BufferedMatrix(x, copy=TRUE)
normalize.BufferedMatrix.quantiles(x, copy=TRUE)
BufferedMatrix.bg.correct.normalize.quantiles(x, copy=TRUE)
```

Arguments

x	a BufferedMatrix containing data to be processed
copy	should the BufferedMatrix be copied or should the input object be changed on output

Value

In the case of `normalize.BufferedMatrix.quantiles` and `bg.correct.BufferedMatrix` a [BufferedMatrix](#) is returned. The function `median.polish.summarize` returns a [matrix](#).

The function `BufferedMatrix.bg.correct.normalize.quantiles` carries out both pre-processing steps with a single command.

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

See Also

[rma](#)

Index

*Topic **manip**

RMA preprocess BufferedMatrix, 3

AffyBatch, 1, 2

AnnotatedDataFrame, 2

bg.correct.BufferedMatrix (RMA
preprocess BufferedMatrix), 3

BufferedMatrix, 1–4

BufferedMatrix.bg.correct.normalize.quantiles
(RMA preprocess
BufferedMatrix), 3

BufferedMatrix.justRMA, 2

BufferedMatrix.read.celfiles, 3

BufferedMatrix.read.probematrix, 1, 2, 3

matrix, 4

median.polish.summarize (RMA
preprocess BufferedMatrix), 3

median.polish.summarize, BufferedMatrix-method
(RMA preprocess
BufferedMatrix), 3

MIAME, 2

normalize.BufferedMatrix.quantiles
(RMA preprocess
BufferedMatrix), 3

read.affybatch, 1

rma, 2, 4

RMA preprocess BufferedMatrix, 3