

# methylumi

February 9, 2012

---

MethyLumi-class      *The base class for storing Illumina Methylation data*

---

## Description

This class inherits from [eSet](#) from the Biobase package and is used as a base class for the other two methylumi classes, [MethyLumiSet](#) and [MethyLumiQC](#).

## Objects from the Class

The `MethyLumi` class is a virtual class and is not meant to be instantiated. Instead, one should instantiate a [MethyLumiSet](#) or a [MethyLumiQC](#) object.

## Slots

`assayData`: Object of class "AssayData"  
`phenoData`: Object of class "AnnotatedDataFrame"  
`featureData`: Object of class "AnnotatedDataFrame" that will hold the annotation columns from the Beadstudio output, if they are available.  
`experimentData`: Object of class "MIAME"  
`annotation`: Object of class "character"; note that this slot is not currently used, but may be used in the future to store the character name of the annotation package, if available.  
`.__classVersion__`: Object of class "Versions"

## Extends

Class "[eSet](#)", directly. Class "[VersionedBiobase](#)", by class "eSet", distance 2. Class "[Versioned](#)", by class "eSet", distance 3.

## Methods

**pvals**<- signature(object = "MethyLumi", value = "matrix"): Set the assay-Data slot of the same name and stores the P-values from BeadStudio

**pvals** signature(object = "MethyLumi"): Get the assayData slot of the same name

**betas**<- signature(object = "MethyLumi", value = "matrix"): Set the assay-Data slot of the same name and represents the methylation values for the samples, analogous to `exprs()` in gene expression data.

**betas** signature(object = "MethyLumi"): Get the assayData slot of the same name

**methylated<-** signature(object = "MethyLumi", value = "matrix"): Set the assayData slot that represents the Methylated single-channel signal

**methylated** signature(object = "MethyLumi"): Get the assayData slot that represents the Methylated single-channel signal

**unmethylated<-** signature(object = "MethyLumi", value = "matrix"): Set the assayData slot that represents the Unmethylated single-channel signal

**unmethylated** signature(object = "MethyLumi"): Get the assayData slot that represents the Unmethylated single-channel signal

**controlTypes** signature(object = "MethyLumi"): Find the unique control type beads in the QCdata slot.

**qcplot** signature(object = "MethyLumi", what, ...): Plot of QC data. This plot can be useful for diagnosing the problems associated with specific samples or arrays. The value for "what" is one of the control types (which can be found by using controlTypes() on the object.

**summary** signature(object = "MethyLumi", ...): summary method for MethyLumi objects.

#### Author(s)

Sean Davis <sdavis2@mail.nih.gov>

#### See Also

[methylumiR](#), [MethyLumiSet](#), [MethyLumiQC](#), [eSet](#)

#### Examples

```
## The class structure
showClass("MethyLumi")
## read in some data
## Read in sample information
samps <- read.table(system.file("extdata/samples.txt",
                              package = "methylumi"), sep="\t", header=TRUE)

## Perform the actual data reading
## This is an example of reading data from a
## Sentrix Array format file (actually two files,
## one for data and one for QC probes)
mldat <- methylumiR(system.file('extdata/EXAMPLEDATA/samples.txt',
                              package='methylumi'),
                  qcfile=system.file('extdata/EXAMPLEDATA/controls.txt',
                                      package="methylumi"),
                  sampleDescriptions=samps)
mldat
## Get history information
getHistory(mldat)
## Get QC data, which is another eSet-derived object
QCdata(mldat)
```

---

MethyLumiM-class	<i>Class "MethyLumiM": for Illumina Methylation microarray data using logRatios</i>
------------------	---

---

## Description

MethyLumiM is a class inherited from [ExpressionSet-class](#). It is designed for Illumina Methylation microarray data. The `exprs` dataMatrix included in the `assayData` slot of MethyLumiM object includes a matrix of M-values, which is the log<sub>2</sub> ratio of methylated and unmethylated probe intensities. The MethyLumiM class include a boxplot function uniquely designed for two-mode histogram data. It also include a `coerce` function to map from [MethyLumi-class](#), [MethyLumiSet-class](#) or other [eSet-class](#) inherited object to MethyLumiM class object.

## Objects from the Class

Objects can be created by calls of the form `new("MethyLumiM", exprs, methylated, unmethylated, detection, methylated.N, unmethylated.N, ..., assayData)`. The "exprs" is a matrix of M-values, which is the log<sub>2</sub> ratio of methylated and unmethylated probe intensities; "methylated" and "unmethylated" are intensity matrix measured by methylated and unmethylated probes of Illumina Infinium methylation microarray; "detection" is the detection p-value outputted by Illumina GenomeStudio software; "methylated.N" and "unmethylated.N" are bead numbers for methylated and unmethylated probes. "exprs", "methylated" and "unmethylated" information are required for MethyLumiM class. When creating a new MethyLumiM object, the information of "exprs", "methylated", "unmethylated" and "detection" can also be provided directly through "assayData".

## Slots

`history`: Object of class "data.frame" recording the operation history of the LumiBatch object.

`controlData`: Object of class "MethyLumiQC" to keep the QC probe measurement information.

`assayData`: Object of class "AssayData", which includes "exprs", "methylated", "unmethylated", "detection", "methylated.N" and "unmethylated.N" data matrix

`phenoData`: Object of class "AnnotatedDataFrame", See [eSet-class](#)

`featureData`: Object of class "AnnotatedDataFrame", See [eSet-class](#)

`experimentData`: Object of class "MIAME", See [eSet-class](#)

`annotation`: Object of class "character", See [eSet-class](#)

`protocolData`: Object of class "AnnotatedDataFrame", See [eSet-class](#)

`.__classVersion__`: Object of class "Versions", See [eSet-class](#)

## Extends

Class "[ExpressionSet](#)", directly. Class "[eSet](#)", by class "ExpressionSet", distance 2. Class "[VersionedBiobase](#)", by class "ExpressionSet", distance 3. Class "[Versioned](#)", by class "ExpressionSet", distance 4.

**Methods**

**boxplot** signature(x = "MethyLumiM"): plot distribution of M-value

**coerce** signature(from = "eSet", to = "MethyLumiM"): map from [MethyLumi-class](#), [MethyLumiSet-class](#) or other [eSet-class](#) inherited object to MethyLumiM class object. MethyLumiM object will only keep "exprs", "methylated", "unmethylated" and "detection" data matrix in the assayData.

**getHistory** signature(object = "MethyLumiM"): access the operation history of MethyLumiM object.

**initialize** signature(.Object = "MethyLumiM"): class initialization

**methylated** signature(object = "MethyLumiM"): retrieve the data matrix measured by methylated probes

**methylated<-** signature(object = "MethyLumiM"): set the data matrix measured by methylated probes

**unmethylated** signature(object = "MethyLumiM"): retrieve the data matrix measured by unmethylated probes

**unmethylated<-** signature(object = "MethyLumiM"): set the data matrix measured by unmethylated probes

**methylated.N** signature(object = "MethyLumiM"): retrieve the data matrix keeping the number of beads of methylated probes

**methylated.N<-** signature(object = "MethyLumiM"): set the data matrix keeping the number of beads of methylated probes

**unmethylated.N** signature(object = "MethyLumiM"): retrieve the data matrix keeping the number of beads of unmethylated probes

**unmethylated.N<-** signature(object = "MethyLumiM"): set the data matrix keeping the number of beads of unmethylated probes

**detection** signature(object = "MethyLumiM"): retrieve detection data matrix in AssayData-class

**detection<-** signature(object = "MethyLumiM"): set detection data matrix in AssayData-class

**controlData** signature(object = "MethyLumiM"): retrieve the controlData in MethyLumiQC-class

**controlData<-** signature(object = "MethyLumiM"): set controlData in MethyLumiQC-class

**Author(s)**

Pan DU

**References**

1. Du, P., Zhang, X., Huang, C.C., Jafari, N., Kibbe, W.A., Hou, L., and Lin, S.M., (2010) 'Comparison of Beta-value and M-value methods for quantifying methylation levels by microarray analysis'

**See Also**

[MethyLumi-class](#) and [MethyLumiSet-class](#)

**Examples**

```
showClass("MethyLumiM")
```

---

MethyLumiQC-class    *Class "MethyLumiQC" for holding Illumina methylation QC data*

---

## Description

This class inherits from the MethyLumi class (and therefore, from eSet in Biobase) and is designed to hold QC data from Illumina Beadstudio output. These data can be potentially useful when determining the cause for quality problems.

## Objects from the Class

Objects can be created by calls of the form `new("MethyLumiQC", assayData, phenoData, featureData, experimentData, annotation, betas)`.

## Slots

**assayData:** Object of class "AssayData"  
**phenoData:** Object of class "AnnotatedDataFrame"  
**featureData:** Object of class "AnnotatedDataFrame" containing the annotation columns from the Illumina Beadstudio output. In particular, the names of the probes describe the types of control probes.  
**experimentData:** Object of class "MIAME"  
**annotation:** Object of class "character", not currently used  
**.\_\_classVersion\_\_:** Object of class "Versions"

## Extends

Class "[MethyLumi](#)", directly. Class "[eSet](#)", by class "MethyLumi", distance 2. Class "[VersionedBiobase](#)", by class "MethyLumi", distance 3. Class "[Versioned](#)", by class "MethyLumi", distance 4.

## Methods

**initialize** signature(.Object = "MethyLumiQC")  
**Cy3.N** signature(object = "MethyLumiQC"): ...  
**Cy3<-** signature(object = "MethyLumiQC", value = "matrix"): ...  
**Cy5.N** signature(object = "MethyLumiQC"): ...  
**Cy5<-** signature(object = "MethyLumiQC", value = "matrix"): ...  
**QCdata<-** signature(object = "MethyLumiSet", value = "MethyLumiQC"): ...  
**combine** signature(x = "MethyLumiQC", y = "MethyLumiQC"): ...  
**controlData<-** signature(object = "MethyLumiSet", value = "MethyLumiQC"): ...  
 ...  
**controlTypes** signature(object = "MethyLumiQC"): determine the character vector of control types from the QCdata information  
**hist** signature(x = "MethyLumiQC"): ...  
**intensitiesByChannel** signature(object = "MethyLumiQC"): ...  
**methyated** signature(object = "MethyLumiQC"): ...

```

negctls.stderr signature(object = "MethyLumiQC", channel = "character"):
  ...
negctls.stderr signature(object = "MethyLumiQC", channel = "missing"):...
negctls signature(object = "MethyLumiQC", channel = "character"):...
negctls signature(object = "MethyLumiQC", channel = "missing"):...
negnorm signature(object = "MethyLumiQC", channel = "character"):...
negnorm signature(object = "MethyLumiQC", channel = "missing"):...
normctls signature(object = "MethyLumiQC"):...
qcplot signature(object = "MethyLumiQC", what, ...): QC plots of various con-
  troltypes
unmethylated signature(object = "MethyLumiQC"):...

```

**Author(s)**

Sean Davis <sdavis2@mail.nih.gov>

**See Also**

[methylumiR](#), [MethyLumiSet](#), [MethyLumi](#), [eSet](#)

**Examples**

```
showClass("MethyLumiQC")
```

---

MethyLumiSet-class *Class "MethyLumiSet" for containing Illumina methylation data*

---

**Description**

This class inherits from the MethyLumi class (and therefore, from eSet in Biobase) and is designed to hold both the intensities and the calculated betas, as well as pvalues if present.

**Objects from the Class**

Objects can be created by calls of the form `new("MethyLumiSet", assayData, phenoData, featureData, experimentData, annotation, betas)`. An object of this type is the main storage class for methylation data from Illumina. Subsetting, etc., works as normal (rows represent genes, columns represent samples). There is also a rudimentary history tracking system that is modeled after that from the lumi package.

**Slots**

**QC:** Object of class "QCDataOrNULL", containing either the [MethyLumiQC](#) object or NULL  
**history:** Object of class "data.frame", containing a running history of transforms to the data contained herein  
**assayData:** Object of class [AssayData](#)  
**phenoData:** Object of class [AnnotatedDataFrame](#)  
**featureData:** Object of class [AnnotatedDataFrame](#), containing the annotation columns from the Illumina Beadstudio output

**experimentData:** Object of class `MIAME`  
**annotation:** Object of class "character", not currently used  
**.\_\_classVersion\_\_:** Object of class "Versions"  
**protocolData:** Object of class "AnnotatedDataFrame" that contains protocol information, including scan date if available

### Extends

Class "`MethyLumi`", directly. Class "`methylData`", directly. Class "`eSet`", by class "`MethyLumi`", distance 2. Class "`VersionedBiobase`", by class "`MethyLumi`", distance 3. Class "`Versioned`", by class "`MethyLumi`", distance 4.

### Methods

**[ signature(x = "MethyLumiSet")]:** subsetting, genes as rows, samples as columns  
**betas<-** signature(object = "MethyLumiSet", value = "matrix"): Set the assayData slot of the same name  
**betas** signature(object = "MethyLumiSet"): Get the assayData slot of the same name  
**boxplot** signature(x = "MethyLumiSet"): boxplot of all sample betas  
**combine** signature(x = "MethyLumiSet", y = "MethyLumiSet")  
**corplot** signature(x = "MethyLumiSet")  
**exprs** signature(object = "MethyLumiSet"): returns m-values  
**getHistory** signature(object = "MethyLumiSet"): returns a data.frame containing the history for this object  
**hist** signature(x = "MethyLumiSet"): histogram of the betas for the data  
**initialize** signature(.Object = "MethyLumiSet")  
**pairs** signature(x = "MethyLumiSet"): pairs plot of the betas for the object. Note that pairs plots of more than a few samples are not very useful.  
**plotSampleIntensities** signature(x = "MethyLumiSet"): The intensities as output by the Beadstudio software often show a considerable amount of dye bias. This method shows a graphical example of this dye bias. In short, for each of the Cy3 and Cy5 channels, a cutoff in beta is used to calculate which Cy3 and Cy5 values should be plotted at high-methylation and low-methylation status. Any offset between Cy3 and Cy5 when plotted in this way likely represents dye bias and will lead to biases in the estimate of beta.  
**QCdata<-** signature(object = "MethyLumiSet", value = "MethyLumiQC"): assign QC data to the QC slot  
**QCdata** signature(object = "MethyLumiSet"): retrieve the QC data.  
**show** signature(object = "MethyLumiSet")  
**methylated<-** signature(object = "MethyLumiSet", value = "matrix"): Set the assayData slot associated with methylated intensity  
**methylated** signature(object = "MethyLumiSet"): Get the assayData slot associated with methylated intensity  
**unmethylated<-** signature(object = "MethyLumiSet", value = "matrix"): Set the assayData slot associated with unmethylated intensity  
**unmethylated** signature(object = "MethyLumiSet"): Get the assayData slot associated with unmethylated intensity

**qcplot** signature(object = "MethyLumiSet", what, ...): QC plots of various controltypes

**controlTypes** signature(object = "MethyLumiSet"): determine the character vector of control types from the QCdata information

**Cy3.N** signature(object = "MethyLumiSet"):...

**Cy5.N** signature(object = "MethyLumiSet"):...

**combine27k450k** signature(x = "MethyLumiSet", y = "MethyLumiSet"):...

**controlData** signature(object = "MethyLumiSet"):...

**controlData<-** signature(object = "MethyLumiSet", value = "MethyLumiQC"):...

...

**featureFilter** signature(eset = "MethyLumiSet"):...

**intensities.IB** signature(x = "MethyLumiSet", channel = "character"):...

**intensities.IB** signature(x = "MethyLumiSet", channel = "missing"):...

**intensities.M** signature(x = "MethyLumiSet", channel = "character"):...

**intensities.M** signature(x = "MethyLumiSet", channel = "missing"):...

**intensities.OOB.allelic** signature(x = "MethyLumiSet", channel = "character", allele = "character"):...

**intensities.OOB.allelic** signature(x = "MethyLumiSet", channel = "missing", allele = "missing"):...

**intensities.OOB** signature(x = "MethyLumiSet", channel = "character"):...

**intensities.OOB** signature(x = "MethyLumiSet", channel = "missing"):...

**intensities.U** signature(x = "MethyLumiSet", channel = "character"):...

**intensities.U** signature(x = "MethyLumiSet", channel = "missing"):...

**intensitiesByChannel** signature(object = "MethyLumiSet"):...

**negctls.stderr** signature(object = "MethyLumiSet", channel = "character"):...

...

**negctls.stderr** signature(object = "MethyLumiSet", channel = "missing"):...

...

**negctls** signature(object = "MethyLumiSet", channel = "character"):...

**negctls** signature(object = "MethyLumiSet", channel = "missing"):...

**negnorm** signature(object = "MethyLumiSet", channel = "character"):...

**negnorm** signature(object = "MethyLumiSet", channel = "missing"):...

**normctls** signature(object = "MethyLumiSet"):...

**plotSampleIntensities** signature(x = "MethyLumiSet"):...

**probeNAs** signature(object = "MethyLumiSet"):...

**sampleNAs** signature(object = "MethyLumiSet"):...

**total.intensity** signature(object = "MethyLumiSet"):...

**varFilter** signature(eset = "MethyLumiSet"):...

**Author(s)**

Sean Davis &amp; Tim Triche, Jr.

**See Also**

[methylumiR](#), [normalizeMethyLumiSet](#), [methylumIDAT](#), [MethyLumiQC](#), [eSet](#)

**Examples**

```
showClass("MethyLumiSet")
```

---

estimateM

*Estimate methylation M-value matrix*

---

**Description**

Estimate methylation M-value matrix from MethyLumiM-class object or eSet-class object, which include methylated and unmethylated probe intensities

**Usage**

```
estimateM(methylumiM, returnType=c("ExpressionSet", "matrix"), offset=1)
```

**Arguments**

methylumiM	MethyLumiM-class object or eSet-class object, which include methylated and unmethylated probe intensities
returnType	determine whether return an ExpressionSet (MethyLumiM in this case) or matrix object
offset	offset added to the methylated and unmethylated probe intensities when estimating the M-value

**Details**

M-value is the log<sub>2</sub> ratio between Illumina methylated and unmethylated probe intensities. As variations of small intensities can cause big changes in the ratio estimation, so an offset is added to methylated and unmethylated probe intensities when estimating the M-value.

Please check the lumi package for more details of estimateM function.

**Value**

A MethyLumiM or matrix object of methylation M-value

**Author(s)**

Pan DU

**References**

Du, P., Zhang, X., Huang, C.C., Jafari, N., Kibbe, W.A., Hou, L., and Lin, S.M., (2010) 'Comparison of Beta-value and M-value methods for quantifying methylation levels by microarray analysis', (under review)

```
extractBarcodeAndPosition
```

*Extract the Barcode and Position Information from Satrix ID*

---

### Description

The satrix IDs from an illumina satrix array contain positional information that might be useful. This function simply extracts that information from the ID itself.

### Usage

```
extractBarcodeAndPosition(satrixids)
```

### Arguments

satrixids     A character vector of satrix IDs that look like: 1632405013\\_R001\\_C001

### Value

A data.frame with three columns:

satrix	numeric, the satrix ID
row	numeric, the satrix row
column	numeric, the satrix column

### Author(s)

Sean Davis <sdavis2@mail.nih.gov>

### See Also

methyLumiR

### Examples

```
extractBarcodeAndPosition(c('12341234_R001_C001'))
```

---

```
featureFilter
```

*Annotation-based Filtering of Features (CpG sites) in a MethyLumiSet or MethyLumiM object*

---

### Description

Features with insufficient annotation carry little value for the subsequent data analysis. The function `featureFilter` provides options of filtering features (CpG sites) from a `MethyLumiSet` (or `MethyLumiM`) object based on available annotation data.

**Usage**

```
featureFilter(eset, require.entrez=FALSE,
             require.GOBP=FALSE, require.GOCC=FALSE,
             require.GOMF=FALSE, exclude.ChrX=FALSE,
             require.closeToTSS=FALSE, range.DistToTSS=c(-500, 300),
             require.CpGisland=FALSE, ...)
```

**Arguments**

`eset` A `MethyLumiSet` or `MethyLumiM` object.

`require.entrez` If `TRUE`, filter out features without an Entrez Gene ID annotation.

`require.GOBP`, `require.GOCC`, `require.GOMF` If `TRUE`, filter out features whose target genes are not annotated to at least one GO term in BP, CC and MF ontology, respectively.

`exclude.ChrX` If `TRUE`, filter out features in chromosome X to avoid gender effect.

`require.closeToTSS` If `TRUE`, filter out features that are not close to transcription start site (TSS). Features without annotation of distance to TSS will also be removed. Can only be used for GoldenGate platform.

`range.DistToTSS` Ignored if `require.closeToTSS` is `FALSE`. A vector of numeric values of length 2, indicating the range of tolerable distance from transcription start site (TSS) in basepair (bp). If `require.closeToTSS` is `TRUE`, features whose distance to TSS falls outside this designated range will be removed. The default value is `c(-500, 300)`, where `-500` represents the distance to TSS from the left and `300` the distance from the right.

`require.CpGisland` If `TRUE`, filter out features that are not in CpG islands.

`...` Unused, but available for specializing methods.

**Value**

The function `featureFilter` returns a list consisting of:

`eset` The filtered `MethyLumiSet` or `MethyLumiM` object.

`filter.log` A list giving details of how many probe sets were removed for each annotation-based filtering step performed.

**Author(s)**

Chao-Jen Wong <[cwon2@fhcrc.org](mailto:cwon2@fhcrc.org)>

**References**

R. Bourgon, R. Gentleman, W. Huber, *Independent filtering increases power for detecting differentially expressed genes*, PNAS, vol. 107, no. 21, pp:9546-9551.

**See Also**

[nsFilter](#)

MethyLumi-accessors

*methylumi accessors*

---

**Description**

These functions serve as getters and setters for information in methylumi classes.

**Usage**

```
betas (object)
pvals (object)
methylated (object)
unmethylated (object)
getHistory (object)
QCdata (object)
```

**Arguments**

object            an object of class MethyLumi or a subclass

**Details**

See the methods definitions in [MethyLumiSet](#) and [MethyLumiQC](#) for details.

**Author(s)**

Sean Davis <sdavis2@mail.nih.gov>

**See Also**

[normalizeMethyLumiSet](#), [MethyLumiSet](#), [MethyLumiQC](#), [eSet](#)

---

getAssayDataNameSubstitutions

*Return a data.frame of AssayData name substitutions.*

---

**Description**

The Illumina methylation platforms use two distinct platforms, the "goldengate" platform and the "infinium" platform. Each of these uses different file formats as well as different assay technologies. To make the downstream data handling more straightforward and uniform between the two different systems, a simple mapping from the column names in the output files from the Illumina software is used to convert things from Red/Green or Cy5/Cy3 to unmethylated/methylated. This function simply returns that mapping.

**Usage**

```
getAssayDataNameSubstitutions ()
```

**Details**

A file in the extdata directory called "substitutions.txt" contains two columns. The function loads this file and uses the first column as a match against column names in the data file (with the "sample part" removed). If matched, the second column gives the replacement.

**Value**

A data.frame with two columns, regex and replacement.

**Author(s)**

Sean Davis <seandavi@gmail.com>

**Examples**

```
getAssayDataNameSubstitutions()
```

---

methylData-class    *Class "methylData", superclass for MethyLumiSet and MethyLumiM*

---

**Description**

A superclass (virtual) for MethyLumiSet and MethyLumiM.

**Objects from the Class**

A virtual Class: No objects may be created from it.

**Methods**

**diagnostics** signature(x = "methylData"): diagnostic plots of data

**methylated.N** signature(object = "methylData"): accessor for assayData element of the same name

**methylated.N<-** signature(object = "methylData", value = "matrix"): replace method for assayData element of the same name

**plotNAs** signature(object = "methylData"): ...

**pval.detect** signature(object = "methylData"): accessor for assayData element of the same name

**pval.detect<-** signature(object = "methylData", value = "numeric"): replace method for assayData element of the same name

**unmethylated.N** signature(object = "methylData"): accessor for assayData element of the same name

**unmethylated.N<-** signature(object = "methylData", value = "matrix"): replace method for assayData element of the same name

**Author(s)**

Tim Triche, Jr.

**See Also**

[MethyLumiSet](#), [MethyLumiM](#)

**Examples**

```
showClass("methylData")
```

---

methylumIDAT	<i>methylumIDAT</i>
--------------	---------------------

---

**Description**

Read a directory of methylumi idat files and return a `MethylumiSet`.

**Usage**

```
methylumIDAT(barcodes = NULL, pdat = NULL, parallel = F, n = T, n.sd =
F, oob = T, idatPath=getwd(), ...)
```

**Arguments**

barcodes	A vector of barcodes to read. Either this argument or <code>pdat</code> must be specified.
pdat	A data.frame describing the samples. A special column named "barcodes" can be used to specify the barcodes to be read.
parallel	If TRUE, an attempt will be made to process using multiple cores on a multicore machine.
n	
n.sd	
oob	
idatPath	The path to the directory containing the idat files.
...	

**Details**

Read a set of .idat files and return a `MethylumiSet` object.

**Value**

A `MethylumiSet` object.

**Author(s)**

Tim Triche, Jr.

## Examples

```
## Not run:
if(require('IlluminaHumanMethylation450k.db')) {
  barcodes <- c('6005486014_R04C02',
               '6005486023_R05C01')
  lumi450k <- methylumIDAT(barcodes, idatPath=system.file('extdata/idat', package='methylum'),
                             sampleNames(lumi450k) <- c('TCGA1', 'TCGA2'))
  show(lumi450k)
}

## End (Not run)
```

---

methylumi-package *Handle Illumina methylation data*

---

## Description

This package contains a class structure for handling methylation data from Illumina as well as utility functions for loading the data from files generated by Illumina. Normalization that attempts to correct for dye bias is also included.

Important data classes include: [MethyLumiSet](#) and [MethyLumiQC](#), both of which are subsets of the [MethyLumi](#) class, which is a subset of the [eSet](#) class.

A worked example of the use of the package can be found by typing: `openVignette()`.

A full listing of the available documentation can be obtained by typing `help.start()` and selecting `methylumi` from the `Packages` link or by typing `library(help="methylumi")`.

## Details

Package: methylumi  
Type: Package  
License: GPL

## Author(s)

Sean Davis <[sdavis2@mail.nih.gov](mailto:sdavis2@mail.nih.gov)>

## References

<http://watson.nci.nih.gov/~sdavis/software/R>

## See Also

[Biobase](#)

---

methyLumiGenerics *Generics defined in methyLumi*

---

**Description**

See the individual classes for details of methods.

**Author(s)**

Sean Davis, Pan Du, and Tim Triche, Jr.

---

methyLumiR *Load data from Illumina methylation platform*

---

**Description**

This function is useful for loading Illumina methylation data into a MethyLumiSet object. Sample information can be supplied and will then be incorporated into the resulting phenoData slot.

**Usage**

```
methyLumiR(filename, qcfile=NULL, sampleDescriptions = NULL, ...)
```

**Arguments**

filename	A filename of the excel-like file from BeadStudio
qcfile	A filename of the excel-like file from BeadStudio
sampleDescriptions	A data.frame that contains at least one column, SampleID (case insensitive). This column MUST match the part of the column headers before the .Avg_Beta, etc. Also, if a column called SampleLabel (case insensitive), it is used for sample labels, IF the sampleLabel column contains unique identifiers
...	Passed into read.delim()

**Details**

Used to construct a MethyLumiSet object...

**Value**

A MethyLumiSet object

**Author(s)**

Sean Davis <sdavis2@mail.nih.gov>

**See Also**

[MethyLumiSet-class](#), [MethyLumiQC-class](#)

**Examples**

```
## Read in sample information
samps <- read.table(system.file("extdata/samples.txt",
                               package = "methylumi"), sep="\t", header=TRUE)

## Perform the actual data reading
## This is an example of reading data from an
## Sentrix Array format file (actually two files,
## one for data and one for QC probes)
mldat <- methylumiR(system.file('extdata/exempladata.samples.txt', package='methylumi'),
                     qcfile=system.file('extdata/exempladata.controls.txt', package="methylumi"),
                     sampleDescriptions=samps)

mldat
```

mldat

*Example SAM format Illumina methylation dataset***Description**

This is an example `MethyLumiSet` object.

**Usage**

```
data(mldat)
```

**Examples**

```
data(mldat)
```

---

```
normalizeMethyLumiSet
```

*Normalize a MethyLumiSet, accounting for dye bias***Description**

The Illumina GoldenGate methylation platform uses two colors, one to represent the unmethylated state and the other to represent the methylated state. This function corrects that dye bias and recalculates the betas based on the corrected intensities.

For `HumanMethylation27` data, the function does nothing.

For `HumanMethylation450` data, the function delegates to `normalizeViaControls()` the task of scaling red and green intensities against a reference array (chip) which defaults to the first chip in a set. The code to do this is based on code from the 'minfi' package and uses the built-in normalization controls to scale the channels of the samples, so that a consistent degree of dye bias is maintained for Infinium II probes across an experiment or set of experiments.

**Usage**

```
normalizeMethyLumiSet(x, beta.cuts = c(0.2, 0.8), mapfun = c("atan", "ratio"))
```

**Arguments**

x	A MethyLumiSet object
beta.cuts	Two numeric values with the first less than the second and between 0 and 1, representing the beta cutoffs that will be used when determining the median intensities to which to correct. See details below.
mapfun	Either "atan" or "ratio". See details below.

**Details**

For HumanMethylation450 data, the function delegates to `normalizeViaControls()` the task of scaling red and green intensities against a reference array (chip) which defaults to the first chip in a set. The code to do this is based on code from the 'minfi' package and uses the built-in normalization controls to scale the channels of the samples, so that a consistent degree of dye bias is maintained for Infinium II probes across an experiment or set of experiments. The remainder of the documentation below is specific to GoldenGate data.

The Illumina GoldenGate methylation platform uses two colors, one to represent the unmethylated state and the other to represent the methylated state. This function corrects that dye bias and recalculates the betas based on the corrected intensities.

As a first step, the medians for each of Cy3 and Cy5 are calculated at high and low betas, representing the (nearly) fully methylated state and the (nearly) fully unmethylated states. Values of Cy3 and Cy5 that are negative are set to zero for this process. Then, the Cy5 medians are adjusted to match those of the Cy3 channel, thereby correcting the dye bias.

To map the new intensities back to betas, one of two map functions can be used. The default is the `atan(Cy3/Cy5)`. The ratio maps using the function `(Cy3/Cy3+Cy5)`. The differences should be very small, but we feel that the `atan` map function is probably the mathematically appropriate way of doing this.

**Value**

A new "MethyLumiSet" that contains the corrected betas and the adjusted intensities.

**Author(s)**

Sean Davis <sdavis2@mail.nih.gov>

**Examples**

```
## Read in sample information
samps <- read.table(system.file("extdata/samples.txt",
                              package = "methylumi"), sep="\t", header=TRUE)

## Perform the actual data reading
## This is an example of reading data from an
## Sentrix Array format file (actually two files,
## one for data and one for QC probes)
mldat <- methylumiR(system.file('extdata/EXAMPLEDATA.samples.txt', package='methylumi'),
                   qcfile=system.file('extdata/EXAMPLEDATA.controls.txt', package="methylumi"),
                   sampleDescriptions=samps)
mldatnorm <- normalizeMethyLumiSet(mldat)
```

---

```
plotSampleIntensities
```

*Plot the sample intensities.*

---

**Description**

The Illumina methylation platforms all show a significant dye bias. The `plotSampleIntensities` method shows the density plots for the two channels allowing direct visualization of the effect.

**Usage**

```
plotSampleIntensities(x, beta.cuts, s)
```

**Arguments**

<code>x</code>	an object of class <code>MethyLumi</code> or a subclass
<code>beta.cuts</code>	cutoffs for low and high beta values
<code>s</code>	sample number to plot

**Examples**

```
data(mldat)
plotSampleIntensities(mldat, s=1)
```

---

```
qcplot
```

*Methods for dealing with control data for Illumina methylation data.*

---

**Description**

The `qcplot` function simply generates a plot of the control probe information for a given `controlType`.

**Usage**

```
qcplot(object, controltype, ...)
controlTypes(object, ...)
```

**Arguments**

<code>object</code>	An object of class <code>MethyLumiSet</code> or <code>MethyLumiQC</code>
<code>controltype</code>	A single character value representing the bead type to plot from the quality control data. The available types are accessible via the <code>controlTypes</code> method.
<code>...</code>	passed to plot function

**Details**

The descriptions of the various control types can be obtained from the Illumina methylation user's guides.

**Author(s)**

Sean Davis <sdavis2@mail.nih.gov>

**See Also**

[MethyLumiSet](#), [MethyLumiQC](#)

**Examples**

```
data(mldat)
controlTypes(mldat)
qcplot(mldat, controlTypes(mldat)[3])
```

---

MethyLumi-strippers

*Strip excessive probe-level data from MethyLumiSets*

---

**Description**

450k datasets with probe-level stderrs, out-of-band intensities, and bead numbers can become huge. These functions help to manage their growth in memory, at least until preprocessing and QC is completed, whereupon the summary data can be exported to a RangedData-based object of some sort for integration.

**Usage**

```
stripMethyLumiSet(object)
stripBeadNs(object)
stripBeadSDs(object)
stripOOB(object)
```

**Arguments**

object            an object of class MethyLumi or a subclass

**Author(s)**

Tim Triche, Jr. <tim.triche@gmail.com>

---

varFilter	<i>Variation-based Filtering of Features (CpG sites) in a MethyLumiSet or MethyLumiM object</i>
-----------	---

---

### Description

The function `varFilter` removes features exhibiting little variation across samples. Such non-specific filtering can be advantageous for downstream data analysis.

### Usage

```
varFilter(eset, var.func=IQR, var.cutoff=0.5, filterByQuantile=TRUE, ...)
```

### Arguments

<code>eset</code>	An <code>MethyLumiSet</code> or <code>MethyLumiM</code> object.
<code>var.func</code>	The function used as the per-feature filtering statistics.
<code>var.cutoff</code>	A numeric value indicating the cutoff value for variation. If <code>filterByQuantile</code> is <code>TRUE</code> , features whose value of <code>var.func</code> is less than <code>var.cutoff-quantile</code> of all <code>var.func</code> value will be removed. If <code>FALSE</code> , features whose values are less than <code>var.cutoff</code> will be removed.
<code>filterByQuantile</code>	A logical indicating whether <code>var.cutoff</code> is to be interpreted as a quantile of all <code>var.func</code> (the default), or as an absolute value.
<code>...</code>	Unused, but available for specializing methods.

### Details

This function is a counterpart of functions `nsFilter` and `varFilter` available from the `genefilter` package. See R. Bourgon et. al. (2010) and `nsFilter` for detail.

It is proven that non-specific filtering, for which the criteria does not depend on sample class, can increase the number of discoveries. Inappropriate choice of test statistics, however, might have adverse effect. `limma`'s moderated  $t$ -statistics, for example, is based on empirical Bayes approach which models the conjugate prior of gene-level variance with an inverse of  $\chi^2$  distribution scaled by observed global variance. As the variance-based filtering removes the set of genes with low variance, the scaled inverse  $\chi^2$  no longer provides a good fit to the data passing the filter, causing the `limma` algorithm to produce a posterior degree-of-freedom of infinity (Bourgon 2010). This leads to two consequences: (i) gene-level variance estimate will be ignored, and (ii) the  $p$ -value will be overly optimistic (Bourgon 2010).

### Value

The function `featureFilter` returns a list consisting of:

<code>eset</code>	The filtered <code>MethyLumiSet</code> or <code>MethyLumiM</code> object.
<code>filter.log</code>	Shows many low-variant features are removed.

### Author(s)

Chao-Jen Wong <cwon2@fhcrc.org>

**References**

R. Bourgon, R. Gentleman, W. Huber, *Independent filtering increases power for detecting differentially expressed genes*, PNAS, vol. 107, no. 21, pp:9546-9551, 2010.

**See Also**

[nsFilter](#)

**Examples**

```
data(mldat)
## keep top 75 percent
filt <- varFilter(mldat, var.cutoff=0.25)
filt$filter.log
dim(filt$eset)
```

# Index

## \*Topic IO

getAssayDataNameSubstitutions,  
12  
MethyLumi-accessors, 12  
methylum-package, 15  
methylumIDAT, 14  
methylumR, 16

## \*Topic classes

methylData-class, 13  
MethyLumi-class, 1  
MethyLumiM-class, 3  
MethyLumiQC-class, 5  
MethyLumiSet-class, 6

## \*Topic datasets

mldat, 17

## \*Topic hplot

plotSampleIntensities, 19  
qcplot, 19

## \*Topic manip

extractBarcodeAndPosition, 10  
normalizeMethyLumiSet, 17

## \*Topic methods

estimateM, 9  
[,MethyLumiM-method  
(MethyLumiM-class), 3  
[,MethyLumiSet-method  
(MethyLumiSet-class), 6  
AnnotatedDataFrame, 6  
AssayData, 6  
betas (MethyLumi-accessors), 12  
betas, MethyLumiM-method  
(MethyLumiM-class), 3  
betas, MethyLumiSet-method  
(MethyLumiSet-class), 6  
betas<- (MethyLumi-accessors), 12  
betas<-, MethyLumiSet, matrix-method  
(MethyLumiSet-class), 6  
Biobase, 15  
boxplot, MethyLumiSet-method  
(MethyLumiSet-class), 6  
combine, MethyLumiM, MethyLumiM-method  
(MethyLumiM-class), 3

combine, MethyLumiQC, MethyLumiQC-method  
(MethyLumiQC-class), 5  
combine, MethyLumiSet, MethyLumiSet-method  
(MethyLumiSet-class), 6  
combine27k450k  
(methylumGenerics), 16  
combine27k450k, MethyLumiSet, MethyLumiSet-method  
(MethyLumiSet-class), 6  
compare.chips  
(methylumGenerics), 16  
controlData (methylumGenerics),  
16  
controlData, MethyLumiM-method  
(MethyLumiM-class), 3  
controlData, MethyLumiSet-method  
(MethyLumiSet-class), 6  
controlData<-  
(methylumGenerics), 16  
controlData<-, MethyLumiM, ANY-method  
(MethyLumiM-class), 3  
controlData<-, MethyLumiSet  
(MethyLumiSet-class), 6  
controlData<-, MethyLumiSet, MethyLumiQC-method  
(MethyLumiQC-class), 5  
controlTypes, 19  
controlTypes (qcplot), 19  
controlTypes, MethyLumiM-method  
(MethyLumiM-class), 3  
controlTypes, MethyLumiQC-method  
(MethyLumiQC-class), 5  
controlTypes, MethyLumiSet-method  
(MethyLumiSet-class), 6  
corplot (MethyLumi-accessors), 12  
corplot, MethyLumiSet-method  
(MethyLumiSet-class), 6  
cy3 (methylumGenerics), 16  
Cy3.N (methylumGenerics), 16  
Cy3.N, MethyLumiQC-method  
(MethyLumiQC-class), 5  
Cy3.N, MethyLumiSet-method  
(MethyLumiSet-class), 6  
Cy3<- (methylumGenerics), 16  
Cy3<-, MethyLumiQC, matrix-method

- (MethyLumiQC-class)*, 5
- cy5 (*methylumiGenerics*), 16
- Cy5.N (*methylumiGenerics*), 16
- Cy5.N, *MethyLumiQC*-method  
(*MethyLumiQC-class*), 5
- Cy5.N, *MethyLumiSet*-method  
(*MethyLumiSet-class*), 6
- Cy5<- (*methylumiGenerics*), 16
- Cy5<-, *MethyLumiQC*, matrix-method  
(*MethyLumiQC-class*), 5
  
- designIItoMandU  
(*methylumiGenerics*), 16
- designItoMandU  
(*methylumiGenerics*), 16
- detection (*methylumiGenerics*), 16
- detection, *MethyLumiM*-method  
(*MethyLumiM-class*), 3
- detection<- (*methylumiGenerics*),  
16
- detection<- , *MethyLumiM*-method  
(*MethyLumiM-class*), 3
- diagnostics (*methylumiGenerics*),  
16
- diagnostics, *methylData*-method  
(*methylData-class*), 13
  
- eSet, 1-3, 5-7, 9, 12, 15
- eSet-class, 3, 4
- estimateM, 9
- ExpressionSet, 3
- ExpressionSet-class, 3
- exprs, *MethyLumiSet*-method  
(*MethyLumiSet-class*), 6
- extractBarcodeAndPosition, 10
  
- featureFilter, 10
- featureFilter, *MethyLumiM*-method  
(*featureFilter*), 10
- featureFilter, *MethyLumiSet*-method  
(*featureFilter*), 10
  
- getAssayDataNameSubstitutions, 12
- getBarcodes (*methylumiGenerics*),  
16
- getHistory (*MethyLumi-accessors*),  
12
- getHistory, *MethyLumiM*-method  
(*MethyLumiM-class*), 3
- getHistory, *MethyLumiSet*-method  
(*MethyLumiSet-class*), 6
- getProtocolData  
(*methylumiGenerics*), 16
  
- hist, *MethyLumiQC*-method  
(*MethyLumiQC-class*), 5
- hist, *MethyLumiSet*-method  
(*MethyLumiSet-class*), 6
  
- IDATsToDFs (*methylumiGenerics*), 16
- IDATtoDF (*methylumiGenerics*), 16
- intensities.IB  
(*methylumiGenerics*), 16
- intensities.IB, *MethyLumiSet*, character-method  
(*MethyLumiSet-class*), 6
- intensities.IB, *MethyLumiSet*, missing-method  
(*MethyLumiSet-class*), 6
- intensities.M  
(*methylumiGenerics*), 16
- intensities.M, *MethyLumiSet*, character-method  
(*MethyLumiSet-class*), 6
- intensities.M, *MethyLumiSet*, missing-method  
(*MethyLumiSet-class*), 6
- intensities.OOB  
(*methylumiGenerics*), 16
- intensities.OOB, *MethyLumiSet*, character-method  
(*MethyLumiSet-class*), 6
- intensities.OOB, *MethyLumiSet*, missing-method  
(*MethyLumiSet-class*), 6
- intensities.OOB.allelic, *MethyLumiSet*, character  
(*MethyLumiSet-class*), 6
- intensities.OOB.allelic, *MethyLumiSet*, missing, n  
(*MethyLumiSet-class*), 6
- intensities.U  
(*methylumiGenerics*), 16
- intensities.U, *MethyLumiSet*, character-method  
(*MethyLumiSet-class*), 6
- intensities.U, *MethyLumiSet*, missing-method  
(*MethyLumiSet-class*), 6
- intensitiesByChannel  
(*methylumiGenerics*), 16
- intensitiesByChannel, *MethyLumiM*-method  
(*MethyLumiM-class*), 3
- intensitiesByChannel, *MethyLumiQC*-method  
(*MethyLumiQC-class*), 5
- intensitiesByChannel, *MethyLumiSet*-method  
(*MethyLumiSet-class*), 6
  
- lumiCSV (*methylumiGenerics*), 16
- lumIDAT (*methylumiGenerics*), 16
  
- mergeProbeDesigns  
(*methylumiGenerics*), 16
- methylated (*MethyLumi-accessors*),  
12
- methylated, *MethyLumi*-method  
(*MethyLumi-class*), 1

- methylated, MethyLumiM-method  
(*MethyLumiM-class*), 3
- methylated, MethyLumiQC-method  
(*MethyLumiQC-class*), 5
- methylated, MethyLumiSet-method  
(*MethyLumiSet-class*), 6
- methylated.N (*methylumiGenerics*),  
16
- methylated.N, methylData-method  
(*methylData-class*), 13
- methylated.N, MethyLumiM-method  
(*MethyLumiM-class*), 3
- methylated.N<-  
(*methylumiGenerics*), 16
- methylated.N<-, methylData, matrix-method  
(*methylData-class*), 13
- methylated.N<-, MethyLumiM, ANY-method  
(*MethyLumiM-class*), 3
- methylated<-  
(*MethyLumi-accessors*), 12
- methylated<-, MethyLumi, matrix-method  
(*MethyLumi-class*), 1
- methylated<-, MethyLumiM, ANY-method  
(*MethyLumiM-class*), 3
- methylated<-, MethyLumiSet, matrix-method  
(*MethyLumiSet-class*), 6
- methylData, 7
- methylData-class, 13
- MethyLumi, 5–7, 15
- methylumi (*methylumi-package*), 15
- MethyLumi-class, 3, 4
- MethyLumi-accessors, 12
- MethyLumi-class, 1
- methylumi-package, 15
- MethyLumi-strippers, 20
- methylumi.bgcorr  
(*methylumiGenerics*), 16
- methylumi.diagnostics  
(*methylumiGenerics*), 16
- methylumiCSV (*methylumiGenerics*),  
16
- methylumIDAT, 9, 14
- methylumiGenerics, 16
- MethyLumiM, 14
- MethyLumiM-class, 3
- MethyLumiQC, 1, 2, 6, 9, 12, 15, 19, 20
- MethyLumiQC-class, 16
- MethyLumiQC-class, 5
- methylumiR, 2, 6, 9, 16
- MethyLumiSet, 1, 2, 6, 12, 14, 15, 17, 19,  
20
- MethyLumiSet-class, 3, 4, 16
- MethyLumiSet-class, 6
- MIAME, 7
- mldat, 17
- NChannelSetToMethyLumiSet  
(*methylumiGenerics*), 16
- negctls (*methylumiGenerics*), 16
- negctls, MethyLumiM, character-method  
(*MethyLumiM-class*), 3
- negctls, MethyLumiM, missing-method  
(*MethyLumiM-class*), 3
- negctls, MethyLumiQC, character-method  
(*MethyLumiQC-class*), 5
- negctls, MethyLumiQC, missing-method  
(*MethyLumiQC-class*), 5
- negctls, MethyLumiSet, character-method  
(*MethyLumiSet-class*), 6
- negctls, MethyLumiSet, missing-method  
(*MethyLumiSet-class*), 6
- negctls.stderr, MethyLumiQC, character-method  
(*MethyLumiQC-class*), 5
- negctls.stderr, MethyLumiQC, missing-method  
(*MethyLumiQC-class*), 5
- negctls.stderr, MethyLumiSet, character-method  
(*MethyLumiSet-class*), 6
- negctls.stderr, MethyLumiSet, missing-method  
(*MethyLumiSet-class*), 6
- negnorm (*methylumiGenerics*), 16
- negnorm, MethyLumiM, character-method  
(*MethyLumiM-class*), 3
- negnorm, MethyLumiM, missing-method  
(*MethyLumiM-class*), 3
- negnorm, MethyLumiQC, character-method  
(*MethyLumiQC-class*), 5
- negnorm, MethyLumiQC, missing-method  
(*MethyLumiQC-class*), 5
- negnorm, MethyLumiSet, character-method  
(*MethyLumiSet-class*), 6
- negnorm, MethyLumiSet, missing-method  
(*MethyLumiSet-class*), 6
- normalizeMethyLumiSet, 9, 12, 17
- normctls (*methylumiGenerics*), 16
- normctls, MethyLumiM-method  
(*MethyLumiM-class*), 3
- normctls, MethyLumiQC-method  
(*MethyLumiQC-class*), 5
- normctls, MethyLumiSet-method  
(*MethyLumiSet-class*), 6
- nsFilter, 11, 21, 22
- pairs, MethyLumiSet-method  
(*MethyLumiSet-class*), 6
- plotNAs (*methylumiGenerics*), 16

- plotNAs, methylData-method  
     (*methylData-class*), 13
- plotNegOob (*methylumiGenerics*), 16
- plotSampleIntensities, 19
- plotSampleIntensities, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- probeNAs (*methylumiGenerics*), 16
- probeNAs, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- probeNAs, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- psummary (*methylumiGenerics*), 16
- pval.detect (*methylumiGenerics*), 16
- pval.detect, methylData-method  
     (*methylData-class*), 13
- pval.detect<-  
     (*methylumiGenerics*), 16
- pval.detect<-, methylData, numeric-method  
     (*methylData-class*), 13
- pvals (*MethyLumi-accessors*), 12
- pvals, MethyLumi-method  
     (*MethyLumi-class*), 1
- pvals, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- pvals<- (*MethyLumi-accessors*), 12
- pvals<-, MethyLumi, matrix-method  
     (*MethyLumi-class*), 1
- qc.probe.plot  
     (*methylumiGenerics*), 16
- QCdata (*MethyLumi-accessors*), 12
- QCdata, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- QCdata, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- QCdata<- (*MethyLumi-accessors*), 12
- QCdata<-, MethyLumiSet  
     (*MethyLumiSet-class*), 6
- QCdata<-, MethyLumiSet, MethyLumiQC-method  
     (*MethyLumiQC-class*), 5
- qcplot, 19
- qcplot, MethyLumi-method  
     (*MethyLumi-class*), 1
- qcplot, MethyLumiQC-method  
     (*MethyLumiQC-class*), 5
- qcplot, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- readMethyLumIDAT  
     (*methylumiGenerics*), 16
- sampleNAs (*methylumiGenerics*), 16
- sampleNAs, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- sampleNAs, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- show, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- stripBeadNs  
     (*MethyLumi-strippers*), 20
- stripBeadSDs  
     (*MethyLumi-strippers*), 20
- stripMethyLumiSet  
     (*MethyLumi-strippers*), 20
- stripOOB (*MethyLumi-strippers*), 20
- subset27kas450k  
     (*methylumiGenerics*), 16
- subset450kas27k  
     (*methylumiGenerics*), 16
- subsetCommonProbes  
     (*methylumiGenerics*), 16
- summary, MethyLumi-method  
     (*MethyLumi-class*), 1
- total.intensity  
     (*methylumiGenerics*), 16
- total.intensity, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- total.intensity, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- unmethylated  
     (*MethyLumi-accessors*), 12
- unmethylated, MethyLumi-method  
     (*MethyLumi-class*), 1
- unmethylated, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- unmethylated, MethyLumiQC-method  
     (*MethyLumiQC-class*), 5
- unmethylated, MethyLumiSet-method  
     (*MethyLumiSet-class*), 6
- unmethylated.N  
     (*methylumiGenerics*), 16
- unmethylated.N, methylData-method  
     (*methylData-class*), 13
- unmethylated.N, MethyLumiM-method  
     (*MethyLumiM-class*), 3
- unmethylated.N<-  
     (*methylumiGenerics*), 16
- unmethylated.N<-, methylData, matrix-method  
     (*methylData-class*), 13
- unmethylated.N<-, MethyLumiM, ANY-method  
     (*MethyLumiM-class*), 3
- unmethylated<-  
     (*MethyLumi-accessors*), 12

unmethylated<-,MethyLumi,matrix-method  
(*MethyLumi-class*), 1

unmethylated<-,MethyLumiM,ANY-method  
(*MethyLumiM-class*), 3

unmethylated<-,MethyLumiSet,matrix-method  
(*MethyLumiSet-class*), 6

varFilter, 21

varFilter,MethyLumiM-method  
(*varFilter*), 21

varFilter,MethyLumiSet-method  
(*varFilter*), 21

Versioned, 1, 3, 5, 7

VersionedBiobase, 1, 3, 5, 7