

Package ‘rrvgo’

May 15, 2025

Type Package

Title Reduce + Visualize GO

Version 1.20.0

Description Reduce and visualize lists of Gene Ontology terms by identifying redundancy based on semantic similarity.

URL <https://www.bioconductor.org/packages/rrvgo>,
<https://ssayols.github.io/rrvgo/index.html>

License GPL-3

Encoding UTF-8

Imports GOSemSim, AnnotationDbi, GO.db, pheatmap, ggplot2, ggrepel, treemap, tm, wordcloud, shiny, grDevices, grid, stats, methods, umap

Suggests knitr, rmarkdown, BiocStyle, testthat (>= 2.1.0), shinydashboard, DT, plotly, heatmaply, magrittr, utils, clusterProfiler, DOSE, slam, org.Ag.eg.db, org.At.tair.db, org.Bt.eg.db, org.Ce.eg.db, org.Cf.eg.db, org.Dm.eg.db, org.Dr.eg.db, org.EcK12.eg.db, org.EcSakai.eg.db, org.Gg.eg.db, org.Hs.eg.db, org.Mm.eg.db, org.Mmu.eg.db, org.Pt.eg.db, org.Rn.eg.db, org.Sc.sgd.db, org.Ss.eg.db, org.Xl.eg.db

VignetteBuilder knitr

RoxygenNote 7.2.3

biocViews Annotation, Clustering, GO, Network, Pathways, Software

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/rrvgo>

git_branch RELEASE_3_21

git_last_commit 4ef9dd7

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-05-14

Author Sergi Sayols [aut, cre],
Sara Elmeligy [ctb]

Maintainer Sergi Sayols <sergisayolspuig@gmail.com>

Contents

| | |
|------------------------------|----|
| calculateSimMatrix | 2 |
| getGoSize | 3 |
| getGoTerm | 4 |
| getTermDisp | 4 |
| getTermUniq | 5 |
| gg_color_hue | 5 |
| heatmapPlot | 6 |
| loadOrgdb | 7 |
| reduceSimMatrix | 7 |
| scatterPlot | 8 |
| shiny_rrvgo | 10 |
| treemapPlot | 10 |
| wordcloudPlot | 11 |

| | |
|--------------|-----------|
| Index | 12 |
|--------------|-----------|

| | |
|--------------------|---|
| calculateSimMatrix | <i>calculateSimMatrix Calculate the score similarity matrix between terms</i> |
|--------------------|---|

Description

calculateSimMatrix Calculate the score similarity matrix between terms

Usage

```
calculateSimMatrix(
  x,
  orgdb,
  keytype = "ENTREZID",
  semdata = GOSemSim::godata(orgdb, ont = ont, keytype = keytype),
  ont = c("BP", "MF", "CC"),
  method = c("Resnik", "Lin", "Rel", "Jiang", "Wang")
)
```

Arguments

| | |
|---------|---|
| x | vector of GO terms |
| orgdb | one of org.* Bioconductor packages (the package name, or the package itself) |
| keytype | keytype passed to AnnotationDbi::keys to retrieve GO terms associated to gene ids in your orgdb |

| | |
|---------|---|
| semdata | object with prepared GO DATA for measuring semantic similarity |
| ont | ontology. One of c("BP", "MF", "CC") |
| method | distance method. One of the supported methods by GOSemSim: c("Resnik", "Lin", "Rel", "Jiang", "Wang") |

Details

All similarity measures available are those implemented in the [GOSemSim package](https://www.bioconductor.org/packages/release/bioc/html/GOSEmSim.html), namely the Resnik, Lin, Relevance, Jiang and Wang methods. See the [Semantic Similarity Measurement Based on GO](https://www.bioconductor.org/packages/release/bioc/vignettes/GOSEmSim/inst/doc/GOSEmSim.html#similarity-measurement-based-on-go) section from the GOSeSim documentation for more details.

Value

a square matrix with similarity scores between terms

Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
```

| | |
|-----------|--|
| getGoSize | <i>getGoSize</i> Get GO term size (# of genes) |
|-----------|--|

Description

getGoSize Get GO term size (# of genes)

Usage

```
getGoSize(terms, orgdb, keytype, children)
```

Arguments

| | |
|----------|---|
| terms | GO terms |
| orgdb | one of org.* Bioconductor packages (the package name, or the package itself) |
| keytype | keytype passed to AnnotationDbi::keys to retrieve GO terms associated to gene ids in your orgdb |
| children | include genes in children terms (based on relationships in the GO DAG hierarchy) |

Value

number of genes associated with each term

| | |
|-----------|---|
| getGoTerm | <i>getGoTerm</i> Get the description of a GO term |
|-----------|---|

Description

getGoTerm Get the description of a GO term

Usage

getGoTerm(x)

Arguments

x GO terms

Value

the Term slot in GO.db::GOTERM[[x]]

| | |
|-------------|--|
| getTermDisp | <i>getTermDisp</i> Calculate the term dispensability score, defined as the semantic similarity threshold a term was assigned to a cluster (namely, the similarity of a term to the cluster representative term). |
|-------------|--|

Description

getTermDisp Calculate the term dispensability score, defined as the semantic similarity threshold a term was assigned to a cluster (namely, the similarity of a term to the cluster representative term).

Usage

getTermDisp(simMatrix, cluster, clusterRep)

Arguments

simMatrix a (square) similarity matrix
cluster the cluster assignment for each term
clusterRep the cluster representative term

Value

a vector of term dispensability scores

| | |
|-------------|--|
| getTermUniq | <i>getTermUniq Calculate the term uniqueness score, defined as 1 minus the average semantic similarity of a term to all other terms.</i> |
|-------------|--|

Description

getTermUniq Calculate the term uniqueness score, defined as 1 minus the average semantic similarity of a term to all other terms.

Usage

```
getTermUniq(simMatrix, cluster = NULL)
```

Arguments

| | |
|-----------|--|
| simMatrix | a (square) similarity matrix |
| cluster | vector with the cluster each entry in the simMatrix belongs to. If NULL, a |

Value

a vector of term uniqueness scores

| | |
|--------------|--|
| gg_color_hue | <i>gg_color_hue Emulate ggplot2 color palette.</i> |
|--------------|--|

Description

gg_color_hue Emulate ggplot2 color palette.

Usage

```
gg_color_hue(n)
```

Arguments

| | |
|---|------------------|
| n | number of colors |
|---|------------------|

Details

It is just equally spaced hues around the color wheel, starting from 15:

Value

a vector with colors (alphanumeric)

Examples

```
## Not run:
plot(1:10, pch=16, cex=2, col=gg_color_hue(10))

## End(Not run)
```

| | |
|-------------|--|
| heatmapPlot | <i>heatmapPlot Plot similarity matrix as a heatmap</i> |
|-------------|--|

Description

heatmapPlot Plot similarity matrix as a heatmap

Usage

```
heatmapPlot(
  simMatrix,
  reducedTerms = NULL,
  annotateParent = TRUE,
  annotationLabel = "parentTerm",
  ...
)
```

Arguments

| | |
|-----------------|--|
| simMatrix | a (square) similarity matrix. |
| reducedTerms | a data.frame with the reduced terms from reduceSimMatrix() |
| annotateParent | whether to add annotation of the parent |
| annotationLabel | display "parent" ids or "parentTerm" string |
| ... | other parameters sent to pheatmap::pheatmap() |

Details

Matrix with similarity scores between terms is represented as a heatmap.

Value

Invisibly a pheatmap object that is a list with components

Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
heatmapPlot(simMatrix, reducedTerms, annotateParent=TRUE, annotationLabel="parentTerm", fontsize=6)
```

| | |
|-----------|---------------------------------------|
| loadOrgdb | <i>loadOrgdb Load an orgdb object</i> |
|-----------|---------------------------------------|

Description

loadOrgdb Load an orgdb object

Usage

```
loadOrgdb(orgdb)
```

Arguments

orgdb one of org.* Bioconductor packages

Value

the loaded orgdb

| | |
|-----------------|--|
| reduceSimMatrix | <i>reduceSimMatrix Reduce a set of GO terms based on their semantic similarity and scores.</i> |
|-----------------|--|

Description

reduceSimMatrix Reduce a set of GO terms based on their semantic similarity and scores.

Usage

```
reduceSimMatrix(
  simMatrix,
  scores = c("uniqueness", "size"),
  threshold = 0.7,
  orgdb,
  keytype = "ENTREZID",
  children = TRUE
)
```

Arguments

simMatrix a (square) similarity matrix

scores one of c("uniqueness", "size"), or a *named* vector with scores provided for each term, where higher values favor choosing the term as the cluster representative. The default "uniqueness" uses a score reflecting how unique the term is. Note: if you like to use p-values as scores, consider `-1*log-transforming them ('-log(p)')`

| | |
|-----------|---|
| threshold | similarity threshold (0-1). Some guidance: Large (allowed similarity=0.9), Medium (0.7), Small (0.5), Tiny (0.4) Defaults to Medium (0.7) |
| orgdb | one of org.* Bioconductor packages (the package name, or the orgdb object itself) |
| keytype | keytype passed to AnnotationDbi::keys to retrieve GO terms associated to gene ids in your orgdb |
| children | when retrieving GO term size, include genes in children terms. (based on relationships in the GO DAG hierarchy). Defaults to TRUE |

Details

Group terms which are at least within a similarity below ‘threshold’. Decide which term remains based on a score. If no score is provided, then decide based on the "uniqueness" or the term "size".

Currently, rrvgo uses the similarity between pairs of terms to compute a distance matrix, defined as $(1 - \text{simMatrix})$. The terms are then hierarchically clustered using complete linkage, and the tree is cut at the desired threshold, picking the term with the highest score as the representative of each group.

Therefore, higher thresholds lead to fewer groups, and the threshold should be read as the minimum similarity between group representatives.

Value

a data.frame identifying the different clusters of terms, the parent term representing the cluster, and some metrics of importance describing how unique and dispensable a term is.

Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
```

scatterPlot

scatterPlot Plot GO terms as scattered points.

Description

scatterPlot Plot GO terms as scattered points.

Usage

```
scatterPlot(
  simMatrix,
  reducedTerms,
  algorithm = c("pca", "umap"),
  onlyParents = FALSE,
```



```
    size = "score",
    addLabel = TRUE,
    labelSize = 3
  )
```

Arguments

| | |
|--------------|--|
| simMatrix | a (square) similarity matrix. |
| reducedTerms | a data.frame with the reduced terms from reduceSimMatrix() |
| algorithm | algorithm for dimensionality reduction. Either pca or umap. |
| onlyParents | plot only parent terms. Point size is the number of aggregated terms under the parent. |
| size | what to use as point size. Can be either GO term's "size" or "score". |
| addLabel | add labels with the most representative term of the group. |
| labelSize | text size in the label. |

Details

Distances between points represent the similarity between terms. Axes are the first 2 components of applying one of this dimensionality reduction algorithms: - a PCoA to the (di)similarity matrix. - a UMAP (Uniform Manifold Approximation and Projection,[1]) Size of the point represents the provided scores or, in its absence, the number of genes the GO term contains.

Value

ggplot2 object ready to be printed (or manipulated)

References

[1] Konopka T (2022). `_umap: Uniform Manifold Approximation and Projection_`. R package version 0.2.8.0, <https://CRAN.R-project.org/package=umap>.

Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
scatterPlot(simMatrix, reducedTerms)
```

| | |
|-------------|---|
| shiny_rrvgo | <i>shiny_rrvgo Launch an interactive web interface.</i> |
|-------------|---|

Description

shiny_rrvgo Launch an interactive web interface.

Usage

```
shiny_rrvgo(...)
```

Arguments

... other params sent to shiny::runApp().

Value

Nothing

| | |
|-------------|--|
| treemapPlot | <i>treemapPlot Plot GO terms as a treemap.</i> |
|-------------|--|

Description

treemapPlot Plot GO terms as a treemap.

Usage

```
treemapPlot(reducedTerms, size = "score", title = "", ...)
```

Arguments

| | |
|--------------|--|
| reducedTerms | a data.frame with the reduced terms from reduceSimMatrix() |
| size | what to use as point size. Can be either GO term's "size" or "score" |
| title | title of the plot. Defaults to nothing |
| ... | other parameters sent to treemap::treemap() |

Value

A list from the call to the 'treemap()' function is silently returned

Examples

```
## Not run:
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
treemapPlot(reducedTerms)

## End(Not run)
```

wordcloudPlot

wordcloudPlot Plot GO reduced terms as a wordcloud.

Description

wordcloudPlot Plot GO reduced terms as a wordcloud.

Usage

```
wordcloudPlot(reducedTerms, onlyParents = TRUE, ...)
```

Arguments

| | |
|--------------|---|
| reducedTerms | a data.frame with the reduced terms from reduceSimMatrix(). |
| onlyParents | use only parent terms to calculate frequencies. |
| ... | other parameters sent to wordcloud::wordcloud() |

Value

Nothing

Examples

```
go_analysis <- read.delim(system.file("extdata/example.txt", package="rrvgo"))
simMatrix <- calculateSimMatrix(go_analysis$ID, orgdb="org.Hs.eg.db", ont="BP", method="Rel")
scores <- setNames(-log10(go_analysis$qvalue), go_analysis$ID)
reducedTerms <- reduceSimMatrix(simMatrix, scores, threshold=0.7, orgdb="org.Hs.eg.db")
wordcloudPlot(reducedTerms, min.freq=1, colors="black")
```

Index

[calculateSimMatrix](#), 2

[getGoSize](#), 3

[getGoTerm](#), 4

[getTermDisp](#), 4

[getTermUniq](#), 5

[gg_color_hue](#), 5

[heatmapPlot](#), 6

[loadOrgdb](#), 7

[reduceSimMatrix](#), 7

[scatterPlot](#), 8

[shiny_rrvgo](#), 10

[treemapPlot](#), 10

[wordcloudPlot](#), 11