

Package ‘mia’

May 2, 2024

Type Package

Version 1.12.0

Title Microbiome analysis

Description mia implements tools for microbiome analysis based on the SummarizedExperiment, SingleCellExperiment and TreeSummarizedExperiment infrastructure. Data wrangling and analysis in the context of taxonomic data is the main scope. Additional functions for common task are implemented such as community indices calculation and summarization.

biocViews Microbiome, Software, DataImport

License Artistic-2.0 | file LICENSE

Encoding UTF-8

LazyData false

Depends R (>= 4.0), SummarizedExperiment, SingleCellExperiment, TreeSummarizedExperiment (>= 1.99.3), MultiAssayExperiment

Imports methods, stats, utils, MASS, ape, decontam, vegan, BiocGenerics, S4Vectors, IRanges, Biostrings, DECIPHER, BiocParallel, DelayedArray, DelayedMatrixStats, scuttle, scater, DirichletMultinomial, rlang, dplyr, tibble, tidyr, bluster, MatrixGenerics

Suggests testthat, knitr, patchwork, BiocStyle, yaml, phyloseq, dada2, stringr, biomformat, reldist, ade4, microbiomeDataSets, rmarkdown

URL <https://github.com/microbiome/mia>

BugReports <https://github.com/microbiome/mia/issues>

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/mia>

git_branch RELEASE_3_19

git_last_commit 38dad1b

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-01

Author Felix G.M. Ernst [aut] (<<https://orcid.org/0000-0001-5064-0928>>),
 Sudarshan A. Shetty [aut] (<<https://orcid.org/0000-0001-7280-9915>>),
 Tuomas Borman [aut, cre] (<<https://orcid.org/0000-0002-8563-8884>>),
 Leo Lahti [aut] (<<https://orcid.org/0000-0001-5537-637X>>),
 Yang Cao [ctb],
 Nathan D. Olson [ctb],
 Levi Waldron [ctb],
 Marcel Ramos [ctb],
 Héctor Corrada Bravo [ctb],
 Jayaram Kancherla [ctb],
 Domenick Braccia [ctb],
 Basil Courbayre [ctb],
 Muluh Muluh [ctb]

Maintainer Tuomas Borman <tuomas.v.borman@utu.fi>

Contents

mia-package	3
addCluster	4
addDivergence	6
agglomerate-methods	8
calculateDMN	12
calculateJSD	15
calculateOverlap	17
calculateUnifrac	19
deprecate	21
dmn_se	23
enterotype	24
esophagus	25
estimateDiversity	26
estimateDominance	31
estimateEvenness	35
estimateRichness	37
getExperimentCrossAssociation	41
getPrevalence	46
GlobalPatterns	51
hierarchy-tree	52
HintikkaXOData	53
importHUMANn	54
importMetaPhlAn	55
importMothur	57
importQIIME2	58
isContaminant	61

makePhyloseqFromTreeSE	63
makeTreeSEFromBiom	64
makeTreeSEFromDADA2	66
makeTreeSEFromPhyloseq	67
meltAssay	68
merge-methods	69
mergeSEs	72
mia-datasets	75
peerj13075	75
perSampleDominantTaxa	76
relabundance	79
runCCA	80
runDPCoA	83
runNMDS	85
splitByRanks	87
splitOn	89
subsampleCounts	91
subsetSamples	93
summaries	94
taxonomy-methods	98
Tengeler2020	101
transformAssay	102
Index	107

 mia-package

 mia *Package*.

Description

mia implements tools for microbiome analysis based on the SummarizedExperiment, SingleCellExperiment and TreeSummarizedExperiment infrastructure. Data wrangling and analysis in the context of taxonomic data is the main scope. Additional functions for common task are implemented such as community indices calculation and summarization.

Author(s)

Maintainer: Tuomas Borman <tuomas.v.borman@utu.fi> ([ORCID](#))

Authors:

- Felix G.M. Ernst <felix.gm.ernst@outlook.com> ([ORCID](#))
- Sudarshan A. Shetty <sudarshanshetty9@gmail.com> ([ORCID](#))
- Leo Lahti <leo.lahti@iki.fi> ([ORCID](#))

Other contributors:

- Yang Cao [contributor]
- Nathan D. Olson <nolson@nist.gov> [contributor]

- Levi Waldron [contributor]
- Marcel Ramos [contributor]
- Héctor Corrada Bravo [contributor]
- Jayaram Kancherla [contributor]
- Domenick Braccia <dbraccia@umd.edu> [contributor]
- Basil Courbayre [contributor]
- Muluh Muluh [contributor]

See Also

[TreeSummarizedExperiment](#)

addCluster	<i>Clustering wrapper</i>
------------	---------------------------

Description

This function returns a `SummarizedExperiment` with clustering information in its `colData` or `rowData`

Usage

```
addCluster(
  x,
  BLUSPARAM,
  assay.type = assay_name,
  assay_name = "counts",
  MARGIN = "features",
  full = FALSE,
  name = "clusters",
  clust.col = "clusters",
  ...
)

## S4 method for signature 'SummarizedExperiment'
addCluster(
  x,
  BLUSPARAM,
  assay.type = assay_name,
  assay_name = "counts",
  MARGIN = "features",
  full = FALSE,
  name = "clusters",
  clust.col = "clusters",
  ...
)
```

Arguments

x	A SummarizedExperiment object.
BLUSPARAM	A BlusterParam object specifying the algorithm to use.
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use assay.type instead. At some point assay_name will be disabled.)
MARGIN	A single character value for specifying whether the transformation is applied sample (column) or feature (row) wise. (By default: MARGIN = "samples")
full	Logical scalar indicating whether the full clustering statistics should be returned for each method.
name	the name to store the result in metadata
clust.col	A single character value indicating the name of the rowData (or colData) where the data will be stored.
...	Additional parameters to use altExps for example

Details

This is a wrapper for the clusterRows function from the [bluster](#) package.

When setting full = TRUE, the clustering information will be stored in the metadata of the object.

By default, clustering is done on the features.

Value

addCluster returns an object of the same type as the x parameter with clustering information named clusters stored in colData or rowData.

Author(s)

Basil Courbayre

Examples

```
library(bluster)
data(GlobalPatterns, package = "mia")
tse <- GlobalPatterns

# Cluster on rows using Kmeans
tse <- addCluster(tse, KmeansParam(centers = 3))

# Clustering done on the samples using Hclust
tse <- addCluster(tse,
  MARGIN = "samples",
  HclustParam(metric = "bray", dist.fun = vegan::vegdist))

# Getting the clusters
colData(tse)$clusters
```

addDivergence *Estimate divergence*

Description

Estimate divergence against a given reference sample.

Usage

```
addDivergence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  name = "divergence",
  reference = "median",
  FUN = vegan::vegdist,
  method = "bray",
  ...
)

## S4 method for signature 'SummarizedExperiment'
addDivergence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  name = "divergence",
  reference = "median",
  FUN = vegan::vegdist,
  method = "bray",
  ...
)
```

Arguments

x	a SummarizedExperiment object.
assay.type	the name of the assay used for calculation of the sample-wise estimates.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
name	a name for the column of the <code>colData</code> the results should be stored in. By default, name is "divergence".
reference	a numeric vector that has length equal to number of features, or a non-empty character value; either 'median' or 'mean'. <code>reference</code> specifies the reference that is used to calculate divergence. by default, reference is "median".
FUN	a function for distance calculation. The function must expect the input matrix as its first argument. With rows as samples and columns as features. By default, FUN is <code>vegan::vegdist</code> .

method	a method that is used to calculate the distance. Method is passed to the function that is specified by FUN. By default, method is "bray".
...	optional arguments

Details

Microbiota divergence (heterogeneity / spread) within a given sample set can be quantified by the average sample dissimilarity or beta diversity with respect to a given reference sample.

This measure is sensitive to sample size. Subsampling or bootstrapping can be applied to equalize sample sizes between comparisons.

Value

x with additional `colData` named `*name*`

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

See Also

[plotColData](#)

- [estimateRichness](#)
- [estimateEvenness](#)
- [estimateDominance](#)

Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns

# By default, reference is median of all samples. The name of column where results
# is "divergence" by default, but it can be specified.
tse <- addDivergence(tse)

# The method that are used to calculate distance in divergence and
# reference can be specified. Here, euclidean distance and dist function from
# stats package are used. Reference is the first sample.
tse <- addDivergence(tse, name = "divergence_first_sample",
                    reference = assays(tse)$counts[,1],
                    FUN = stats::dist, method = "euclidean")

# Reference can also be median or mean of all samples.
# By default, divergence is calculated by using median. Here, mean is used.
tse <- addDivergence(tse, name = "divergence_average", reference = "mean")

# All three divergence results are stored in colData.
colData(tse)
```

 agglomerate-methods *Agglomerate data using taxonomic information*

Description

Agglomeration functions can be used to sum-up data based on specific criteria such as taxonomic ranks, variables or prevalence.

Usage

```
agglomerateByRank(x, ...)
```

```
mergeFeaturesByRank(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
agglomerateByRank(
```

```
  x,
  rank = taxonomyRanks(x)[1],
  onRankOnly = FALSE,
  na.rm = FALSE,
  empty.fields = c(NA, "", " ", "\t", "-", "_"),
  ...
)
```

```
## S4 method for signature 'SummarizedExperiment'
mergeFeaturesByRank(
```

```
  x,
  rank = taxonomyRanks(x)[1],
  onRankOnly = FALSE,
  na.rm = FALSE,
  empty.fields = c(NA, "", " ", "\t", "-", "_"),
  ...
)
```

```
## S4 method for signature 'SingleCellExperiment'
agglomerateByRank(x, ..., altexp = NULL, strip_altexp = TRUE)
```

```
## S4 method for signature 'SingleCellExperiment'
mergeFeaturesByRank(x, ..., altexp = NULL, strip_altexp = TRUE)
```

```
## S4 method for signature 'TreeSummarizedExperiment'
agglomerateByRank(
```

```
  x,
  ...,
  agglomerate.tree = agglomerateTree,
  agglomerateTree = FALSE
)
```



```

## S4 method for signature 'TreeSummarizedExperiment'
mergeFeaturesByRank(x, ..., agglomerate.tree = FALSE)

agglomerateByPrevalence(x, ...)

## S4 method for signature 'SummarizedExperiment'
agglomerateByPrevalence(
  x,
  rank = taxonomyRanks(x)[1L],
  other_label = "Other",
  ...
)

```

Arguments

x	a SummarizedExperiment object
...	arguments passed to <code>agglomerateByRank</code> function for <code>SummarizedExperiment</code> objects, to <code>getPrevalence</code> and <code>getPrevalentTaxa</code> and used in <code>agglomeratebyPrevalence</code> , to mergeRows and sumCountsAcrossFeatures . <ul style="list-style-type: none"> • <code>remove_empty_ranks</code>A single boolean value for selecting whether to remove those columns of <code>rowData</code> that include only NAs after agglomeration. (By default: <code>remove_empty_ranks = FALSE</code>) • <code>make_unique</code>A single boolean value for selecting whether to make row-names unique. (By default: <code>make_unique = TRUE</code>) • <code>detection</code>Detection threshold for absence/presence. Either an absolute value compared directly to the values of <code>x</code> or a relative value between 0 and 1, if <code>as_relative = FALSE</code>. • <code>prevalence</code>Prevalence threshold (in 0 to 1). The required prevalence is strictly greater by default. To include the limit, set <code>include_lowest</code> to <code>TRUE</code>. • <code>as.relative</code>Logical scalar: Should the detection threshold be applied on compositional (relative) abundances? (default: <code>FALSE</code>)
rank	a single character defining a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.
onRankOnly	<code>TRUE</code> or <code>FALSE</code> : Should information only from the specified rank be used or from ranks equal and above? See details. (default: <code>onRankOnly = FALSE</code>)
na.rm	<code>TRUE</code> or <code>FALSE</code> : Should taxa with an empty rank be removed? Use it with caution, since empty entries on the selected rank will be dropped. This setting can be tweaked by defining <code>empty.fields</code> to your needs. (default: <code>na.rm = TRUE</code>)
empty.fields	a character value defining, which values should be regarded as empty. (Default: <code>c(NA, "", " ", "\t")</code>). They will be removed if <code>na.rm = TRUE</code> before agglomeration.
altexp	String or integer scalar specifying an alternative experiment containing the input data.

<code>strip_altextp</code>	TRUE or FALSE: Should alternative experiments be removed prior to agglomeration? This prevents to many nested alternative experiments by default (default: <code>strip_altextp = TRUE</code>)
<code>agglomerate.tree</code>	TRUE or FALSE: should <code>rowTree()</code> also be agglomerated? (Default: <code>agglomerate.tree = FALSE</code>)
<code>agglomerateTree</code>	alias for <code>agglomerate.tree</code> .
<code>other_label</code>	A single character valued used as the label for the summary of non-prevalent taxa. (default: <code>other_label = "Other"</code>)

Details

Depending on the available taxonomic data and its structure, setting `onRankOnly = TRUE` has certain implications on the interpretability of your results. If no loops exist (loops meaning two higher ranks containing the same lower rank), the results should be comparable. You can check for loops using [detectLoop](#).

Agglomeration sums up the values of assays at the specified taxonomic level. With certain assays, e.g. those that include binary or negative values, this summing can produce meaningless values. In those cases, consider performing agglomeration first, and then applying the transformation afterwards.

`agglomerateByPrevalence` sums up the values of assays at the taxonomic level specified by rank (by default the highest taxonomic level available) and selects the summed results that exceed the given population prevalence at the given detection level. The other summed values (below the threshold) are agglomerated in an additional row taking the name indicated by `other_label` (by default "Other").

Value

`agglomerateByRank` returns a taxonomically-agglomerated, optionally-pruned object of the same class as `x`.

`agglomerateByPrevalence` returns a taxonomically-agglomerated object of the same class as `x` and based on prevalent taxonomic results.

See Also

[mergeRows](#), [sumCountsAcrossFeatures](#)

Examples

```
data(GlobalPatterns)
# print the available taxonomic ranks
colnames(rowData(GlobalPatterns))
taxonomyRanks(GlobalPatterns)

# agglomerate at the Family taxonomic rank
x1 <- agglomerateByRank(GlobalPatterns, rank="Family")
## How many taxa before/after agglomeration?
nrow(GlobalPatterns)
```

```

nrow(x1)

# agglomerate the tree as well
x2 <- agglomerateByRank(GlobalPatterns, rank="Family",
                        agglomerate.tree = TRUE)
nrow(x2) # same number of rows, but
rowTree(x1) # ... different
rowTree(x2) # ... tree

# If assay contains binary or negative values, summing might lead to meaningless
# values, and you will get a warning. In these cases, you might want to do
# agglomeration again at chosen taxonomic level.
tse <- transformAssay(GlobalPatterns, method = "pa")
tse <- agglomerateByRank(tse, rank = "Genus")
tse <- transformAssay(tse, method = "pa")

# removing empty labels by setting na.rm = TRUE
sum(is.na(rowData(GlobalPatterns)$Family))
x3 <- agglomerateByRank(GlobalPatterns, rank="Family", na.rm = TRUE)
nrow(x3) # different from x2

# Because all the rownames are from the same rank, rownames do not include
# prefixes, in this case "Family:".
print(rownames(x3[1:3,]))

# To add them, use getTaxonomyLabels function.
rownames(x3) <- getTaxonomyLabels(x3, with_rank = TRUE)
print(rownames(x3[1:3,]))

# use 'remove_empty_ranks' to remove columns that include only NAs
x4 <- agglomerateByRank(GlobalPatterns, rank="Phylum", remove_empty_ranks = TRUE)
head(rowData(x4))

# If the assay contains NAs, you might want to consider replacing them,
# since summing-up NAs lead to NA
x5 <- GlobalPatterns
# Replace first value with NA
assay(x5)[1,1] <- NA
x6 <- agglomerateByRank(x5, "Kingdom")
head( assay(x6) )
# Replace NAs with 0. This is justified when we are summing-up counts.
assay(x5)[ is.na(assay(x5)) ] <- 0
x6 <- agglomerateByRank(x5, "Kingdom")
head( assay(x6) )

## Look at enterotype dataset...
data(enterotype)
## Print the available taxonomic ranks. Shows only 1 available rank,
## not useful for agglomerateByRank
taxonomyRanks(enterotype)
## Data can be aggregated based on prevalent taxonomic results
tse <- GlobalPatterns
tse <- agglomerateByPrevalence(tse,

```

```

rank = "Phylum",
detection = 1/100,
prevalence = 50/100,
as_relative = TRUE)

tse

# Here data is aggregated at the taxonomic level "Phylum". The five phyla
# that exceed the population prevalence threshold of 50/100 represent the
# five first rows of the assay in the aggregated data. The sixth and last row
# named by default "Other" takes the summed up values of all the other phyla
# that are below the prevalence threshold.

assay(tse)[,1:5]

```

calculatedMN

Dirichlet-Multinomial Mixture Model: Machine Learning for Microbiome Data

Description

These functions are accessors for functions implemented in the [DirichletMultinomial](#) package

Usage

```

calculateDMN(x, ...)

## S4 method for signature 'ANY'
calculateDMN(
  x,
  k = 1,
  BPPARAM = SerialParam(),
  seed = runif(1, 0, .Machine$integer.max),
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateDMN(
  x,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  transposed = FALSE,
  ...
)

runDMN(x, name = "DMN", ...)

```

```
getDMN(x, name = "DMN", ...)

## S4 method for signature 'SummarizedExperiment'
getDMN(x, name = "DMN")

bestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"), ...)

## S4 method for signature 'SummarizedExperiment'
bestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"))

getBestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"), ...)

## S4 method for signature 'SummarizedExperiment'
getBestDMNFit(x, name = "DMN", type = c("laplace", "AIC", "BIC"))

calculateDMNgroup(x, ...)

## S4 method for signature 'ANY'
calculateDMNgroup(
  x,
  variable,
  k = 1,
  seed = runif(1, 0, .Machine$integer.max),
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateDMNgroup(
  x,
  variable,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  transposed = FALSE,
  ...
)

performDMNgroupCV(x, ...)

## S4 method for signature 'ANY'
performDMNgroupCV(
  x,
  variable,
  k = 1,
  seed = runif(1, 0, .Machine$integer.max),
  ...
)
```

```
## S4 method for signature 'SummarizedExperiment'
performDMNgroupCV(
  x,
  variable,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  transposed = FALSE,
  ...
)
```

Arguments

x	a numeric matrix with samples as rows or a SummarizedExperiment object.
...	optional arguments not used.
k	the number of Dirichlet components to fit. See dmn
BPPARAM	A BiocParallelParam object specifying whether the UniFrac calculation should be parallelized.
seed	random number seed. See dmn
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
exprs_values	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead.)
transposed	Logical scalar, is x transposed with samples in rows?
name	the name to store the result in metadata
type	the type of measure used for the goodness of fit. One of 'laplace', 'AIC' or 'BIC'.
variable	a variable from <code>colData</code> to use as a grouping variable. Must be a character of factor.

Value

`calculateDMN` and `getDMN` return a list of DMN objects, one element for each value of k provided.

`bestDMNFit` returns the index for the best fit and `getBestDMNFit` returns a single DMN object.

`calculateDMNgroup` returns a [DMNGroup](#) object

`performDMNgroupCV` returns a `data.frame`

See Also

[DMN-class](#), [DMNGroup-class](#), [dmn](#), [dmngroup](#), [cvdmngroup](#), [accessors for DMN objects](#)

Examples

```

fl <- system.file(package="DirichletMultinomial", "extdata", "Twins.csv")
counts <- as.matrix(read.csv(fl, row.names=1))
fl <- system.file(package="DirichletMultinomial", "extdata", "TwinStudy.t")
pheno0 <- scan(fl)
lvls <- c("Lean", "Obese", "Overwt")
pheno <- factor(lvls[pheno0 + 1], levels=lvls)
colData <- DataFrame(pheno = pheno)

tse <- TreeSummarizedExperiment(assays = list(counts = counts),
                               colData = colData)

library(bluster)

# Compute DMM algorithm and store result in metadata
tse <- cluster(tse, name = "DMM", DmmParam(k = 1:3, type = "laplace"),
              MARGIN = "samples", full = TRUE)

# Get the list of DMN objects
metadata(tse)$DMM$dmm

# Get and display which objects fits best
bestFit <- metadata(tse)$DMM$best
bestFit

# Get the model that generated the best fit
bestModel <- metadata(tse)$DMM$dmm[[bestFit]]
bestModel

# Get the sample-cluster assignment probability matrix
head(metadata(tse)$DMM$prob)

# Get the weight of each component for the best model
bestModel@mixture$Weight

```

calculateJSD

Calculate the Jensen-Shannon Divergence

Description

This function calculates the Jensen-Shannon Divergence (JSD) in a [SummarizedExperiment](#) object.

Usage

```

## S4 method for signature 'ANY'
calculateJSD(x, ...)

## S4 method for signature 'SummarizedExperiment'
calculateJSD(

```

```

x,
assay.type = assay_name,
assay_name = exprs_values,
exprs_values = "counts",
transposed = FALSE,
...
)

runJSD(x, BPPARAM = SerialParam(), chunkSize = nrow(x))

```

Arguments

x	a numeric matrix or a SummarizedExperiment .
...	optional arguments not used.
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use assay.type instead. At some point assay_name will be disabled.)
exprs_values	a single character value for specifying which assay to use for calculation. (Please use assay.type instead.)
transposed	Logical scalar, is x transposed with cells in rows?
BPPARAM	A BiocParallelParam object specifying whether the JSD calculation should be parallelized.
chunkSize	an integer scalar, defining the size of data send to the individual worker. Only has an effect, if BPPARAM defines more than one worker. (default: chunkSize = nrow(x))

Value

a sample-by-sample distance matrix, suitable for NMDS, etc.

Author(s)

Susan Holmes <susan@stat.stanford.edu>. Adapted for phyloseq by Paul J. McMurdie. Adapted for mia by Felix G.M. Ernst

References

Jensen-Shannon Divergence and Hilbert space embedding. Bent Fuglede and Flemming Topsøe University of Copenhagen, Department of Mathematics <http://www.math.ku.dk/~topsoe/ISIT2004JSD.pdf>

See Also

http://en.wikipedia.org/wiki/Jensen-Shannon_divergence

Examples

```

data(enterotype)
library(scater)

jsd <- calculateJSD(enterotype)
class(jsd)
head(jsd)

enterotype <- runMDS(enterotype, FUN = calculateJSD, name = "JSD",
                    exprs_values = "counts")
head(reducedDim(enterotype))
head(attr(reducedDim(enterotype), "eig"))
attr(reducedDim(enterotype), "GOF")

```

calculateOverlap	<i>Estimate overlap</i>
------------------	-------------------------

Description

This function calculates overlap for all sample-pairs in a [SummarizedExperiment](#) object.

Usage

```

calculateOverlap(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  detection = 0,
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateOverlap(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  detection = 0,
  ...
)

runOverlap(x, ...)

## S4 method for signature 'SummarizedExperiment'
runOverlap(x, name = "overlap", ...)

```

Arguments

<code>x</code>	a SummarizedExperiment object containing a tree.
<code>assay.type</code>	A single character value for selecting the assay to calculate the overlap.
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>detection</code>	A single numeric value for selecting detection threshold for absence/presence of features. Feature that has abundance under threshold in either of samples, will be discarded when evaluating overlap between samples.
<code>...</code>	Optional arguments not used.
<code>name</code>	A single character value specifying the name of overlap matrix that is stored in <code>reducedDim(x)</code> .

Details

These function calculates overlap between all the sample-pairs. Overlap reflects similarity between sample-pairs.

When overlap is calculated using relative abundances, the higher the value the higher the similarity is, When using relative abundances, overlap value 1 means that all the abundances of features are equal between two samples, and 0 means that samples have completely different relative abundances.

Value

`calculateOverlap` returns sample-by-sample distance matrix. `runOverlap` returns `x` that includes overlap matrix in its `reducedDim`.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

See Also

[calculateJSD](#) [calculateUnifrac](#)

Examples

```
data(esophagus)
tse <- esophagus
tse <- transformAssay(tse, method = "relabundance")
overlap <- calculateOverlap(tse, assay_name = "relabundance")
overlap

# Store result to reducedDim
tse <- runOverlap(tse, assay.type = "relabundance", name = "overlap_between_samples")
head(reducedDims(tse)$overlap_between_samples)
```

calculateUnifrac	<i>Calculate weighted or unweighted (Fast) Unifrac distance</i>
------------------	---

Description

This function calculates the (Fast) Unifrac distance for all sample-pairs in a [TreeSummarizedExperiment](#) object.

Usage

```
calculateUnifrac(x, tree, ...)  
  
## S4 method for signature 'ANY,phylo'  
calculateUnifrac(  
  x,  
  tree,  
  weighted = FALSE,  
  normalized = TRUE,  
  BPPARAM = SerialParam(),  
  ...  
)  
  
## S4 method for signature 'TreeSummarizedExperiment,missing'  
calculateUnifrac(  
  x,  
  assay.type = assay_name,  
  assay_name = exprs_values,  
  exprs_values = "counts",  
  tree_name = "phylo",  
  transposed = FALSE,  
  ...  
)  
  
runUnifrac(  
  x,  
  tree,  
  weighted = FALSE,  
  normalized = TRUE,  
  nodeLab = NULL,  
  BPPARAM = SerialParam(),  
  ...  
)
```

Arguments

x a numeric matrix or a [TreeSummarizedExperiment](#) object containing a tree.

Please note that `runUnifrac` expects a matrix with samples per row and not per column. This is implemented to be compatible with other distance calculations such as `dist` as much as possible.

<code>tree</code>	if <code>x</code> is a matrix, a <code>phylo</code> object matching the matrix. This means that the phylo object and the columns should relate to the same type of features (aka. microorganisms).
<code>...</code>	optional arguments not used.
<code>weighted</code>	TRUE or FALSE: Should use weighted-Unifrac calculation? Weighted-Unifrac takes into account the relative abundance of species/taxa shared between samples, whereas unweighted-Unifrac only considers presence/absence. Default is FALSE, meaning the unweighted-Unifrac distance is calculated for all pairs of samples.
<code>normalized</code>	TRUE or FALSE: Should the output be normalized such that values range from 0 to 1 independent of branch length values? Default is TRUE. Note that (unweighted) Unifrac is always normalized by total branch-length, and so this value is ignored when <code>weighted == FALSE</code> .
<code>BPPARAM</code>	A <code>BiocParallelParam</code> object specifying whether the Unifrac calculation should be parallelized.
<code>assay.type</code>	a single character value for specifying which assay to use for calculation.
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>exprs_values</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead.)
<code>tree_name</code>	a single character value for specifying which tree will be used in calculation. (By default: <code>tree_name = "phylo"</code>)
<code>transposed</code>	Logical scalar, is <code>x</code> transposed with cells in rows, i.e., is Unifrac distance calculated based on rows (FALSE) or columns (TRUE). (By default: <code>transposed = FALSE</code>)
<code>nodeLab</code>	if <code>x</code> is a matrix, a character vector specifying links between rows/columns and tips of <code>tree</code> . The length must equal the number of rows/columns of <code>x</code> . Furthermore, all the node labs must be present in <code>tree</code> .

Details

Please note that if `calculateUnifrac` is used as a FUN for `runMDS`, the argument `ntop` has to be set to `nrow(x)`.

Value

a sample-by-sample distance matrix, suitable for NMDS, etc.

Author(s)

Paul J. McMurdie. Adapted for `mia` by Felix G.M. Ernst

References

<http://bmf.colorado.edu/unifrac/>

The main implementation (Fast Unifrac) is adapted from the algorithm's description in:

Hamady, Lozupone, and Knight, "Fast UniFrac: facilitating high-throughput phylogenetic analyses of microbial communities including analysis of pyrosequencing and PhyloChip data." *The ISME Journal* (2010) 4, 17–27.

See also additional descriptions of Unifrac in the following articles:

Lozupone, Hamady and Knight, "Unifrac - An Online Tool for Comparing Microbial Community Diversity in a Phylogenetic Context.", *BMC Bioinformatics* 2006, 7:371

Lozupone, Hamady, Kelley and Knight, "Quantitative and qualitative (beta) diversity measures lead to different insights into factors that structure microbial communities." *Appl Environ Microbiol.* 2007

Lozupone C, Knight R. "Unifrac: a new phylogenetic method for comparing microbial communities." *Appl Environ Microbiol.* 2005 71 (12):8228-35.

Examples

```
data(esophagus)
library(scater)
calculateUnifrac(esophagus, weighted = FALSE)
calculateUnifrac(esophagus, weighted = TRUE)
calculateUnifrac(esophagus, weighted = TRUE, normalized = FALSE)
# for using calculateUnifrac in conjunction with runMDS the tree argument
# has to be given separately. In addition, subsetting using ntop must
# be disabled
esophagus <- runMDS(esophagus, FUN = calculateUnifrac, name = "Unifrac",
                   tree = rowTree(esophagus),
                   exprs_values = "counts",
                   ntop = nrow(esophagus))
reducedDim(esophagus)
```

deprecate

These functions will be deprecated. Please use other functions instead.

Description

These functions will be deprecated. Please use other functions instead.

Usage

```
cluster(x, ...)

## S4 method for signature 'SummarizedExperiment'
cluster(x, ...)

addTaxonomyTree(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'  
addTaxonomyTree(x, ...)  
  
taxonomyTree(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
taxonomyTree(x, ...)  
  
mergeFeaturesByPrevalence(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
mergeFeaturesByPrevalence(x, ...)  
  
loadFromBiom(...)  
  
loadFromQIIME2(...)  
  
readQZA(...)  
  
loadFromMothur(...)  
  
loadFromMetaphlan(...)  
  
loadFromHumann(...)  
  
full_join(x, ...)  
  
## S4 method for signature 'ANY'  
full_join(x, ...)  
  
inner_join(x, ...)  
  
## S4 method for signature 'ANY'  
inner_join(x, ...)  
  
left_join(x, ...)  
  
## S4 method for signature 'ANY'  
left_join(x, ...)  
  
right_join(x, ...)  
  
## S4 method for signature 'ANY'  
right_join(x, ...)  
  
plotNMDS(x, ...)
```

```
estimateDivergence(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
estimateDivergence(x, ...)
```

Arguments

x A [SummarizedExperiment](#) object.
... Additional parameters. See dedicated function.

dmn_se	<i>dmn_se</i>
--------	---------------

Description

dmn_se is a dataset on twins' microbiome where samples are stratified by their community composition through Dirichlet Multinomial Mixtures (DMM). It was derived from the **DirichletMultinomial** package.

Usage

```
data(dmn_se)
```

Format

A SummarizedExperiment with 130 features and 278 samples. The rowData contains no taxonomic information. The colData includes:

pheno participant's weight condition (Lean, Overwt and Obese)

Author(s)

Turnbaugh, PJ et al.

References

Holmes I, Harris K, Quince C (2012). Dirichlet Multinomial Mixtures: Generative Models for Microbial Metagenomics. PLoS ONE 7(2): e30126. <https://doi.org/10.1371/journal.pone.0030126>

Turnbaugh PJ, Hamady M, Yatsunenko T, Cantarel BL, Duncan A, et al. (2009). A core gut microbiome in obese and lean twins. Nature 457: 480–484. <https://doi.org/10.1038/nature07540>

See Also

[mia-datasets](#) [calculateDMN](#)

 enterotype

enterotype

Description

The enterotype data of the human gut microbiome includes taxonomic profiling for 280 fecal samples from 22 subjects based on shotgun DNA sequencing. The authors claimed that the data naturally clumps into three community-level clusters, or "enterotypes", that are not immediately explained by sequencing technology or demographic features of the subjects. In a later addendum from 2014 the authors stated that enterotypes should not be seen as discrete clusters, but as a way of stratifying samples to reduce complexity. It was converted into a TreeSummarizedExperiment from the **phyloseq** package.

Usage

```
data(enterotype)
```

Format

A TreeSummarizedExperiment with 553 features and 280 samples. The rowData contains taxonomic information at Genus level. The colData includes:

Enterotype enterotype the sample belongs to (1, 2 and 3)

Sample_ID sample ID of samples from all studies

SeqTech sequencing technology

SampleID sample ID of complete samples

Project original project from which sample was obtained (gill06, turnbaugh09, MetaHIT, MicroObes, MicroAge and kurokawa07)

Nationality participant's nationality (american, danish, spanish, french, italian and japanese)

Gender participant's gender (F or M)

Age participant's age (0.25 – 87)

ClinicalStatus participant's clinical status (healthy, obese, CD, UC and elderly)

Author(s)

Arumugam, M., Raes, J., et al.

Source

http://www.bork.embl.de/Docu/Arumugam_et_al_2011/downloads.html

References

Arumugam, M., et al. (2011). Enterotypes of the human gut microbiome. *Nature*, 473(7346), 174-180. <https://doi.org/10.1038/nature09944>

Arumugam, M., et al. (2014). Addendum: Enterotypes of the human gut microbiome. *Nature* 506, 516 (2014). <https://doi.org/10.1038/nature13075>

See Also[mia-datasets](#)

`esophagus`*esophagus*

Description

This small dataset from a human esophageal community includes 3 samples from 3 human adults based on biopsies analysed with 16S rDNA PCR. The 16S rRNA sequence processing is provided in the mothur wiki from the link below. It was converted into a TreeSummarizedExperiment from the **phyloseq** package.

Usage

```
data(esophagus)
```

Format

A TreeSummarizedExperiment with 58 features and 3 samples. The rowData contains no taxonomic information. The colData is empty.

Author(s)

Pei et al. <zhiheng.pei@med.nyu.edu>.

Source

http://www.mothur.org/wiki/Esophageal_community_analysis

References

Pei, Z., Bini, E. J., Yang, L., Zhou, M., Francois, F., & Blaser, M. J. (2004). Bacterial biota in the human distal esophagus. *Proceedings of the National Academy of Sciences of the United States of America*, 101(12), 4250-4255. <https://doi.org/10.1073/pnas.0306398101>

McMurdie, J. & Holmes, S. (2013) *phyloseq*: An R Package for reproducible interactive analysis and graphics of microbiome census data. *PLoS ONE*. 8(4):e61217. <https://doi.org/10.1371/journal.pone.0061217>

See Also[mia-datasets](#)

estimateDiversity	<i>Estimate (alpha) diversity measures</i>
-------------------	--

Description

Several functions for calculating (alpha) diversity indices, including the vegan package options and some others.

Usage

```
estimateDiversity(
  x,
  assay.type = "counts",
  assay_name = NULL,
  index = c("coverage", "fisher", "gini_simpson", "inverse_simpson",
    "log_modulo_skewness", "shannon"),
  name = index,
  ...
)

## S4 method for signature 'SummarizedExperiment'
estimateDiversity(
  x,
  assay.type = "counts",
  assay_name = NULL,
  index = c("coverage", "fisher", "gini_simpson", "inverse_simpson",
    "log_modulo_skewness", "shannon"),
  name = index,
  ...,
  BPPARAM = SerialParam()
)

## S4 method for signature 'TreeSummarizedExperiment'
estimateDiversity(
  x,
  assay.type = "counts",
  assay_name = NULL,
  index = c("coverage", "faith", "fisher", "gini_simpson", "inverse_simpson",
    "log_modulo_skewness", "shannon"),
  name = index,
  tree_name = "phylo",
  ...,
  BPPARAM = SerialParam()
)

estimateFaith(
  x,
```

```

    tree = "missing",
    assay.type = "counts",
    assay_name = NULL,
    name = "faith",
    ...
)

## S4 method for signature 'SummarizedExperiment,phylo'
estimateFaith(
  x,
  tree,
  assay.type = "counts",
  assay_name = NULL,
  name = "faith",
  node_lab = NULL,
  ...
)

## S4 method for signature 'TreeSummarizedExperiment,missing'
estimateFaith(
  x,
  assay.type = "counts",
  assay_name = NULL,
  name = "faith",
  tree_name = "phylo",
  ...
)

```

Arguments

x	a SummarizedExperiment object or TreeSummarizedExperiment . The latter is recommended for microbiome data sets and tree-based alpha diversity indices.
assay.type	the name of the assay used for calculation of the sample-wise estimates.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
index	a character vector, specifying the diversity measures to be calculated.
name	a name for the column(s) of the <code>colData</code> the results should be stored in. By default this will use the original names of the calculated indices.
...	optional arguments: <ul style="list-style-type: none"> • <code>threshold</code> A numeric value in the unit interval, determining the threshold for coverage index. By default, <code>threshold</code> is 0.9. • <code>quantile</code> Arithmetic abundance classes are evenly cut up to to this quantile of the data. The assumption is that abundances higher than this are not common, and they are classified in their own group. By default, <code>quantile</code> is 0.5.

- `num_of_classes` The number of arithmetic abundance classes from zero to the quantile cutoff indicated by `quantile`. By default, `num_of_classes` is 50.
- `only.tips` A boolean value specifying whether to remove internal nodes when Faith's index is calculated. When `only.tips=TRUE`, those rows that are not tips of tree are removed. (By default: `only.tips=FALSE`)

<code>BPPARAM</code>	A BiocParallelParam object specifying whether calculation of estimates should be parallelized.
<code>tree_name</code>	a single character value for specifying which rowTree will be used to calculate faith index. (By default: <code>tree_name = "phylo"</code>)
<code>tree</code>	A phylogenetic tree that is used to calculate 'faith' index. If <code>x</code> is a <code>TreeSummarizedExperiment</code> , <code>rowTree(x)</code> is used by default.
<code>node_lab</code>	NULL or a character vector specifying the links between rows and node labels of tree. If a certain row is not linked with the tree, missing instance should be noted as NA. When NULL, all the rownames should be found from the tree. (By default: <code>node_lab = NULL</code>)

Details

The available indices include the 'Coverage', 'Faith's phylogenetic diversity', 'Fisher alpha', 'Gini-Simpson', 'Inverse Simpson', 'log-modulo skewness', and 'Shannon' indices. See details for more information and references.

Alpha diversity is a joint quantity that combines elements or community richness and evenness. Diversity increases, in general, when species richness or evenness increase.

By default, this function returns all indices.

- 'coverage' Number of species needed to cover a given fraction of the ecosystem (50 percent by default). Tune this with the `threshold` argument.
- 'faith' Faith's phylogenetic alpha diversity index measures how long the taxonomic distance is between taxa that are present in the sample. Larger values represent higher diversity. Using this index requires `rowTree`. (Faith 1992)
If the data includes features that are not in tree's tips but in internal nodes, there are two options. First, you can keep those features, and prune the tree to match features so that each tip can be found from the features. Other option is to remove all features that are not tips. (See `only.tips` parameter)
- 'fisher' Fisher's alpha; as implemented in [vegan::fisher.alpha](#). (Fisher et al. 1943)
- 'gini_simpson' Gini-Simpson diversity i.e. $1 - \lambda$, where λ is the Simpson index, calculated as the sum of squared relative abundances. This corresponds to the diversity index 'simpson' in [vegan::diversity](#). This is also called Gibbs–Martin, or Blau index in sociology, psychology and management studies. The Gini-Simpson index (1-lambda) should not be confused with Simpson's dominance (λ), Gini index, or inverse Simpson index ($1/\lambda$).
- 'inverse_simpson' Inverse Simpson diversity: $1/\lambda$ where $\lambda = \sum(p^2)$ and p refers to relative abundances. This corresponds to the diversity index 'invsimpson' in [vegan::diversity](#). Don't confuse this with the closely related Gini-Simpson index

- 'log_modulo_skewness' The rarity index characterizes the concentration of species at low abundance. Here, we use the skewness of the frequency distribution of arithmetic abundance classes (see Magurran & McGill 2011). These are typically right-skewed; to avoid taking log of occasional negative skews, we follow Locey & Lennon (2016) and use the log-modulo transformation that adds a value of one to each measure of skewness to allow logarithmization.
- 'shannon' Shannon diversity (entropy).

Value

x with additional `colData` named `*name*`

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

References

- Beisel J-N. et al. (2003) A Comparative Analysis of Diversity Index Sensitivity. *Internal Rev. Hydrobiol.* 88(1):3-15. https://portais.ufg.br/up/202/o/2003-comparative_evennes_index.pdf
- Bulla L. (1994) An index of diversity and its associated diversity measure. *Oikos* 70:167–171
- Faith D.P. (1992) Conservation evaluation and phylogenetic diversity. *Biological Conservation* 61(1):1-10.
- Fisher R.A., Corbet, A.S. & Williams, C.B. (1943) The relation between the number of species and the number of individuals in a random sample of animal population. *Journal of Animal Ecology* 12, 42-58.
- Locey K.J. & Lennon J.T. (2016) Scaling laws predict global microbial diversity. *PNAS* 113(21):5970-5975.
- Magurran A.E., McGill BJ, eds (2011) *Biological Diversity: Frontiers in Measurement and Assessment*. (Oxford Univ Press, Oxford), Vol 12.
- Smith B. & Wilson JB. (1996) A Consumer's Guide to Diversity Indices. *Oikos* 76(1):70-82.

See Also

[plotColData](#)

- [estimateRichness](#)
- [estimateEvenness](#)
- [estimateDominance](#)
- [diversity](#)
- [estimateR](#)

Examples

```

data(GlobalPatterns)
tse <- GlobalPatterns

# All index names as known by the function
index <- c("shannon", "gini_simpson", "inverse_simpson", "coverage", "fisher",
"faith", "log_modulo_skewness")

# Corresponding polished names
name <- c("Shannon", "GiniSimpson", "InverseSimpson", "Coverage", "Fisher",
"Faith", "LogModSkewness")

# Calculate diversities
tse <- estimateDiversity(tse, index = index)

# The colData contains the indices with their code names by default
colData(tse)[, index]

# Removing indices
colData(tse)[, index] <- NULL

# 'threshold' can be used to determine threshold for 'coverage' index
tse <- estimateDiversity(tse, index = "coverage", threshold = 0.75)
# 'quantile' and 'num_of_classes' can be used when
# 'log_modulo_skewness' is calculated
tse <- estimateDiversity(tse, index = "log_modulo_skewness",
  quantile = 0.75, num_of_classes = 100)

# It is recommended to specify also the final names used in the output.
tse <- estimateDiversity(tse,
  index = c("shannon", "gini_simpson", "inverse_simpson", "coverage",
"fisher", "faith", "log_modulo_skewness"),
  name = c("Shannon", "GiniSimpson", "InverseSimpson", "Coverage",
"Fisher", "Faith", "LogModSkewness"))

# The colData contains the indices by their new names provided by the user
colData(tse)[, name]

# Compare the indices visually
pairs(colData(tse)[, name])

# Plotting the diversities - use the selected names
library(scater)
plotColData(tse, "Shannon")
# ... by sample type
plotColData(tse, "Shannon", "SampleType")

# combining different plots
library(patchwork)
plot_index <- c("Shannon", "GiniSimpson")
plots <- lapply(plot_index,
  plotColData,

```

```

        object = tse,
        x = "SampleType",
        colour_by = "SampleType")
plots <- lapply(plots,"+",
  theme(axis.text.x = element_text(angle=45,hjust=1)))
names(plots) <- plot_index
plots$Shannon + plots$GiniSimpson + plot_layout(guides = "collect")

```

estimateDominance	<i>Estimate dominance measures</i>
-------------------	------------------------------------

Description

This function calculates community dominance indices. This includes the ‘Absolute’, ‘Berger-Parker’, ‘Core abundance’, ‘Gini’, ‘McNaughton’s’, ‘Relative’, and ‘Simpson’s’ indices.

Usage

```

estimateDominance(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("absolute", "dbp", "core_abundance", "gini", "dmn", "relative",
    "simpson_lambda"),
  ntaxa = 1,
  aggregate = TRUE,
  name = index,
  ...,
  BPPARAM = SerialParam()
)

## S4 method for signature 'SummarizedExperiment'
estimateDominance(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("absolute", "dbp", "core_abundance", "gini", "dmn", "relative",
    "simpson_lambda"),
  ntaxa = 1,
  aggregate = TRUE,
  name = index,
  ...,
  BPPARAM = SerialParam()
)

```

Arguments

x	a <code>SummarizedExperiment</code> object
assay.type	A single character value for selecting the <code>assay</code> to calculate the sample-wise estimates.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
index	a character vector, specifying the indices to be calculated.
ntaxa	Optional and only used for the <code>Absolute</code> and <code>Relative</code> dominance indices: The n-th position of the dominant taxa to consider (default: <code>ntaxa = 1</code>). Disregarded for the indices “ <code>dbp</code> ”, “ <code>core_abundance</code> ”, “ <code>Gini</code> ”, “ <code>dmn</code> ”, and “ <code>Simpson</code> ”.
aggregate	Optional and only used for the <code>Absolute</code> , <code>dbp</code> , <code>Relative</code> , and <code>dmn</code> dominance indices: Aggregate the values for top members selected by <code>ntaxa</code> or not. If <code>TRUE</code> , then the sum of relative abundances is returned. Otherwise the relative abundance is returned for the single taxa with the indicated rank (default: <code>aggregate = TRUE</code>). Disregarded for the indices “ <code>core_abundance</code> ”, “ <code>gini</code> ”, “ <code>dmn</code> ”, and “ <code>simpson</code> ”.
name	A name for the column(s) of the <code>colData</code> where the calculated Dominance indices should be stored in.
...	additional arguments currently not used.
BPPARAM	A <code>BiocParallelParam</code> object specifying whether calculation of estimates should be parallelized. (Currently not used)

Details

A dominance index quantifies the dominance of one or few species in a community. Greater values indicate higher dominance.

Dominance indices are in general negatively correlated with alpha diversity indices (species richness, evenness, diversity, rarity). More dominant communities are less diverse.

`estimateDominance` calculates the following community dominance indices:

- ‘`absolute`’ Absolute index equals to the absolute abundance of the most dominant n species of the sample (specify the number with the argument `ntaxa`). Index gives positive integer values.
- ‘`dbp`’ Berger-Parker index (See Berger & Parker 1970) calculation is a special case of the ‘`relative`’ index. `dbp` is the relative abundance of the most abundant species of the sample. Index gives values in interval 0 to 1, where bigger value represent greater dominance.

$$dbp = \frac{N_1}{N_{tot}}$$

where N_1 is the absolute abundance of the most dominant species and N_{tot} is the sum of absolute abundances of all species.

- ‘`core_abundance`’ Core abundance index is related to core species. Core species are species that are most abundant in all samples, i.e., in whole data set. Core species are defined as those species that have prevalence over 50\ species must be prevalent in 50\ calculate the core abundance index. Core abundance index is sum of relative abundances of core species in the sample. Index gives values in interval 0 to 1, where bigger value represent greater dominance.

$$core_abundance = \frac{N_{core}}{N_{tot}}$$

where N_{core} is the sum of absolute abundance of the core species and N_{tot} is the sum of absolute abundances of all species.

- 'gini' Gini index is probably best-known from socio-economic contexts (Gini 1921). In economics, it is used to measure, for example, how unevenly income is distributed among population. Here, Gini index is used similarly, but income is replaced with abundance.

If there is small group of species that represent large portion of total abundance of microbes, the inequality is large and Gini index closer to 1. If all species has equally large abundances, the equality is perfect and Gini index equals 0. This index should not be confused with Gini-Simpson index, which quantifies diversity.

- 'dmn' McNaughton's index is the sum of relative abundances of the two most abundant species of the sample (McNaughton & Wolf, 1970). Index gives values in the unit interval:

$$dmn = (N_1 + N_2)/N_{tot}$$

where N_1 and N_2 are the absolute abundances of the two most dominant species and N_{tot} is the sum of absolute abundances of all species.

- 'relative' Relative index equals to the relative abundance of the most dominant n species of the sample (specify the number with the argument ntaxa). This index gives values in interval 0 to 1.

$$relative = N_1/N_{tot}$$

where N_1 is the absolute abundance of the most dominant species and N_{tot} is the sum of absolute abundances of all species.

- 'simpson_lambda' Simpson's (dominance) index or Simpson's lambda is the sum of squared relative abundances. This index gives values in the unit interval. This value equals the probability that two randomly chosen individuals belongs to the same species. The higher the probability, the greater the dominance (See e.g. Simpson 1949).

$$lambda = \sum(p^2)$$

where p refers to relative abundances.

There is also a more advanced Simpson dominance index (Simpson 1949). However, this is not provided and the simpler squared sum of relative abundances is used instead as the alternative index is not in the unit interval and it is highly correlated with the simpler variant implemented here.

Value

x with additional `colData` named `*name*`

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

References

- Berger WH & Parker FL (1970) Diversity of Planktonic Foraminifera in Deep-Sea Sediments. *Science* 168(3937):1345-1347. doi: 10.1126/science.168.3937.1345
- Gini C (1921) Measurement of Inequality of Incomes. *The Economic Journal* 31(121): 124-126. doi: 10.2307/2223319
- McNaughton, SJ and Wolf LL. (1970). Dominance and the niche in ecological systems. *Science* 167:13, 1-139
- Simpson EH (1949) Measurement of Diversity. *Nature* 163(688). doi: 10.1038/163688a0

See Also

- [estimateRichness](#)
- [estimateEvenness](#)
- [estimateDiversity](#)

Examples

```
data(esophagus)

# Calculates Simpson's lambda (can be used as a dominance index)
esophagus <- estimateDominance(esophagus, index="simpson_lambda")

# Shows all indices
colData(esophagus)

# Indices must be written correctly (e.g. dbp, not dbp), otherwise an error
# gets thrown
esophagus <- estimateDominance(esophagus, index="dbp")
# Calculates dbp and Core Abundance indices
esophagus <- estimateDominance(esophagus, index=c("dbp", "core_abundance"))
# Shows all indices
colData(esophagus)
# Shows dbp index
colData(esophagus)$dbp
# Deletes dbp index
colData(esophagus)$dbp <- NULL
# Shows all indices, dbp is deleted
colData(esophagus)
# Deletes all indices
colData(esophagus) <- NULL

# Calculates all indices
esophagus <- estimateDominance(esophagus)
# Shows all indices
colData(esophagus)
# Deletes all indices
colData(esophagus) <- NULL

# Calculates all indices with explicitly specified names
esophagus <- estimateDominance(esophagus,
```

```

index = c("dbp", "dmn", "absolute", "relative",
          "simpson_lambda", "core_abundance", "gini"),
name   = c("BergerParker", "McNaughton", "Absolute", "Relative",
          "SimpsonLambda", "CoreAbundance", "Gini")
)
# Shows all indices
colData(esophagus)

```

estimateEvenness	<i>Estimate Evenness measures</i>
------------------	-----------------------------------

Description

This function calculates community evenness indices. These include the ‘Camargo’, ‘Pielou’, ‘Simpson’, ‘Evar’ and ‘Bulla’ evenness measures. See details for more information and references.

Usage

```

estimateEvenness(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("pielou", "camargo", "simpson_evenness", "evar", "bulla"),
  name = index,
  ...
)

## S4 method for signature 'SummarizedExperiment'
estimateEvenness(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("camargo", "pielou", "simpson_evenness", "evar", "bulla"),
  name = index,
  ...,
  BPPARAM = SerialParam()
)

```

Arguments

x	a SummarizedExperiment object
assay.type	A single character value for selecting the assay used for calculation of the sample-wise estimates.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
index	a character vector, specifying the evenness measures to be calculated.

name	a name for the column(s) of the colData the results should be stored in.
...	optional arguments:
	<ul style="list-style-type: none"> • threshold a numeric threshold. assay values below or equal to this threshold will be set to zero.
BPPARAM	A <code>BiocParallelParam</code> object specifying whether calculation of estimates should be parallelized.

Details

Evenness is a standard index in community ecology, and it quantifies how evenly the abundances of different species are distributed. The following evenness indices are provided:

By default, this function returns all indices.

The available evenness indices include the following (all in lowercase):

- 'camargo' Camargo's evenness (Camargo 1992)
- 'simpson_evenness' Simpson's evenness is calculated as inverse Simpson diversity ($1/\lambda$) divided by observed species richness S : $(1/\lambda)/S$.
- 'pielou' Pielou's evenness (Pielou, 1966), also known as Shannon or Shannon-Weaver/Wiener/Weiner evenness; $H/\ln(S)$. The Shannon-Weaver is the preferred term; see Spellerberg and Fedor (2003).
- 'evar' Smith and Wilson's Evar index (Smith & Wilson 1996).
- 'bulla' Bulla's index (O) (Bulla 1994).

Desirable statistical evenness metrics avoid strong bias towards very large or very small abundances; are independent of richness; and range within the unit interval with increasing evenness (Smith & Wilson 1996). Evenness metrics that fulfill these criteria include at least camargo, simpson, smith-wilson, and bulla. Also see Magurran & McGill (2011) and Beisel et al. (2003) for further details.

Value

x with additional `colData` named `*name*`

References

- Beisel J-N. et al. (2003) A Comparative Analysis of Evenness Index Sensitivity. *Internal Rev. Hydrobiol.* 88(1):3-15. URL: https://portais.ufg.br/up/202/o/2003-comparative_evenness_index.pdf
- Bulla L. (1994) An index of evenness and its associated diversity measure. *Oikos* 70:167–171.
- Camargo, JA. (1992) New diversity index for assessing structural alterations in aquatic communities. *Bull. Environ. Contam. Toxicol.* 48:428–434.
- Locey KJ and Lennon JT. (2016) Scaling laws predict global microbial diversity. *PNAS* 113(21):5970-5975; doi:10.1073/pnas.1521291113.
- Magurran AE, McGill BJ, eds (2011) Biological Diversity: Frontiers in Measurement and Assessment (Oxford Univ Press, Oxford), Vol 12.
- Pielou, EC. (1966) The measurement of diversity in different types of biological collections. *J Theoretical Biology* 13:131–144.

Smith B and Wilson JB. (1996) A Consumer's Guide to Evenness Indices. *Oikos* 76(1):70-82.

Spellerberg and Fedor (2003). A tribute to Claude Shannon (1916 –2001) and a plea for more rigorous use of species richness, species diversity and the 'Shannon–Wiener' Index. *Alpha Ecology & Biogeography* 12, 177–197.

See Also

[plotColData](#)

- [estimateRichness](#)
- [estimateDominance](#)
- [estimateDiversity](#)

Examples

```
data(esophagus)
tse <- esophagus

# Specify index and their output names
index <- c("pielou", "camargo", "simpson_evenness", "evar", "bulla")
name <- c("Pielou", "Camargo", "SimpsonEvenness", "Evar", "Bulla")

# Estimate evenness and give polished names to be used in the output
tse <- estimateEvenness(tse, index = index, name = name)

# Check the output
head(colData(tse))
```

estimateRichness	<i>Estimate richness measures</i>
------------------	-----------------------------------

Description

Several functions for calculation of community richness indices available via wrapper functions. They are implemented via the `vegan` package.

Usage

```
estimateRichness(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("ace", "chao1", "hill", "observed"),
  name = index,
  detection = 0,
  ...,
  BPPARAM = SerialParam()
```

```

)

## S4 method for signature 'SummarizedExperiment'
estimateRichness(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  index = c("ace", "chao1", "hill", "observed"),
  name = index,
  detection = 0,
  ...,
  BPPARAM = SerialParam()
)

```

Arguments

<code>x</code>	a SummarizedExperiment object.
<code>assay.type</code>	the name of the assay used for calculation of the sample-wise estimates.
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>index</code>	a character vector, specifying the richness measures to be calculated.
<code>name</code>	a name for the column(s) of the <code>colData</code> the results should be stored in.
<code>detection</code>	a numeric value for selecting detection threshold for the abundances. The default detection threshold is 0.
<code>...</code>	additional parameters passed to <code>estimateRichness</code>
<code>BPPARAM</code>	A BiocParallelParam object specifying whether calculation of estimates should be parallelized.

Details

These include the ‘ace’, ‘Chao1’, ‘Hill’, and ‘Observed’ richness measures. See details for more information and references.

The richness is calculated per sample. This is a standard index in community ecology, and it provides an estimate of the number of unique species in the community. This is often not directly observed for the whole community but only for a limited sample from the community. This has led to alternative richness indices that provide different ways to estimate the species richness.

Richness index differs from the concept of species diversity or evenness in that it ignores species abundance, and focuses on the binary presence/absence values that indicate simply whether the species was detected.

The function takes all index names in full lowercase. The user can provide the desired spelling through the argument `name` (see examples).

The following richness indices are provided.

- ‘ace’ Abundance-based coverage estimator (ACE) is another nonparametric richness index that uses sample coverage, defined based on the sum of the probabilities of the observed species. This method divides the species into abundant (more than 10 reads or observations)

and rare groups in a sample and tends to underestimate the real number of species. The ACE index ignores the abundance information for the abundant species, based on the assumption that the abundant species are observed regardless of their exact abundance. We use here the bias-corrected version (O'Hara 2005, Chiu et al. 2014) implemented in [estimateR](#). For an exact formulation, see [estimateR](#). Note that this index comes with an additional column with standard error information.

- 'chao1' This is a nonparametric estimator of species richness. It assumes that rare species carry information about the (unknown) number of unobserved species. We use here the bias-corrected version (O'Hara 2005, Chiu et al. 2014) implemented in [estimateR](#). This index implicitly assumes that every taxa has equal probability of being observed. Note that it gives a lower bound to species richness. The bias-corrected for an exact formulation, see [estimateR](#). This estimator uses only the singleton and doubleton counts, and hence it gives more weight to the low abundance species. Note that this index comes with an additional column with standard error information.
- 'hill' Effective species richness aka Hill index (see e.g. Chao et al. 2016). Currently only the case 1D is implemented. This corresponds to the exponent of Shannon diversity. Intuitively, the effective richness indicates the number of species whose even distribution would lead to the same diversity than the observed community, where the species abundances are unevenly distributed.
- 'observed' The *observed richness* gives the number of species that is detected above a given detection threshold in the observed sample (default 0). This is conceptually the simplest richness index. The corresponding index in the **vegan** package is "richness".

Value

x with additional [colData](#) named *name*

Author(s)

Leo Lahti. Contact: microbiome.github.io

References

- Chao A. (1984) Non-parametric estimation of the number of classes in a population. *Scand J Stat.* 11:265–270.
- Chao A, Chun-Huo C, Jost L (2016). Phylogenetic Diversity Measures and Their Decomposition: A Framework Based on Hill Numbers. *Biodiversity Conservation and Phylogenetic Systematics*, Springer International Publishing, pp. 141–172, doi:10.1007/978-3-319-22461-9_8.
- Chiu, C.H., Wang, Y.T., Walther, B.A. & Chao, A. (2014). Improved nonparametric lower bound of species richness via a modified Good-Turing frequency formula. *Biometrics* 70, 671-682.
- O'Hara, R.B. (2005). Species richness estimators: how many species can dance on the head of a pin? *J. Anim. Ecol.* 74, 375-386.

See Also

[plotColData](#)

- [estimateR](#)

Examples

```
data(esophagus)

# Calculates all richness indices by default
esophagus <- estimateRichness(esophagus)

# Shows all indices
colData(esophagus)

# Shows Hill index
colData(esophagus)$hill

# Deletes hill index
colData(esophagus)$hill <- NULL

# Shows all indices, hill is deleted
colData(esophagus)

# Delete the remaining indices
colData(esophagus[, c("observed", "chao1", "ace")] <- NULL

# Calculates observed richness index and saves them with specific names
esophagus <- estimateRichness(esophagus,
  index = c("observed", "chao1", "ace", "hill"),
  name = c("Observed", "Chao1", "ACE", "Hill"))

# Show the new indices
colData(esophagus)

# Deletes all colData (including the indices)
colData(esophagus) <- NULL

# Calculate observed richness excluding singletons (detection limit 1)
esophagus <- estimateRichness(esophagus, index="observed", detection = 1)

# Deletes all colData (including the indices)
colData(esophagus) <- NULL

# Indices must be written correctly (all lowercase), otherwise an error
# gets thrown
esophagus <- estimateRichness(esophagus, index="ace")

# Calculates Chao1 and ACE indices only
esophagus <- estimateRichness(esophagus, index=c("chao1", "ace"),
  name=c("Chao1", "ACE"))

# Deletes all colData (including the indices)
colData(esophagus) <- NULL

# Names of columns can be chosen arbitrarily, but the length of arguments
# must match.
esophagus <- estimateRichness(esophagus,
```



```

index = c("ace", "chao1"),
name = c("index1", "index2")

# Shows all indices
colData(esophagus)

```

```
getExperimentCrossAssociation
```

Calculate correlations between features of two experiments.

Description

Calculate correlations between features of two experiments.

Usage

```

getExperimentCrossAssociation(x, ...)

## S4 method for signature 'MultiAssayExperiment'
getExperimentCrossAssociation(
  x,
  experiment1 = 1,
  experiment2 = 2,
  assay.type1 = assay_name1,
  assay_name1 = "counts",
  assay.type2 = assay_name2,
  assay_name2 = "counts",
  altexp1 = NULL,
  altexp2 = NULL,
  colData_variable1 = NULL,
  colData_variable2 = NULL,
  MARGIN = 1,
  method = c("kendall", "spearman", "categorical", "pearson"),
  mode = "table",
  p_adj_method = c("fdr", "BH", "bonferroni", "BY", "hochberg", "holm", "hommel", "none"),
  p_adj_threshold = NULL,
  cor_threshold = NULL,
  sort = FALSE,
  filter_self_correlations = FALSE,
  verbose = TRUE,
  test_significance = FALSE,
  show_warnings = TRUE,
  paired = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'

```

```

getExperimentCrossAssociation(x, experiment2 = x, ...)

testExperimentCrossAssociation(x, ...)

## S4 method for signature 'ANY'
testExperimentCrossAssociation(x, ...)

testExperimentCrossCorrelation(x, ...)

## S4 method for signature 'ANY'
testExperimentCrossCorrelation(x, ...)

getExperimentCrossCorrelation(x, ...)

## S4 method for signature 'ANY'
getExperimentCrossCorrelation(x, ...)

```

Arguments

x	A MultiAssayExperiment or SummarizedExperiment object.
...	Additional arguments: <ul style="list-style-type: none"> • <code>symmetric</code> A single boolean value for specifying if measure is symmetric or not. When <code>symmetric = TRUE</code>, associations are calculated only for unique variable-pairs, and they are assigned to corresponding variable-pair. This decreases the number of calculations in 2-fold meaning faster execution. (By default: <code>symmetric = FALSE</code>) • <code>association_FUN</code> A function that is used to calculate (dis-)similarity between features. Function must take matrix as an input and give numeric values as an output. Adjust method and other parameters correspondingly. Supported functions are, for example, <code>stats::dist</code> and <code>vegan::vegdist</code>.
experiment1	A single character or numeric value for selecting the experiment 1 from <code>experiments(x)</code> of <code>MultiassayExperiment</code> object. (By default: <code>experiment1 = 1</code>)
experiment2	A single character or numeric value for selecting the experiment 2 from <code>experiments(x)</code> of <code>MultiAssayExperiment</code> object or <code>altExp(x)</code> of <code>TreeSummarizedExperiment</code> object. Alternatively, <code>experiment2</code> can also be <code>TreeSE</code> object when <code>x</code> is <code>TreeSE</code> object. (By default: <code>experiment2 = 2</code> when <code>x</code> is <code>MAE</code> and <code>experiment2 = x</code> when <code>x</code> is <code>TreeSE</code>)
assay.type1	A single character value for selecting the assay of experiment 1 to be transformed. (By default: <code>assay.type1 = "counts"</code>)
assay_name1	a single character value for specifying which assay of experiment 1 to use for calculation. (Please use <code>assay.type1</code> instead. At some point <code>assay_name1</code> will be disabled.)
assay.type2	A single character value for selecting the assay of experiment 2 to be transformed. (By default: <code>assay.type2 = "counts"</code>)
assay_name2	a single character value for specifying which assay of experiment 2 to use for calculation. (Please use <code>assay.type2</code> instead. At some point <code>assay_name2</code> will be disabled.)

altexp1	A single numeric or character value specifying alternative experiment from the altExp of experiment 1. If NULL, then the experiment is itself and altExp option is disabled. (By default: altexp1 = NULL)
altexp2	A single numeric or character value specifying alternative experiment from the altExp of experiment 2. If NULL, then the experiment is itself and altExp option is disabled. (By default: altexp2 = NULL)
colData_variable1	A character value specifying column(s) from colData of experiment 1. If colData_variable1 is used, assay.type1 is disabled. (By default: colData_variable1 = NULL)
colData_variable2	A character value specifying column(s) from colData of experiment 2. If colData_variable2 is used, assay.type2 is disabled. (By default: colData_variable2 = NULL)
MARGIN	A single numeric value for selecting if association are calculated row-wise / for features (1) or column-wise / for samples (2). Must be 1 or 2. (By default: MARGIN = 1)
method	A single character value for selecting association method ('kendall', 'pearson', or 'spearman' for continuous/numeric; 'categorical' for discrete) (By default: method = "kendall")
mode	A single character value for selecting output format Available formats are 'table' and 'matrix'. (By default: mode = "table")
p_adj_method	A single character value for selecting adjustment method of p-values. Passed to p.adjust function. (By default: p_adj_method = "fdr")
p_adj_threshold	A single numeric value (from 0 to 1) for selecting adjusted p-value threshold for filtering. (By default: p_adj_threshold = NULL)
cor_threshold	A single numeric absolute value (from 0 to 1) for selecting correlation threshold for filtering. (By default: cor_threshold = NULL)
sort	A single boolean value for selecting whether to sort features or not in result matrices. Used method is hierarchical clustering. (By default: sort = FALSE)
filter_self_correlations	A single boolean value for selecting whether to filter out correlations between identical items. Applies only when correlation between experiment itself is tested, i.e., when assays are identical. (By default: filter_self_correlations = FALSE)
verbose	A single boolean value for selecting whether to get messages about progress of calculation.
test_significance	A single boolean value for selecting whether to test statistical significance of associations.
show_warnings	A single boolean value for selecting whether to show warnings that might occur when correlations and p-values are calculated.
paired	A single boolean value for specifying if samples are paired or not. colnames must match between twp experiments. paired is disabled when MARGIN = 1. (By default: paired = FALSE)

Details

These functions calculates associations between features of two experiments. `getExperimentCrossAssociation` calculates only associations by default. `testExperimentCrossAssociation` calculates also significance of associations.

We recommend the non-parametric Kendall's tau as the default method for association analysis. Kendall's tau has desirable statistical properties and robustness at lower sample sizes. Spearman rank correlation can provide faster solutions when running times are critical.

Value

These functions return associations in table or matrix format. In table format, returned value is a data frame that includes features and associations (and p-values) in columns. In matrix format, returned value is a one matrix when only associations are calculated. If also significances are tested, then returned value is a list of matrices.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

Examples

```
data(HintikkaX0Data)
mae <- HintikkaX0Data

# Subset so that less observations / quicker to run, just for example
mae[[1]] <- mae[[1]][1:20, 1:10]
mae[[2]] <- mae[[2]][1:20, 1:10]
# Several rows in the counts assay have a standard deviation of zero
# Remove them, since they do not add useful information about cross-association
mae[[1]] <- mae[[1]][rowSds(assay(mae[[1]])) > 0, ]
# Transform data
mae[[1]] <- transformAssay(mae[[1]], method = "rclr")

# Calculate cross-correlations
result <- getExperimentCrossAssociation(mae, method = "pearson", assay.type2 = "nmr")
# Show first 5 entries
head(result, 5)

# Use altExp option to specify alternative experiment from the experiment
altExp(mae[[1]], "Phylum") <- agglomerateByRank(mae[[1]], rank = "Phylum")
# Transform data
altExp(mae[[1]], "Phylum") <- transformAssay(altExp(mae[[1]], "Phylum"), method = "relabundance")
# When mode = "matrix", the return value is a matrix
result <- getExperimentCrossAssociation(mae, experiment2 = 2,
                                       assay.type1 = "relabundance", assay.type2 = "nmr",
                                       altexp1 = "Phylum",
                                       method = "pearson", mode = "matrix")

# Show first 5 entries
head(result, 5)

# testExperimentCorrelation additionally returns significances
```

```

# filter_self_correlations = TRUE filters self correlations
# p_adj_threshold can be used to filter those features that do not
# have any correlations whose p-value is lower than the threshold
result <- testExperimentCrossAssociation(mae[[1]], experiment2 = mae[[1]], method = "pearson",
                                       filter_self_correlations = TRUE,
                                       p_adj_threshold = 0.05)

# Show first 5 entries
head(result, 5)

# getExperimentCrossAssociation also returns significances when
# test_significance = TRUE
# Warnings can be suppressed by using show_warnings = FALSE
result <- getExperimentCrossAssociation(mae[[1]], experiment2 = mae[[2]], method = "pearson",
                                       assay.type2 = "nmr",
                                       mode = "matrix", test_significance = TRUE,
                                       show_warnings = FALSE)

# Returned value is a list of matrices
names(result)

# Calculate Bray-Curtis dissimilarity between samples. If dataset includes
# paired samples, you can use paired = TRUE.
result <- getExperimentCrossAssociation(mae[[1]], mae[[1]], MARGIN = 2, paired = FALSE,
                                       association_FUN = vegan::vegdist, method = "bray")

# If experiments are equal and measure is symmetric (e.g., taxa1 vs taxa2 == taxa2 vs taxa1),
# it is possible to speed-up calculations by calculating association only for unique
# variable-pairs. Use "symmetric" to choose whether to measure association for only
# other half of of variable-pairs.
result <- getExperimentCrossAssociation(mae, experiment1 = "microbiota", experiment2 = "microbiota",
                                       assay.type1 = "counts", assay.type2 = "counts",
                                       symmetric = TRUE)

# For big data sets, the calculations might take a long time.
# To speed them up, you can take a random sample from the data.
# When dealing with complex biological problems, random samples can be
# enough to describe the data. Here, our random sample is 30 % of whole data.
sample_size <- 0.3
tse <- mae[[1]]
tse_sub <- tse[ sample( seq_len( nrow(tse) ), sample_size * nrow(tse) ), ]
result <- testExperimentCrossAssociation(tse_sub)

# It is also possible to choose variables from colData and calculate association
# between assay and sample metadata or between variables of sample metadata
mae[[1]] <- estimateDiversity(mae[[1]])
# colData_variable works similarly to assay.type. Instead of fetching an assay
# named assay.type from assay slot, it fetches a column named colData_variable
# from colData.
result <- getExperimentCrossAssociation(mae[[1]], assay.type1 = "counts",
                                       colData_variable2 = c("shannon", "coverage"))

```

getPrevalence	<i>Calculation prevalence information for features across samples</i>
---------------	---

Description

These functions calculate the population prevalence for taxonomic ranks in a [SummarizedExperiment-class](#) object.

Usage

```

getPrevalence(x, ...)

## S4 method for signature 'ANY'
getPrevalence(
  x,
  detection = 0,
  include_lowest = FALSE,
  sort = FALSE,
  na.rm = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
getPrevalence(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  as_relative = FALSE,
  rank = NULL,
  ...
)

getPrevalentFeatures(x, ...)

## S4 method for signature 'ANY'
getPrevalentFeatures(x, prevalence = 50/100, include_lowest = FALSE, ...)

## S4 method for signature 'SummarizedExperiment'
getPrevalentFeatures(
  x,
  rank = NULL,
  prevalence = 50/100,
  include_lowest = FALSE,
  ...
)

getPrevalentTaxa(x, ...)

```

```
## S4 method for signature 'ANY'
getPrevalentTaxa(x, ...)

getRareFeatures(x, ...)

## S4 method for signature 'ANY'
getRareFeatures(x, prevalence = 50/100, include_lowest = FALSE, ...)

## S4 method for signature 'SummarizedExperiment'
getRareFeatures(
  x,
  rank = NULL,
  prevalence = 50/100,
  include_lowest = FALSE,
  ...
)

getRareTaxa(x, ...)

## S4 method for signature 'ANY'
getRareTaxa(x, ...)

subsetByPrevalentFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsetByPrevalentFeatures(x, rank = NULL, ...)

subsetByPrevalentTaxa(x, ...)

## S4 method for signature 'ANY'
subsetByPrevalentTaxa(x, ...)

subsetByRareFeatures(x, ...)

## S4 method for signature 'SummarizedExperiment'
subsetByRareFeatures(x, rank = NULL, ...)

subsetByRareTaxa(x, ...)

## S4 method for signature 'ANY'
subsetByRareTaxa(x, ...)

getPrevalentAbundance(
  x,
  assay.type = assay_name,
  assay_name = "relabundance",
  ...
)
```

```

)

## S4 method for signature 'ANY'
getPrevalentAbundance(
  x,
  assay.type = assay_name,
  assay_name = "relabundance",
  ...
)

## S4 method for signature 'SummarizedExperiment'
getPrevalentAbundance(x, assay.type = assay_name, assay_name = "counts", ...)

```

Arguments

x	a SummarizedExperiment object
...	additional arguments <ul style="list-style-type: none"> • If <code>!is.null(rank)</code> arguments are passed on to agglomerateByRank. See ?agglomerateByRank for more details. Note that you can specify whether to remove empty ranks with <code>agg.na.rm</code> instead of <code>na.rm</code>. (default: FALSE) • for <code>getPrevalentFeatures</code>, <code>getRareFeatures</code>, <code>subsetByPrevalentFeatures</code> and <code>subsetByRareFeatures</code> additional parameters passed to <code>getPrevalence</code> • for <code>getPrevalentAbundance</code> additional parameters passed to <code>getPrevalentFeatures</code>
detection	Detection threshold for absence/presence. Either an absolute value compared directly to the values of x or a relative value between 0 and 1, if <code>as_relative = FALSE</code> .
include_lowest	logical scalar: Should the lower boundary of the detection and prevalence cutoffs be included? (default: FALSE)
sort	logical scalar: Should the result be sorted by prevalence? (default: FALSE)
na.rm	logical scalar: Should NA values be omitted when calculating prevalence? (default: <code>na.rm = TRUE</code>)
assay.type	A single character value for selecting the assay to use for prevalence calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
as_relative	logical scalar: Should the detection threshold be applied on compositional (relative) abundances? (default: FALSE)
rank	a single character defining a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function.
prevalence	Prevalence threshold (in 0 to 1). The required prevalence is strictly greater by default. To include the limit, set <code>include_lowest</code> to TRUE.

Details

`getPrevalence` calculates the relative frequency of samples that exceed the detection threshold. For `SummarizedExperiment` objects, the prevalence is calculated for the selected taxonomic rank,

otherwise for the rows. The absolute population prevalence can be obtained by multiplying the prevalence by the number of samples (`ncol(x)`). If `as_relative = FALSE` the relative frequency (between 0 and 1) is used to check against the detection threshold.

The core abundance index from `getPrevalentAbundance` gives the relative proportion of the core species (in between 0 and 1). The core taxa are defined as those that exceed the given population prevalence threshold at the given detection level as set for `getPrevalentFeatures`.

`subsetPrevalentFeatures` and `subsetRareFeatures` return a subset of `x`. The subset includes the most prevalent or rare taxa that are calculated with `getPrevalentFeatures` or `getRareFeatures` respectively.

`getPrevalentFeatures` returns taxa that are more prevalent with the given detection threshold for the selected taxonomic rank.

`getRareFeatures` returns complement of `getPrevalentTaxa`.

Value

`subsetPrevalentFeatures` and `subsetRareFeatures` return subset of `x`.

All other functions return a named vectors:

- `getPrevalence` returns a numeric vector with the names being set to either the row names of `x` or the names after agglomeration.
- `getPrevalentAbundance` returns a numeric vector with the names corresponding to the column name of `x` and include the joint abundance of prevalent taxa.
- `getPrevalentTaxa` and `getRareFeatures` return a character vector with only the names exceeding the threshold set by prevalence, if the rownames of `x` is set. Otherwise an integer vector is returned matching the rows in `x`.

Author(s)

Leo Lahti For `getPrevalentAbundance`: Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

References

A Salonen et al. The adult intestinal core microbiota is determined by analysis depth and health status. *Clinical Microbiology and Infection* 18(S4):16-20, 2012. To cite the R package, see `citation('mia')`

See Also

[agglomerateByRank](#), [getTopTaxa](#)

Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns
# Get prevalence estimates for individual ASV/OTU
prevalence.frequency <- getPrevalence(tse,
                                     detection = 0,
```

```

                                sort = TRUE,
                                as_relative = TRUE)
head(prevalence.frequency)

# Get prevalence estimates for phylums
# - the getPrevalence function itself always returns population frequencies
prevalence.frequency <- getPrevalence(tse,
                                     rank = "Phylum",
                                     detection = 0,
                                     sort = TRUE,
                                     as_relative = TRUE)

head(prevalence.frequency)

# - to obtain population counts, multiply frequencies with the sample size,
# which answers the question "In how many samples is this phylum detectable"
prevalence.count <- prevalence.frequency * ncol(tse)
head(prevalence.count)

# Detection threshold 1 (strictly greater by default);
# Note that the data (GlobalPatterns) is here in absolute counts
# (and not compositional, relative abundances)
# Prevalence threshold 50 percent (strictly greater by default)
prevalent <- getPrevalentFeatures(tse,
                                 rank = "Phylum",
                                 detection = 10,
                                 prevalence = 50/100,
                                 as_relative = FALSE)

head(prevalent)

# Gets a subset of object that includes prevalent taxa
altExp(tse, "prevalent") <- subsetByPrevalentFeatures(tse,
                                                      rank = "Family",
                                                      detection = 0.001,
                                                      prevalence = 0.55,
                                                      as_relative = TRUE)

altExp(tse, "prevalent")

# getRareFeatures returns the inverse
rare <- getRareFeatures(tse,
                       rank = "Phylum",
                       detection = 1/100,
                       prevalence = 50/100,
                       as_relative = TRUE)

head(rare)

# Gets a subset of object that includes rare taxa
altExp(tse, "rare") <- subsetByRareFeatures(tse,
                                            rank = "Class",
                                            detection = 0.001,
                                            prevalence = 0.001,
                                            as_relative = TRUE)

altExp(tse, "rare")

```

```
# Names of both experiments, prevalent and rare, can be found from slot altExpNames
tse

data(esophagus)
getPrevalentAbundance(esophagus, assay.type = "counts")
```

GlobalPatterns

GlobalPatterns

Description

GlobalPatterns compared the microbial communities from 25 environmental samples and three known "mock communities" at an average depth of 3.1 million reads per sample. Authors reproduced diversity patterns seen in many other published studies, while investigating technical bias by applying the same techniques to simulated microbial communities of known composition. Special thanks are given to J. Gregory Caporaso for providing the OTU-clustered data files for inclusion in the **phyloseq** package, from which this data was converted to TreeSummarizedExperiment.

Usage

```
data(GlobalPatterns)
```

Format

A TreeSummarizedExperiment with 19216 features and 26 samples. The rowData contains taxonomic information at Kingdom, Phylum, Class, Order, Family, Genus and Species levels. The colData includes:

X.SampleID Sample ID taken from the corresponding study

Primer primer used for sequencing

Final_Barcode final barcode (6 nucleotides)

Barcode_truncated_plus_T truncated barcode with an added tyrosine (6 nucleotides)

Barcode_full_length complete barcode with a length of 11 nucleotides

SampleType sampling type by collection site (Soil, Feces, Skin, Tongue, Freshwater, Creek Freshwater, Ocean, Estuary Sediment and Mock)

Description additional information (sampling location, environmental factors and study type)

Author(s)

Caporaso, J. G., et al.

References

Caporaso, J. G., et al. (2011). Global patterns of 16S rRNA diversity at a depth of millions of sequences per sample. PNAS, 108, 4516-4522. <https://doi.org/10.1073/pnas.1000080107>

See Also[mia-datasets](#)

hierarchy-tree	<i>Calculate hierarchy tree</i>
----------------	---------------------------------

Description

These functions generate a hierarchy tree using taxonomic information from a [SummarizedExperiment](#) object and add this hierarchy tree into the rowTree.

Usage

```
getHierarchyTree(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getHierarchyTree(x)  
  
addHierarchyTree(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
addHierarchyTree(x)
```

Arguments

x a [SummarizedExperiment](#) object
... optional arguments not used currently.

Details

addHierarchyTree calculates a hierarchy tree from the available taxonomic information and add it to rowTree.

getHierarchyTree generates a hierarchy tree from the available taxonomic information. Internally it uses [toTree](#) and [resolveLoop](#) to sanitize data if needed.

Please note that a hierarchy tree is not an actual phylogenetic tree. A phylogenetic tree represents evolutionary relationships among features. On the other hand, a hierarchy tree organizes species into a hierarchical structure based on their taxonomic ranks.

Value

- addHierarchyTree: a TreeSummarizedExperiment whose phylo tree represents the hierarchy among available taxonomy information
- getHierarchyTree: a phylo tree representing the hierarchy among available taxonomy information.

Examples

```
# Generate a tree based on taxonomic rank hierarchy (a hierarchy tree).
data(GlobalPatterns)
tse <- GlobalPatterns
getHierarchyTree(tse)

# Add a hierarchy tree to a TreeSummarizedExperiment.
# Please note that any tree already stored in rowTree() will be overwritten.
tse <- addHierarchyTree(tse)
tse
```

HintikkaXOData

HintikkaXOData

Description

HintikkaXO is a multiomics dataset from a rat experiment studying effect of fat and prebiotics in diet. It contains high-throughput profiling data from 40 rat samples, including 39 biomarkers, 38 metabolites (NMR), and 12706 OTUs from 318 species, measured from Cecum. This is diet comparison study with High/Low fat diet and xylo-oligosaccharide supplementation. Column metadata is common for all experiments (microbiota, metabolites, biomarkers) and is described below.

Usage

```
data(HintikkaXOData)
```

Format

A MultiAssayExperiment with 3 experiments (microbiota, metabolites and biomarkers). rowData of the microbiota experiment contains taxonomic information at Phylum, Class, Order, Family, Genus, Species and OTU levels. The metabolites and biomarkers experiments contain 38 NMR metabolites and 39 biomarkers, respectively. The colData includes:

Sample Sample ID (character)

Rat Rat ID (factor)

Site Site of measurement ("Cecum"); single value

Diet Diet group (factor; combination of the Fat and XOS fields)

Fat Fat in Diet (factor; Low/High)

XOS XOS Diet Supplement (numeric; 0/1)

Author(s)

Hintikka L et al.

References

Hintikka L et al. (2021): Xylo-oligosaccharides in prevention of hepatic steatosis and adipose tissue inflammation: associating taxonomic and metabolomic patterns in fecal microbiota with bi-clustering. *International Journal of Environmental Research and Public Health* 18(8):4049. <https://doi.org/10.3390/ijerph18084049>

See Also

[mia-datasets](#)

importHUMANn

Import HUMANn results to TreeSummarizedExperiment

Description

Import HUMANn results to TreeSummarizedExperiment

Arguments

file	a single character value defining the file path of the HUMANn file. The file must be in merged HUMANn format.
colData	a DataFrame-like object that includes sample names in rownames, or a single character value defining the file path of the sample metadata file. The file must be in tsv format (default: colData = NULL).
...	additional arguments: <ul style="list-style-type: none"> assay.type: A single character value for naming assay (default: assay.type = "counts") removeTaxaPrefixes: TRUE or FALSE: Should taxonomic prefixes be removed? (default: removeTaxaPrefixes = FALSE) remove.suffix: TRUE or FALSE: Should suffixes of sample names be removed? HUMANn pipeline adds suffixes to sample names. Suffixes are formed from file names. By selecting remove.suffix = TRUE, you can remove pattern from end of sample names that is shared by all. (default: remove.suffix = FALSE)

Details

Import HUMANn (currently version 3.0 supported) results of functional predictions based on metagenome composition (e.g. pathways or gene families). The input must be in merged HUMANn format. (See [the HUMANn documentation and humann_join_tables method.](#))

The function parses gene/pathway information along with taxonomy information from the input file. This information is stored to rowData. Abundances are stored to assays.

Usually the workflow includes also taxonomy data from Metaphlan. See [importMetaPhlan](#) to load the data to TreeSE.

Value

A [TreeSummarizedExperiment](#) object

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

References

Beghini F, McIver LJ, Blanco-Míguez A, Dubois L, Asnicar F, Maharjan S, Mailyan A, Manghi P, Scholz M, Thomas AM, Valles-Colomer M, Weingart G, Zhang Y, Zolfo M, Huttenhower C, Franzosa EA, & Segata N (2021) Integrating taxonomic, functional, and strain-level profiling of diverse microbial communities with bioBakery 3. *eLife*. 10:e65088.

See Also

[importMetaPhlAn](#) [makeTreeSEFromPhylouseq](#) [makeTreeSEFromBiom](#) [makeTreeSEFromDADA2](#) [importQIIME2](#)
[importMothur](#)

Examples

```
# File path
file_path <- system.file("extdata", "humann_output.tsv", package = "mia")
# Import data
tse <- importHUMANn(file_path)
tse
```

importMetaPhlAn

Import Metaphlan results to TreeSummarizedExperiment

Description

Import Metaphlan results to TreeSummarizedExperiment

Arguments

file	a single character value defining the file path of the Metaphlan file. The file must be in merged Metaphlan format.
colData	a DataFrame-like object that includes sample names in rownames, or a single character value defining the file path of the sample metadata file. The file must be in tsv format (default: colData = NULL).
sample_meta	a DataFrame-like object that includes sample names in rownames, or a single character value defining the file path of the sample metadata file. The file must be in tsv format (default: sample_meta = NULL).
phy_tree	a single character value defining the file path of the phylogenetic tree. (default: phy_tree = NULL).

- ... additional arguments:
- `assay.type`: A single character value for naming `assay` (default: `assay.type = "counts"`)
 - `assay.name`: A single character value for specifying which assay to use for calculation. (Please use `assay.type` instead. At some point `assay.name` will be disabled.)
 - `removeTaxaPrefixes`: TRUE or FALSE: Should taxonomic prefixes be removed? (default: `removeTaxaPrefixes = FALSE`)
 - `remove.suffix`: TRUE or FALSE: Should suffixes of sample names be removed? Metaphlan pipeline adds suffixes to sample names. Suffixes are formed from file names. By selecting `remove.suffix = TRUE`, you can remove pattern from end of sample names that is shared by all. (default: `remove.suffix = FALSE`)
 - `set.ranks`: TRUE or FALSE: Should the columns in the `rowData` that are treated as taxonomy ranks be updated according to the ranks found in the imported data? (default: `set.ranks = FALSE`)

Details

Import Metaphlan (versions 2, 3 and 4 supported) results. Input must be in merged Metaphlan format. (See [the Metaphlan documentation and merge_metaphlan_tables method](#).) Data is imported so that data at the lowest rank is imported as a `TreeSummarizedExperiment` object. Data at higher rank is imported as a `SummarizedExperiment` objects which are stored to `altExp` of `TreeSummarizedExperiment` object.

Currently Metaphlan versions 2, 3, and 4 are supported.

Value

A `TreeSummarizedExperiment` object

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

References

Beghini F, McIver LJ, Blanco-Míguez A, Dubois L, Asnicar F, Maharjan S, Mailyan A, Manghi P, Scholz M, Thomas AM, Valles-Colomer M, Weingart G, Zhang Y, Zolfo M, Huttenhower C, Franzosa EA, & Segata N (2021) Integrating taxonomic, functional, and strain-level profiling of diverse microbial communities with bioBakery 3. *eLife*. 10:e65088. doi: 10.7554/eLife.65088

See Also

[importHUMANn](#) [makeTreeSEFromPhyloseq](#) [makeTreeSEFromBiom](#) [makeTreeSEFromDADA2](#) [importQIIME2](#)
[importMothur](#)

Examples

```
# (Data is from tutorial
# https://github.com/biobakery/biobakery/wiki/metaphlan3#merge-outputs)

# File path
file_path <- system.file("extdata", "merged_abundance_table.txt", package = "mia")
# Import data
tse <- importMetaPhlAn(file_path)
# Data at the lowest rank
tse
# Data at higher rank is stored in altExp
altExps(tse)
# Higher rank data is in SE format, for example, Phylum rank
altExp(tse, "Phylum")
```

importMothur

Import Mothur results as a TreeSummarizedExperiment

Description

This method creates a `TreeSummarizedExperiment` object from Mothur files provided as input.

Usage

```
importMothur(sharedFile, taxonomyFile = NULL, designFile = NULL)
```

Arguments

<code>sharedFile</code>	a single character value defining the file path of the feature table to be imported. The File has to be in shared file format as defined in Mothur documentation.
<code>taxonomyFile</code>	a single character value defining the file path of the taxonomy table to be imported. The File has to be in taxonomy file or constaxonomy file format as defined in Mothur documentation. (default: <code>taxonomyFile = NULL</code>).
<code>designFile</code>	a single character value defining the file path of the sample metadata to be imported. The File has to be in desing file format as defined in Mothur documentation. (default: <code>designFile = NULL</code>).

Details

Results exported from Mothur can be imported as a `SummarizedExperiment` using `importMothur`. Except for the `sharedFile`, the other data types, `taxonomyFile`, and `designFile`, are optional, but are highly encouraged to be provided.

Value

A `TreeSummarizedExperiment` object

Author(s)

Leo Lahti and Tuomas Borman. Contact: [microbiome.github.io](https://github.com/microbiome)

References

<https://mothur.org/> https://mothur.org/wiki/shared_file/ https://mothur.org/wiki/taxonomy_file/ https://mothur.org/wiki/constaxonomy_file/ https://mothur.org/wiki/design_file/

See Also

[makeTreeSEFromPhyloseq](#) [makeTreeSEFromBiom](#) [makeTreeSEFromDADA2](#) [importQIIME2](#)

Examples

```
# Abundance table
counts <- system.file("extdata", "mothur_example.shared", package = "mia")
# Taxa table (in "cons.taxonomy" or "taxonomy" format)
taxa <- system.file("extdata", "mothur_example.cons.taxonomy", package = "mia")
#taxa <- system.file("extdata", "mothur_example.taxonomy", package = "mia")
# Sample meta data
meta <- system.file("extdata", "mothur_example.design", package = "mia")

# Creates se object from files
se <- importMothur(counts, taxa, meta)
# Convert SE to TreeSE
tse <- as(se, "TreeSummarizedExperiment")
tse
```

```
importQIIME2
```

```
  Import QIIME2 results to TreeSummarizedExperiment
```

Description

Results exported from QIIME2 can be imported as a `TreeSummarizedExperiment` using `importQIIME2`. Except for the `featureTableFile`, the other data types, `taxonomyTableFile`, `refSeqFile` and `phyTreeFile`, are optional, but are highly encouraged to be provided.

Import the QIIME2 artifacts to R.

Usage

```
importQIIME2(
  featureTableFile,
  taxonomyTableFile = NULL,
  sampleMetaFile = NULL,
  featureNamesAsRefSeq = TRUE,
  refSeqFile = NULL,
  phyTreeFile = NULL,
```

```

    ...
)

importQZA(file, temp = tempdir(), ...)

```

Arguments

featureTableFile	a single character value defining the file path of the feature table to be imported.
taxonomyTableFile	a single character value defining the file path of the taxonomy table to be imported. (default: taxonomyTableFile = NULL).
sampleMetaFile	a single character value defining the file path of the sample metadata to be imported. The file has to be in tsv format. (default: sampleMetaFile = NULL).
featureNamesAsRefSeq	TRUE or FALSE: Should the feature names of the feature table be regarded as reference sequences? This setting will be disregarded, if refSeqFile is not NULL. If the feature names do not contain valid DNA characters only, the reference sequences will not be set.
refSeqFile	a single character value defining the file path of the reference sequences for each feature. (default: refSeqFile = NULL).
phyTreeFile	a single character value defining the file path of the phylogenetic tree. (default: phyTreeFile = NULL).
...	additional arguments: <ul style="list-style-type: none"> temp: the temporary directory used for decompressing the data. (default: tempdir()) removeTaxaPrefixes: TRUE or FALSE: Should taxonomic prefixes be removed? (default: removeTaxaPrefixes = FALSE)
file	character, path of the input qza file. Only files in format of BIOMV210DirFmt (feature table), TSVTaxonomyDirectoryFormat (taxonomic table), NewickDirectoryFormat (phylogenetic tree) and DNASequencesDirectoryFormat (representative sequences) are supported right now.
temp	character, a temporary directory in which the qza file will be decompressed to, default tempdir().

Details

Both arguments featureNamesAsRefSeq and refSeqFile can be used to define reference sequences of features. featureNamesAsRefSeq is only taken into account, if refSeqFile is NULL. No reference sequences are tried to be created, if featureNameAsRefSeq is FALSE and refSeqFile is NULL.

Value

A [TreeSummarizedExperiment](#) object

matrix object for feature table, [DataFrame](#) for taxonomic table, [ape::phylo](#) object for phylogenetic tree, [Biostrings::DNAStrngSet](#) for representative sequences of taxa.

Author(s)

Yang Cao

References

Bolyen E et al. 2019: Reproducible, interactive, scalable and extensible microbiome data science using QIIME 2. *Nature Biotechnology* 37: 852–857. <https://doi.org/10.1038/s41587-019-0209-9>
<https://qiime2.org>

See Also

[makeTreeSEFromPhyloseq](#) [makeTreeSEFromBiom](#) [makeTreeSEFromDADA2](#) [importMothur](#)

Examples

```
featureTableFile <- system.file("extdata", "table.qza", package = "mia")
taxonomyTableFile <- system.file("extdata", "taxonomy.qza", package = "mia")
sampleMetaFile <- system.file("extdata", "sample-metadata.tsv", package = "mia")
phyTreeFile <- system.file("extdata", "tree.qza", package = "mia")
refSeqFile <- system.file("extdata", "refseq.qza", package = "mia")
tse <- importQIIME2(
  featureTableFile = featureTableFile,
  taxonomyTableFile = taxonomyTableFile,
  sampleMetaFile = sampleMetaFile,
  refSeqFile = refSeqFile,
  phyTreeFile = phyTreeFile
)

tse
# Read individual files
featureTableFile <- system.file("extdata", "table.qza", package = "mia")
taxonomyTableFile <- system.file("extdata", "taxonomy.qza", package = "mia")
sampleMetaFile <- system.file("extdata", "sample-metadata.tsv", package = "mia")

assay <- importQZA(featureTableFile)
rowData <- importQZA(taxonomyTableFile, removeTaxaPrefixes = TRUE)
coldata <- read.table(sampleMetaFile, header = TRUE, sep = "\t", comment.char = "")

# Assign rownames
rownames(coldata) <- coldata[, 1]
coldata[, 1] <- NULL

# Order coldata based on assay
coldata <- coldata[match(colnames(assay), rownames(coldata)), ]

# Create SE from individual files
se <- SummarizedExperiment(assays = list(assay), rowData = rowData, colData = coldata)
se
```

isContaminant	<i>decontam functions</i>
---------------	---------------------------

Description

The decontam functions `isContaminant` and `isNotContaminant` are made available for [SummarizedExperiment](#) objects.

Usage

```
## S4 method for signature 'SummarizedExperiment'
isContaminant(
  seqtab,
  assay.type = assay_name,
  assay_name = "counts",
  name = "isContaminant",
  concentration = NULL,
  control = NULL,
  batch = NULL,
  threshold = 0.1,
  normalize = TRUE,
  detailed = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
isNotContaminant(
  seqtab,
  assay.type = assay_name,
  assay_name = "counts",
  name = "isNotContaminant",
  control = NULL,
  threshold = 0.5,
  normalize = TRUE,
  detailed = FALSE,
  ...
)

addContaminantQC(x, name = "isContaminant", ...)

## S4 method for signature 'SummarizedExperiment'
addContaminantQC(x, name = "isContaminant", ...)

addNotContaminantQC(x, name = "isNotContaminant", ...)

## S4 method for signature 'SummarizedExperiment'
addNotContaminantQC(x, name = "isNotContaminant", ...)
```

Arguments

seqtab, x	a SummarizedExperiment
assay.type	A single character value for selecting the assay to use.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
name	A name for the column of the <code>colData</code> in which the contaminant information should be stored.
concentration	NULL or a single character value. Defining a column with numeric values from the <code>colData</code> to use as concentration information. (default: <code>concentration = NULL</code>)
control	NULL or a single character value. Defining a column with logical values from the <code>colData</code> to define control and non-control samples. (default: <code>control = NULL</code>)
batch	NULL or a single character value. Defining a column with values interpretable as a factor from the <code>colData</code> to use as batch information. (default: <code>batch = NULL</code>)
threshold	numeric scalar. See decontam:isContaminant or decontam:isNotContaminant
normalize, detailed	logical scalar. See decontam:isContaminant or decontam:isNotContaminant
...	<ul style="list-style-type: none"> • for <code>isContaminant/ isNotContaminant</code>: arguments passed on to decontam:isContaminant or decontam:isNotContaminant • for <code>addContaminantQC/addNotContaminantQC</code>: arguments passed on to <code>isContaminant/ isNotContaminant</code>

Value

for `isContaminant/ isNotContaminant` a `DataFrame` or for `addContaminantQC/addNotContaminantQC` a modified object of `class(x)`

See Also

[decontam:isContaminant](#), [decontam:isNotContaminant](#)

Examples

```
data(esophagus)
# setup of some mock data
colData(esophagus)$concentration <- c(1,2,3)
colData(esophagus)$control <- c(FALSE,FALSE,TRUE)

isContaminant(esophagus,
              method = "frequency",
              concentration = "concentration")
esophagus <- addContaminantQC(esophagus,
                             method = "frequency",
                             concentration = "concentration")

colData(esophagus)
```

```
isNotContaminant(esophagus, control = "control")
esophagus <- addNotContaminantQC(esophagus, control = "control")
colData(esophagus)
```

```
makePhyloseqFromTreeSE
```

Create a phyloseq object from a TreeSummarizedExperiment object

Description

This function creates a phyloseq object from a TreeSummarizedExperiment object. By using `assay.type`, it is possible to specify which table from assay is added to the phyloseq object.

Usage

```
makePhyloseqFromTreeSE(x, ...)

## S4 method for signature 'SummarizedExperiment'
makePhyloseqFromTreeSE(x, assay.type = "counts", assay_name = NULL, ...)

## S4 method for signature 'TreeSummarizedExperiment'
makePhyloseqFromTreeSE(x, tree_name = "phylo", ...)

makePhyloseqFromTreeSummarizedExperiment(x, ...)

## S4 method for signature 'ANY'
makePhyloseqFromTreeSummarizedExperiment(x, ...)
```

Arguments

<code>x</code>	a TreeSummarizedExperiment object
<code>...</code>	additional arguments
<code>assay.type</code>	A single character value for selecting the assay to be included in the phyloseq object that is created. (By default: <code>assay.type = "counts"</code>)
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>tree_name</code>	a single character value for specifying which tree will be included in the phyloseq object that is created, (By default: <code>tree_name = "phylo"</code>)

Details

`makePhyloseqFromTreeSE` is used for creating a phyloseq object from TreeSummarizedExperiment object.

Value

An object of class Phyloseq object.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

Examples

```
# Get tse object
data(GlobalPatterns)
tse <- GlobalPatterns

# Create a phyloseq object from it
phy <- makePhyloseqFromTreeSE(tse)
phy

# By default the chosen table is counts, but if there are other tables,
# they can be chosen with assay.type.

# Counts relative abundances table
tse <- transformAssay(tse, method = "relabundance")
phy2 <- makePhyloseqFromTreeSE(tse, assay.type = "relabundance")
phy2
```

makeTreeSEFromBiom *Loading a biom file*

Description

For convenience a few functions are available to convert data from a ‘biom’ file or object into a [TreeSummarizedExperiment](#)

Usage

```
importBIOM(file, ...)

makeTreeSEFromBiom(
  obj,
  removeTaxaPrefixes = FALSE,
  rankFromPrefix = FALSE,
  remove.artifacts = FALSE,
  ...
)

makeTreeSummarizedExperimentFromBiom(obj, ...)
```


Arguments

file	biom file location
...	additional arguments <ul style="list-style-type: none"> • pattercharacter value specifying artifacts to be removed. If patterns = "auto", special characters are removed. (default: pattern = "auto")
obj	object of type biom
removeTaxaPrefixes	TRUE or FALSE: Should taxonomic prefixes be removed? The prefixes is removed only from detected taxa columns meaning that rankFromPrefix should be enabled in the most cases. (default removeTaxaPrefixes = FALSE)
rankFromPrefix	TRUE or FALSE: If file does not have taxonomic ranks on feature table, should they be scrapped from prefixes? (default rankFromPrefix = FALSE)
remove.artifacts	TRUE or FALSE: If file have some taxonomic character naming artifacts, should they be removed. (default remove.artifacts = FALSE)

Value

An object of class [TreeSummarizedExperiment](#)

See Also

[makeTreeSEFromPhyloseq](#) [makeTreeSEFromDADA2](#) [importQIIME2](#) [importMothur](#)

Examples

```
# Load biom file
library(biomformat)
biom_file <- system.file("extdata", "rich_dense_otu_table.biom",
                        package = "biomformat")

# Make TreeSE from biom file
tse <- importBIOM(biom_file)

# Make TreeSE from biom object
biom_object <- biomformat::read_biom(biom_file)
tse <- makeTreeSEFromBiom(biom_object)

# Get taxonomyRanks from prefixes and remove prefixes
tse <- importBIOM(biom_file,
                 rankFromPrefix = TRUE,
                 removeTaxaPrefixes = TRUE)

# Load another biom file
biom_file <- system.file("extdata/testdata", "Aggregated_humanization2.biom",
                        package = "mia")

# Clean artifacts from taxonomic data
tse <- importBIOM(biom_file,
                 remove.artifacts = TRUE)
```

makeTreeSEFromDADA2 *Coerce 'DADA2' results to TreeSummarizedExperiment*

Description

makeTreeSEFromDADA2 is a wrapper for the mergePairs function from the dada2 package.

Usage

```
makeTreeSEFromDADA2(...)
```

```
makeTreeSummarizedExperimentFromDADA2(...)
```

Arguments

... See mergePairs function for more details.

Details

A count matrix is constructed via makeSequenceTable(mergePairs(...)) and rownames are dynamically created as ASV(N) with N from 1 to nrow of the count tables. The colnames and rownames from the output of makeSequenceTable are stored as colnames and in the referenceSeq slot of the TreeSummarizedExperiment, respectively.

Value

An object of class TreeSummarizedExperiment

See Also

[makeTreeSEFromPhyloseq](#) [makeTreeSEFromBiom](#) [importQIIME2](#) [importMothur](#)

Examples

```
if(requireNamespace("dada2")) {  
  fnF <- system.file("extdata", "sam1F.fastq.gz", package="dada2")  
  fnR = system.file("extdata", "sam1R.fastq.gz", package="dada2")  
  dadaF <- dada2::dada(fnF, selfConsist=TRUE)  
  dadaR <- dada2::dada(fnR, selfConsist=TRUE)  
  
  tse <- makeTreeSEFromDADA2(dadaF, fnF, dadaR, fnR)  
  tse  
}
```

`makeTreeSEFromPhyloseq`*Coerce a phyloseq object to a TreeSummarizedExperiment*

Description

`makeTreeSEFromPhyloseq` converts phyloseq objects into `TreeSummarizedExperiment` objects.

Usage

```
makeTreeSEFromPhyloseq(obj)
```

```
makeTreeSummarizedExperimentFromPhyloseq(obj)
```

```
## S4 method for signature 'ANY'  
makeTreeSummarizedExperimentFromPhyloseq(obj)
```

Arguments

`obj` a phyloseq object

Details

All data stored in a phyloseq object is transferred.

Value

An object of class `TreeSummarizedExperiment`

See Also

[makeTreeSEFromBiom](#) [makeTreeSEFromDADA2](#) [importQIIME2](#) [importMothur](#)

Examples

```
if (requireNamespace("phyloseq")) {  
  data(GlobalPatterns, package="phyloseq")  
  makeTreeSEFromPhyloseq(GlobalPatterns)  
  data(enterotype, package="phyloseq")  
  makeTreeSEFromPhyloseq(enterotype)  
  data(esophagus, package="phyloseq")  
  makeTreeSEFromPhyloseq(esophagus)  
}
```

`meltAssay`*Converting a [SummarizedExperiment](#) object into a long data.frame*

Description

`meltAssay` Converts a [SummarizedExperiment](#) object into a long data.frame which can be used for tidyverse-tools.

Usage

```
meltAssay(  
  x,  
  assay.type = assay_name,  
  assay_name = "counts",  
  add_row_data = NULL,  
  add_col_data = NULL,  
  feature_name = "FeatureID",  
  sample_name = "SampleID",  
  ...  
)  
  
## S4 method for signature 'SummarizedExperiment'  
meltAssay(  
  x,  
  assay.type = assay_name,  
  assay_name = "counts",  
  add_row_data = NULL,  
  add_col_data = NULL,  
  feature_name = "FeatureID",  
  sample_name = "SampleID",  
  ...  
)
```

Arguments

<code>x</code>	A numeric matrix or a SummarizedExperiment
<code>assay.type</code>	a character value to select an assayNames
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>add_row_data</code>	NULL, TRUE or a character vector to select information from the <code>rowData</code> to add to the molten assay data. If <code>add_row_data = NULL</code> no data will be added, if <code>add_row_data = TRUE</code> all data will be added and if <code>add_row_data</code> is a character vector, it will be used to subset to given column names in <code>rowData</code> . (default: <code>add_row_data = NULL</code>)

add_col_data	NULL, TRUE or a character vector to select information from the colData to add to the molten assay data. If add_col_data = NULL no data will be added, if add_col_data = TRUE all data will be added and if add_col_data is a character vector, it will be used to subset to given column names in colData. (default: add_col_data = NULL)
feature_name	a character scalar to use as the output's name for the feature identifier. (default: feature_name = "FeatureID")
sample_name	a character scalar to use as the output's name for the sample identifier. (default: sample_name = "SampleID")
...	optional arguments: <ul style="list-style-type: none"> • check_names A boolean value passed to data.frame function's check.name argument. Determines if sample names are checked that they are syntactically valid variable names and are not duplicated. If they are not, sample names are modified. (default: check_names = TRUE)

Details

If the colData contains a column "SampleID" or the rowData contains a column "FeatureID", they will be renamed to "SampleID_col" and "FeatureID_row", if row names or column names are set.

Value

A tibble with the molten data. The assay values are given in a column named like the selected assay assay.type. In addition, a column "FeatureID" will contain the rownames, if set, and analogously a column "SampleID" with the colnames, if set

Author(s)

Sudarshan A. Shetty

Examples

```
data(GlobalPatterns)
molten_tse <- meltAssay(GlobalPatterns,
                        assay.type = "counts",
                        add_row_data = TRUE,
                        add_col_data = TRUE
                        )

molten_tse
```

merge-methods

Merge a subset of the rows or columns of a SummarizedExperiment

Description

mergeRows/mergeCols merge data on rows or columns of a SummarizedExperiment as defined by a factor alongside the chosen dimension. Metadata from the rowData or colData are retained as defined by archetype.

Usage

```

mergeRows(x, f, archetype = 1L, ...)

mergeCols(x, f, archetype = 1L, ...)

mergeFeatures(x, f, archetype = 1L, ...)

mergeSamples(x, f, archetype = 1L, ...)

## S4 method for signature 'SummarizedExperiment'
mergeRows(x, f, archetype = 1L, ...)

## S4 method for signature 'SummarizedExperiment'
mergeCols(x, f, archetype = 1L, ...)

## S4 method for signature 'SummarizedExperiment'
mergeFeatures(x, f, archetype = 1L, ...)

## S4 method for signature 'SummarizedExperiment'
mergeSamples(x, f, archetype = 1L, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeRows(x, f, archetype = 1L, mergeTree = FALSE, mergeRefSeq = FALSE, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeCols(x, f, archetype = 1L, mergeTree = FALSE, ...)

## S4 method for signature 'TreeSummarizedExperiment'
mergeFeatures(
  x,
  f,
  archetype = 1L,
  mergeTree = FALSE,
  mergeRefSeq = FALSE,
  ...
)

## S4 method for signature 'TreeSummarizedExperiment'
mergeSamples(x, f, archetype = 1L, mergeTree = FALSE, ...)

```

Arguments

x	a SummarizedExperiment or a TreeSummarizedExperiment
f	A factor for merging. Must be the same length as <code>nrow(x)/ncol(x)</code> . Rows/Cols corresponding to the same level will be merged. If <code>length(levels(f)) == nrow(x)/ncol(x)</code> , x will be returned unchanged.
archetype	Of each level of f, which element should be regarded as the archetype and metadata in the columns or rows kept, while merging? This can be single in-

	teger value or an integer vector of the same length as <code>levels(f)</code> . (Default: <code>archetype = 1L</code> , which means the first element encountered per factor level will be kept)
...	Optional arguments: <ul style="list-style-type: none"> • Passed on to sumCountsAcrossFeatures, with the exception of <code>subset_row</code>, <code>subset_col</code>
<code>mergeTree</code>	TRUE or FALSE: Should <code>rowTree()</code> also be merged? (Default: <code>mergeTree = FALSE</code>)
<code>mergeRefSeq</code>	TRUE or FALSE: Should a consensus sequence be calculated? If set to FALSE, the result from <code>archetype</code> is returned; If set to TRUE the result from DECIPHER::ConsensusSequence is returned. (Default: <code>mergeRefSeq = FALSE</code>)

Details

[assay](#) are agglomerated, i.e. summed up. If the assay contains values other than counts or absolute values, this can lead to meaningless values being produced.

These functions are similar to [sumCountsAcrossFeatures](#). However, additional support for `TreeSummarizedExperiment` was added and science field agnostic names were used. In addition the `archetype` argument lets the user select how to preserve row or column data.

For merge data of assays the function from `scuttle` are used.

Value

An object of the same class as `x` with the specified entries merged into one entry in all relevant components.

See Also

[sumCountsAcrossFeatures](#)

Examples

```
data(esophagus)
esophagus
plot(rowTree(esophagus))
# get a factor for merging
f <- factor(regmatches(rownames(esophagus),
                        regexpr("[0-9]*_[0-9]*", rownames(esophagus))))
merged <- mergeRows(esophagus, f, mergeTree = TRUE)
plot(rowTree(merged))
#
data(GlobalPatterns)
GlobalPatterns
merged <- mergeCols(GlobalPatterns, colData(GlobalPatterns)$SampleType)
merged
```

mergeSEs

Merge SE objects into single SE object.

Description

Merge SE objects into single SE object.

Usage

```
mergeSEs(x, ...)

## S4 method for signature 'SimpleList'
mergeSEs(
  x,
  assay.type = "counts",
  assay_name = NULL,
  join = "full",
  missing_values = NA,
  collapse_samples = FALSE,
  collapse_features = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
mergeSEs(x, y = NULL, ...)

## S4 method for signature 'list'
mergeSEs(x, ...)
```

Arguments

x	a SummarizedExperiment object or a list of SummarizedExperiment objects.
...	optional arguments (not used).
assay.type	A character value for selecting the assay to be merged. (By default: assay.type = "counts")
assay_name	(Deprecated) alias for assay.type.
join	A single character value for selecting the joining method. Must be 'full', 'inner', 'left', or 'right'. 'left' and 'right' are disabled when more than two objects are being merged. (By default: join = "full")
missing_values	NA, 0, or a single character values specifying the notation of missing values. (By default: missing_values = NA)
collapse_samples	A boolean value for selecting whether to collapse identically named samples to one. (By default: collapse_samples = FALSE)

collapse_features	A boolean value for selecting whether to collapse identically named features to one. Since all taxonomy information is taken into account, this concerns rownames-level (usually strain level) comparison. Often OTU or ASV level is just an arbitrary number series from sequencing machine meaning that the OTU information is not comparable between studies. With this option, it is possible to specify whether these strains are combined if their taxonomy information along with OTU number matches. (By default: collapse_features = TRUE)
verbose	A single boolean value to choose whether to show messages. (By default: verbose = TRUE)
y	a SummarizedExperiment object when x is a SummarizedExperiment object. Disabled when x is a list.

Details

This function merges multiple [SummarizedExperiment](#) objects. It combines `rowData`, `assays`, and `colData` so that the output includes each unique row and column ones. The merging is done based on `rownames` and `colnames`. `rowTree` and `colTree` are preserved if linkage between rows/cols and the tree is found.

Equally named rows are interpreted as equal. Further matching based on `rowData` is not done. For samples, collapsing is disabled by default meaning that equally named samples that are stored in different objects are interpreted as unique. Collapsing can be enabled with `collapse_samples = TRUE` when equally named samples describe the same sample.

If, for example, all rows are not shared with individual objects, there are missing values in assays. The notation of missing can be specified with the `missing_values` argument. If input consists of [TreeSummarizedExperiment](#) objects, also `rowTree`, `colTree`, and `referenceSeq` are preserved if possible. The data is preserved if all the rows or columns can be found from it.

Compared to `cbind` and `rbind` `mergeSEs` allows more freely merging since `cbind` and `rbind` expect that rows and columns are matching, respectively.

You can choose joining methods from `'full'`, `'inner'`, `'left'`, and `'right'`. In all the methods, all the samples are included in the result object. However, with different methods, it is possible to choose which rows are included.

- `full` – all unique features
- `inner` – all shared features
- `left` – all the features of the first object
- `right` – all the features of the second object

The output depends on the input. If the input contains [SummarizedExperiment](#) object, then the output will be [SummarizedExperiment](#). When all the input objects belong to [TreeSummarizedExperiment](#), the output will be [TreeSummarizedExperiment](#).

Value

A single [SummarizedExperiment](#) object.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

See Also

- `TreeSummarizedExperiment::cbind`
- `TreeSummarizedExperiment::rbind`
- `full_join`
- `inner_join`
- `left_join`
- `right_join`

Examples

```
data(GlobalPatterns)
data(esophagus)
data(enterotype)

# Take only subsets so that it wont take so long
tse1 <- GlobalPatterns[1:100, ]
tse2 <- esophagus
tse3 <- enterotype[1:100, ]

# Merge two TreeSEs
tse <- mergeSEs(tse1, tse2)

# Merge a list of TreeSEs
list <- SimpleList(tse1, tse2, tse3)
tse <- mergeSEs(list, assay.type = "counts", missing_values = 0)
tse

# With 'join', it is possible to specify the merging method. Subsets are used
# here just to show the functionality
tse_temp <- mergeSEs(tse[1:10, 1:10], tse[5:100, 11:20], join = "left")
tse_temp

# If your objects contain samples that describe one and same sample,
# you can collapse equally named samples to one by specifying 'collapse_samples'
tse_temp <- mergeSEs(list(tse[1:10, 1], tse[1:20, 1], tse[1:5, 1]),
                    collapse_samples = TRUE,
                    join = "inner")
tse_temp

# Merge all available assays
tse <- transformAssay(tse, method="relabundance")
ts1 <- transformAssay(tse1, method="relabundance")
tse_temp <- mergeSEs(tse, tse1, assay.type = assayNames(tse))
```

mia-datasets

mia datasets

Description

mia provides various datasets derived from independent experimental studies. The datasets represent instances of the `TreeSummarizedExperiment` and `MultiAssayExperiment` containers and can serve as tools to practice the mia functionality.

Details

Currently, the following datasets are available:

- `dmn_se`: A `SummarizedExperiment` with 130 features and 278 samples
- `enterotype`: A `TreeSummarizedExperiment` with 553 features and 280 samples
- `esophagus`: A `TreeSummarizedExperiment` with 58 features and 3 samples
- `GlobalPatterns`: A `TreeSummarizedExperiment` with 19216 features and 26 samples
- `HintikkaX0Data`: A `MultiAssayExperiment` with 3 experiments (microbiota, metabolites and biomarkers)
- `peerj13075`: A `TreeSummarizedExperiment` with 674 features and 58 samples
- `Tengeler2020`: A `TreeSummarizedExperiment` with 151 features and 27 samples

Examples

```
# Load dataset from mia
library(mia)
data("GlobalPatterns", package = "mia")

# In this case, the dataset is a TreeSE, so it is renamed as tse
tse <- GlobalPatterns

# Print summary
tse
```

peerj13075

peerj13075

Description

peerj13075 includes skin microbial profiles of 58 volunteers with multiple factors. 16S r-RNA sequencing of V3-V4 regions was done to generate millions of read using illumina platform. A standard bioinformatic and statistical analysis done to explore skin bacterial diversity and its association with age, diet, geographical locations. The authors investigated significant association of skin microbiota with individual's geographical location.

Usage

```
data(peerj13075)
```

Format

A TreeSummarizedExperiment with 674 features and 58 samples. The rowData contains taxonomic information at kingdom, phylum, class, order, family and genus level. The colData includes:

Sample sample ID

Geographical_location city where participant lives (Ahmednagar, Pune and Nashik)

Gender participant's gender (Male or Female)

Age participant's age group (Middle_age, Adult and Elderly)

Diet participant's diet (Veg or Mixed)

Author(s)

Potbhare, R., et al.

References

Potbhare, R., RaviKumar, A., Munukka, E., Lahti, L., & Ashma, R. (2022). Skin microbiota diversity among genetically unrelated individuals of Indian origin. PeerJ, 10, e13075. <https://doi.org/10.7717/peerj.13075> Supplemental information includes OTU table and taxonomy table publicly-accessible from: <https://www.doi.org/10.7717/peerj.13075/supp-1> <https://www.doi.org/10.7717/peerj.13075/supp-2>

See Also

[mia-datasets](#)

perSampleDominantTaxa *Get dominant taxa*

Description

These functions return information about the most dominant taxa in a [SummarizedExperiment](#) object.

Usage

```
perSampleDominantFeatures(  
  x,  
  assay.type = assay_name,  
  assay_name = "counts",  
  rank = NULL,  
  other.name = "Other",
```

```
n = NULL,  
complete = TRUE,  
...  
)  
  
## S4 method for signature 'SummarizedExperiment'  
perSampleDominantFeatures(  
  x,  
  assay.type = assay_name,  
  assay_name = "counts",  
  rank = NULL,  
  other.name = "Other",  
  n = NULL,  
  complete = TRUE,  
  ...  
)  
  
perSampleDominantTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
perSampleDominantTaxa(x, ...)  
  
addPerSampleDominantFeatures(  
  x,  
  name = "dominant_taxa",  
  other.name = "Other",  
  n = NULL,  
  ...  
)  
  
## S4 method for signature 'SummarizedExperiment'  
addPerSampleDominantFeatures(  
  x,  
  name = "dominant_taxa",  
  other.name = "Other",  
  n = NULL,  
  complete = FALSE,  
  ...  
)  
  
addPerSampleDominantTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
addPerSampleDominantTaxa(x, ...)
```

Arguments

x A [SummarizedExperiment](#) object.

assay.type	A single character value for selecting the assay to use for identifying dominant taxa.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
rank	A single character defining a taxonomic rank. Must be a value of the output of <code>taxonomyRanks()</code> .
other.name	A name for features that are not included in the most frequent dominant features in the data. Default is "Other".
n	The number of features that are the most frequent dominant features. Default is NULL, which defaults that each sample is assigned a dominant taxon.
complete	A boolean value to manage multiple dominant taxa for a sample. Default for <code>perSampleDominantTaxa</code> is TRUE to include all equally dominant taxa for each sample. <code>complete = FALSE</code> samples one taxa for the samples that have multiple. Default for <code>addPerSampleDominantTaxa</code> is FALSE to add a column with only one dominant taxon assigned for each sample into <code>colData</code> . <code>complete = TRUE</code> adds a list that includes all dominant taxa for each sample into <code>colData</code> .
...	Additional arguments passed on to <code>agglomerateByRank()</code> when <code>rank</code> is specified.
name	A name for the column of the <code>colData</code> where the dominant taxa will be stored in when using <code>addPerSampleDominantFeatures</code> .

Details

`addPerSampleDominantFeatures` extracts the most abundant taxa in a [SummarizedExperiment](#) object, and stores the information in the `colData`. It is a wrapper for `perSampleDominantFeatures`. With `rank` parameter, it is possible to agglomerate taxa based on taxonomic ranks. E.g. if 'Genus' rank is used, all abundances of same Genus are added together, and those families are returned. See `agglomerateByRank()` for additional arguments to deal with missing values or special characters.

Value

`perSampleDominantFeatures` returns a named character vector `x` while `addPerSampleDominantFeatures` returns [SummarizedExperiment](#) with additional column in `colData` named `*name*`.

Author(s)

Leo Lahti, Tuomas Borman and Sudarshan A. Shetty.

Examples

```
data(GlobalPatterns)
x <- GlobalPatterns

# Finds the dominant taxa.
sim.dom <- perSampleDominantFeatures(x, rank="Genus")

# Add information to colData
x <- addPerSampleDominantFeatures(x, rank = "Genus", name="dominant_genera")
colData(x)
```

relabundance	<i>Getter / setter for relative abundance data</i>
--------------	--

Description

This function is being deprecated and will be removed in future releases. Please use `assay(x, "relabundance")` instead, which provides a more flexible and robust way to access and modify relative abundance data stored in the assay slot of a [TreeSummarizedExperiment](#) object.

Usage

```
relabundance(x, ...)  
  
relabundance(x) <- value  
  
## S4 method for signature 'SummarizedExperiment'  
relabundance(x)  
  
## S4 replacement method for signature 'SummarizedExperiment'  
relabundance(x) <- value
```

Arguments

x	a TreeSummarizedExperiment object
...	optional arguments not used currently.
value	a matrix to store as the 'relabundance' assay

Value

For `relabundance`, the matrix stored with the name "relabundance".

Examples

```
data(GlobalPatterns)  
# Calculates relative abundances  
GlobalPatterns <- transformAssay(GlobalPatterns, method="relabundance")  
# Fetches calculated relative abundances  
# head(assay(GlobalPatterns, "relabundance"))
```

Description

These functions perform Canonical Correspondence Analysis on data stored in a SummarizedExperiment.

Usage

```
calculateCCA(x, ...)
```

```
runCCA(x, ...)
```

```
calculateRDA(x, ...)
```

```
runRDA(x, ...)
```

```
## S4 method for signature 'ANY'
```

```
calculateCCA(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
```

```
calculateCCA(  
  x,  
  formula,  
  variables,  
  test.signif = TRUE,  
  assay.type = assay_name,  
  assay_name = exprs_values,  
  exprs_values = "counts",  
  scores = "wa",  
  ...  
)
```

```
## S4 method for signature 'SingleCellExperiment'
```

```
runCCA(x, formula, variables, altexp = NULL, name = "CCA", ...)
```

```
## S4 method for signature 'ANY'
```

```
calculateRDA(x, ...)
```

```
## S4 method for signature 'SummarizedExperiment'
```

```
calculateRDA(  
  x,  
  formula,  
  variables,  
  test.signif = TRUE,  
  assay.type = assay_name,  
  assay_name = exprs_values,  
  ...  
)
```



```

    exprs_values = "counts",
    scores = "wa",
    ...
)

## S4 method for signature 'SingleCellExperiment'
runRDA(x, formula, variables, altexp = NULL, name = "RDA", ...)

```

Arguments

x	For calculate* a SummarizedExperiment or a numeric matrix with columns as samples For run* a SingleCellExperiment or a derived object.
...	additional arguments passed to <code>vegan::cca</code> or <code>vegan::dbrda</code> and other internal functions. <ul style="list-style-type: none"> • <code>method</code> a dissimilarity measure to be applied in dbRDA and possible following homogeneity test. (By default: <code>method="euclidean"</code>) • <code>scale</code> a logical scalar, should the expression values be standardized? <code>scale</code> is disabled when using *RDA functions. Please scale before performing RDA. (By default: <code>scale=TRUE</code>) • <code>full</code> a logical scalar, should all the results from the significance calculations be returned. When <code>full=FALSE</code>, only summary tables are returned. (By default: <code>full=FALSE</code>) • <code>homogeneity.test</code> a single character value for specifying the significance test used to analyse <code>vegan::betadisper</code> results. Options include 'permanova' (<code>vegan::permutest</code>), 'anova' (<code>stats::anova</code>) and 'tukeyhsd' (<code>stats::TukeyHSD</code>). (By default: <code>homogeneity.test="permanova"</code>)
formula	If x is a SummarizedExperiment a formula can be supplied. Based on the right-hand side of the given formula <code>colData</code> is subset to <code>variables</code> . <code>variables</code> and <code>formula</code> can be missing, which turns the CCA analysis into a CA analysis and dbRDA into PCoA/MDS.
variables	When x is a SummarizedExperiment , <code>variables</code> can be used to specify variables from <code>colData</code> . When x is a matrix, <code>variables</code> is a <code>data.frame</code> or an object coercible to one containing the variables to use. All variables are used. Please subset, if you want to consider only some of them. <code>variables</code> and <code>formula</code> can be missing, which turns the CCA analysis into a CA analysis and dbRDA into PCoA/MDS.
test.signif	a logical scalar, should the PERMANOVA and analysis of multivariate homogeneity of group dispersions be performed. (By default: <code>test.signif = TRUE</code>)
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
exprs_values	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead.)

scores	A string specifying scores to be returned. Must be 'wa' (site scores found as weighted averages (cca) or weighted sums (rda) of v with weights Xbar, but the multiplying effect of eigenvalues removed) or 'u' ((weighted) orthonormal site scores). (By default: scores='wa')
altexp	String or integer scalar specifying an alternative experiment containing the input data.
name	String specifying the name to be used to store the result in the reducedDims of the output.

Details

*CCA functions utilize `vegan::cca` and *RDA functions `vegan::dbRDA`. By default `dbRDA` is done with euclidean distances which equals to RDA.

Significance tests are done with `vegan::anova.cca` (PERMANOVA). Group dispersion, i.e., homogeneity within groups is analyzed with `vegan::betadisper` (multivariate homogeneity of groups dispersions (variances)) and statistical significance of homogeneity is tested with a test specified by `homogeneity.test` parameter.

Value

For `calculateCCA` a matrix with samples as rows and CCA dimensions as columns. Attributes include calculated `cca/rda` object and significance analysis results.

For `runCCA` a modified `x` with the results stored in `reducedDim` as the given name.

See Also

For more details on the actual implementation see [cca](#) and [dbrda](#)

Examples

```
library(scater)
data(GlobalPatterns)
GlobalPatterns <- runCCA(GlobalPatterns, data ~ SampleType)
plotReducedDim(GlobalPatterns,"CCA", colour_by = "SampleType")

# Fetch significance results
attr(reducedDim(GlobalPatterns, "CCA"), "significance")

GlobalPatterns <- runRDA(GlobalPatterns, data ~ SampleType)
plotReducedDim(GlobalPatterns,"CCA", colour_by = "SampleType")

# Specify dissimilarity measure
GlobalPatterns <- transformAssay(GlobalPatterns, method = "relabundance")
GlobalPatterns <- runRDA(
  GlobalPatterns, data ~ SampleType, assay.type = "relabundance", method = "bray")

# To scale values when using *RDA functions, use transformAssay(MARGIN = "features", ...)
tse <- GlobalPatterns
tse <- transformAssay(tse, MARGIN = "features", method = "z")
# Data might include taxa that do not vary. Remove those because after z-transform
```

```

# their value is NA
tse <- tse[ rowSums( is.na( assay(tse, "z") ) ) == 0, ]
# Calculate RDA
tse <- runRDA(tse, formula = data ~ SampleType,
              assay.type = "z", name = "rda_scaled", na.action = na.omit)
# Plot
plotReducedDim(tse,"rda_scaled", colour_by = "SampleType")
# A common choice along with PERMANOVA is ANOVA when statistical significance
# of homogeneity of groups is analysed. Moreover, full significance test results
# can be returned.
tse <- runRDA(tse, data ~ SampleType, homogeneity.test = "anova", full = TRUE)

```

runDPCoA

Calculation of Double Principal Correspondance analysis

Description

Double Principal Correspondance analysis is made available via the ade4 package in typical fashion. Results are stored in the reducedDims and are available for all the expected functions.

Usage

```

calculateDPCoA(x, y, ...)

## S4 method for signature 'ANY,ANY'
calculateDPCoA(
  x,
  y,
  ncomponents = 2,
  ntop = NULL,
  subset_row = NULL,
  scale = FALSE,
  transposed = FALSE,
  ...
)

## S4 method for signature 'TreeSummarizedExperiment,missing'
calculateDPCoA(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  tree_name = "phylo"
)

runDPCoA(x, ..., altexp = NULL, name = "DPCoA")

```

Arguments

x	For <code>calculateDPCoA</code> , a numeric matrix of expression values where rows are features and columns are cells. Alternatively, a <code>TreeSummarizedExperiment</code> containing such a matrix. For <code>runDPCoA</code> a TreeSummarizedExperiment containing the expression values as well as a <code>rowTree</code> to calculate y using cophenetic.phylo .
y	a <code>dist</code> or a symmetric matrix compatible with <code>ade4:dpcoa</code>
...	Currently not used.
ncomponents	Numeric scalar indicating the number of DPCoA dimensions to obtain.
ntop	Numeric scalar specifying the number of features with the highest variances to use for dimensionality reduction. Alternatively <code>NULL</code> , if all features should be used. (default: <code>ntop = NULL</code>)
subset_row	Vector specifying the subset of features to use for dimensionality reduction. This can be a character vector of row names, an integer vector of row indices or a logical vector.
scale	Logical scalar, should the expression values be standardized?
transposed	Logical scalar, is x transposed with cells in rows?
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
exprs_values	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead.)
tree_name	a single character value for specifying which <code>rowTree</code> will be used in calculation. (By default: <code>tree_name = "phylo"</code>)
altexp	String or integer scalar specifying an alternative experiment containing the input data.
name	String specifying the name to be used to store the result in the <code>reducedDims</code> of the output.

Details

In addition to the reduced dimension on the features, the reduced dimension for samples are returned as well as `sample_red` attribute. `eig`, `feature_weights` and `sample_weights` are returned as attributes as well.

Value

For `calculateDPCoA` a matrix with samples as rows and CCA dimensions as columns

For `runDPCoA` a modified x with the results stored in `reducedDim` as the given name

See Also

[plotReducedDim](#) [reducedDims](#)

Examples

```

data(esophagus)
dpcoa <- calculateDPCoA(esophagus)
head(dpcoa)

esophagus <- runDPCoA(esophagus)
reducedDims(esophagus)

library(scater)
plotReducedDim(esophagus, "DPCoA")

```

runNMDS

Perform non-metric MDS on sample-level data

Description

Perform non-metric multi-dimensional scaling (nMDS) on samples, based on the data in a `SingleCellExperiment` object.

Usage

```

calculateNMDS(x, ...)

## S4 method for signature 'ANY'
calculateNMDS(
  x,
  FUN = vegdist,
  nmdsFUN = c("isoMDS", "monoMDS"),
  ncomponents = 2,
  ntop = 500,
  subset_row = NULL,
  scale = FALSE,
  transposed = FALSE,
  keep_dist = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
calculateNMDS(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  FUN = vegdist
)

```

```
## S4 method for signature 'SingleCellExperiment'
calculateNMDS(
  x,
  ...,
  assay.type = assay_name,
  assay_name = exprs_values,
  exprs_values = "counts",
  dimred = NULL,
  n_dimred = NULL,
  FUN = vegdist
)

runNMDS(x, ..., altexp = NULL, name = "NMDS")
```

Arguments

x	For calculateNMDS, a numeric matrix of expression values where rows are features and columns are cells. Alternatively, a TreeSummarizedExperiment containing such a matrix. For runNMDS a SingleCellExperiment
...	additional arguments to pass to FUN and nmdsFUN.
FUN	a function or character value with a function name returning a dist object
nmdsFUN	a character value to choose the scaling implementation, either “isoMDS” for MASS::isoMDS or “monoMDS” for vegan::monoMDS
ncomponents	Numeric scalar indicating the number of NMDS dimensions to obtain.
ntop	Numeric scalar specifying the number of features with the highest variances to use for dimensionality reduction.
subset_row	Vector specifying the subset of features to use for dimensionality reduction. This can be a character vector of row names, an integer vector of row indices or a logical vector.
scale	Logical scalar, should the expression values be standardized?
transposed	Logical scalar, is x transposed with cells in rows?
keep_dist	Logical scalar indicating whether the dist object calculated by FUN should be stored as ‘dist’ attribute of the matrix returned/stored by calculateNMDS/runNMDS.
assay.type	a single character value for specifying which assay to use for calculation.
assay_name	a single character value for specifying which assay to use for calculation. (Please use assay.type instead. At some point assay_name will be disabled.)
exprs_values	a single character value for specifying which assay to use for calculation. (Please use assay.type instead.)
dimred	String or integer scalar specifying the existing dimensionality reduction results to use.
n_dimred	Integer scalar or vector specifying the dimensions to use if dimred is specified.
altexp	String or integer scalar specifying an alternative experiment containing the input data.

name String specifying the name to be used to store the result in the reducedDims of the output.

Details

Either `MASS::isoMDS` or `vegan::monoMDS` are used internally to compute the NMDS components. If you supply a custom FUN, make sure that the arguments of FUN and `nmDSFUN` do not collide.

Value

For `calculateNMDS`, a matrix is returned containing the MDS coordinates for each sample (row) and dimension (column).

Author(s)

Felix Ernst

See Also

[MASS::isoMDS](#), [vegan::monoMDS](#) for NMDS component calculation.
[plotMDS](#), to quickly visualize the results.

Examples

```
# generate some example data
mat <- matrix(1:60, nrow = 6)
df <- DataFrame(n = c(1:6))
tse <- TreeSummarizedExperiment(assays = list(counts = mat),
                               rowData = df)

#
calculateNMDS(tse)

#
data(esophagus)
esophagus <- runNMDS(esophagus, FUN = vegan::vegdist, name = "BC")
esophagus <- runNMDS(esophagus, FUN = vegan::vegdist, name = "euclidean",
                    method = "euclidean")
reducedDims(esophagus)
```

splitByRanks

Split/Unsplit a SingleCellExperiment by taxonomic ranks

Description

`splitByRanks` takes a `SummarizedExperiment`, splits it along the taxonomic ranks, aggregates the data per rank, converts the input to a `SingleCellExperiment` objects and stores the aggregated data as alternative experiments.

Usage

```

splitByRanks(x, ...)

## S4 method for signature 'SummarizedExperiment'
splitByRanks(x, ranks = taxonomyRanks(x), na.rm = TRUE, ...)

## S4 method for signature 'SingleCellExperiment'
splitByRanks(x, ranks = taxonomyRanks(x), na.rm = TRUE, ...)

## S4 method for signature 'TreeSummarizedExperiment'
splitByRanks(x, ranks = taxonomyRanks(x), na.rm = TRUE, ...)

unsplitByRanks(x, ...)

## S4 method for signature 'SingleCellExperiment'
unsplitByRanks(x, ranks = taxonomyRanks(x), keep_reducedDims = FALSE, ...)

## S4 method for signature 'TreeSummarizedExperiment'
unsplitByRanks(x, ranks = taxonomyRanks(x), keep_reducedDims = FALSE, ...)

```

Arguments

x	a SummarizedExperiment object
...	arguments passed to agglomerateByRank function for SummarizedExperiment objects and other functions. See agglomerateByRank for more details.
ranks	a character vector defining taxonomic ranks. Must all be values of taxonomyRanks() function.
na.rm	TRUE or FALSE: Should taxa with an empty rank be removed? Use it with caution, since results with NA on the selected rank will be dropped. This setting can be tweaked by defining <code>empty.fields</code> to your needs. (default: <code>na.rm = TRUE</code>)
keep_reducedDims	TRUE or FALSE: Should the <code>reducedDims(x)</code> be transferred to the result? Please note, that this breaks the link between the data used to calculate the reduced dims. (default: <code>keep_reducedDims = FALSE</code>)

Details

`unsplitByRanks` takes these alternative experiments and flattens them again into a single [SummarizedExperiment](#).

`splitByRanks` will use by default all available taxonomic ranks, but this can be controlled by setting `ranks` manually. NA values are removed by default, since they would not make sense, if the result should be used for `unsplitByRanks` at some point. The input data remains unchanged in the returned [SingleCellExperiment](#) objects.

`unsplitByRanks` will remove any NA value on each taxonomic rank so that no ambiguous data is created. In addition, a column `taxonomicLevel` is created or overwritten in the `rowData` to specify from which alternative experiment this originates from. This can also be used for [splitAltExps](#) to split the result along the same factor again. The input data from the base objects is not returned,

only the data from the `altExp()`. Be aware that changes to `rowData` of the base object are not returned, whereas only the `colData` of the base object is kept.

Value

For `splitByRanks`: `SummarizedExperiment` objects in a `SimpleList`.

For `unsplitByRanks`: `x`, with `rowData` and assay data replaced by the unsplit data. `colData` of `x` is kept as well and any existing `rowTree` is dropped as well, since existing `rowLinks` are not valid anymore.

See Also

[splitOn](#) [unsplitOn](#) [mergeRows](#), [sumCountsAcrossFeatures](#), [agglomerateByRank](#), [altExps](#), [splitAltExps](#)

Examples

```
data(GlobalPatterns)
# print the available taxonomic ranks
taxonomyRanks(GlobalPatterns)

# splitByRanks
altExps(GlobalPatterns) <- splitByRanks(GlobalPatterns)
altExps(GlobalPatterns)
altExp(GlobalPatterns, "Kingdom")
altExp(GlobalPatterns, "Species")

# unsplitByRanks
x <- unsplitByRanks(GlobalPatterns)
x
```

splitOn	<i>Split TreeSummarizedExperiment column-wise or row-wise based on grouping variable</i>
---------	--

Description

Split `TreeSummarizedExperiment` column-wise or row-wise based on grouping variable

Usage

```
splitOn(x, ...)

## S4 method for signature 'SummarizedExperiment'
splitOn(x, f = NULL, ...)

## S4 method for signature 'SingleCellExperiment'
splitOn(x, f = NULL, ...)
```

```
## S4 method for signature 'TreeSummarizedExperiment'
splitOn(x, f = NULL, update_rowTree = FALSE, ...)

unsplitOn(x, ...)

## S4 method for signature 'list'
unsplitOn(x, update_rowTree = FALSE, ...)

## S4 method for signature 'SimpleList'
unsplitOn(x, update_rowTree = FALSE, ...)

## S4 method for signature 'SingleCellExperiment'
unsplitOn(x, altExpNames = names(altExps(x)), keep_reducedDims = FALSE, ...)
```

Arguments

x	A SummarizedExperiment object or a list of SummarizedExperiment objects.
...	Arguments passed to mergeRows/mergeCols function for SummarizedExperiment objects and other functions. See mergeRows for more details. <ul style="list-style-type: none"> • use_names A single boolean value to select whether to name elements of list by their group names.
f	A single character value for selecting the grouping variable from <code>rowData</code> or <code>colData</code> or a factor or vector with the same length as one of the dimensions. If <code>f</code> matches with both dimensions, <code>MARGIN</code> must be specified. Split by cols is not encouraged, since this is not compatible with storing the results in <code>altExps</code> .
update_rowTree	TRUE or FALSE: Should the <code>rowTree</code> be updated based on splitted data? Option is enabled when <code>x</code> is a TreeSummarizedExperiment object or a list of such objects. (By default: <code>update_rowTree = FALSE</code>)
altExpNames	a character vector specifying the alternative experiments to be unsplit. (By default: <code>altExpNames = names(altExps(x))</code>)
keep_reducedDims	TRUE or FALSE: Should the <code>reducedDims(x)</code> be transferred to the result? Please note, that this breaks the link between the data used to calculate the reduced dims. (By default: <code>keep_reducedDims = FALSE</code>)

Details

`splitOn` split data based on grouping variable. Splitting can be done column-wise or row-wise. The returned value is a list of [SummarizedExperiment](#) objects; each element containing members of each group.

Value

For `splitOn`: [SummarizedExperiment](#) objects in a [SimpleList](#).

For `unsplitOn`: `x`, with `rowData` and assay data replaced by the unsplit data. `colData` of `x` is kept as well and any existing `rowTree` is dropped as well, since existing `rowLinks` are not valid anymore.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

See Also

[splitByRanks](#) [unsplitByRanks](#) [mergeRows](#), [sumCountsAcrossFeatures](#), [agglomerateByRank](#), [altExps](#), [splitAltExps](#)

Examples

```
data(GlobalPatterns)
tse <- GlobalPatterns
# Split data based on SampleType.
se_list <- splitOn(tse, f = "SampleType")

# List of SE objects is returned.
se_list

# Create arbitrary groups
rowData(tse)$group <- sample(1:3, nrow(tse), replace = TRUE)
colData(tse)$group <- sample(1:3, ncol(tse), replace = TRUE)

# Split based on rows
# Each element is named based on their group name. If you don't want to name
# elements, use use_name = FALSE. Since "group" can be found from rowData and colData
# you must use MARGIN.
se_list <- splitOn(tse, f = "group", use_names = FALSE, MARGIN = 1)

# When column names are shared between elements, you can store the list to altExps
altExps(tse) <- se_list

altExps(tse)

# If you want to split on columns and update rowTree, you can do
se_list <- splitOn(tse, f = colData(tse)$group, update_rowTree = TRUE)

# If you want to combine groups back together, you can use unsplitBy
unsplitOn(se_list)
```

subsampleCounts

Subsample Counts

Description

subsampleCounts will randomly subsample counts in SummarizedExperiment and return the a modified object in which each sample has same number of total observations/counts/reads.

Usage

```

subsampleCounts(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  min_size = min(colSums2(assay(x))),
  replace = TRUE,
  name = "subsamped",
  verbose = TRUE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
subsampleCounts(
  x,
  assay.type = assay_name,
  assay_name = "counts",
  min_size = min(colSums2(assay(x))),
  replace = TRUE,
  name = "subsamped",
  verbose = TRUE,
  ...
)

```

Arguments

<code>x</code>	A SummarizedExperiment object.
<code>assay.type</code>	A single character value for selecting the SummarizedExperiment assay used for random subsampling. Only counts are useful and other transformed data as input will give meaningless output.
<code>assay_name</code>	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
<code>min_size</code>	A single integer value equal to the number of counts being simulated this can equal to lowest number of total counts found in a sample or a user specified number.
<code>replace</code>	Logical Default is TRUE. The default is with replacement (<code>replace=TRUE</code>). See phyloseq::rarefy_even_depth for details on implications of this parameter.
<code>name</code>	A single character value specifying the name of transformed abundance table.
<code>verbose</code>	Logical Default is TRUE. When TRUE an additional message about the random number used is printed.
<code>...</code>	additional arguments not used

Details

Although the subsampling approach is highly debated in microbiome research, we include the `subsampleCounts` function because there may be some instances where it can be useful. Note

that the output of `subsetSamples` is not the equivalent as the input and any result have to be verified with the original dataset. To maintain the reproducibility, please define the seed using `set.seed()` before implement this function.

Value

`subsetSamples` return `x` with subsampled data.

Author(s)

Sudarshan A. Shetty and Felix G.M. Ernst

References

McMurdie PJ, Holmes S. Waste not, want not: why rarefying microbiome data is inadmissible. *PLoS computational biology*. 2014 Apr 3;10(4):e1003531.

Gloor GB, Macklaim JM, Pawlowsky-Glahn V & Egozcue JJ (2017) Microbiome Datasets Are Compositional: And This Is Not Optional. *Frontiers in Microbiology* 8: 2224. doi: 10.3389/fmicb.2017.02224

Weiss S, Xu ZZ, Peddada S, Amir A, Bittinger K, Gonzalez A, Lozupone C, Zaneveld JR, Vázquez-Baeza Y, Birmingham A, Hyde ER. Normalization and microbial differential abundance strategies depend upon data characteristics. *Microbiome*. 2017 Dec;5(1):1-8.

Examples

```
# When samples in TreeSE are less than specified min_size, they will be removed.
# If after subsampling features are not present in any of the samples,
# they will be removed.
data(GlobalPatterns)
tse <- GlobalPatterns
set.seed(123)
tse.subsampled <- subsetSamples(tse,
                               min_size = 60000,
                               name = "subsampled"
                              )

tse.subsampled
dim(tse)
dim(tse.subsampled)
```

subsetSamples

Subset functions

Description

To make a transition from `phyloseq` easier, the `subsetSamples` and `subsetFeatures` functions are implemented. To avoid name clashes they are named differently.

Usage

```
subsetSamples(x, ...)  
  
subsetFeatures(x, ...)  
  
subsetTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
subsetSamples(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
subsetFeatures(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
subsetTaxa(x, ...)
```

Arguments

x a `SummarizedExperiment` object
... See `subset`. drop is not supported.

Details

However, the use of these functions is discouraged since subsetting using `[]` works on both dimension at the same time, is more flexible and is used throughout R to subset data with two or more dimension. Therefore, these functions will be removed in Bioconductor release 3.15 (April, 2022).

Value

A subset of x

Examples

```
data(GlobalPatterns)  
subsetSamples(GlobalPatterns, colData(GlobalPatterns)$SampleType == "Soil")  
# Vector that is used to specify subset must not include NAs  
subsetFeatures(GlobalPatterns, rowData(GlobalPatterns)$Phylum == "Actinobacteria" &  
              !is.na(rowData(GlobalPatterns)$Phylum))
```

Description

To query a `SummarizedExperiment` for interesting features, several functions are available.

Usage

```
getTopFeatures(  
  x,  
  top = 5L,  
  method = c("mean", "sum", "median"),  
  assay.type = assay_name,  
  assay_name = "counts",  
  na.rm = TRUE,  
  ...  
)  
  
## S4 method for signature 'SummarizedExperiment'  
getTopFeatures(  
  x,  
  top = 5L,  
  method = c("mean", "sum", "median", "prevalence"),  
  assay.type = assay_name,  
  assay_name = "counts",  
  na.rm = TRUE,  
  ...  
)  
  
getTopTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getTopTaxa(x, ...)  
  
getUniqueFeatures(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getUniqueFeatures(x, rank = NULL, ...)  
  
getUniqueTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
getUniqueTaxa(x, ...)  
  
countDominantFeatures(x, group = NULL, name = "dominant_taxa", ...)  
  
## S4 method for signature 'SummarizedExperiment'  
countDominantFeatures(x, group = NULL, name = "dominant_taxa", ...)  
  
countDominantTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'  
countDominantTaxa(x, ...)  
  
## S4 method for signature 'SummarizedExperiment'
```

```
summary(object, assay.type = assay_name, assay_name = "counts")
```

Arguments

x	A SummarizedExperiment object.
top	Numeric value, how many top taxa to return. Default return top five taxa.
method	Specify the method to determine top taxa. Either sum, mean, median or prevalence. Default is 'mean'.
assay.type	a character value to select an assayNames By default it expects count data.
assay_name	a single character value for specifying which assay to use for calculation. (Please use assay.type instead. At some point assay_name will be disabled.)
na.rm	For <code>getTopFeatures</code> logical argument for calculation method specified to argument method. Default is TRUE.
...	Additional arguments passed on to <code>agglomerateByRank()</code> when rank is specified for <code>countDominantFeatures</code> .
rank	A single character defining a taxonomic rank. Must be a value of the output of <code>taxonomyRanks()</code> .
group	With group, it is possible to group the observations in an overview. Must be one of the column names of <code>colData</code> .
name	The column name for the features. The default is 'dominant_taxa'.
object	A SummarizedExperiment object.

Details

The `getTopFeatures` extracts the most top abundant "FeatureID"s in a [SummarizedExperiment](#) object.

The `getUniqueFeatures` is a basic function to access different taxa at a particular taxonomic rank. `countDominantFeatures` returns information about most dominant taxa in a tibble. Information includes their absolute and relative abundances in whole data set.

The `summary` will return a summary of counts for all samples and features in [SummarizedExperiment](#) object.

Value

The `getTopFeatures` returns a vector of the most top abundant "FeatureID"s

The `getUniqueFeatures` returns a vector of unique taxa present at a particular rank

The `countDominantFeatures` returns an overview in a tibble. It contains dominant taxa in a column named `*name*` and its abundance in the data set.

The `summary` returns a list with two tibbles

Author(s)

Leo Lahti, Tuomas Borman and Sudarshan A. Shetty

See Also[getPrevalentFeatures](#)[perCellQCMetrics](#), [perFeatureQCMetrics](#), [addPerCellQC](#), [addPerFeatureQC](#), [quickPerCellQC](#)**Examples**

```
data(GlobalPatterns)
top_taxa <- getTopFeatures(GlobalPatterns,
                          method = "mean",
                          top = 5,
                          assay.type = "counts")

top_taxa

# Use 'detection' to select detection threshold when using prevalence method
top_taxa <- getTopFeatures(GlobalPatterns,
                          method = "prevalence",
                          top = 5,
                          assay_name = "counts",
                          detection = 100)

top_taxa

# Top taxa os specific rank
getTopFeatures(agglomerateByRank(GlobalPatterns,
                                rank = "Genus",
                                na.rm = TRUE))

# Gets the overview of dominant taxa
dominant_taxa <- countDominantFeatures(GlobalPatterns,
                                       rank = "Genus")

dominant_taxa

# With group, it is possible to group observations based on specified groups
# Gets the overview of dominant taxa
dominant_taxa <- countDominantFeatures(GlobalPatterns,
                                       rank = "Genus",
                                       group = "SampleType",
                                       na.rm = TRUE)

dominant_taxa

# Get an overview of sample and taxa counts
summary(GlobalPatterns, assay_name= "counts")

# Get unique taxa at a particular taxonomic rank
# sort = TRUE means that output is sorted in alphabetical order
# With na.rm = TRUE, it is possible to remove NAs
# sort and na.rm can also be used in function getTopFeatures
getUniqueFeatures(GlobalPatterns, "Phylum", sort = TRUE)
```

taxonomy-methods *Functions for accessing taxonomic data stored in rowData.*

Description

These function work on data present in `rowData` and define a way to represent taxonomic data alongside the features of a `SummarizedExperiment`.

Usage

```
TAXONOMY_RANKS

taxonomyRanks(x)

## S4 method for signature 'SummarizedExperiment'
taxonomyRanks(x)

taxonomyRankEmpty(
  x,
  rank = taxonomyRanks(x)[1L],
  empty.fields = c(NA, "", " ", "\t", "-", "_")
)

## S4 method for signature 'SummarizedExperiment'
taxonomyRankEmpty(
  x,
  rank = taxonomyRanks(x)[1],
  empty.fields = c(NA, "", " ", "\t", "-", "_")
)

checkTaxonomy(x, ...)

## S4 method for signature 'SummarizedExperiment'
checkTaxonomy(x)

setTaxonomyRanks(ranks)

getTaxonomyRanks()

getTaxonomyLabels(x, ...)

## S4 method for signature 'SummarizedExperiment'
getTaxonomyLabels(
  x,
  empty.fields = c(NA, "", " ", "\t", "-", "_"),
  with_rank = FALSE,
  make_unique = TRUE,
```

```

    resolve_loops = FALSE,
    ...
)

mapTaxonomy(x, ...)

## S4 method for signature 'SummarizedExperiment'
mapTaxonomy(x, taxa = NULL, from = NULL, to = NULL, use_grep1 = FALSE)

IdTaxaToDataFrame(from)

```

Arguments

x	a SummarizedExperiment object
rank	a single character defining a taxonomic rank. Must be a value of <code>taxonomyRanks()</code> function
empty.fields	a character value defining, which values should be regarded as empty. (Default: <code>c(NA, "", " ", "\t")</code>). They will be removed if <code>na.rm = TRUE</code> before agglomeration
...	optional arguments not used currently.
ranks	A vector of ranks to be set
with_rank	TRUE or FALSE: Should the level be add as a suffix? For example: "Phylum:Crenarchaeota" (default: <code>with_rank = FALSE</code>)
make_unique	TRUE or FALSE: Should the labels be made unique, if there are any duplicates? (default: <code>make_unique = TRUE</code>)
resolve_loops	TRUE or FALSE: Should <code>resolveLoops</code> be applied to the taxonomic data? Please note that has only an effect, if the data is unique. (default: <code>resolve_loops = TRUE</code>)
taxa	a character vector, which is used for subsetting the taxonomic information. If no information is found, NULL is returned for the individual element. (default: NULL)
from	<ul style="list-style-type: none"> For <code>mapTaxonomy</code>: a scalar character value, which must be a valid taxonomic rank. (default: NULL) otherwise a Taxa object as returned by <code>IdTaxa</code>
to	a scalar character value, which must be a valid taxonomic rank. (default: NULL)
use_grep1	TRUE or FALSE: should pattern matching via <code>grep1</code> be used? Otherwise literal matching is used. (default: FALSE)

Format

a character vector of length 8 containing the taxonomy ranks recognized. In functions this is used as case insensitive.

Details

`taxonomyRanks` returns, which columns of `rowData(x)` are regarded as columns containing taxonomic information.

`taxonomyRankEmpty` checks, if a selected rank is empty of information.

`checkTaxonomy` checks, if taxonomy information is valid and whether it contains any problems. This is a soft test, which reports some diagnostic and might mature into a data validator used upon object creation.

`getTaxonomyLabels` generates a character vector per row consisting of the lowest taxonomic information possible. If data from different levels, is to be mixed, the taxonomic level is prepended by default.

`IdTaxaToDataFrame` extracts taxonomic results from results of `IdTaxa`.

`mapTaxonomy` maps the given features (taxonomic groups; `taxa`) to the specified taxonomic level (to argument) in `rowData` of the `SummarizedExperiment` data object (i.e. `rowData(x)[, taxonomyRanks(x)]`). If the argument `to` is not provided, then all matching taxonomy rows in `rowData` will be returned. This function allows handy conversions between different

Taxonomic information from the `IdTaxa` function of DECIPHER package are returned as a special class. With `as(taxa, "DataFrame")` the information can be easily converted to a `DataFrame` compatible with storing the taxonomic information a `rowData`. Please note that the assigned confidence information are returned as `metatdata` and can be accessed using `metadata(df)$confidence`.

Value

- `taxonomyRanks`: a character vector with all the taxonomic ranks found in `colnames(rowData(x))`
- `taxonomyRankEmpty`: a logical value
- `mapTaxonomy`: a list per element of `taxa`. Each element is either a `DataFrame`, a character or `NULL`. If all character results have the length of one, a single character vector is returned.

See Also

[agglomerateByRank](#), [toTree](#), [resolveLoop](#)

Examples

```
data(GlobalPatterns)
GlobalPatterns
taxonomyRanks(GlobalPatterns)

checkTaxonomy(GlobalPatterns)

table(taxonomyRankEmpty(GlobalPatterns, "Kingdom"))
table(taxonomyRankEmpty(GlobalPatterns, "Species"))

getTaxonomyLabels(GlobalPatterns[1:20,])

# mapTaxonomy
## returns the unique taxonomic information
mapTaxonomy(GlobalPatterns)
```

```
# returns specific unique taxonomic information
mapTaxonomy(GlobalPatterns, taxa = "Escherichia")
# returns information on a single output
mapTaxonomy(GlobalPatterns, taxa = "Escherichia", to="Family")

# setTaxonomyRanks
tse <- GlobalPatterns
colnames(rowData(tse))[1] <- "TAXA1"

setTaxonomyRanks(colnames(rowData(tse)))
# Taxonomy ranks set to: taxa1 phylum class order family genus species

# getTaxonomyRanks is to get/check if the taxonomic ranks is set to "TAXA1"
getTaxonomyRanks()
```

Tengeler2020

Tengeler2020

Description

Tengeler2020 includes gut microbiota profiles of 27 persons with ADHD. A standard bioinformatic and statistical analysis done to demonstrate that altered microbial composition could be a driver of altered brain structure and function and concomitant changes in the animals' behavior. This was investigated by colonizing young, male, germ-free C57BL/6JOLA_{Hsd} mice with microbiota from individuals with and without ADHD.

Usage

```
data(Tengeler2020)
```

Format

A TreeSummarizedExperiment with 151 features and 27 samples. The rowData contains taxonomic information at Kingdom, Phylum, Class, Order, Family and Genus level. The colData includes:

patient_status clinical status of the patient (ADHD or Control)

cohort cohort to which the patient belongs (Cohort_1, Cohort_2 and Cohort_3)

patient_status_vs_cohort combination of patient_status and cohort

sample_name unique sample ID

Author(s)

A.C. Tengeler, et al.

References

Tengeler, A.C., Dam, S.A., Wiesmann, M. et al. Gut microbiota from persons with attention-deficit/hyperactivity disorder affects the brain in mice. *Microbiome* 8, 44 (2020). <https://doi.org/10.1186/s40168-020-00816-x>

Supplemental information includes Home-cage activity, methods, results and imaging parameters and publicly-accessible from: https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM1_ESM.docx https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM2_ESM.docx https://static-content.springer.com/esm/art%3A10.1186%2Fs40168-020-00816-x/MediaObjects/40168_2020_816_MOESM3_ESM.docx

See Also

[mia-datasets](#)

transformAssay	<i>Transform assay</i>
----------------	------------------------

Description

Variety of transformations for abundance data, stored in assay. See details for options.

Usage

```
transformSamples(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("alr", "chi.square", "clr", "frequency", "hellinger", "log", "log10",
    "log2", "normalize", "pa", "rank", "rclr", "relabundance", "rrank", "total"),
  name = method,
  ...
)

## S4 method for signature 'SummarizedExperiment'
transformSamples(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("alr", "chi.square", "clr", "frequency", "hellinger", "log", "log10",
    "log2", "normalize", "pa", "rank", "rclr", "relabundance", "rrank", "total"),
  name = method,
  pseudocount = FALSE,
  ...
)
```

```

transformAssay(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("alr", "chi.square", "clr", "frequency", "hellinger", "log", "log10",
    "log2", "max", "normalize", "pa", "range", "rank", "rclr", "relabundance", "rrank",
    "standardize", "total", "z"),
  MARGIN = "samples",
  name = method,
  pseudocount = FALSE,
  ...
)

transformCounts(x, ...)

## S4 method for signature 'SummarizedExperiment'
transformAssay(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("alr", "chi.square", "clr", "frequency", "hellinger", "log", "log10",
    "log2", "max", "normalize", "pa", "range", "rank", "rclr", "relabundance", "rrank",
    "standardize", "total", "z"),
  MARGIN = "samples",
  name = method,
  pseudocount = FALSE,
  ...
)

transformFeatures(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("frequency", "log", "log10", "log2", "max", "pa", "range", "standardize",
    "z"),
  name = method,
  pseudocount = FALSE,
  ...
)

## S4 method for signature 'SummarizedExperiment'
transformFeatures(
  x,
  assay.type = "counts",
  assay_name = NULL,
  method = c("frequency", "log", "log10", "log2", "max", "pa", "range", "standardize",
    "z"),
  name = method,

```

```

    pseudocount = FALSE,
    ...
  )

ZTransform(x, MARGIN = "features", ...)

## S4 method for signature 'SummarizedExperiment'
ZTransform(x, MARGIN = "features", ...)

relAbundanceCounts(x, ...)

## S4 method for signature 'SummarizedExperiment'
relAbundanceCounts(x, ...)

```

Arguments

x	A SummarizedExperiment object.
assay.type	A single character value for selecting the assay to be transformed.
assay_name	a single character value for specifying which assay to use for calculation. (Please use <code>assay.type</code> instead. At some point <code>assay_name</code> will be disabled.)
method	A single character value for selecting the transformation method.
name	A single character value specifying the name of transformed abundance table.
...	additional arguments passed on to <code>vegan::decostand</code> : <ul style="list-style-type: none"> • <code>ref_vals</code>: A single value which will be used to fill reference sample's column in returned assay when calculating <code>alr</code>. (default: <code>ref_vals = NA</code>)
pseudocount	TRUE, FALSE, or a numeric value. When TRUE, automatically adds the minimum positive value of <code>assay.type</code> . When FALSE, does not add any pseudocount (<code>pseudocount = 0</code>). Alternatively, a user-specified numeric value can be added as <code>pseudocount</code> .
MARGIN	A single character value for specifying whether the transformation is applied sample (column) or feature (row) wise. (By default: <code>MARGIN = "samples"</code>)

Details

These `transformCount` function provides a variety of options for transforming abundance data. The transformed data is calculated and stored in a new assay. The previously available wrappers `transformSamples`, `transformFeatures` `ZTransform`, and `relAbundanceCounts` have been deprecated.

The `transformAssay` provides sample-wise (column-wise) or feature-wise (row-wise) transformation to the abundance table (assay) based on specified `MARGIN`.

The available transformation methods include:

- 'alr' Additive log ratio (alr) transformation, please refer to [decostand](#) for details.
- 'chi.square' Chi square transformation, please refer to [decostand](#) for details.
- 'clr' Centered log ratio (clr) transformation, please refer to [decostand](#) for details.
- 'frequency' Frequency transformation, please refer to [decostand](#) for details.

- 'hellinger' Hellinger transformation, please refer to [decostand](#) for details.
- 'log' Logarithmic transformation, please refer to [decostand](#) for details.
- 'log10' log10 transformation can be used for reducing the skewness of the data.

$$\log_{10} = \log_{10} x$$

where x is a single value of data.

- 'log2' log2 transformation can be used for reducing the skewness of the data.

$$\log_2 = \log_2 x$$

where x is a single value of data.

- 'normalize' Make margin sum of squares equal to one. Please refer to [decostand](#) for details.
- 'pa' Transforms table to presence/absence table. Please refer to [decostand](#) for details.
- 'rank' Rank transformation, please refer to [decostand](#) for details.
- 'rclr' Robust clr transformation, please refer to [decostand](#) for details.
- 'relabundance' Relative transformation (alias for 'total'), please refer to [decostand](#) for details.
- 'rrank' Relative rank transformation, please refer to [decostand](#) for details.
- 'standardize' Scale 'x' to zero mean and unit variance (alias for 'z'), please refer to [decostand](#) for details.
- 'total' Divide by margin total (alias for 'relabundance'), please refer to [decostand](#) for details.
- 'z' Z transformation (alias for 'standardize'), please refer to [decostand](#) for details.

Value

transformAssay returns the input object x , with a new transformed abundance table named `name` added in the `assay`.

Author(s)

Leo Lahti and Tuomas Borman. Contact: microbiome.github.io

Examples

```
data(esophagus, package="mia")
tse <- esophagus

# By specifying 'method', it is possible to apply different transformations,
# e.g. compositional transformation.
tse <- transformAssay(tse, method = "relabundance")

# The target of transformation can be specified with "assay.type"
# Pseudocount can be added by specifying 'pseudocount'.

# Perform CLR with smallest positive value as pseudocount
tse <- transformAssay(tse, assay.type = "relabundance", method = "clr",
                     pseudocount = TRUE
                     )
```


Index

- * **datasets**
 - dmn_se, [23](#)
 - enterotype, [24](#)
 - esophagus, [25](#)
 - GlobalPatterns, [51](#)
 - HintikkaXOData, [53](#)
 - mia-datasets, [75](#)
 - peerj13075, [75](#)
 - taxonomy-methods, [98](#)
 - Tengeler2020, [101](#)
- ?agglomerateByRank, [48](#)
- [, [94](#)

- addCluster, [4](#)
- addCluster, SummarizedExperiment-method (addCluster), [4](#)
- addContaminantQC (isContaminant), [61](#)
- addContaminantQC, SummarizedExperiment-method (isContaminant), [61](#)
- addDivergence, [6](#)
- addDivergence, SummarizedExperiment-method (addDivergence), [6](#)
- addHierarchyTree (hierarchy-tree), [52](#)
- addHierarchyTree, SummarizedExperiment-method (hierarchy-tree), [52](#)
- addNotContaminantQC (isContaminant), [61](#)
- addNotContaminantQC, SummarizedExperiment-method (isContaminant), [61](#)
- addPerCellQC, [97](#)
- addPerFeatureQC, [97](#)
- addPerSampleDominantFeatures (perSampleDominantTaxa), [76](#)
- addPerSampleDominantFeatures, SummarizedExperiment-method (perSampleDominantTaxa), [76](#)
- addPerSampleDominantTaxa (perSampleDominantTaxa), [76](#)
- addPerSampleDominantTaxa, SummarizedExperiment-method (perSampleDominantTaxa), [76](#)
- addTaxonomyTree (deprecate), [21](#)

- addTaxonomyTree, SummarizedExperiment-method (deprecate), [21](#)
- agglomerate-methods, [8](#)
- agglomerateByPrevalence (agglomerate-methods), [8](#)
- agglomerateByPrevalence, SummarizedExperiment-method (agglomerate-methods), [8](#)
- agglomerateByRank, [48](#), [49](#), [88](#), [89](#), [91](#), [100](#)
- agglomerateByRank (agglomerate-methods), [8](#)
- agglomerateByRank, SingleCellExperiment-method (agglomerate-methods), [8](#)
- agglomerateByRank, SummarizedExperiment-method (agglomerate-methods), [8](#)
- agglomerateByRank, TreeSummarizedExperiment-method (agglomerate-methods), [8](#)
- altExps, [89](#), [91](#)
- ape::phylo, [59](#)
- assay, [18](#), [32](#), [35](#), [42](#), [48](#), [54](#), [56](#), [62](#), [63](#), [71](#), [72](#), [78](#), [104](#), [105](#)
- assayNames, [68](#), [96](#)

- bestDMNFit (calculateDMN), [12](#)
- bestDMNFit, SummarizedExperiment-method (calculateDMN), [12](#)
- BiocParallelParam, [14](#), [16](#), [20](#), [28](#), [32](#), [36](#), [38](#)
- biom, [65](#)
- Biostings::DNAStrngSet, [59](#)
- bluster, [5](#)
- BlusterParam, [5](#)

- calculateCCA (runCCA), [80](#)
- calculateCCA, ANY-method (runCCA), [80](#)
- calculateCCA, SummarizedExperiment-method (runCCA), [80](#)
- calculateDMN, [12](#), [23](#)
- calculateDMN, ANY-method (calculateDMN), [12](#)
- calculateDMN, SummarizedExperiment-method (calculateDMN), [12](#)

- calculateDMNgroup (calculateDMN), 12
- calculateDMNgroup, ANY-method (calculateDMN), 12
- calculateDMNgroup, SummarizedExperiment-method (calculateDMN), 12
- calculateDPCoA (runDPCoA), 83
- calculateDPCoA, ANY, ANY-method (runDPCoA), 83
- calculateDPCoA, TreeSummarizedExperiment, missing-method (runDPCoA), 83
- calculateJSD, 15, 18
- calculateJSD, ANY-method (calculateJSD), 15
- calculateJSD, SummarizedExperiment-method (calculateJSD), 15
- calculateNMDS (runNMDS), 85
- calculateNMDS, ANY-method (runNMDS), 85
- calculateNMDS, SingleCellExperiment-method (runNMDS), 85
- calculateNMDS, SummarizedExperiment-method (runNMDS), 85
- calculateOverlap, 17
- calculateOverlap, SummarizedExperiment-method (calculateOverlap), 17
- calculateRDA (runCCA), 80
- calculateRDA, ANY-method (runCCA), 80
- calculateRDA, SummarizedExperiment-method (runCCA), 80
- calculateUnifrac, 18, 19
- calculateUnifrac, ANY, phylo-method (calculateUnifrac), 19
- calculateUnifrac, TreeSummarizedExperiment, missing-method (calculateUnifrac), 19
- cca, 82
- checkTaxonomy (taxonomy-methods), 98
- checkTaxonomy, SummarizedExperiment-method (taxonomy-methods), 98
- cluster (deprecate), 21
- cluster, SummarizedExperiment-method (deprecate), 21
- colData, 7, 29, 33, 36, 39, 78
- cophenetic.phylo, 84
- countDominantFeatures (summaries), 94
- countDominantFeatures, SummarizedExperiment-method (summaries), 94
- countDominantTaxa (summaries), 94
- countDominantTaxa, SummarizedExperiment-method (summaries), 94
- dbrda, 82
- DECIPHER::ConsensusSequence, 71
- decontam:isContaminant, 62
- decontam:isNotContaminant, 62
- decostand, 104, 105
- deprecate, 21
- detectLoop, 10
- DirichletMultinomial, 12
- dist, 20, 86
- diversity, 29
- dmn, 14
- dmn_se, 23, 75
- DMNGroup, 14
- dmngroup, 14
- enterotype, 24, 75
- esophagus, 25, 75
- estimateDivergence (deprecate), 21
- estimateDivergence, SummarizedExperiment-method (deprecate), 21
- estimateDiversity, 26, 34, 37
- estimateDiversity, SummarizedExperiment-method (estimateDiversity), 26
- estimateDiversity, TreeSummarizedExperiment-method (estimateDiversity), 26
- estimateDominance, 7, 29, 31, 37
- estimateDominance, SummarizedExperiment-method (estimateDominance), 31
- estimateEvenness, 7, 29, 34, 35
- estimateEvenness, SummarizedExperiment-method (estimateEvenness), 35
- estimateFaith (estimateDiversity), 26
- estimateFaith, SummarizedExperiment, phylo-method (estimateDiversity), 26
- estimateFaith, TreeSummarizedExperiment, missing-method (estimateDiversity), 26
- estimateR, 29, 39
- estimateRichness, 7, 29, 34, 37, 37
- estimateRichness, SummarizedExperiment-method (estimateRichness), 37
- full_join, 74
- full_join (deprecate), 21
- full_join, ANY-method (deprecate), 21
- getBestDMNFit (calculateDMN), 12
- getBestDMNFit, SummarizedExperiment-method (calculateDMN), 12
- getDMN (calculateDMN), 12

- getDMN, SummarizedExperiment-method
(calculateDMN), 12
- getExperimentCrossAssociation, 41
- getExperimentCrossAssociation, MultiAssayExperiment-method
(getExperimentCrossAssociation), 41
- getExperimentCrossAssociation, SummarizedExperiment-method
(getExperimentCrossAssociation), 41
- getExperimentCrossCorrelation
(getExperimentCrossAssociation), 41
- getExperimentCrossCorrelation, ANY-method
(getExperimentCrossAssociation), 41
- getHierarchyTree (hierarchy-tree), 52
- getHierarchyTree, SummarizedExperiment-method
(hierarchy-tree), 52
- getPrevalence, 46
- getPrevalence, ANY-method
(getPrevalence), 46
- getPrevalence, SummarizedExperiment-method
(getPrevalence), 46
- getPrevalentAbundance (getPrevalence), 46
- getPrevalentAbundance, ANY-method
(getPrevalence), 46
- getPrevalentAbundance, SummarizedExperiment-method
(getPrevalence), 46
- getPrevalentFeatures, 97
- getPrevalentFeatures (getPrevalence), 46
- getPrevalentFeatures, ANY-method
(getPrevalence), 46
- getPrevalentFeatures, SummarizedExperiment-method
(getPrevalence), 46
- getPrevalentTaxa (getPrevalence), 46
- getPrevalentTaxa, ANY-method
(getPrevalence), 46
- getRareFeatures (getPrevalence), 46
- getRareFeatures, ANY-method
(getPrevalence), 46
- getRareFeatures, SummarizedExperiment-method
(getPrevalence), 46
- getRarePrevalentTaxa (getPrevalence), 46
- getRareTaxa (getPrevalence), 46
- getRareTaxa, ANY-method (getPrevalence), 46
- getTaxonomyLabels (taxonomy-methods), 98
- getTaxonomyLabels, SummarizedExperiment-method
(taxonomy-methods), 98
- getTaxonomyRanks (taxonomy-methods), 98
- getTopFeatures (summaries), 94
- getTopFeatures, SummarizedExperiment-method
(summaries), 94
- getTopTaxa, 49
- getTopTaxa (summaries), 94
- getTopTaxa, SummarizedExperiment-method
(summaries), 94
- getUniqueFeatures (summaries), 94
- getUniqueFeatures, SummarizedExperiment-method
(summaries), 94
- getUniqueTaxa (summaries), 94
- getUniqueTaxa, SummarizedExperiment-method
(summaries), 94
- GlobalPatterns, 51, 75
- hierarchy-tree, 52
- HintikkaXOData, 53, 75
- IdTaxa, 99, 100
- IdTaxaToDataFrame (taxonomy-methods), 98
- importBIOM (makeTreeSEFromBiom), 64
- importHUMANn, 54, 56
- importMetaPhlan, 54, 55, 55
- importMothur, 55, 56, 57, 60, 65–67
- importQIIME2, 55, 56, 58, 58, 65–67
- importQZA (importQIIME2), 58
- inner_join, 74
- inner_join (deprecate), 21
- inner_join, ANY-method (deprecate), 21
- isContaminant, 61
- isContaminant, SummarizedExperiment-method
(isContaminant), 61
- isNotContaminant, SummarizedExperiment-method
(isContaminant), 61
- left_join, 74
- left_join (deprecate), 21
- left_join, ANY-method (deprecate), 21
- loadFromBiom (deprecate), 21
- loadFromHumann (deprecate), 21
- loadFromMetaphlan (deprecate), 21
- loadFromMothur (deprecate), 21
- loadFromQIIME2 (deprecate), 21
- makePhyloseqFromTreeSE, 63
- makePhyloseqFromTreeSE, SummarizedExperiment-method
(makePhyloseqFromTreeSE), 63

- makePhyloseqFromTreeSE, TreeSummarizedExperiment-method
 - (makePhyloseqFromTreeSE), 63
- makePhyloseqFromTreeSummarizedExperiment
 - (makePhyloseqFromTreeSE), 63
- makePhyloseqFromTreeSummarizedExperiment, ANY-method
 - (makePhyloseqFromTreeSE), 63
- makeTreeSEFromBiom, 55, 56, 58, 60, 64, 66, 67
- makeTreeSEFromDADA2, 55, 56, 58, 60, 65, 66, 67
- makeTreeSEFromPhyloseq, 55, 56, 58, 60, 65, 66, 67
- makeTreeSummarizedExperimentFromBiom
 - (makeTreeSEFromBiom), 64
- makeTreeSummarizedExperimentFromDADA2
 - (makeTreeSEFromDADA2), 66
- makeTreeSummarizedExperimentFromPhyloseq
 - (makeTreeSEFromPhyloseq), 67
- makeTreeSummarizedExperimentFromPhyloseq, ANY-method
 - (makeTreeSEFromPhyloseq), 67
- mapTaxonomy (taxonomy-methods), 98
- mapTaxonomy, SummarizedExperiment-method
 - (taxonomy-methods), 98
- MASS::isoMDS, 86, 87
- meltAssay, 68
- meltAssay, SummarizedExperiment-method
 - (meltAssay), 68
- merge-methods, 69
- mergeCols (merge-methods), 69
- mergeCols, SummarizedExperiment-method
 - (merge-methods), 69
- mergeCols, TreeSummarizedExperiment-method
 - (merge-methods), 69
- mergeFeatures (merge-methods), 69
- mergeFeatures, SummarizedExperiment-method
 - (merge-methods), 69
- mergeFeatures, TreeSummarizedExperiment-method
 - (merge-methods), 69
- mergeFeaturesByPrevalence (deprecate), 21
- mergeFeaturesByPrevalence, SummarizedExperiment-method
 - (deprecate), 21
- mergeFeaturesByRank
 - (agglomerate-methods), 8
- mergeFeaturesByRank, SingleCellExperiment-method
 - (agglomerate-methods), 8
- mergeFeaturesByRank, SummarizedExperiment-method
 - (agglomerate-methods), 8
- mergeFeaturesByRank, TreeSummarizedExperiment-method
 - (agglomerate-methods), 8
- mergeRows, SummarizedExperiment-method
 - (merge-methods), 69
- mergeRows, TreeSummarizedExperiment-method
 - (merge-methods), 69
- mergeSamples (merge-methods), 69
- mergeSamples, SummarizedExperiment-method
 - (merge-methods), 69
- mergeSamples, TreeSummarizedExperiment-method
 - (merge-methods), 69
- mergeSEs, 72
- mergeSEs, list-method (mergeSEs), 72
- mergeSEs, SimpleList-method (mergeSEs), 72
- mergeSEs, SummarizedExperiment-method (mergeSEs), 72
- mergeSmamples (merge-methods), 69
- metadata, 5, 14
- mia (mia-package), 3
- mia-datasets, 75
- mia-package, 3
- MultiAssayExperiment, 42
- name, 38
- peerj13075, 75, 75
- perCellQCMetrics, 97
- perFeatureQCMetrics, 97
- performDMNgroupCV (calculateDMN), 12
- performDMNgroupCV, ANY-method
 - (calculateDMN), 12
- performDMNgroupCV, SummarizedExperiment-method
 - (calculateDMN), 12
- perSampleDominantFeatures
 - (perSampleDominantTaxa), 76
- perSampleDominantFeatures, SummarizedExperiment-method
 - (perSampleDominantTaxa), 76
- perSampleDominantTaxa, 76
- perSampleDominantTaxa, SummarizedExperiment-method
 - (perSampleDominantTaxa), 76
- phylo, 20
- phyloseq::rarefy_even_depth, 92
- plotColData, 7, 29, 37, 39
- plotMDS, 87
- plotNMDS (deprecate), 21
- plotReducedDim, 84

- quickPerCellQC, [97](#)
- rarefyCounts (subsamplingCounts), [91](#)
- readQZA (deprecate), [21](#)
- reducedDims, [84](#)
- relabundance, [79](#)
- relabundance, SummarizedExperiment-method (relabundance), [79](#)
- relabundance<- (relabundance), [79](#)
- relabundance<- , SummarizedExperiment-method (relabundance), [79](#)
- relAbundanceCounts (transformAssay), [102](#)
- relAbundanceCounts, SummarizedExperiment-method (transformAssay), [102](#)
- resolveLoop, [52](#), [100](#)
- right_join, [74](#)
- right_join (deprecate), [21](#)
- right_join, ANY-method (deprecate), [21](#)
- runCCA, [80](#)
- runCCA, SingleCellExperiment-method (runCCA), [80](#)
- runDMN (calculateDMN), [12](#)
- runDPCoA, [83](#)
- runJSD (calculateJSD), [15](#)
- runNMDS, [85](#)
- runOverlap (calculateOverlap), [17](#)
- runOverlap, SummarizedExperiment-method (calculateOverlap), [17](#)
- runRDA (runCCA), [80](#)
- runRDA, SingleCellExperiment-method (runCCA), [80](#)
- runUnifrac (calculateUnifrac), [19](#)
- setTaxonomyRanks (taxonomy-methods), [98](#)
- SingleCellExperiment, [81](#), [86](#)
- splitAltExps, [88](#), [89](#), [91](#)
- splitByRanks, [87](#), [91](#)
- splitByRanks, SingleCellExperiment-method (splitByRanks), [87](#)
- splitByRanks, SummarizedExperiment-method (splitByRanks), [87](#)
- splitByRanks, TreeSummarizedExperiment-method (splitByRanks), [87](#)
- splitOn, [89](#), [89](#)
- splitOn, SingleCellExperiment-method (splitOn), [89](#)
- splitOn, SummarizedExperiment-method (splitOn), [89](#)
- splitOn, TreeSummarizedExperiment-method (splitOn), [89](#)
- subsamplingCounts, [91](#)
- subsamplingCounts, SummarizedExperiment-method (subsamplingCounts), [91](#)
- subset, [94](#)
- subsetByPrevalentFeatures (getPrevalence), [46](#)
- subsetByPrevalentFeatures, SummarizedExperiment-method (getPrevalence), [46](#)
- subsetByPrevalentTaxa (getPrevalence), [46](#)
- subsetByPrevalentTaxa, ANY-method (getPrevalence), [46](#)
- subsetByRareFeatures (getPrevalence), [46](#)
- subsetByRareFeatures, SummarizedExperiment-method (getPrevalence), [46](#)
- subsetByRareTaxa (getPrevalence), [46](#)
- subsetByRareTaxa, ANY-method (getPrevalence), [46](#)
- subsetFeatures (subsetSamples), [93](#)
- subsetFeatures, SummarizedExperiment-method (subsetSamples), [93](#)
- subsetSamples, [93](#)
- subsetSamples, SummarizedExperiment-method (subsetSamples), [93](#)
- subsetTaxa (subsetSamples), [93](#)
- subsetTaxa, SummarizedExperiment-method (subsetSamples), [93](#)
- sumCountsAcrossFeatures, [9](#), [10](#), [71](#), [89](#), [91](#)
- summaries, [94](#)
- SummarizedExperiment, [5](#), [6](#), [9](#), [14–18](#), [23](#), [27](#), [32](#), [35](#), [38](#), [42](#), [48](#), [52](#), [61](#), [62](#), [68](#), [70](#), [72](#), [73](#), [76–78](#), [81](#), [88](#), [90](#), [94](#), [96](#), [99](#), [104](#)
- summary, SummarizedExperiment-method (summaries), [94](#)
- taxonomy-methods, [98](#)
- TAXONOMY_RANKS (taxonomy-methods), [98](#)
- taxonomyRankEmpty (taxonomy-methods), [98](#)
- taxonomyRankEmpty, SummarizedExperiment-method (taxonomy-methods), [98](#)
- taxonomyRanks (taxonomy-methods), [98](#)
- taxonomyRanks, SummarizedExperiment-method (taxonomy-methods), [98](#)
- taxonomyTree (deprecate), [21](#)
- taxonomyTree, SummarizedExperiment-method (deprecate), [21](#)

Tengeler2020, [75](#), [101](#)
testExperimentCrossAssociation
 (getExperimentCrossAssociation),
 [41](#)
testExperimentCrossAssociation, ANY-method
 (getExperimentCrossAssociation),
 [41](#)
testExperimentCrossCorrelation
 (getExperimentCrossAssociation),
 [41](#)
testExperimentCrossCorrelation, ANY-method
 (getExperimentCrossAssociation),
 [41](#)
toTree, [52](#), [100](#)
transformAssay, [102](#)
transformAssay, SummarizedExperiment-method
 (transformAssay), [102](#)
transformCounts (transformAssay), [102](#)
transformFeatures (transformAssay), [102](#)
transformFeatures, SummarizedExperiment-method
 (transformAssay), [102](#)
transformSamples (transformAssay), [102](#)
transformSamples, SummarizedExperiment-method
 (transformAssay), [102](#)
TreeSummarizedExperiment, [4](#), [19](#), [27](#),
 [55–57](#), [59](#), [64](#), [65](#), [70](#), [79](#), [84](#)
twins (dmn_se), [23](#)

unsplitByRanks, [91](#)
unsplitByRanks (splitByRanks), [87](#)
unsplitByRanks, SingleCellExperiment-method
 (splitByRanks), [87](#)
unsplitByRanks, TreeSummarizedExperiment-method
 (splitByRanks), [87](#)
unsplitOn, [89](#)
unsplitOn (splitOn), [89](#)
unsplitOn, list-method (splitOn), [89](#)
unsplitOn, SimpleList-method (splitOn),
 [89](#)
unsplitOn, SingleCellExperiment-method
 (splitOn), [89](#)

vegan::diversity, [28](#)
vegan::fisher.alpha, [28](#)
vegan::monoMDS, [86](#), [87](#)

ZTransform (transformAssay), [102](#)
ZTransform, SummarizedExperiment-method
 (transformAssay), [102](#)