Package 'CytoPipelineGUI'

April 29, 2025

Title GUI's for visualization of flow cytometry data analysis pipelines

Version 1.7.0

Description This package is the companion of the `CytoPipeline` package. It provides GUI's (shiny apps) for the visualization of flow cytometry data analysis pipelines that are run with `CytoPipeline`. Two shiny applications are provided, i.e. an interactive flow frame assessment and comparison tool and an interactive scale transformations visualization and adjustment tool.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

BugReports https://github.com/UCLouvain-CBIO/CytoPipelineGUI/issues

URL https://uclouvain-cbio.github.io/CytoPipelineGUI

biocViews FlowCytometry, Preprocessing, QualityControl, WorkflowStep, ImmunoOncology, Software, Visualization, GUI, ShinyApps

Collate plots.R shiny-functions.R shiny-scaleTransform-module.R shiny.R CytoPipelineGUI-package.R

Depends R (>= 4.4), CytoPipeline

Imports shiny, plotly, ggplot2, flowCore

Suggests testthat (>= 3.0.0), vdiffr, diffviewer, knitr, rmarkdown, BiocStyle, patchwork

VignetteBuilder knitr

Config/testthat/edition 3

git_url https://git.bioconductor.org/packages/CytoPipelineGUI

git_branch devel

git_last_commit cfdd65f

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-04-29

Author Philippe Hauchamps [aut, cre] (ORCID:
<https://orcid.org/0000-0003-2865-1852>),
Laurent Gatto [aut] (ORCID: <https://orcid.org/0000-0002-1520-2268>),
Dan Lin [ctb]

Maintainer Philippe Hauchamps <philippe.hauchamps@uclouvain.be>

Contents

CytoPipelineCheckApp 2
CytoPipelineGUI 3
plotDiffFlowFrame 4
plotScaleTransformedChannel 7
plotSelectedFlowFrame 9
plotSelectedWorkflow 11
ScaleTransformApp 12

Index **14**

`CytoPipelineCheckApp` *interactive visualization of flow cytometry data analysis pipeline objects stored in cache*

Description

interactive visualization of flow cytometry data analysis pipeline objects stored in cache

Usage

```
CytoPipelineCheckApp(dir = ".", debug = FALSE)
```

Arguments

`dir`	the root directory into which the engine will look for existing CytoPipeline experiments
`debug`	if TRUE, will output messages on the console tracking the shiny events, for debugging purposes

Value

no return value

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
```

```
    file.path(
        rawDataDir,
        list.files(
            rawDataDir,
            pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <- CytoPipeline(
    jsonPath,
    experimentName = experimentName,
    sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))

# run shiny app

if (interactive())
    CytoPipelineCheckApp(dir = outputDir)
```

`CytoPipelineGUI` *CytoPipelineGUI package*

Description

`CytoPipelineGUI` is the companion package of `CytoPipeline`, and is used for interactive visualization. It implements two shiny applications :

- a shiny app for interactive comparison of flow frames that are the results of CytoProcessingSteps of the same or different CytoPipeline experiments. It is launched using the following statement: `CytoPipelineCheckApp()`
- a shiny app for interactive visualization and manual adjustments of scale transformation objects. It is launched using the following statement: `ScaleTransformApp()`

Author(s)

Maintainer: Philippe Hauchamps <philippe.hauchamps@uclouvain.be> (ORCID)

Authors:

- Laurent Gatto <laurent.gatto@uclouvain.be> (ORCID)

Other contributors:

- Dan Lin <dan.8.lin@gsk.com> [contributor]

See Also

CytoPipeline, CytoPipelineCheckApp, ScaleTransformApp

`plotDiffFlowFrame` *Plot the difference plot between two flow frames from a CytoPipeline run*

Description

Based on an experiment name, this function will gather the required flowFrames from the CytoPipeline disk cache and display a difference plot using the user chosen 1D or 2D view.

Usage

```
plotDiffFlowFrame(
  experimentNameFrom,
  experimentNameTo,
  whichQueueFrom,
  whichQueueTo,
  sampleFileFrom,
  sampleFileTo,
  path,
  flowFrameNameFrom,
  flowFrameNameTo,
  xChannelLabelFrom,
  xChannelLabelTo,
  yChannelLabelFrom,
  yChannelLabelTo,
  interactive = FALSE,
  useAllCells,
  nDisplayCells,
  useFixedLinearRange,
  linearRange,
  transfoListName = " "
)
```

Arguments

`experimentNameFrom`
: the experiment name (representing a pipeline run) from which to extract the flow frame ('from' situation)

`experimentNameTo`
: the experiment name (representing a pipeline run) from which to extract the flow frame ('to' situation)

`whichQueueFrom`
: "pre-processing" or "scale transform" ('from' situation)

`whichQueueTo`
: "pre-processing" or "scale transform" ('to' situation)

`sampleFileFrom`
: in case 'whichQueueFrom' is set to 'pre-processing, which sample file to look at for the 'from' situation. This can be a number or a character.
  - if whichQueueFrom == "scale transform", the sampleFileFrom is ignored
  - if NULL and whihQueueFrom == "pre-processing", the sampleFileFrom is defaulted to the first one belonging to the experiment

`sampleFileTo`
: same as sampleFileFrom, but for the 'to' situation

`path` the root path to look for the CytoPipeline experiment cache

`flowFrameNameFrom`
for the 'from' situation, the name of the object to fetch (as referenced in the pipeline workflow)

`flowFrameNameTo`
for the 'to' situation, the name of the object to fetch (as referenced in the pipeline workflow)

`xChannelLabelFrom`
the label of the channel to be displayed on the x axis: the conventional syntax is : `channelName + " - " + channelMarker`

`xChannelLabelTo`
should be equal to xChannelLabelFrom (otherwise no plot is returned but NULL)

`yChannelLabelFrom`
the label of the channel to be displayed on the y axis: the conventional syntax is : `channelName + " - " + channelMarker`

`yChannelLabelTo`
should be equal to yChannelLabelFrom (otherwise no plot is returned but NULL)

`interactive` if TRUE, uses ggplot_shiny

`useAllCells` if TRUE, no subsampling will be done

`nDisplayCells` if useAllCells == FALSE, the number of subsampled cells

`useFixedLinearRange`
if TRUE, all channels using a linear scale will use a fixed range set by linearRange

`linearRange` set for all channels using a linear scale, if useFixedLinearRange == TRUE

`transfoListName`
if not set to " ", the transformation list (as an object name ending with "_obj", as referenced in the pipeline workflow) to be used for for display.

Value

a ggplot (or plotly if interactive = TRUE) object

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
    file.path(
        rawDataDir,
        list.files(rawDataDir, pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <- CytoPipeline(
    jsonPath,
    experimentName = experimentName,
```

```
    sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))


plotDiffFlowFrame(
    experimentNameFrom = experimentName,
    whichQueueFrom = "pre-processing",
    sampleFileFrom = 1,
    flowFrameNameFrom = "remove_doublets_obj",
    xChannelLabelFrom = "FSC-A : NA",
    yChannelLabelFrom = "SSC-A : NA",
    path = outputDir,
    experimentNameTo = experimentName,
    whichQueueTo = "pre-processing",
    sampleFileTo = 1,
    flowFrameNameTo = "remove_debris_obj",
    xChannelLabelTo = "FSC-A : NA",
    yChannelLabelTo = "SSC-A : NA",
    useAllCells = TRUE,
    nDisplayCells = 0,
    useFixedLinearRange = TRUE,
    linearRange = c(-100, 262144))

plotDiffFlowFrame(
    experimentNameFrom = experimentName,
    whichQueueFrom = "pre-processing",
    sampleFileFrom = 1,
    flowFrameNameFrom = "remove_doublets_obj",
    xChannelLabelFrom = "FSC-A : NA",
    yChannelLabelFrom = "SSC-A : NA",
    path = outputDir,
    experimentNameTo = experimentName,
    whichQueueTo = "pre-processing",
    sampleFileTo = 1,
    flowFrameNameTo = "remove_debris_obj",
    xChannelLabelTo = "FSC-A : NA",
    yChannelLabelTo = "SSC-A : NA",
    useAllCells = FALSE,
    nDisplayCells = 100,
    useFixedLinearRange = FALSE,
    linearRange = NULL)

plotDiffFlowFrame(
    experimentNameFrom = experimentName,
    whichQueueFrom = "pre-processing",
    sampleFileFrom = 1,
    flowFrameNameFrom = "remove_debris_obj",
    xChannelLabelFrom = "FSC-A : NA",
    yChannelLabelFrom = "Comp-525/50Violet-A : L/D Aqua - Viability",
    path = outputDir,
    experimentNameTo = experimentName,
    whichQueueTo = "pre-processing",
    sampleFileTo = 1,
```

```
    flowFrameNameTo = "remove_dead_cells_obj",
    xChannelLabelTo = "FSC-A : NA",
    yChannelLabelTo = "Comp-525/50Violet-A : L/D Aqua - Viability",
    useAllCells = TRUE,
    nDisplayCells = 0,
    useFixedLinearRange = FALSE,
    linearRange = NULL,
    transfoListName = "scale_transform_estimate_obj")
```

`plotScaleTransformedChannel` *Plot a flow frame in 1D with explicit user given scale transform*

Description

This function plots a 1D view, i.e. the marginal distribution for one specified channel, of the given flow frame, using the specific user-provided scale transformation parameters.

Usage

```
plotScaleTransformedChannel(
  ff,
  channel,
  applyTransform = c("axis scale only", "data"),
  transfoType = c("linear", "logicle"),
  linA,
  linB,
  negDecades,
  width,
  posDecades
)
```

Arguments

`ff`	the `flowFrame` to be plotted
`channel`	the name of the channel of which to display the marginal distribution (i.e. the channel name used as column in the ff expression matrix).
`applyTransform`	if "data", data are explicitly transformed using the user provided sclae transformation parameters, before display if "axis scale only" (default), the data are not transformed, i.e. only the x axis scale is defined according to the scale transformation parameters.
`transfoType`	the transformation type, currently only `linear` and `logicle`(bi-exponential) are supported.
`linA`	the intercept parameter of the linear transformation.
`linB`	the slope parameter of the linear transformation.
`negDecades`	the number of additional decades on the negative side for the logicle transformation.
`width`	the width parameter of the logicle transformation.
`posDecades`	the number of positive decades of the logicle tranformation.

Value

a ggplot object

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
    file.path(
        rawDataDir,
        list.files(rawDataDir, pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <- CytoPipeline(
    jsonPath,
    experimentName = experimentName,
    sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))

ff <- CytoPipeline::getCytoPipelineFlowFrame(
pipL2,
path = outputDir,
whichQueue = "scale transform",
objectName = "flowframe_aggregate_obj"
)

plotScaleTransformedChannel(
    ff,
    channel = "FSC-A",
    transfoType = "linear",
    linA = 0.0002,
    linB = -0.5)

plotScaleTransformedChannel(
    ff,
    channel = "Comp-670/30Violet-A",
    transfoType = "logicle",
    negDecades = 1,
    width = 0.5,
    posDecades = 4
)

plotScaleTransformedChannel(
    ff,
    channel = "CD3",
```

```
    applyTransform = "data",
    transfoType = "logicle",
    negDecades = 1,
    width = 0.5,
    posDecades = 4
)
```

`plotSelectedFlowFrame` *Plot a flow frame from a CytoPipeline run*

Description

Based on an experiment name, this function will gather the required flowFrame from the CytoPipeline disk cache and display it using the user chosen 1D or 2D view.

Usage

```
plotSelectedFlowFrame(
  experimentName,
  whichQueue,
  sampleFile,
  flowFrameName,
  path,
  xChannelLabel,
  yChannelLabel,
  useAllCells,
  nDisplayCells,
  useFixedLinearRange,
  linearRange,
  transfoListName = " "
)
```

Arguments

`experimentName`	the experiment name (representing a pipeline run) from which to extract the flow frame
`whichQueue`	"pre-processing" or "scale transform"
`sampleFile`	in case 'whichQueue' is set to 'pre-processing, which sample file to look at. This can be a number or a character. • if whichQueue == "scale transform", the sampleFile is ignored • if NULL and whichQueue == "pre-processing", the sampleFile is defaulted to the first one belonging to the experiment
`flowFrameName`	the name of the object to fetch (as referenced in the pipeline workflow)
`path`	the root path to look for the CytoPipeline experiment cache
`xChannelLabel`	the label of the channel to be displayed on the x axis: the conventional syntax is : `channelName` + " - " + `channelMarker`
`yChannelLabel`	the label of the channel to be displayed on the y axis: the conventional syntax is : `channelName` + " - " + `channelMarker`

useAllCells if TRUE, no subsampling will be done

nDisplayCells if useAllCells == FALSE, the number of subsampled cells

useFixedLinearRange
if TRUE, all channels using a linear scale will use a fixed range set by linearRange

linearRange set for all channels using a linear scale, if useFixedLinearRange == TRUE

transfoListName
if not set to " ", the transformation list (as an object name ending with "_obj", as referenced in the pipeline workflow) to be used for for display.

Value

a ggplot object

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
    file.path(
        rawDataDir,
        list.files(rawDataDir, pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <- CytoPipeline(
    jsonPath,
    experimentName = experimentName,
    sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))

plotSelectedFlowFrame(
    experimentName = experimentName,
    whichQueue = "pre-processing",
    sampleFile = 1,
    flowFrameName = "remove_debris_obj",
    path = outputDir,
    xChannelLabel = "FSC-A : NA",
    yChannelLabel = "SSC-A : NA",
    useAllCells = TRUE,
    nDisplayCells = 0,
    useFixedLinearRange = TRUE,
    linearRange = c(-100, 262144))

plotSelectedFlowFrame(
```

```
    experimentName = experimentName,
    whichQueue = "pre-processing",
    sampleFile = 1,
    flowFrameName = "remove_debris_obj",
    path = outputDir,
    xChannelLabel = "FSC-A : NA",
    yChannelLabel = "SSC-A : NA",
    useAllCells = FALSE,
    nDisplayCells = 100,
    useFixedLinearRange = FALSE,
    linearRange = NULL)

plotSelectedFlowFrame(
    experimentName = experimentName,
    whichQueue = "pre-processing",
    sampleFile = 1,
    flowFrameName = "remove_debris_obj",
    path = outputDir,
    xChannelLabel = "Comp-670/30Violet-A : BV785 - CD3",
    yChannelLabel = "Comp-780/60Red-A : APCCy7 - CD4",
    useAllCells = TRUE,
    nDisplayCells = 0,
    useFixedLinearRange = FALSE,
    linearRange = NULL,
    transfoListName = "scale_transform_estimate_obj")
```

`plotSelectedWorkflow` *Plot a pipeline workflow from a CytoPipeline run*

Description

Plot a pipeline workflow from a CytoPipeline run

Usage

```
plotSelectedWorkflow(experimentName, whichQueue, sampleFile, path = path)
```

Arguments

`experimentName`	the experiment name (representing a pipeline run) from which to extract the workflow
`whichQueue`	"pre-processing" or "scale transform"
`sampleFile`	in case 'whichQueue' is set to 'pre-processing, which sample file to look at. This can be a number or a character. • if whichQueue == "scale transform", the sampleFile is ignored • if NULL and whichQueue == "pre-processing", the sampleFile is defaulted to the first one belonging to the experiment
`path`	the root path to look for the CytoPipeline experiment cache

Value

nothing, but displays the plot as a side effect

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
    file.path(
        rawDataDir,
        list.files(rawDataDir, pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <- CytoPipeline(
    jsonPath,
    experimentName = experimentName,
    sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))

plotSelectedWorkflow(
    experimentName = experimentName,
    whichQueue = "pre-processing",
    sampleFile = sampleFiles[1],
    path = outputDir)

plotSelectedWorkflow(
    experimentName = experimentName,
    whichQueue = "scale transform",
    sampleFile = NULL,
    path = outputDir)
```

`ScaleTransformApp` *interactive display and modification of scale transform list*

Description

this application allows the user to visualize a scale transformation list, possibly amending it channel after channel, and save the results on disk. The needed input tranformation list and flow frame for visualization needs to be read from a CytoPipeline experiments stored in cache.

Usage

```
ScaleTransformApp(dir = ".")
```

Arguments

dir	the root directory into which the engine will look for existing CytoPipeline experiments

Value

no return value

Examples

```
# run CytoPipeline object first

outputDir <- base::tempdir()


rawDataDir <-
    system.file("extdata", package = "CytoPipeline")
experimentName <- "OMIP021_PeacoQC"
sampleFiles <-
    file.path(rawDataDir, list.files(rawDataDir, pattern = "Donor"))
jsonDir <- system.file("extdata", package = "CytoPipeline")
jsonPath <- file.path(jsonDir, "pipelineParams.json")

pipL2 <-
    CytoPipeline(
        jsonPath,
        experimentName = experimentName,
        sampleFiles = sampleFiles)

suppressWarnings(execute(
    pipL2,
    rmCache = TRUE,
    path = outputDir))

# run shiny app

if (interactive())
    ScaleTransformApp(dir = outputDir)
```

Index

∗ **internal**
CytoPipelineGUI, 3

CytoPipeline, *3*
CytoPipelineCheckApp, 2, *3*
CytoPipelineGUI, 3
CytoPipelineGUI-package
(CytoPipelineGUI), 3

plotDiffFlowFrame, 4
plotScaleTransformedChannel, 7
plotSelectedFlowFrame, 9
plotSelectedWorkflow, 11

ScaleTransformApp, *3*, 12