

Package ‘MungeSumstats’

February 2, 2023

Type Package

Title Standardise summary statistics from GWAS

Version 1.7.16

Description The *MungeSumstats* package is designed to facilitate the standardisation of GWAS summary statistics. It reformats inputted summary statistics to include SNP, CHR, BP and can look up these values if any are missing. It also performs dozens of QC and filtering steps to ensure high data quality and minimise inter-study differences.

URL <https://github.com/neurogenomics/MungeSumstats>

BugReports <https://github.com/neurogenomics/MungeSumstats/issues>

License Artistic-2.0

Depends R(>= 4.1)

Imports magrittr, data.table, utils, R.utils, dplyr, stats,
GenomicRanges, IRanges, GenomeInfoDb, BSgenome, Biostrings,
stringr, VariantAnnotation, googleAuthR, httr, jsonlite,
methods, parallel, rtracklayer (>= 1.59.1), RCurl

biocViews SNP, WholeGenome, Genetics, ComparativeGenomics,
GenomeWideAssociation, GenomicVariation, Preprocessing

RoxygenNote 7.2.3

Encoding UTF-8

Roxygen list(markdown = TRUE)

Suggests SNPlocs.Hsapiens.dbSNP144.GRCh37,
SNPlocs.Hsapiens.dbSNP144.GRCh38,
SNPlocs.Hsapiens.dbSNP155.GRCh37,
SNPlocs.Hsapiens.dbSNP155.GRCh38,
BSgenome.Hsapiens.1000genomes.hs37d5,
BSgenome.Hsapiens.NCBI.GRCh38, BiocGenerics, S4Vectors,
rmarkdown, markdown, knitr, testthat (>= 3.0.0), UpSetR,
BiocStyle, covr, Rsamtools, MatrixGenerics, badger,
BiocParallel, GenomicFiles

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/MungeSumstats>

git_branch master

git_last_commit cd43ad3

git_last_commit_date 2023-01-21

Date/Publication 2023-02-02

Author Alan Murphy [aut, cre] (<<https://orcid.org/0000-0002-2487-8753>>),
 Brian Schilder [aut, ctb] (<<https://orcid.org/0000-0001-5949-2191>>),
 Nathan Skene [aut] (<<https://orcid.org/0000-0002-6807-3180>>)

Maintainer Alan Murphy <alanmurph94@hotmail.com>

R topics documented:

api_query	5
axel	6
check_access_token	7
check_allele_flip	7
check_allele_merge	9
check_bi_allelic	10
check_chr	11
check_col_order	12
check_drop_indels	12
check_dup_bp	13
check_dup_col	14
check_dup_row	15
check_dup_snp	16
check_effect_columns_nonzero	17
check_empty_cols	18
check_four_step_col	18
check_frq	19
check_frq_maf	20
check_info_score	20
check_ldsc_format	21
check_miss_data	22
check_multi_gwas	23
check_multi_rs_snp	24
check_no_allele	25
check_no_chr_bp	26
check_no_rs_snp	27
check_no_snp	29
check_numeric	30
check_n_int	31
check_n_num	31
check_on_ref_genome	32
check_pos_se	33

check_range_p_val	35
check_row_snp	36
check_save_path	37
check_signed_col	38
check_small_p_val	39
check_strand_ambiguous	40
check_tabular	41
check_two_step_col	41
check_vcf	42
check_vital_col	42
check_zscore	43
column_dictionary	44
compute_nsize	45
compute_sample_size	46
compute_sample_size_n	47
compute_sample_size_neff	48
convert_sumstats	49
DF_to_dt	50
downloader	50
download_vcf	51
drop_duplicate_cols	53
drop_duplicate_rows	53
find_sumstats	54
formatted_example	55
format_sumstats	56
get_access_token	62
get_chain_file	62
get_genome_build	63
get_genome_builds	64
get_query_content	65
get_unique_name_log_file	66
get_vcf_sample_ids	66
granges_to_dt	67
gwasinfo	67
hg19ToHg38	68
hg38ToHg19	68
ieua-298	69
import_sumstats	69
index_tabular	74
index_vcf	76
is_tabix	77
legacy_ids	77
liftover	78
list_sumstats	79
load_ref_genome_data	80
load_snp_loc_data	81
logs_example	81
make_allele_upper	82

message	82
message_parallel	83
parse_dropped_chrom	83
parse_dropped_duplicates	84
parse_dropped_INFO	84
parse_dropped_nonA1A2	85
parse_dropped_nonBiallelic	85
parse_dropped_nonRef	86
parse_flipped	86
parse_genome_build	87
parse_idStandard	87
parse_logs	88
parse_pval_large	88
parse_pval_neg	89
parse_pval_small	89
parse_report	90
parse_snps_freq_05	90
parse_snps_not_formatted	91
parse_time	91
preview_sumstats	92
raw_ALSvcf	92
raw_eduAttainOkbay	93
read_header	93
read_sumstats	94
read_vcf	95
read_vcf_genome	97
read_vcf_info	98
read_vcf_markername	98
read_vcf_parallel	99
read_vcf_pval	100
register_cores	101
remove_empty_cols	101
report_summary	102
select_api	102
select_vcf_fields	103
sort_coords	104
sort_coords_datatable	104
sort_coord_genomicranges	105
standardise_header	105
sumstatsColHeaders	106
supported_suffixes	107
to_granges	108
to_vranges	108
unlist_dt	109
validate_parameters	109
vcf2df	113
write_sumstats	115

`api_query`*Wrapper for sending queries and payloads to API*

Description

There are a number of different GET and POST endpoints in the GWAS database API. This is a generic way to access them

Usage

```
api_query(  
  path,  
  query = NULL,  
  access_token = check_access_token(),  
  method = "GET",  
  silent = TRUE,  
  encode = "json",  
  timeout = 300  
)
```

Arguments

<code>path</code>	Either a full query path (e.g. for get) or an endpoint (e.g. for post) queries
<code>query</code>	If post query, provide a list of arguments as the payload. NULL by default
<code>access_token</code>	Google OAuth2 access token. Used to authenticate level of access to data. By default, checks if already authenticated through <code>get_access_token</code> and if not then does not perform authentication.
<code>method</code>	GET (default) or POST, DELETE etc
<code>silent</code>	TRUE/FALSE to be passed to htrr call. TRUE by default
<code>encode</code>	Default = json, see <code>htrr::POST</code> for options
<code>timeout</code>	Default = 300, avoid increasing this, preferentially simplify the query first.

Value

htrr response object

`axel`*axel downloader*

Description

R wrapper for axel, which enables multi-threaded download of a single large file.

Usage

```
axel(  
  input_url,  
  output_path,  
  background = FALSE,  
  nThread = 1,  
  force_overwrite = FALSE,  
  quiet = TRUE,  
  alternate = TRUE,  
  check_certificates = FALSE  
)
```

Arguments

<code>input_url</code>	<code>input_url</code> .
<code>output_path</code>	<code>output_path</code> .
<code>background</code>	Run in background
<code>nThread</code>	Number of threads to parallelize over.
<code>force_overwrite</code>	Overwrite existing file.
<code>quiet</code>	Run quietly.
<code>alternate</code>	<code>alternate</code> ,
<code>check_certificates</code>	<code>check_certificates</code>

Value

Path where the file has been downloaded

See Also

<https://github.com/axel-download-accelerator/axel/>

Other downloaders: [downloader\(\)](#)

check_access_token	<i>Check if authentication has been made</i>
--------------------	--

Description

If a call to get_access_token() has been made then it will have generated mrbase.oauth. Pass the token if it is present, if not, return NULL and do not authenticate.

Usage

```
check_access_token()
```

Value

NULL or access_token depending on current authentication state

check_allele_flip	<i>Ensure A1 & A2 are correctly named, if GWAS SNP constructed as Alternative/Reference or Risk/Nonrisk alleles these SNPs will need to be converted to Reference/Alternative or Nonrisk/Risk. Here non-risk is defined as what's on the reference genome (this may not always be the case).</i>
-------------------	--

Description

Ensure A1 & A2 are correctly named, if GWAS SNP constructed as Alternative/Reference or Risk/Nonrisk alleles these SNPs will need to be converted to Reference/Alternative or Nonrisk/Risk. Here non-risk is defined as what's on the reference genome (this may not always be the case).

Usage

```
check_allele_flip(
  sumstats_dt,
  path,
  ref_genome,
  rsids,
  allele_flip_check,
  allele_flip_drop,
  allele_flip_z,
  allele_flip_frq,
  bi_allelic_filter,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
```

```

nThread,
log_files,
standardise_headers = FALSE,
mapping_file,
dbSNP
)

```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
allele_flip_check	Binary Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.
allele_flip_drop	Binary Should the SNPs for which neither their A1 or A2 base pair values match a reference genome be dropped. Default is TRUE.
allele_flip_z	Binary should the Z-score be flipped along with effect and FRQ columns like Beta? It is assumed to be calculated off the effect size not the P-value and so will be flipped i.e. default TRUE.
allele_flip_frq	Binary should the frequency (FRQ) column be flipped along with effect and z-score columns like Beta? Default TRUE.
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
standardise_headers	Run standardise_sumstats_column_headers_crossplatform first.

mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

A list containing two data tables:

- sumstats_dt: the modified summary statistics data.table object.
- rsids: snpsById, filtered to SNPs of interest if loaded already. Or else NULL.
- log_files: log file list

check_allele_merge	<i>Ensure that A1:A2 or A1/A2 or A1>A2 or A2>A1 aren't merged into 1 column</i>
--------------------	---

Description

Ensure that A1:A2 or A1/A2 or A1>A2 or A2>A1 aren't merged into 1 column

Usage

```
check_allele_merge(sumstats_dt, path)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted

Value

list containing sumstats_dt, the modified summary statistics data table object.

check_bi_allelic	<i>Remove non-biallelic SNPs</i>
------------------	----------------------------------

Description

Remove non-biallelic SNPs

Usage

```
check_bi_allelic(
  sumstats_dt,
  path,
  ref_genome,
  bi_allelic_filter,
  rsids,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  dbSNP
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

A list containing two data tables:

- `sumstats_dt`: the modified summary statistics data table object
- `rsids`: `snpsById`, filtered to SNPs of interest if loaded already. Or else `NULL`.
- `log_files`: log file list

check_chr

Ensure all SNPs on specified chromosomes are removed

Description

Ensure all SNPs on specified chromosomes are removed

Usage

```
check_chr(
  sumstats_dt,
  path,
  rmv_chr,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  make_uppercase = TRUE,
  rmv_chrPrefix = TRUE
)
```

Arguments

<code>path</code>	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to <code>MungeSumstats</code> using the <code>path</code> parameter.
<code>rmv_chr</code>	vector or character The chromosomes on which the SNPs should be removed. Use <code>NULL</code> if no filtering necessary. Default is X, Y and mitochondrial.
<code>log_folder_ind</code>	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting <code>sumstats</code> file. The only exception to this rule is if output is <code>vcf</code> , then log file saved as <code>.tsv.gz</code> . Default is <code>FALSE</code> .
<code>tabix_index</code>	Index the formatted summary statistics with <code>tabix</code> for fast querying.
<code>nThread</code>	Number of threads to use for parallel processes.
<code>log_files</code>	list of log file locations
<code>rmv_chrPrefix</code>	Remove "chr" or "CHR" from chromosome names. Default is <code>TRUE</code> .

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_col_order	<i>Ensure that the first three columns are SNP, CHR, BP in that order and then A1, A2 if present</i>
-----------------	--

Description

Ensure that the first three columns are SNP, CHR, BP in that order and then A1, A2 if present

Usage

```
check_col_order(sumstats_dt, path)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted

Value

list containing sumstats_dt, the modified summary statistics data table object

check_drop_indels	<i>Drop Indels from summary statistics</i>
-------------------	--

Description

Drop Indels from summary statistics

Usage

```
check_drop_indels(
  sumstats_dt,
  drop_indels,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
drop_indels	Binary, should any indels found in the sumstats be dropped? These can not be checked against a reference dataset and will have the same RS ID and position as SNPs which can affect downstream analysis. Default is False.
path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.

Value

list containing sumstats_dt, the modified summary statistics data table object

Source

```
sumstats_dt <- MungeSumstats::formatted_example()
sumstats <- check_drop_indels(sumstats_dt
= sumstats_dt, drop_indels = TRUE)
```

check_dup_bp

Ensure all rows have unique positions, drop those that don't

Description

Ensure all rows have unique positions, drop those that don't

Usage

```
check_dup_bp(
  sumstats_dt,
  bi_allelic_filter,
  check_dups,
  indels,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
check_dups	whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with <code>tabix</code> for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and log files list

check_dup_col	<i>Ensure that no columns are duplicated</i>
---------------	--

Description

Ensure that no columns are duplicated

Usage

```
check_dup_col(sumstats_dt, path)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted

Value

list containing sumstats_dt, the modified summary statistics data table object

check_dup_row	<i>Ensure all rows are unique based on SNP,CHR,BP,A1,A2, drop those that aren't</i>
---------------	---

Description

Ensure all rows are unique based on SNP,CHR,BP,A1,A2, drop those that aren't

Usage

```
check_dup_row(
  sumstats_dt,
  check_dups,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

check_dups	whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.
path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and log files list

check_dup_snp	<i>Ensure all rows have unique SNP IDs, drop those that don't</i>
---------------	---

Description

Ensure all rows have unique SNP IDs, drop those that don't

Usage

```
check_dup_snp(
  sumstats_dt,
  indels,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  bi_allelic_filter,
  check_dups
)
```

Arguments

indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
check_dups	whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.

Value

list containing sumstats_dt, the modified summary statistics data table object and log files list

 check_effect_columns_nonzero

Ensure that the standard error (se) is positive for all SNPs

Description

Ensure that the standard error (se) is positive for all SNPs

Usage

```
check_effect_columns_nonzero(
  sumstats_dt,
  path,
  effect_columns_nonzero,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

- | | |
|------------------------|---|
| path | Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter. |
| effect_columns_nonzero | Binary should the effect columns in the data BETA,OR (odds ratio),LOG_ODDS,SIGNED_SUMSTAT be checked to ensure no SNP=0. Those that do are removed(if present in sumstats file). Default FALSE. |
| log_folder_ind | Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE. |
| tabix_index | Index the formatted summary statistics with tabix for fast querying. |
| nThread | Number of threads to use for parallel processes. |
| log_files | list of log file locations |

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_empty_cols *Check for empty columns*

Description

Empty columns contain only ".", NA, or 0

Usage

```
check_empty_cols(sumstats_dt, sampled_rows = NULL, verbose = TRUE)
```

Arguments

sampled_rows First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.

verbose Print messages.

Value

empty_cols

check_four_step_col *Ensure that CHR:BP:A2:A1 aren't merged into 1 column*

Description

Ensure that CHR:BP:A2:A1 aren't merged into 1 column

Usage

```
check_four_step_col(sumstats_dt, path)
```

Arguments

sumstats_dt data table obj of the summary statistics file for the GWAS

path Filepath for the summary statistics file to be formatted

Value

list containing sumstats_dt, the modified summary statistics data table object

check_frq	<i>Ensure all SNPs have frq score above threshold</i>
-----------	---

Description

Ensure all SNPs have frq score above threshold

Usage

```
check_frq(
  sumstats_dt,
  path,
  FRQ_filter,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
FRQ_filter	numeric The minimum value permissible of the frequency(FRQ) of the SNP (i.e. Allele Frequency (AF)) (if present in sumstats file). By default no filtering is done, i.e. value of 0.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_frq_maf	<i>Check that FRQ column refers to minor/effect allele frequency not major</i>
---------------	--

Description

Check that FRQ column refers to minor/effect allele frequency not major

Usage

```
check_frq_maf(sumstats_dt, frq_is_maf)
```

Arguments

frq_is_maf	Conventionally the FRQ column is intended to show the minor/effect allele frequency (MAF) but sometimes the major allele frequency can be inferred as the FRQ column. This logical variable indicates that the FRQ column should be renamed to MAJOR_ALLELE_FRQ if the frequency values appear to relate to the major allele i.e. >0.5. By default this mapping won't occur i.e. is TRUE.
------------	---

Value

sumstats_dt, the modified summary statistics data table object

check_info_score	<i>Ensure all SNPs have info score above threshold</i>
------------------	--

Description

Ensure all SNPs have info score above threshold

Usage

```
check_info_score(  
  sumstats_dt,  
  INFO_filter,  
  log_folder_ind,  
  check_save_out,  
  tabix_index,  
  nThread,  
  log_files  
)
```

Arguments

INFO_filter	numeric	The minimum value permissible of the imputation information score (if present in sumstats file). Default 0.9.
log_folder_ind	Binary	Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index		Index the formatted summary statistics with tabix for fast querying.
nThread		Number of threads to use for parallel processes.
log_files		list of log file locations.

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_ldsc_format *Ensures that parameters are compatible with LDSC format*

Description

Format summary statistics for direct input to Linkage Disequilibrium Score (LDSC) regression without the need to use their munge_sumstats.py script first.

Usage

```
check_ldsc_format(
  sumstats_dt,
  save_format,
  convert_n_int,
  allele_flip_check,
  compute_z,
  compute_n
)
```

Arguments

sumstats_dt		data table obj of the summary statistics file for the GWAS.
save_format		Output format of sumstats. Options are NULL - standardised output format from MungeSumstats, LDSC - output format compatible with LDSC and openGWAS - output compatible with openGWAS VCFs. Default is NULL.
convert_n_int	Binary, if N (the number of samples) is not an integer, should this be rounded?	Default is TRUE.
allele_flip_check	Binary	Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.

compute_z	Whether to compute Z-score column. Default is FALSE. This can be computed from Beta and SE with (Beta/SE) or P ($Z:=\text{sign}(\text{BETA})\sqrt{\text{stats::qchisq}(P,1,\text{lower}=\text{FALSE})}$). Note that imputing the Z-score from P for every SNP will not be perfectly correct and may result in a loss of power. This should only be done as a last resort. Use 'BETA' to impute by BETA/SE and 'P' to impute by SNP p-value.
compute_n	Whether to impute N. Default of 0 won't impute, any other integer will be imputed as the N (sample size) for every SNP in the dataset. Note that imputing the sample size for every SNP is not correct and should only be done as a last resort. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one of these for this field or a vector of multiple. Sum and an integer value creates an N column in the output whereas giant, metal or ldsc create an Neff or effective sample size. If multiples are passed, the formula used to derive it will be indicated.

Details

[LDSC documentation.](#)

Value

Formatted summary statistics

Source

[LDSC GitHub](#)

check_miss_data	<i>Remove SNPs with missing data</i>
-----------------	--------------------------------------

Description

Remove SNPs with missing data

Usage

```
check_miss_data(
  sumstats_dt,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and a log file list.

check_multi_gwas	<i>Ensure that only one model in GWAS sumstats or only one trait tested</i>
------------------	---

Description

Ensure that only one model in GWAS sumstats or only one trait tested

Usage

```
check_multi_gwas(sumstats_dt, path, analysis_trait, mapping_file)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted
analysis_trait	If multiple traits were studied, name of the trait for analysis from the GWAS. Default is NULL
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.

Value

list containing sumstats_dt, the modified summary statistics data table object

check_multi_rs_snp *Ensure that SNP ids don't have multiple rs ids on one line*

Description

Ensure that SNP ids don't have multiple rs ids on one line

Usage

```
check_multi_rs_snp(
  sumstats_dt,
  path,
  remove_multi_rs_snp,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
remove_multi_rs_snp	Binary Sometimes summary statistics can have multiple RSIDs on one row (i.e. related to one SNP), for example "rs5772025_rs397784053". This can cause an error so by default, the first RS ID will be kept and the rest removed e.g."rs5772025". If you want to just remove these SNPs entirely, set it to TRUE. Default is FALSE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list.

check_no_allele	<i>Ensure that A1 & A2 are present, if not can find it with SNP and other allele</i>
-----------------	--

Description

More care needs to be taken if one of A1/A2 is present, before imputing the other allele flipping needs to be checked

Usage

```
check_no_allele(
  sumstats_dt,
  path,
  ref_genome,
  rsids,
  imputation_ind,
  allele_flip_check,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  bi_allelic_filter,
  dbSNP
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.

allele_flip_check	Binary Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

A list containing two data tables:

- sumstats_dt: the modified summary statistics data table object
- rsids: snpsById, filtered to SNPs of interest if loaded already. Or else NULL.
- allele_flip_check: does the dataset require allele flip check
- log_files: log file list
- bi_allelic_filter: should multi-allelic SNPs be filtered out

check_no_chr_bp	<i>Ensure that CHR and BP are missing if SNP is present, can find them</i>
-----------------	--

Description

Ensure that CHR and BP are missing if SNP is present, can find them

Usage

```
check_no_chr_bp(
  sumstats_dt,
  path,
  ref_genome,
  rsids,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  dbSNP
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

A list containing two data tables:

- `sumstats_dt` : the modified summary statistics data table object
- `rsids` : `snpsById`, filtered to SNPs of interest if loaded already. Or else NULL
- `log_files` : log file list

check_no_rs_snp	<i>Ensure that SNP appears to be valid RSIDs (starts with rs)</i>
-----------------	---

Description

Ensure that SNP appears to be valid RSIDs (starts with rs)

Usage

```

check_no_rs_snp(
  sumstats_dt,
  path,
  ref_genome,
  snp_ids_are_rs_ids,
  indels,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  dbSNP
)

```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
snp_ids_are_rs_ids	Binary Should the supplied SNP ID's be assumed to be RSIDs. If not, imputation using the SNP ID for other columns like base-pair position or chromosome will not be possible. If set to FALSE, the SNP RS ID will be imputed from the reference genome if possible. Default is TRUE.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list.

check_no_snp

Ensure that SNP is present if not can find it with CHR and BP

Description

Ensure that SNP is present if not can find it with CHR and BP

Usage

```
check_no_snp(
  sumstats_dt,
  path,
  ref_genome,
  indels,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  dbSNP,
  verbose = TRUE
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.

log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
dbSNP	version of dbSNP to be used for imputation (144 or 155).
verbose	should messages be printed. Default it TRUE.

Value

list containing sumstats_dt, the modified summary statistics data table object and the log files list

check_numeric	<i>Check numeric columns</i>
---------------	------------------------------

Description

Checks for any columns that should be numeric, and ensures that they are indeed numeric.

Usage

```
check_numeric(sumstats_dt, cols = c("P", "SE", "FRQ", "MAF", "BETA"))
```

Arguments

sumstats_dt	Summary stats with column names already standardised by format_sumstats .
cols	Names of columns that should be numeric. If any of these columns are not actually present in sumstats_dt, they will be skipped.

Value

sumstats_dt

check_n_int	<i>Ensure that the N column is all integers</i>
-------------	---

Description

Ensure that the N column is all integers

Usage

```
check_n_int(sumstats_dt, path, convert_n_int, imputation_ind)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted
convert_n_int	Binary, if N (the number of samples) is not an integer, should this be rounded? Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). Note these columns will be in the formatted summary statistics returned. Default is FALSE.

Value

list containing sumstats_dt, the modified summary statistics data table object.

check_n_num	<i>Ensure all SNPs have N less than X std dev below mean</i>
-------------	--

Description

In case some SNPs were genotyped by a specialized genotyping array and have substantially more samples than others. These will be removed.

Usage

```
check_n_num(
  sumstats_dt,
  path,
  N_std,
  N_dropNA = FALSE,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
N_std	numeric The number of standard deviations above the mean a SNP's N is needed to be removed. Default is 5.
N_dropNA	Drop rows where N is missing. Default is TRUE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_on_ref_genome *Ensure all SNPs are on the reference genome*

Description

Ensure all SNPs are on the reference genome

Usage

```
check_on_ref_genome(
  sumstats_dt,
  path,
  ref_genome,
  on_ref_genome,
  indels = indels,
  rsids,
  imputation_ind,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  dbSNP
)
```


Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
on_ref_genome	Binary Should a check take place that all SNPs are on the reference genome by SNP ID. Default is TRUE.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
dbSNP	version of dbSNP to be used for imputation (144 or 155).

Value

A list containing two data tables:

- `sumstats_dt` : the modified summary statistics data table object
- `rsids` : `snpById`, filtered to SNPs of interest if loaded already. Or else NULL
- `log_files` : log file list

check_pos_se	<i>Ensure that the standard error (se) is positive for all SNPs Also impute se if missing</i>
--------------	---

Description

Ensure that the standard error (se) is positive for all SNPs Also impute se if missing

Usage

```

check_pos_se(
  sumstats_dt,
  path,
  pos_se,
  log_folder_ind,
  imputation_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files,
  impute_se
)

```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
pos_se	Binary Should the standard Error (SE) column be checked to ensure it is greater than 0? Those that are, are removed (if present in sumstats file). Default TRUE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations
impute_se	Binary, whether the standard error should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation so could have an effect on downstream analysis. Use with caution. The different methods MungeSumstats will try and impute se (in this order or priority) are: <ol style="list-style-type: none"> 1. BETA / Z 2. abs(BETA/ qnorm(P/2)) Default is FALSE.

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_range_p_val *Ensure that the p values are not >1 and if so set to 1*

Description

Ensure that the p values are not >1 and if so set to 1

Usage

```
check_range_p_val(sumstats_dt, convert_large_p, convert_neg_p, imputation_ind)
```

Arguments

sumstats_dt data table obj of the summary statistics file for the GWAS

convert_large_p Binary, should p-values >1 be converted to 1? P-values >1 should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.

convert_neg_p Binary, should p-values <0 be converted to 0? Negative p-values should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.

imputation_ind Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. **Note** these columns will be in the formatted summary statistics returned. Default is FALSE.

Value

list containing sumstats_dt, the modified summary statistics data table object

Source

```
sumstats_dt <- MungeSumstats::formatted_example() sumstats_dt$P[1:3] <- 5 sumstats_dt$P[6:10]
<- -5 sumstats <- check_range_p_val(sumstats_dt = sumstats_dt, convert_large_p = TRUE,
convert_neg_p = TRUE, imputation_ind = TRUE)
```

check_row_snp	<i>Ensure all rows have SNPs beginning with rs or SNP, drop those that don't</i>
---------------	--

Description

Ensure all rows have SNPs beginning with rs or SNP, drop those that don't

Usage

```
check_row_snp(
  sumstats_dt,
  path,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and log file list

check_save_path	<i>Check if save path and log folder is appropriate</i>
-----------------	---

Description

Check if save path and log folder is appropriate

Usage

```
check_save_path(
  save_path,
  log_folder,
  log_folder_ind,
  tabix_index,
  write_vcf = FALSE,
  verbose = TRUE
)
```

Arguments

save_path	File path to save formatted data. Defaults to <code>tempfile(fileext=".tsv.gz")</code> .
log_folder	Filepath to the directory for the log files and the log of MungeSumstats messages to be stored. Default is a temporary directory. Note the name of the log files (log messages and log outputs) are now the same as the name of the file specified in the save path parameter with the extension <code>'_log_msg.txt'</code> and <code>'_log_output.txt'</code> respectively.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as <code>.tsv.gz</code> . Default is FALSE.
tabix_index	Index the formatted summary statistics with <code>tabix</code> for fast querying.
write_vcf	Whether to write as VCF (TRUE) or tabular file (FALSE).
verbose	Print messages.

Value

Corrected save_path, the file type, the separator, corrected log_folder, the log file extension.

check_signed_col	<i>Ensure that there is at least one signed column in summary statistics file Impute beta if user requests</i>
------------------	--

Description

Ensure that there is at least one signed column in summary statistics file Impute beta if user requests

Usage

```
check_signed_col(
  sumstats_dt,
  impute_beta,
  log_folder_ind,
  rsids,
  imputation_ind,
  check_save_out,
  tabix_index,
  log_files,
  nThread
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
impute_beta	Binary, whether BETA should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation (for Z & SE approach) so could have an effect on downstream analysis. Use with caution. The different methods MungeSumstats will try and impute beta (in this order or priority) are: <ol style="list-style-type: none"> 1. log(OR) 2. Z x SE Default value is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
log_files	list of log file locations
nThread	Number of threads to use for parallel processes.

Value

null

check_small_p_val	<i>Ensure that the non-negative p-values are not 5e-324 or lower, if so set to 0</i>
-------------------	--

Description

Ensure that the non-negative p-values are not 5e-324 or lower, if so set to 0

Usage

```
check_small_p_val(sumstats_dt, convert_small_p, imputation_ind)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
convert_small_p	Binary, should non-negative p-values $\leq 5e-324$ be converted to 0? Small p-values pass the R limit and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.

Value

list containing sumstats_dt, the modified summary statistics data table object

Source

```
sumstats_dt <- MungeSumstats::formatted_example() sumstats_dt$P[1:3] <- 5e-324 sumstats_dt$P[6:10]
<- "5e-324" sumstats <- check_small_p_val(sumstats_dt = sumstats_dt, convert_small_p
= TRUE, imputation_ind = TRUE)
```

 check_strand_ambiguous

Remove SNPs with strand-ambiguous alleles

Description

Remove SNPs with strand-ambiguous alleles

Usage

```
check_strand_ambiguous(
  sumstats_dt,
  path,
  ref_genome,
  strand_ambig_filter,
  log_folder_ind,
  check_save_out,
  tabix_index,
  nThread,
  log_files
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
strand_ambig_filter	Binary Should SNPs with strand-ambiguous alleles be removed. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
nThread	Number of threads to use for parallel processes.
log_files	list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

check_tabular	<i>Ensure valid tabular format</i>
---------------	------------------------------------

Description

Ensure valid tabular format

Usage

```
check_tabular(header)
```

Arguments

header	The summary statistics file for the GWAS
--------	--

Value

Whether the file is tabular

check_two_step_col	<i>Ensure that CHR:BP aren't merged into 1 column</i>
--------------------	---

Description

Ensure that CHR:BP aren't merged into 1 column

Usage

```
check_two_step_col(sumstats_dt, path)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
path	Filepath for the summary statistics file to be formatted

Value

list containing sumstats_dt, the modified summary statistics data table object

check_vcf	<i>Check if the inputted file is in VCF format</i>
-----------	--

Description

Check if the inputted file is in VCF format

Usage

```
check_vcf(header)
```

Arguments

header	Header of the GWAS summary statistics file.
--------	---

Value

Whether the file is vcf or not

check_vital_col	<i>Ensure that all necessary columns are in the summary statistics file</i>
-----------------	---

Description

Ensure that all necessary columns are in the summary statistics file

Usage

```
check_vital_col(sumstats_dt)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS
-------------	--

Value

null

check_zscore	<i>Check for Z-score column</i>
--------------	---------------------------------

Description

The following ensures that a Z-score column is present. The Z-score formula we used here is a R implementation of the formula used in [LDSC's munge_sumstats.py](#):

Usage

```
check_zscore(
  sumstats_dt,
  imputation_ind,
  compute_z = "BETA",
  force_new_z = FALSE,
  standardise_headers = FALSE,
  mapping_file
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). Note these columns will be in the formatted summary statistics returned. Default is FALSE.
compute_z	Whether to compute Z-score column. Default is FALSE. This can be computed from Beta and SE with (Beta/SE) or P ($Z := \text{sign}(\text{BETA}) * \sqrt{\text{stats}::\text{qchisq}(P, 1, \text{lower} = \text{FALSE})}$). Note that imputing the Z-score from P for every SNP will not be perfectly correct and may result in a loss of power. This should only be done as a last resort. Use 'BETA' to impute by BETA/SE and 'P' to impute by SNP p-value.
force_new_z	When a "Z" column already exists, it will be used by default. To override and compute a new Z-score column from P set force_new_z=TRUE.
standardise_headers	Run standardise_sumstats_column_headers_crossplatform first.
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.

Details

```
np.sqrt(chi2.isf(P, 1))
```

The R implementation is adapted from the `GenomicSEM::munge` function, after optimizing for speed using `data.table`:

```
sumstats_dt[,Z:=sign(BETA)*sqrt(stats::qchisq(P, 1, lower=FALSE))]
```

NOTE: `compute_z` is set to `TRUE` by default to ensure standardisation of the "Z" column (which can be computed differently in different datasets).

Value

```
list("sumstats_dt"=sumstats_dt)
```

column_dictionary	<i>Map column names to positions.</i>
-------------------	---------------------------------------

Description

Useful in situations where you need to specify columns by index instead of name (e.g. awk queries).

Usage

```
column_dictionary(file_path)
```

Arguments

file_path	Path to full summary stats file (or any really file you want to make a column dictionary for).
-----------	--

Value

Named list of column positions.

Source

Borrowed function from [echotabix](#).

```
eduAttainOkbayPth <- system.file("extdata", "eduAttainOkbay.txt", package = "MungeSumstats")
) tmp <- tempfile(fileext = ".tsv") file.copy(eduAttainOkbayPth, tmp) cdict <- MungeSumstats:::column_di
= tmp)
```

compute_nsize	<i>Check for N column if not present and user wants, impute N based on user's sample size. NOTE this will be the same value for each SNP which is not necessarily correct and may cause issues down the line. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one or multiple of these.</i>
---------------	---

Description

Check for N column if not present and user wants, impute N based on user's sample size. **NOTE** this will be the same value for each SNP which is not necessarily correct and may cause issues down the line. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one or multiple of these.

Usage

```
compute_nsize(
  sumstats_dt,
  imputation_ind = FALSE,
  compute_n = c("ldsc", "giant", "metal", "sum"),
  standardise_headers = FALSE,
  force_new = FALSE,
  return_list = TRUE
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). Note these columns will be in the formatted summary statistics returned. Default is FALSE.
compute_n	How to compute per-SNP sample size (new column "N"). <ul style="list-style-type: none"> • 0: N will not be computed. • >0: If any number >0 is provided, that value will be set as N for every row. Note: Computing N this way is incorrect and should be avoided if at all possible. • "sum": N will be computed as: cases (N_CAS) + controls (N_CON), so long as both columns are present. • "ldsc": N will be computed as effective sample size: $N_{eff} = (N_{CAS} + N_{CON}) * (N_{CAS} / (N_{CAS} + N_{CON})) / \text{mean}(N_{CAS} / (N_{CAS} + N_{CON}))$ • "giant": N will be computed as effective sample size: $N_{eff} = 2 / (1/N_{CAS} + 1/N_{CON})$. • "metal": N will be computed as effective sample size: $N_{eff} = 4 / (1/N_{CAS} + 1/N_{CON})$.

standardise_headers Standardise headers first.

force_new If "Neff" (or "N") already exists in sumstats_dt, replace it with the recomputed version.

return_list Return the sumstats_dt within a named list (default: TRUE).

Value

list("sumstats_dt"=sumstats_dt)

Examples

```
sumstats_dt <- MungeSumstats::formatted_example()
sumstats_dt2 <- MungeSumstats::compute_nsize(sumstats_dt=sumstats_dt,
                                             compute_n=10000)
```

compute_sample_size *Compute (effective) sample size*

Description

Computes sample sum (as new column "N") or effective sample size (ESS) (as new column "Neff"). Computing ESS is important as it takes into account the proportion of cases to controls (i.e. class imbalance) so as not to overestimate your statistical power.

Usage

```
compute_sample_size(
  sumstats_dt,
  method = c("ldsc", "giant", "metal", "sum"),
  force_new = FALSE,
  append_method_name = FALSE
)
```

Arguments

sumstats_dt Summary statistics data.table.

method Method for computing (effective) sample size.

- "ldsc" :

$$Neff = (N_{CAS} + N_{CON}) * (N_{CAS} / (N_{CAS} + N_{CON})) / \text{mean}((N_{CAS} / (N_{CAS} + N_{CON}))[(N_{CAS} + N_{CON}) == \max(N_{CAS} + N_{CON})])$$
[bulik/ldsc GitHub Issue](#) [bulik/ldsc GitHub code](#)
- "giant" :

$$Neff = 2 / (1/N_{CAS} + 1/N_{CON})$$
[Winkler et al. 2014, Nature](#)

- "metal" :

$$N_{eff} = 4 / (1/N_{CAS} + 1/N_{CON})$$
[Willer et al. 2010, Bioinformatics](#)
 - "sum" :

$$N = N_{CAS} + N_{CON}$$
 Simple summation of cases and controls that does not account for class imbalance.
 - "<integer>" :

$$N = \text{<integer>}$$
 If method is a positive integer, it will be used as N for every row.
- force_new If "Neff" (or "N") already exists in sumstats_dt, replace it with the recomputed version.
- append_method_name should Neff column have an indicator to explain the method that makes it., Default is FALSE unless multiple methods are passed

Details

There are many different formulas for calculating ESS, but LDSC is probably the best method available here, as it doesn't assume that the proportion of controls:cases is 2:1 (as in GIANT) or 4:1 (as in METAL).

Value

A data.table with a new column "Neff" or "N"

compute_sample_size_n *Add user supplied sample size*

Description

Add user supplied sample size

Usage

```
compute_sample_size_n(sumstats_dt, method, force_new = FALSE)
```

Arguments

- sumstats_dt Summary statistics data.table.
- method Method for computing (effective) sample size.
- "ldsc" :

$$N_{eff} = (N_{CAS} + N_{CON}) * (N_{CAS} / (N_{CAS} + N_{CON})) / \text{mean}((N_{CAS} / (N_{CAS} + N_{CON}))[(N_{CAS} + N_{CON}) == \text{max}(N_{CAS} + N_{CON})])$$
[bulik/ldsc GitHub Issue](#) [bulik/ldsc GitHub code](#)

- "giant" :
 $N_{eff} = 2/(1/N_{CAS} + 1/N_{CON})$
[Winkler et al. 2014, Nature](#)
- "metal" :
 $N_{eff} = 4/(1/N_{CAS} + 1/N_{CON})$
[Willer et al. 2010, Bioinformatics](#)
- "sum" :
 $N = N_{CAS} + N_{CON}$
 Simple summation of cases and controls that does not account for class imbalance.
- "<integer>" :
 $N = \text{integer}$
 If method is a positive integer, it will be used as N for every row.

force_new If "Neff" (or "N") already exists in sumstats_dt, replace it with the recomputed version.

Value

No return

compute_sample_size_neff
Compute Neff/N

Description

Compute Neff/N

Usage

```
compute_sample_size_neff(  
  sumstats_dt,  
  method,  
  force_new = FALSE,  
  append_method_name = FALSE  
)
```

Arguments

sumstats_dt Summary statistics data.table.

method Method for computing (effective) sample size.

- "ldsc" :
 $N_{eff} = (N_{CAS} + N_{CON}) * (N_{CAS} / (N_{CAS} + N_{CON})) / \text{mean}((N_{CAS} / (N_{CAS} + N_{CON}))[(N_{CAS} + N_{CON}) == \max(N_{CAS} + N_{CON})])$
[bulik/ldsc GitHub Issue](#) [bulik/ldsc GitHub code](#)

- "giant" :
 $N_{eff} = 2/(1/N_{CAS} + 1/N_{CON})$
Winkler et al. 2014, Nature
- "metal" :
 $N_{eff} = 4/(1/N_{CAS} + 1/N_{CON})$
Willer et al. 2010, Bioinformatics
- "sum" :
 $N = N_{CAS} + N_{CON}$
Simple summation of cases and controls that does not account for class imbalance.
- "<integer>" :
 $N = \text{integer}$
If method is a positive integer, it will be used as N for every row.

force_new If "Neff" (or "N") already exists in sumstats_dt, replace it with the recomputed version.

append_method_name should Neff column have an indicator to explain the method that makes it., Default is FALSE unless multiple methods are passed

Value

No return

convert_sumstats *Convert summary statistics to desired object type*

Description

Convert summary statistics to desired object type

Usage

```
convert_sumstats(
  sumstats_dt,
  return_format = c("data.table", "vranges", "granges")
)
```

Arguments

return_format Object type to convert to; "data.table", "GenomicRanges" or "VRanges"(default is "data.table").

Value

Summary statistics in the converted format

DF_to_dt	<i>DataFrame to data.table</i>
----------	--------------------------------

Description

Efficiently convert [DataFrame](#) to [data.table](#).

Usage

```
DF_to_dt(DF)
```

Arguments

DF [DataFrame](#) object.

Value

VCF data in [data.table](#) format.

Source

[Solution from Bioc forum](#)

downloader	<i>downloader wrapper</i>
------------	---------------------------

Description

R wrapper for [axel](#) (multi-threaded) and [download.file](#) (single-threaded) download functions.

Usage

```
downloader(  
  input_url,  
  output_path,  
  download_method = "axel",  
  background = FALSE,  
  force_overwrite = FALSE,  
  quiet = TRUE,  
  show_progress = TRUE,  
  continue = TRUE,  
  nThread = 1,  
  alternate = TRUE,  
  check_certificates = TRUE,  
  timeout = 10 * 60  
)
```

Arguments

input_url	input_url.
output_path	output_path.
download_method	"axel" (multi-threaded) or "download.file" (single-threaded) .
background	Run in background
force_overwrite	Overwrite existing file.
quiet	Run quietly.
show_progress	show_progress.
continue	continue.
nThread	Number of threads to parallelize over.
alternate	alternate,
check_certificates	check_certificates
timeout	How many seconds before giving up on download. Passed to download.file. Default: 10*60 (10min).

Value

Local path to downloaded file.

Source

Suggestion to avoid 'proc\$get_built_file() : Build process failed'

See Also

Other downloaders: [axel\(\)](#)

download_vcf

Download VCF file and its index file from Open GWAS

Description

Ideally, we would use [gwasvcf](#) instead but it hasn't been made available on CRAN or Bioconductor yet, so we can't include it as a dep.

Usage

```
download_vcf(
  vcf_url,
  vcf_dir = tempdir(),
  vcf_download = TRUE,
  download_method = "download.file",
  force_new = FALSE,
  quiet = FALSE,
  timeout = 10 * 60,
  nThread = 1
)
```

Arguments

vcf_url	Remote URL to VCF file.
vcf_dir	Where to download the original VCF from Open GWAS. <i>WARNING:</i> This is set to <code>tempdir()</code> by default. This means the raw (pre-formatted) VCFs be deleted upon ending the R session. Change this to keep the raw VCF file on disk (e.g. <code>vcf_dir="/raw_vcf"</code>).
vcf_download	Download the original VCF from Open GWAS.
download_method	"axel" (multi-threaded) or "download.file" (single-threaded) .
force_new	Overwrite a previously downloaded VCF with the same path name.
quiet	Run quietly.
timeout	How many seconds before giving up on download. Passed to <code>download.file</code> . Default: 10*60 (10min).
nThread	Number of threads to parallelize over.

Value

List containing the paths to the downloaded VCF and its index file.

Examples

```
#only run the examples if user has internet access:
if(try(is.character(getURL("www.google.com")))==TRUE){
  vcf_url <- "https://gwas.mrcieu.ac.uk/files/ieu-a-298/ieu-a-298.vcf.gz"
  out_paths <- download_vcf(vcf_url = vcf_url)
}
```

`drop_duplicate_cols` *Drop duplicate columns*

Description

Drop columns with identical names (if any exist) within a `data.table`.

Usage

```
drop_duplicate_cols(dt)
```

Arguments

`dt` `data.table`

Value

Null output

`drop_duplicate_rows` *Drop duplicate rows*

Description

Drop rows with duplicate values across all columns.

Usage

```
drop_duplicate_rows(dt, verbose = TRUE)
```

Arguments

`dt` `data.table`
`verbose` Print messages.

Value

Filtered `dt`.

 find_sumstats

Search Open GWAS for datasets matching criteria

Description

For each argument, searches for any datasets matching a case-insensitive substring search in the respective metadata column. Users can supply a single character string or a list/vector of character strings.

Usage

```
find_sumstats(
  ids = NULL,
  traits = NULL,
  years = NULL,
  consortia = NULL,
  authors = NULL,
  populations = NULL,
  categories = NULL,
  subcategories = NULL,
  builds = NULL,
  pmids = NULL,
  min_sample_size = NULL,
  min_ncase = NULL,
  min_ncontrol = NULL,
  min_nsnp = NULL,
  include_NAs = FALSE,
  access_token = check_access_token()
)
```

Arguments

ids	List of Open GWAS study IDs (e.g. c("prot-a-664", "ieu-b-4760")).
traits	List of traits (e.g. c("parkinson", "Alzheimer")).
years	List of years (e.g. seq(2015,2021) or c(2010, 2012, 2021)).
consortia	List of consortia (e.g. c("MRC-IEU", "Neale Lab")).
authors	List of authors (e.g. c("Elsworth", "Kunkle", "Neale")).
populations	List of populations (e.g. c("European", "Asian")).
categories	List of categories (e.g. c("Binary", "Continuous", "Disease", "Risk factor")).
subcategories	List of categories (e.g. c("neurological", "Immune", "cardio")).
builds	List of genome builds (e.g. c("hg19", "grch37")).
pmids	List of PubMed ID (exact matches only) (e.g. c(29875488, 30305740, 28240269)).
min_sample_size	Minimum total number of study participants (e.g. 5000).

min_ncase	Minimum number of case participants (e.g. 1000).
min_ncontrol	Minimum number of control participants (e.g. 1000).
min_nsnp	Minimum number of SNPs (e.g. 200000).
include_NAs	Include datasets with missing metadata for size criteria (i.e. min_sample_size, min_ncase, or min_ncontrol).
access_token	Google OAuth2 access token. Used to authenticate level of access to data

Details

By default, returns metadata for all studies currently in Open GWAS database.

Value

(Filtered) GWAS metadata table.

Examples

```
# Only run the examples if user has internet access:
if(try(is.character(getURL("www.google.com"))==TRUE)){
### By ID
metagwas <- find_sumstats(ids = c(
  "ieu-b-4760",
  "prot-a-1725",
  "prot-a-664"
))
### By ID and sample size
metagwas <- find_sumstats(
  ids = c("ieu-b-4760", "prot-a-1725", "prot-a-664"),
  min_sample_size = 5000
)
### By criteria
metagwas <- find_sumstats(
  traits = c("alzheimer", "parkinson"),
  years = seq(2015, 2021)
)
}
```

formatted_example *Formatted example*

Description

Returns an example of summary stats that have had their column names already standardised with [standardise_header](#).

Usage

```
formatted_example(
  path = system.file("extdata", "eduAttainOkbay.txt", package = "MungeSumstats"),
  formatted = TRUE,
  sorted = TRUE
)
```

Arguments

path	Path to raw example file. Default to built-in dataset.
formatted	Whether the column names should be formatted (default:TRUE).
sorted	Whether the rows should be sorted by genomic coordinates (default:TRUE).

Value

sumstats_dt

Examples

```
sumstats_dt <- MungeSumstats::formatted_example()
```

format_sumstats	<i>Check that summary statistics from GWAS are in a homogeneous format</i>
-----------------	--

Description

Check that summary statistics from GWAS are in a homogeneous format

Usage

```
format_sumstats(
  path,
  ref_genome = NULL,
  convert_ref_genome = NULL,
  chain_source = "ensembl",
  convert_small_p = TRUE,
  convert_large_p = TRUE,
  convert_neg_p = TRUE,
  compute_z = FALSE,
  force_new_z = FALSE,
  compute_n = 0L,
  convert_n_int = TRUE,
  impute_beta = FALSE,
  es_is_beta = TRUE,
  impute_se = FALSE,
  analysis_trait = NULL,
```



```

INFO_filter = 0.9,
FRQ_filter = 0,
pos_se = TRUE,
effect_columns_nonzero = FALSE,
N_std = 5,
N_dropNA = TRUE,
rmv_chr = c("X", "Y", "MT"),
rmv_chrPrefix = TRUE,
on_ref_genome = TRUE,
strand_ambig_filter = FALSE,
allele_flip_check = TRUE,
allele_flip_drop = TRUE,
allele_flip_z = TRUE,
allele_flip_frq = TRUE,
bi_allelic_filter = TRUE,
snp_ids_are_rs_ids = TRUE,
remove_multi_rs_snp = FALSE,
frq_is_maf = TRUE,
indels = TRUE,
drop_indels = FALSE,
dbSNP = 155,
check_dups = TRUE,
sort_coordinates = TRUE,
nThread = 1,
save_path = tempfile(fileext = ".tsv.gz"),
write_vcf = FALSE,
tabix_index = FALSE,
return_data = FALSE,
return_format = "data.table",
ldsc_format = FALSE,
save_format = NULL,
log_folder_ind = FALSE,
log_mungesumstats_msgs = FALSE,
log_folder = tempdir(),
imputation_ind = FALSE,
force_new = FALSE,
mapping_file = sumstatsColHeaders
)

```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
convert_ref_genome	name of the reference genome to convert to ("GRCh37" or "GRCh38"). This

	will only occur if the current genome build does not match. Default is not to convert the genome build (NULL).
chain_source	source of the chain file to use in liftover, if converting genome build ("ucsc" or "ensembl"). Note that the UCSC chain files require a license for commercial use. The Ensembl chain is used by default ("ensembl").
convert_small_p	Binary, should non-negative p-values $\leq 5e-324$ be converted to 0? Small p-values pass the R limit and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.
convert_large_p	Binary, should p-values >1 be converted to 1? P-values >1 should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.
convert_neg_p	Binary, should p-values <0 be converted to 0? Negative p-values should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.
compute_z	Whether to compute Z-score column. Default is FALSE. This can be computed from Beta and SE with (Beta/SE) or $P (Z:=\text{sign}(\text{BETA})*\sqrt{\text{stats::qchisq}(P,1,\text{lower}=\text{FALSE})})$. Note that imputing the Z-score from P for every SNP will not be perfectly correct and may result in a loss of power. This should only be done as a last resort. Use 'BETA' to impute by BETA/SE and 'P' to impute by SNP p-value.
force_new_z	When a "Z" column already exists, it will be used by default. To override and compute a new Z-score column from P set force_new_z=TRUE.
compute_n	Whether to impute N. Default of 0 won't impute, any other integer will be imputed as the N (sample size) for every SNP in the dataset. Note that imputing the sample size for every SNP is not correct and should only be done as a last resort. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one of these for this field or a vector of multiple. Sum and an integer value creates an N column in the output whereas giant, metal or ldsc create an Neff or effective sample size. If multiples are passed, the formula used to derive it will be indicated.
convert_n_int	Binary, if N (the number of samples) is not an integer, should this be rounded? Default is TRUE.
impute_beta	Binary, whether BETA should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation (for Z & SE approach) so could have an effect on downstream analysis. Use with caution. The different methods MungeSumstats will try and impute beta (in this order or priority) are: <ol style="list-style-type: none"> 1. $\log(\text{OR})$ 2. $Z \times \text{SE}$ Default value is FALSE.
es_is_beta	Binary, whether to map ES to BETA. We take BETA to be any BETA-like value (including Effect Size). If this is not the case for your sumstats, change this to FALSE. Default is TRUE.
impute_se	Binary, whether the standard error should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation so could have an effect on downstream analysis. Use with caution. The different methods MungeSumstats will try and impute se (in this order or priority) are:

	1. BETA / Z 2. abs(BETA/ qnorm(P/2)) Default is FALSE.
analysis_trait	If multiple traits were studied, name of the trait for analysis from the GWAS. Default is NULL.
INFO_filter	numeric The minimum value permissible of the imputation information score (if present in sumstats file). Default 0.9.
FRQ_filter	numeric The minimum value permissible of the frequency(FRQ) of the SNP (i.e. Allele Frequency (AF)) (if present in sumstats file). By default no filtering is done, i.e. value of 0.
pos_se	Binary Should the standard Error (SE) column be checked to ensure it is greater than 0? Those that are, are removed (if present in sumstats file). Default TRUE.
effect_columns_nonzero	Binary should the effect columns in the data BETA,OR (odds ratio),LOG_ODDS,SIGNED_SUMSTAT be checked to ensure no SNP=0. Those that do are removed(if present in sumstats file). Default FALSE.
N_std	numeric The number of standard deviations above the mean a SNP's N is needed to be removed. Default is 5.
N_dropNA	Drop rows where N is missing.Default is TRUE.
rmv_chr	vector or character The chromosomes on which the SNPs should be removed. Use NULL if no filtering necessary. Default is X, Y and mitochondrial.
rmv_chrPrefix	Remove "chr" or "CHR" from chromosome names. Default is TRUE.
on_ref_genome	Binary Should a check take place that all SNPs are on the reference genome by SNP ID. Default is TRUE.
strand_ambig_filter	Binary Should SNPs with strand-ambiguous alleles be removed. Default is FALSE.
allele_flip_check	Binary Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.
allele_flip_drop	Binary Should the SNPs for which neither their A1 or A2 base pair values match a reference genome be dropped. Default is TRUE.
allele_flip_z	Binary should the Z-score be flipped along with effect and FRQ columns like Beta? It is assumed to be calculated off the effect size not the P-value and so will be flipped i.e. default TRUE.
allele_flip_frq	Binary should the frequency (FRQ) column be flipped along with effect and z-score columns like Beta? Default TRUE.
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
snp_ids_are_rs_ids	Binary Should the supplied SNP ID's be assumed to be RSIDs. If not, imputation using the SNP ID for other columns like base-pair position or chromosome will not be possible. If set to FALSE, the SNP RS ID will be imputed from the reference genome if possible. Default is TRUE.

remove_multi_rs_snp	Binary Sometimes summary statistics can have multiple RSIDs on one row (i.e. related to one SNP), for example "rs5772025_rs397784053". This can cause an error so by default, the first RS ID will be kept and the rest removed e.g. "rs5772025". If you want to just remove these SNPs entirely, set it to TRUE. Default is FALSE.
frq_is_maf	Conventionally the FRQ column is intended to show the minor/effect allele frequency (MAF) but sometimes the major allele frequency can be inferred as the FRQ column. This logical variable indicates that the FRQ column should be renamed to MAJOR_ALLELE_FRQ if the frequency values appear to relate to the major allele i.e. >0.5. By default this mapping won't occur i.e. is TRUE.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
drop_indels	Binary, should any indels found in the sumstats be dropped? These can not be checked against a reference dataset and will have the same RS ID and position as SNPs which can affect downstream analysis. Default is False.
dbSNP	version of dbSNP to be used for imputation (144 or 155).
check_dups	whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.
sort_coordinates	Whether to sort by coordinates of resulting sumstats
nThread	Number of threads to use for parallel processes.
save_path	File path to save formatted data. Defaults to tempfile(fileext=".tsv.gz").
write_vcf	Whether to write as VCF (TRUE) or tabular file (FALSE).
tabix_index	Index the formatted summary statistics with tabix for fast querying.
return_data	Return data.table, GRanges or VRanges directly to user. Otherwise, return the path to the save data. Default is FALSE.
return_format	If return_data is TRUE. Object type to be returned ("data.table", "vranges", "granges").
ldsc_format	DEPRECATED, do not use. Use save_format="LDSC" instead.
save_format	Output format of sumstats. Options are NULL - standardised output format from MungeSumstats, LDSC - output format compatible with LDSC and openGWAS - output compatible with openGWAS VCFs. Default is NULL.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
log_mungesumstats_msgs	Binary Should a log be stored containing all messages and errors printed by MungeSumstats in a run. Default is FALSE
log_folder	Filepath to the directory for the log files and the log of MungeSumstats messages to be stored. Default is a temporary directory. Note the name of the log files (log messages and log outputs) are now the same as the name of the file specified in the save_path parameter with the extension '_log_msg.txt' and '_log_output.txt' respectively.

imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
force_new	If a formatted file of the same names as save_path exists, formatting will be skipped and this file will be imported instead (default). Set force_new=TRUE to override this.
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.

Value

The address for the modified sumstats file or the actual data dependent on user choice. Also, if log files wanted by the user, the return in both above instances are a list.

Examples

```
# Pass path to Educational Attainment Okbay sumstat file to a temp directory

eduAttainOkbayPth <- system.file("extdata", "eduAttainOkbay.txt",
  package = "MungeSumstats"
)

## Call uses reference genome as default with more than 2GB of memory,
## which is more than what 32-bit Windows can handle so remove certain checks
## Using dbSNP = 144 for speed as it's smaller but you should use 155 unless
## you know what you are doing and need 144

is_32bit_windows <-
  .Platform$OS.type == "windows" && .Platform$r_arch == "i386"
if (!is_32bit_windows) {
  reformatted <- format_sumstats(
    path = eduAttainOkbayPth,
    ref_genome = "GRCh37",
    dbSNP = 144
  )
} else {
  reformatted <- format_sumstats(
    path = eduAttainOkbayPth,
    ref_genome = "GRCh37",
    on_ref_genome = FALSE,
    strand_ambig_filter = FALSE,
    bi_allelic_filter = FALSE,
    allele_flip_check = FALSE,
```

```

        dbSNP=144
    )
}
# returned location has the updated summary statistics file

```

get_access_token	<i>Get access token for OAuth2 access to MR Base</i>
------------------	--

Description

Get access token for OAuth2 access to MR Base

Usage

```
get_access_token()
```

Value

access token string

get_chain_file	<i>Download chain file for liftover</i>
----------------	---

Description

Download chain file for liftover

Usage

```

get_chain_file(
  from = c("hg38", "hg19"),
  to = c("hg19", "hg38"),
  chain_source = c("ucsc", "ensembl"),
  save_dir = tempdir(),
  verbose = TRUE
)

```

Arguments

from	genome build converted from ("hg38", "hg19")
to	genome build converted to ("hg19", "hg38")
chain_source	chain file source used ("ucsc" as default, or "ensembl")
save_dir	where is the chain file saved? Default is a temp directory
verbose	extra messages printed? Default is TRUE

Value

loaded chain file for liftover

Source

[UCSC chain files](#)

[Ensembl chain files](#)

get_genome_build	<i>Infers the genome build of the summary statistics file (GRCh37 or GRCh38) from the data. Uses SNP (RSID) & CHR & BP to get genome build.</i>
------------------	---

Description

Infers the genome build of the summary statistics file (GRCh37 or GRCh38) from the data. Uses SNP (RSID) & CHR & BP to get genome build.

Usage

```
get_genome_build(
  sumstats,
  nThread = 1,
  sampled_snps = 10000,
  standardise_headers = TRUE,
  mapping_file = sumstatsColHeaders,
  dbSNP = 155,
  header_only = FALSE
)
```

Arguments

sumstats	data table/data frame obj of the summary statistics file for the GWAS ,or file path to summary statistics file.
nThread	Number of threads to use for parallel processes.
sampled_snps	Downsample the number of SNPs used when inferring genome build to save time.
standardise_headers	Run standardise_sumstats_column_headers_crossplatform.
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.

dbSNP	version of dbSNP to be used (144 or 155). Default is 155.
header_only	Instead of reading in the entire sumstats file, only read in the first N rows where N=sampled_snps. This should help speed up cases where you have to read in sumstats from disk each time.

Value

ref_genome the genome build of the data

get_genome_builds *Infer genome builds*

Description

Infers the genome build of summary statistics files (GRCh37 or GRCh38) from the data. Uses SNP (RSID) & CHR & BP to get genome build.

Usage

```
get_genome_builds(
  sumstats_list,
  header_only = TRUE,
  sampled_snps = 10000,
  names_from_paths = FALSE,
  dbSNP = 155,
  nThread = 1
)
```

Arguments

sumstats_list	A named list of paths to summary statistics, or a named list of data.table objects.
header_only	Instead of reading in the entire sumstats file, only read in the first N rows where N=sampled_snps. This should help speed up cases where you have to read in sumstats from disk each time.
sampled_snps	Downsample the number of SNPs used when inferring genome build to save time.
names_from_paths	Infer the name of each item in sumstats_list from its respective file path. Only works if sumstats_list is a list of paths.
dbSNP	version of dbSNP to be used (144 or 155). Default is 155.
nThread	Number of threads to use for parallel processes.

Details

Iterative version of get_genome_build.

Value

ref_genome the genome build of the data

Examples

```
# Pass path to Educational Attainment Okbay sumstat file to a temp directory

eduAttainOkbayPth <- system.file("extdata", "eduAttainOkbay.txt",
  package = "MungeSumstats"
)
sumstats_list <- list(ss1 = eduAttainOkbayPth, ss2 = eduAttainOkbayPth)

## Call uses reference genome as default with more than 2GB of memory,
## which is more than what 32-bit Windows can handle so remove certain checks
is_32bit_windows <-
  .Platform$OS.type == "windows" && .Platform$r_arch == "i386"
if (!is_32bit_windows) {

  #multiple sumstats can be passed at once to get all their genome builds:
  #ref_genomes <- get_genome_builds(sumstats_list = sumstats_list)
  #just passing first here for speed
  sumstats_list_quick <- list(ss1 = eduAttainOkbayPth)
  ref_genomes <- get_genome_builds(sumstats_list = sumstats_list_quick,
    dbSNP=144)
}
```

get_query_content *Parse out json response from httr object*

Description

Parse out json response from httr object

Usage

```
get_query_content(response)
```

Arguments

response Output from httr

Value

Parsed json output from query, often in form of data frame. If status code is not successful then return the actual response.

```
get_unique_name_log_file
```

Simple function to ensure the new entry name to a list doesn't have the same name as another entry

Description

Simple function to ensure the new entry name to a list doesn't have the same name as another entry

Usage

```
get_unique_name_log_file(name, log_files)
```

Arguments

name	proposed name for the entry
log_files	list of log file locations

Value

a unique name (character)

```
get_vcf_sample_ids
```

Get VCF sample ID(s)

Description

Get VCF sample ID(s)

Usage

```
get_vcf_sample_ids(path)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
------	--

Value

sample_id

granges_to_dt	<i>GenomicRanges to data.table</i>
---------------	------------------------------------

Description

Convert a [GRanges](#) into a [data.table](#).

Usage

```
granges_to_dt(gr)
```

Arguments

`gr` A [GRanges](#) object.

Value

A [data.table](#) object.

Source

Code adapted from [GenomicDistributions](#).

gwasinfo	<i>Get list of studies with available GWAS summary statistics through API</i>
----------	---

Description

Get list of studies with available GWAS summary statistics through API

Usage

```
gwasinfo(id = NULL, access_token = check_access_token())
```

Arguments

`id` List of MR-Base IDs to retrieve. If NULL (default) retrieves all available datasets

`access_token` Google OAuth2 access token. Used to authenticate level of access to data

Value

Dataframe of details for all available studies

hg19ToHg38

UCSC Chain file hg19 to hg38

Description

UCSC Chain file hg19 to hg38, .chain.gz file, downloaded from <https://hgdownload.cse.ucsc.edu/goldenpath/hg19/liftOver/> on 09/10/21

Format

gunzipped chain file

Details

UCSC Chain file hg19 to hg38, .chain.gz file, downloaded on 09/10/21 To be used as a back up if the download from UCSC fails.

hg19ToHg38.over.chain.gz

NA

Source

The chain file was downloaded from <https://hgdownload.cse.ucsc.edu/goldenpath/hg19/liftOver/>
utils::download.file('ftp://hgdownload.cse.ucsc.edu/goldenPath/hg19/liftOver/hg19ToHg38.over.chain.gz')

hg38ToHg19

UCSC Chain file hg38 to hg19

Description

UCSC Chain file hg38 to hg19, .chain.gz file, downloaded from <https://hgdownload.cse.ucsc.edu/goldenpath/hg19/liftOver/> on 09/10/21

Format

gunzipped chain file

Details

UCSC Chain file hg38 to hg19, .chain.gz file, downloaded on 09/10/21 To be used as a back up if the download from UCSC fails.

hg38ToHg19.over.chain.gz

NA

Source

The chain file was downloaded from [https://hgdownload.cse.ucsc.edu/goldenpath/hg38/liftOver/Utils::download.file\('ftp://hgdownload.cse.ucsc.edu/goldenPath/hg38/liftOver/hg38ToHg19.over.chain.](https://hgdownload.cse.ucsc.edu/goldenpath/hg38/liftOver/Utils::download.file('ftp://hgdownload.cse.ucsc.edu/goldenPath/hg38/liftOver/hg38ToHg19.over.chain.)

 ieu-a-298

Local ieu-a-298 file from IEU Open GWAS

Description

Local ieu-a-298 file from IEU Open GWAS, downloaded on 09/10/21.

Format

gunzipped tsv file

Details

Local ieu-a-298 file from IEU Open GWAS, downloaded on 09/10/21. This is done in case the download in the package vignette fails.

ieu-a-298.tsv.gz

NA

Source

The file was downloaded with: `MungeSumstats::import_sumstats(ids = "ieu-a-298", ref_genome = "GRCH37")`

 import_sumstats

Import full genome-wide GWAS summary statistics from Open GWAS

Description

Requires internet access to run.

Usage

```
import_sumstats(
  ids,
  vcf_dir = tempdir(),
  vcf_download = TRUE,
  save_dir = tempdir(),
  write_vcf = FALSE,
  download_method = "download.file",
  quiet = TRUE,
  force_new = FALSE,
  force_new_vcf = FALSE,
  nThread = 1,
  parallel_across_ids = FALSE,
  ...
)
```

Arguments

ids	List of Open GWAS study IDs (e.g. <code>c("prot-a-664", "ieu-b-4760")</code>).
vcf_dir	Where to download the original VCF from Open GWAS. <i>WARNING:</i> This is set to <code>tempdir()</code> by default. This means the raw (pre-formatted) VCFs be deleted upon ending the R session. Change this to keep the raw VCF file on disk (e.g. <code>vcf_dir="/raw_vcf"</code>).
vcf_download	Download the original VCF from Open GWAS.
save_dir	Directory to save formatted summary statistics in.
write_vcf	Whether to write as VCF (TRUE) or tabular file (FALSE).
download_method	"axel" (multi-threaded) or "download.file" (single-threaded) .
quiet	Run quietly.
force_new	If a formatted file of the same names as <code>save_path</code> exists, formatting will be skipped and this file will be imported instead (default). Set <code>force_new=TRUE</code> to override this.
force_new_vcf	Overwrite a previously downloaded VCF with the same path name.
nThread	Number of threads to use for parallel processes.
parallel_across_ids	If <code>parallel_across_ids=TRUE</code> and <code>nThread>1</code> , then each ID in <code>ids</code> will be processed in parallel.
...	Arguments passed on to format_sumstats
path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to <code>MungeSumstats</code> using the <code>path</code> parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.

`convert_ref_genome` name of the reference genome to convert to ("GRCh37" or "GRCh38"). This will only occur if the current genome build does not match. Default is not to convert the genome build (NULL).

`chain_source` source of the chain file to use in liftover, if converting genome build ("ucsc" or "ensembl"). Note that the UCSC chain files require a license for commercial use. The Ensembl chain is used by default ("ensembl").

`convert_small_p` Binary, should non-negative p-values $\leq 5e-324$ be converted to 0? Small p-values pass the R limit and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.

`convert_large_p` Binary, should p-values > 1 be converted to 1? P-values > 1 should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.

`convert_neg_p` Binary, should p-values < 0 be converted to 0? Negative p-values should not be possible and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.

`compute_z` Whether to compute Z-score column. Default is FALSE. This can be computed from Beta and SE with (Beta/SE) or $P (Z := \text{sign}(\text{BETA}) * \sqrt{\text{stats::qchisq}(P, 1, \text{lower} = \text{FALSE})})$. **Note** that imputing the Z-score from P for every SNP will not be perfectly correct and may result in a loss of power. This should only be done as a last resort. Use 'BETA' to impute by BETA/SE and 'P' to impute by SNP p-value.

`force_new_z` When a "Z" column already exists, it will be used by default. To override and compute a new Z-score column from P set `force_new_z=TRUE`.

`compute_n` Whether to impute N. Default of 0 won't impute, any other integer will be imputed as the N (sample size) for every SNP in the dataset. **Note** that imputing the sample size for every SNP is not correct and should only be done as a last resort. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one of these for this field or a vector of multiple. Sum and an integer value creates an N column in the output whereas giant, metal or ldsc create an Neff or effective sample size. If multiples are passed, the formula used to derive it will be indicated.

`convert_n_int` Binary, if N (the number of samples) is not an integer, should this be rounded? Default is TRUE.

`impute_beta` Binary, whether BETA should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation (for Z & SE approach) so could have an effect on downstream analysis. Use with caution. The different methods MungeSumstats will try and impute beta (in this order or priority) are:

1. log(OR)
 2. Z x SE
- Default value is FALSE.

`es_is_beta` Binary, whether to map ES to BETA. We take BETA to be any BETA-like value (including Effect Size). If this is not the case for your sumstats, change this to FALSE. Default is TRUE.

`impute_se` Binary, whether the standard error should be imputed using other effect data if it isn't present in the sumstats. Note that this imputation is an approximation so could have an effect on downstream analysis. Use with

caution. The different methods MungeSumstats will try and impute se (in this order or priority) are:

1. BETA / Z
2. $\text{abs}(\text{BETA} / \text{qnorm}(P/2))$ Default is FALSE.

analysis_trait If multiple traits were studied, name of the trait for analysis from the GWAS. Default is NULL.

INFO_filter numeric The minimum value permissible of the imputation information score (if present in sumstats file). Default 0.9.

FRQ_filter numeric The minimum value permissible of the frequency (FRQ) of the SNP (i.e. Allele Frequency (AF)) (if present in sumstats file). By default no filtering is done, i.e. value of 0.

pos_se Binary Should the standard Error (SE) column be checked to ensure it is greater than 0? Those that are, are removed (if present in sumstats file). Default TRUE.

effect_columns_nonzero Binary should the effect columns in the data BETA, OR (odds ratio), LOG_ODDS, SIGNED_SUMSTAT be checked to ensure no SNP=0. Those that do are removed (if present in sumstats file). Default FALSE.

N_std numeric The number of standard deviations above the mean a SNP's N is needed to be removed. Default is 5.

N_dropNA Drop rows where N is missing. Default is TRUE.

rmv_chr vector or character The chromosomes on which the SNPs should be removed. Use NULL if no filtering necessary. Default is X, Y and mitochondrial.

rmv_chrPrefix Remove "chr" or "CHR" from chromosome names. Default is TRUE.

on_ref_genome Binary Should a check take place that all SNPs are on the reference genome by SNP ID. Default is TRUE.

strand_ambig_filter Binary Should SNPs with strand-ambiguous alleles be removed. Default is FALSE.

allele_flip_check Binary Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.

allele_flip_drop Binary Should the SNPs for which neither their A1 or A2 base pair values match a reference genome be dropped. Default is TRUE.

allele_flip_z Binary should the Z-score be flipped along with effect and FRQ columns like Beta? It is assumed to be calculated off the effect size not the P-value and so will be flipped i.e. default TRUE.

allele_flip_frq Binary should the frequency (FRQ) column be flipped along with effect and z-score columns like Beta? Default TRUE.

bi_allelic_filter Binary Should non-biallelic SNPs be removed. Default is TRUE.

snp_ids_are_rs_ids Binary Should the supplied SNP ID's be assumed to be RSIDs. If not, imputation using the SNP ID for other columns like base-pair position or chromosome will not be possible. If set to FALSE, the SNP RS ID will be imputed from the reference genome if possible. Default is TRUE.

- `remove_multi_rs_snp` Binary Sometimes summary statistics can have multiple RSIDs on one row (i.e. related to one SNP), for example "rs5772025_rs397784053". This can cause an error so by default, the first RS ID will be kept and the rest removed e.g. "rs5772025". If you want to just remove these SNPs entirely, set it to TRUE. Default is FALSE.
- `frq_is_maf` Conventionally the FRQ column is intended to show the minor/effect allele frequency (MAF) but sometimes the major allele frequency can be inferred as the FRQ column. This logical variable indicates that the FRQ column should be renamed to MAJOR_ALLELE_FRQ if the frequency values appear to relate to the major allele i.e. >0.5. By default this mapping won't occur i.e. is TRUE.
- `indels` Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
- `drop_indels` Binary, should any indels found in the sumstats be dropped? These can not be checked against a reference dataset and will have the same RS ID and position as SNPs which can affect downstream analysis. Default is False.
- `dbSNP` version of dbSNP to be used for imputation (144 or 155).
- `check_dups` whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.
- `sort_coordinates` Whether to sort by coordinates of resulting sumstats
- `save_path` File path to save formatted data. Defaults to `tempfile(fileext=".tsv.gz")`.
- `tabix_index` Index the formatted summary statistics with `tabix` for fast querying.
- `return_data` Return data. table, GRanges or VRanges directly to user. Otherwise, return the path to the save data. Default is FALSE.
- `return_format` If `return_data` is TRUE. Object type to be returned ("data.table", "vranges", "granges").
- `ldsc_format` DEPRECATED, do not use. Use `save_format="LDSC"` instead.
- `save_format` Output format of sumstats. Options are NULL - standardised output format from MungeSumstats, LDSC - output format compatible with LDSC and openGWAS - output compatible with openGWAS VCFs. Default is NULL.
- `log_folder_ind` Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
- `log_mungesumstats_msgs` Binary Should a log be stored containing all messages and errors printed by MungeSumstats in a run. Default is FALSE
- `log_folder` Filepath to the directory for the log files and the log of MungeSumstats messages to be stored. Default is a temporary directory. Note the name of the log files (log messages and log outputs) are now the same as the name of the file specified in the save path parameter with the extension `'_log_msg.txt'` and `'_log_output.txt'` respectively.
- `imputation_ind` Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a

field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. **Note** these columns will be in the formatted summary statistics returned. Default is FALSE.

`mapping_file` MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See `data(sumstatsColHeaders)` for default mapping and necessary format.

Value

Either a named list of data objects or paths, depending on the arguments passed to `format_sumstats`.

Examples

```
#only run the examples if user has internet access:
if(try(is.character(getURL("www.google.com")))==TRUE){
### Search by criteria
metagwas <- find_sumstats(
  traits = c("parkinson", "alzheimer"),
  min_sample_size = 5000
)
### Only use a subset for testing purposes
ids <- (dplyr::arrange(metagwas, nsnp))$id

### Default usage
## You can supply \code{import_sumstats()}
## with a list of as many OpenGWAS IDs as you want,
## but we'll just give one to save time.

## Call uses reference genome as default with more than 2GB of memory,
## which is more than what 32-bit Windows can handle so remove certain checks
## commented out down to runtime
# datasets <- import_sumstats(ids = ids[1])
}
```

index_tabular

Tabix-index file: table

Description

Convert summary stats file to tabix format.

Usage

```
index_tabular(  
  path,  
  chrom_col = "CHR",  
  start_col = "BP",  
  end_col = start_col,  
  overwrite = TRUE,  
  remove_tmp = TRUE,  
  verbose = TRUE  
)
```

Arguments

path	Path to GWAS summary statistics file.
chrom_col	Name of the chromosome column in sumstats_dt (e.g. "CHR").
start_col	Name of the starting genomic position column in sumstats_dt (e.g. "POS", "start").
end_col	Name of the ending genomic position column in sumstats_dt (e.g. "POS", "end"). Can be the same as start_col when sumstats_dt only contains SNPs that span 1 base pair (bp) each.
overwrite	A logical(1) indicating whether dest should be over-written, if it already exists.
remove_tmp	Remove the temporary uncompressed version of the file (.tsv).
verbose	Print messages.

Value

Path to tabix-indexed tabular file

Source

Borrowed function from [echotabix](#).

See Also

Other tabix: [index_vcf\(\)](#)

Examples

```
sumstats_dt <- MungeSumstats::formatted_example()  
path <- tempfile(fileext = ".tsv")  
MungeSumstats::write_sumstats(sumstats_dt = sumstats_dt, save_path = path)  
indexed_file <- MungeSumstats::index_tabular(path = path)
```

`index_vcf`*Tabix-index file: VCF*

Description

Convert summary stats file to tabix format

Usage

```
index_vcf(path, verbose = TRUE)
```

Arguments

<code>path</code>	Path to VCF.
<code>verbose</code>	Print messages.

Value

Path to tabix-indexed tabular file

Source

Borrowed function from [echotabix](#).

See Also

Other tabix: [index_tabular\(\)](#)

Examples

```
eduAttainOkbayPth <- system.file("extdata", "eduAttainOkbay.txt",
                                package = "MungeSumstats")
sumstats_dt <- data.table::fread(eduAttainOkbayPth, nThread = 1)
sumstats_dt <-
MungeSumstats::standardise_sumstats_column_headers_crossplatform(
  sumstats_dt = sumstats_dt)$sumstats_dt
sumstats_dt <- MungeSumstats::sort_coords(sumstats_dt = sumstats_dt)
path <- tempfile(fileext = ".tsv")
MungeSumstats::write_sumstats(sumstats_dt = sumstats_dt, save_path = path)

indexed_file <- MungeSumstats::index_tabular(path = path)
```

is_tabix	<i>Is tabix</i>
----------	-----------------

Description

Is a file bgz-compressed and tabix-indexed.

Usage

```
is_tabix(path)
```

Arguments

path	Path to file.
------	---------------

Value

logical: whether the file is tabix-indexed or not.

logical

legacy_ids	<i>Convert current IDs to legacy IDs</i>
------------	--

Description

Convert current IDs to legacy IDs

Usage

```
legacy_ids(x)
```

Arguments

x	Vector of ids
---	---------------

Value

vector of back compatible ids

liftover	<i>Genome build liftover</i>
----------	------------------------------

Description

Transfer genomic coordinates from one genome build to another.

Usage

```
liftover(
  sumstats_dt,
  convert_ref_genome,
  ref_genome,
  chain_source = "ensembl",
  imputation_ind = TRUE,
  chrom_col = "CHR",
  start_col = "BP",
  end_col = start_col,
  as_granges = FALSE,
  style = "NCBI",
  verbose = TRUE
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
convert_ref_genome	name of the reference genome to convert to ("GRCh37" or "GRCh38"). This will only occur if the current genome build does not match. Default is not to convert the genome build (NULL).
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
chain_source	chain file source used ("ucsc" as default, or "ensembl")
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
chrom_col	Name of the chromosome column in sumstats_dt (e.g. "CHR").
start_col	Name of the starting genomic position column in sumstats_dt (e.g. "POS", "start").
end_col	Name of the ending genomic position column in sumstats_dt (e.g. "POS", "end"). Can be the same as start_col when sumstats_dt only contains SNPs that span 1 base pair (bp) each.

as_granges	Return results as GRanges instead of a data.table (default: FALSE).
style	Style to return GRanges object in (e.g. "NCBI" = 4; "UCSC" = "chr4"); (default: "NCBI").
verbose	Print messages.

Value

Lifted summary stats in `data.table` or [GRanges](#) format.

Source

[liftOver](#)
[UCSC chain files](#)
[Ensembl chain files](#)

Examples

```
sumstats_dt <- MungeSumstats::formatted_example()

sumstats_dt_hg38 <- liftover(sumstats_dt=sumstats_dt,
                             ref_genome = "hg19",
                             convert_ref_genome="hg38")
```

list_sumstats	<i>List munged summary statistics</i>
---------------	---------------------------------------

Description

Searches for and lists local GWAS summary statistics files munged by [format_sumstats](#) or [import_sumstats](#).

Usage

```
list_sumstats(
  save_dir = getwd(),
  pattern = "*.tsv.gz$",
  ids_from_file = TRUE,
  verbose = TRUE
)
```

Arguments

save_dir	Top-level directory to recursively search for summary statistics files within.
pattern	Regex pattern to search for files with.
ids_from_file	Try to extract dataset IDs from file names. If FALSE, will infer IDs from the directory names instead.
verbose	Print messages.

Value

Named vector of summary stats paths.

Examples

```
save_dir <- system.file("extdata", package = "MungeSumstats")
munged_files <- MungeSumstats::list_sumstats(save_dir = save_dir)
```

load_ref_genome_data *Load the reference genome data for SNPs of interest*

Description

Load the reference genome data for SNPs of interest

Usage

```
load_ref_genome_data(snps, ref_genome, dbSNP = c(144, 155), msg = NULL)
```

Arguments

snps	Character vector SNPs by rs_id from sumstats file of interest.
ref_genome	Name of the reference genome used for the GWAS (GRCh37 or GRCh38)
dbSNP	version of dbSNP to be used (144 or 155)
msg	Optional name of the column missing from the dataset in question. Default is NULL

Value

data table of snpsById, filtered to SNPs of interest.

Source

```
sumstats_dt <- formatted_example() rsids <- MungeSumstats::load_ref_genome_data(snps
= sumstats_dt$SNP, ref_genome = "GRCh37", dbSNP=144)
```

load_snp_loc_data	<i>Loads the SNP locations and alleles for Homo sapiens extracted from NCBI dbSNP Build 144. Reference genome version is dependent on user input.</i>
-------------------	---

Description

Loads the SNP locations and alleles for Homo sapiens extracted from NCBI dbSNP Build 144. Reference genome version is dependent on user input.

Usage

```
load_snp_loc_data(ref_genome, dbSNP = c(144, 155), msg = NULL)
```

Arguments

ref_genome	name of the reference genome used for the GWAS (GRCh37 or GRCh38)
dbSNP	version of dbSNP to be used (144 or 155)
msg	Optional name of the column missing from the dataset in question

Value

SNP_LOC_DATA SNP positions and alleles for Homo sapiens extracted from NCBI dbSNP Build 144

Examples

```
SNP_LOC_DATA <- load_snp_loc_data("GRCH37", dbSNP=144)
```

logs_example	<i>Example logs file</i>
--------------	--------------------------

Description

Example logs file produced by [format_sumstats](#).

Usage

```
logs_example(read = FALSE)
```

Arguments

read	Whether to read the logs file into memory.
------	--

Value

Path to logs file.

Source

```
eduAttainOkbayPth <- system.file("extdata", "eduAttainOkbay.txt", package = "MungeSumstats")
sumstats_dt <- data.table::fread(eduAttainOkbayPth) ##### Introduce values that need
to be fixed ##### sumstats_dt$Pval[10:15] <- 5 sumstats_dt$Pval[20:22] <- -5 sumstats_dt$Pval[23:25]
<- "5e-324" ss_path <- tempfile() data.table::fwrite(sumstats_dt, ss_path) log_folder
<- tempdir() reformatted <- MungeSumstats::format_sumstats(path = ss_path, ref_genome
= "GRCh37", log_folder = log_folder, log_mungesumstats_msgs = TRUE, log_folder_ind =
TRUE,) file.copy(reformatted$log_files$MungeSumstats_log_msg, "inst/extdata", overwrite
= TRUE)
```

make_allele_upper	<i>Ensure A1 and A2 are upper case</i>
-------------------	--

Description

Ensure A1 and A2 are upper case

Usage

```
make_allele_upper(sumstats_dt, log_files)
```

Arguments

log_files list of log file locations

Value

list containing sumstats_dt, the modified summary statistics data table object and the log file list

messenger	<i>Print messages</i>
-----------	-----------------------

Description

Print messages with option to silence.

Usage

```
messenger(..., v = TRUE)
```

Arguments

- ... Message input.
- v Whether to print messages.

Value

Null output.

`message_parallel` *Send messages to console even from within parallel processes*

Description

Send messages to console even from within parallel processes

Usage

`message_parallel(...)`

Value

A message

`parse_dropped_chrom` *Parse number of SNPs dropped due to being on chrom X, Y or MT*

Description

Support function for [parse_logs](#).

Usage

`parse_dropped_chrom(1)`

Arguments

- 1 Lines of text from log file.

Value

Numeric

parse_dropped_duplicates

Parse number of SNPs dropped due to being duplicates

Description

Support function for [parse_logs](#).

Usage

parse_dropped_duplicates(1)

Arguments

1 Lines of text from log file.

Value

Numeric

parse_dropped_INFO

Parse number of SNPs dropped due to being below the INFO threshold

Description

Support function for [parse_logs](#).

Usage

parse_dropped_INFO(1)

Arguments

1 Lines of text from log file.

Value

Numeric

parse_dropped_nonA1A2 *Parse number of SNPs dropped due to not matching the ref genome A1 or A2*

Description

Support function for [parse_logs](#).

Usage

parse_dropped_nonA1A2(1)

Arguments

1 Lines of text from log file.

Value

Numeric

parse_dropped_nonBiallelic
Parse number of SNPs dropped due to not being bi-allelic

Description

Support function for [parse_logs](#).

Usage

parse_dropped_nonBiallelic(1)

Arguments

1 Lines of text from log file.

Value

Numeric

parse_dropped_nonRef *Parse number of SNPs dropped due to being in the ref genome*

Description

Support function for [parse_logs](#).

Usage

```
parse_dropped_nonRef(1)
```

Arguments

1 Lines of text from log file.

Value

Numeric

parse_flipped *Parse number of SNPs flipped to align with the ref genome*

Description

Support function for [parse_logs](#).

Usage

```
parse_flipped(1)
```

Arguments

1 Lines of text from log file.

Value

Numeric

parse_genome_build *Genome build inferred from the summary statistics*

Description

Support function for [parse_logs](#).

Usage

```
parse_genome_build(1)
```

Arguments

1 Lines of text from log file.

Value

Character

parse_idStandard *Standardised IEU MRC OpenGWAS ID*

Description

Support function for [parse_logs](#).

Usage

```
parse_idStandard(1)
```

Arguments

1 Lines of text from log file.

Value

Character

parse_logs	<i>Parse data from log files</i>
------------	----------------------------------

Description

Parses data from the log files generated by [format_sumstats](#) or [import_sumstats](#) when the argument `log_mungesumstats_msgs` is set to TRUE.

Usage

```
parse_logs(  
  save_dir = getwd(),  
  pattern = "MungeSumstats_log_msg.txt$",  
  verbose = TRUE  
)
```

Arguments

<code>save_dir</code>	Top-level directory to recursively search for log files within.
<code>pattern</code>	Regex pattern to search for files with.
<code>verbose</code>	Print messages.

Value

[data.table](#) of parsed log data.

Examples

```
save_dir <- system.file("extdata", package = "MungeSumstats")  
log_data <- MungeSumstats::parse_logs(save_dir = save_dir)
```

parse_pval_large	<i>Parse number of SNPs with p-values >1</i>
------------------	---

Description

Support function for [parse_logs](#).

Usage

```
parse_pval_large(1)
```

Arguments

1	Lines of text from log file.
---	------------------------------

Value

Numeric

parse_pval_neg	<i>Parse number of SNPs with p-values <0</i>
----------------	---

Description

Support function for [parse_logs](#).

Usage

```
parse_pval_neg(1)
```

Arguments

1 Lines of text from log file.

Value

Numeric

parse_pval_small	<i>Parse number of SNPs with non-negative p-values $\leq 5e-324$</i>
------------------	---

Description

Support function for [parse_logs](#).

Usage

```
parse_pval_small(1)
```

Arguments

1 Lines of text from log file.

Value

Numeric

parse_report	<i>Parse "Summary statistics report" metrics</i>
--------------	--

Description

Support function for [parse_logs](#).

Usage

```
parse_report(1, entry = 1, line = 1)
```

Arguments

1	Lines of text from log file.
---	------------------------------

Value

Numeric

parse_snps_freq_05	<i>Parse number/percent of SNPs with <i>FREQ</i> values >0.5</i>
--------------------	---

Description

Support function for [parse_logs](#).

Usage

```
parse_snps_freq_05(1, percent = FALSE)
```

Arguments

1	Lines of text from log file.
---	------------------------------

Value

Numeric

`parse_snps_not_formatted`
Parse number of SNPs not correctly formatted

Description

Support function for [parse_logs](#).

Usage

`parse_snps_not_formatted(1)`

Arguments

1 Lines of text from log file.

Value

Numeric

`parse_time` *Parse the total time taken the munge the file*

Description

Support function for [parse_logs](#).

Usage

`parse_time(1)`

Arguments

1 Lines of text from log file.

Value

Character

```
preview_sumstats      Preview formatted sum stats saved to disk
```

Description

Prints the first n lines of the sum stats.

Usage

```
preview_sumstats(save_path, nrows = 5L)
```

Arguments

save_path File path to save formatted data. Defaults to tempfile(fileext=".tsv.gz").

Value

No return

```
raw_ALSvcf      GWAS Amyotrophic lateral sclerosis ieu open GWAS project - Subset
```

Description

VCF (VCFv4.2) of the GWAS Amyotrophic lateral sclerosis ieu open GWAS project Dataset: ebi-a-GCST005647. A subset of 99 SNPs

Format

vcf document with 528 items relating to 99 SNPs

Details

A VCF file (VCFv4.2) of the GWAS Amyotrophic lateral sclerosis ieu open GWAS project has been subsetted here to act as an example summary statistic file in VCF format which has some issues in the formatting. MungeSumstats can correct these issues and produced a standardised summary statistics format.

ALSvcf.vcf

NA

Source

The summary statistics VCF (VCFv4.2) file was downloaded from <https://gwas.mrcieu.ac.uk/datasets/ebi-a-GCST005647/> and formatted to a .rda with the following: #Get example VCF dataset, use GWAS Amyotrophic lateral sclerosis ALS_GWAS_VCF <- readLines("ebi-a-GCST005647.vcf.gz") #Subset to just the first 99 SNPs ALSvcf <- ALS_GWAS_VCF[1:528] writeLines(ALSvcf, "inst/extdata/ALSvcf.v")

raw_eduAttainOkbay	<i>GWAS Educational Attainment Okbay 2016 - Subset</i>
--------------------	--

Description

GWAS Summary Statistics on Educational Attainment by Okbay et al 2016: PMID: 27898078
 PMCID: PMC5509058 DOI: 10.1038/ng1216-1587b. A subset of 93 SNPs

Format

txt document with 94 items

Details

GWAS Summary Statistics on Educational Attainment by Okbay et al 2016 has been subsetted here to act as an example summary statistic file which has some issues in the formatting. MungeSumstats can correct these issues.

eduAttainOkbay.txt

NA

Source

The summary statistics file was downloaded from <https://www.nature.com/articles/ng.3552> and formatted to a .rda with the following: #Get example dataset, use Educational-Attainment_Okbay_2016
 link<-"Educational-Attainment_Okbay_2016/EduYears_Discovery_5000.txt" eduAttainOkbay<-readLines(link)
 #There is an issue where values end with .0, this 0 is removed in func #There are also SNPs
 not on ref genome or arebi/tri allelic #So need to remove these in this dataset as its used
 for testing tmp <- tempfile() writelines(eduAttainOkbay, con=tmp) eduAttainOkbay <- data.table::fread(tm
 #DT read removes the .0's #remove those not on ref genome and withbi/tri allelic rmv <-
 c("rs192818565", "rs79925071", "rs1606974", "rs1871109", "rs73074378", "rs7955289") eduAttainOkbay
 <- eduAttainOkbay[!MarkerName data.table::fwrite(eduAttainOkbay, file=tmp, sep="\t")
 eduAttainOkbay <- readLines(tmp) writelines(eduAttainOkbay, "inst/extdata/eduAttainOkbay.txt")

read_header	<i>Read in file header</i>
-------------	----------------------------

Description

Read in file header

Usage

```
read_header(path, n = 2L, skip_vcf_metadata = FALSE, nThread = 1)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
n	integer. The (maximal) number of lines to read. Negative values indicate that one should read up to the end of input on the connection.
skip_vcf_metadata	logical, should VCF metadata be ignored
nThread	Number of threads to use for parallel processes.

Value

First n lines of the VCF header

Examples

```
path <- system.file("extdata", "eduAttain0kbay.txt",
                    package = "MungeSumstats")
header <- read_header(path = path)
```

read_sumstats

Determine summary statistics file type and read them into memory

Description

Determine summary statistics file type and read them into memory

Usage

```
read_sumstats(
  path,
  nrows = Inf,
  standardise_headers = FALSE,
  samples = 1,
  sampled_rows = 10000L,
  nThread = 1,
  mapping_file = sumstatsColHeaders
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats using the path parameter.
nrows	integer. The (maximal) number of lines to read. If Inf, will read in all rows.

standardise_headers	Standardise headers first.
samples	Which samples to use: <ul style="list-style-type: none"> • 1 : Only the first sample will be used (<i>DEFAULT</i>). • NULL : All samples will be used. • c("<sample_id1>", "<sample_id2>", ...) : Only user-selected samples will be used (case-insensitive).
sampled_rows	First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.
nThread	Number of threads to use for parallel processes.
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.

Value

data.table of formatted summary statistics

Examples

```
path <- system.file("extdata", "eduAttainOkbay.txt",
  package = "MungeSumstats"
)
eduAttainOkbay <- read_sumstats(path = path)
```

read_vcf	<i>Read in VCF file</i>
----------	-------------------------

Description

Read in a VCF file as a [VCF](#) or a [data.table](#). Can optionally save the VCF/data.table as well.

Usage

```
read_vcf(
  path,
  as_datatable = TRUE,
  save_path = NULL,
  tabix_index = FALSE,
  samples = 1,
  which = NULL,
  use_params = TRUE,
  sampled_rows = 10000L,
```

```

download = TRUE,
vcf_dir = tempdir(),
download_method = "download.file",
force_new = FALSE,
mt_thresh = 100000L,
nThread = 1,
verbose = TRUE
)

```

Arguments

path	Path to local or remote VCF file.
as_datatable	Return the data as a data.table (default: TRUE) or a VCF (FALSE).
save_path	File path to save formatted data. Defaults to <code>tempfile(fileext=".tsv.gz")</code> .
tabix_index	Index the formatted summary statistics with tabix for fast querying.
samples	Which samples to use: <ul style="list-style-type: none"> • 1 : Only the first sample will be used (<i>DEFAULT</i>). • NULL : All samples will be used. • <code>c("<sample_id1>","<sample_id2>",...)</code> : Only user-selected samples will be used (case-insensitive).
which	A GRanges describing the sequences and ranges to be queried. Variants whose POS lies in the interval(s) [<code>start</code> , <code>end</code>] are returned. If <code>which</code> is not specified all ranges are returned.
use_params	When TRUE (default), increases the speed of reading in the VCF by omitting columns that are empty based on the head of the VCF (NAs only). NOTE that that this requires the VCF to be sorted, bgzip-compressed, tabix-indexed, which read_vcf will attempt to do.
sampled_rows	First N rows to sample. Set NULL to use full <code>sumstats_file</code> . when determining whether cols are empty.
download	Download the VCF (and its index file) to a temp folder before reading it into R. This is important to keep TRUE when <code>nThread</code> >1 to avoid making too many queries to remote file.
vcf_dir	Where to download the original VCF from Open GWAS. <i>WARNING</i> : This is set to <code>tempdir()</code> by default. This means the raw (pre-formatted) VCFs be deleted upon ending the R session. Change this to keep the raw VCF file on disk (e.g. <code>vcf_dir="/raw_vcf"</code>).
download_method	"axel" (multi-threaded) or "download.file" (single-threaded) .
force_new	If a formatted file of the same names as <code>save_path</code> exists, formatting will be skipped and this file will be imported instead (default). Set <code>force_new=TRUE</code> to override this.
mt_thresh	When the number of rows (variants) in the VCF is < <code>mt_thresh</code> , only use single-threading for reading in the VCF. This is because the overhead of parallelisation outweighs the speed benefits when VCFs are small.
nThread	Number of threads to use for parallel processes.
verbose	Print messages.

Value

The VCF file in data.table format.

Source

```
##### Benchmarking ##### library(VCFwrenchR) library(VariantAnnotation) path <- "https://gwas.mrcieu.ac.uk/files/ieu-a-298/ieu-a-298.vcf.gz"
vcf <- VariantAnnotation::readVcf(file = path) N <- 1e5 vcf_sub <- vcf[1:N,] res <- microbenchmark::microbenchmark("vcf2df"={dat1 <- MungeSumstats::vcf2df(vcf = vcf_sub)}, "VCFwrenchR"={dat2 <- as.data.frame(x = vcf_sub)}, "VRanges"={dat3 <- data.table::as.data.table(methods::as(vcf_sub, "VRanges"))}, times=1)
```

[Discussion on VariantAnnotation GitHub](#)

[Discussion on VariantAnnotation GitHub](#)

Examples

```
##### Local file #####
path <- system.file("extdata", "ALSvcf.vcf", package="MungeSumstats")
sumstats_dt <- read_vcf(path = path)

##### Remote file #####
## Small GWAS (0.2Mb)
# path <- "https://gwas.mrcieu.ac.uk/files/ieu-a-298/ieu-a-298.vcf.gz"
# sumstats_dt2 <- read_vcf(path = path)

## Large GWAS (250Mb)
# path <- "https://gwas.mrcieu.ac.uk/files/ubm-a-2929/ubm-a-2929.vcf.gz"
# sumstats_dt3 <- read_vcf(path = path, nThread=11)

### Very large GWAS (500Mb)
# path <- "https://gwas.mrcieu.ac.uk/files/ieu-a-1124/ieu-a-1124.vcf.gz"
# sumstats_dt4 <- read_vcf(path = path, nThread=11)
```

read_vcf_genome

Read VCF genome

Description

Get the genome build of a remote or local VCF file.

Usage

```
read_vcf_genome(
  header = NULL,
  validate = FALSE,
  default_genome = "HG19/GRCh37",
  verbose = TRUE
)
```

Arguments

header	Header extracted by scanVcfHeader .
validate	Validate genome name using mapGenomeBuilds .
default_genome	When no genome can be extracted, default to this genome build.
verbose	Print messages.

Value

genome

read_vcf_info	<i>Read VCF: INFO column</i>
---------------	------------------------------

Description

Parse INFO column in VCF file.

Usage

```
read_vcf_info(sumstats_dt)
```

Arguments

sumstats_dt	Summary stats data.table.
-------------	---------------------------

Value

Null output.

read_vcf_markername	<i>Read VCF: MarkerName column</i>
---------------------	------------------------------------

Description

Parse MarkerName/SNP column in VCF file.

Usage

```
read_vcf_markername(sumstats_dt)
```

Arguments

sumstats_dt	Summary stats data.table.
-------------	---------------------------

Value

Null output.

read_vcf_parallel *Read VCF: parallel*

Description

Read a VCF file across 1 or more threads in parallel. If `tilewidth` is not specified, the size of each chunk will be determined by total genome size divided by `ntile`. By default, `ntile` is equal to the number of threads, `nThread`. For further discussion on how this function was optimised, see [here](#) and [here](#).

Usage

```
read_vcf_parallel(
  path,
  samples = 1,
  which = NULL,
  use_params = TRUE,
  as_datatable = TRUE,
  sampled_rows = 10000L,
  include_xy = FALSE,
  download = TRUE,
  vcf_dir = tempdir(),
  download_method = "download.file",
  force_new = FALSE,
  tilewidth = NULL,
  mt_thresh = 100000L,
  nThread = 1,
  ntile = nThread,
  verbose = TRUE
)
```

Arguments

<code>path</code>	Path to local or remote VCF file.
<code>samples</code>	Which samples to use: <ul style="list-style-type: none"> • 1 : Only the first sample will be used (<i>DEFAULT</i>). • NULL : All samples will be used. • c("<sample_id1>", "<sample_id2>", ...) : Only user-selected samples will be used (case-insensitive).
<code>which</code>	A GRanges describing the sequences and ranges to be queried. Variants whose POS lies in the interval(s) [<code>start</code> , <code>end</code>] are returned. If <code>which</code> is not specified all ranges are returned.
<code>use_params</code>	When TRUE (default), increases the speed of reading in the VCF by omitting columns that are empty based on the head of the VCF (NAs only). NOTE that that this requires the VCF to be sorted, bgzip-compressed, tabix-indexed, which read_vcf will attempt to do.

as_datatable	Return the data as a data.table (default: TRUE) or a VCF (FALSE).
sampld_rows	First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.
download	Download the VCF (and its index file) to a temp folder before reading it into R. This is important to keep TRUE when nThread>1 to avoid making too many queries to remote file.
vcf_dir	Where to download the original VCF from Open GWAS. <i>WARNING:</i> This is set to tempdir() by default. This means the raw (pre-formatted) VCFs be deleted upon ending the R session. Change this to keep the raw VCF file on disk (e.g. vcf_dir="./raw_vcf").
download_method	"axel" (multi-threaded) or "download.file" (single-threaded) .
force_new	If a formatted file of the same names as save_path exists, formatting will be skipped and this file will be imported instead (default). Set force_new=TRUE to override this.
tilewidth	The desired tile width. The effective tile width might be slightly different but is guaranteed to never be more than the desired width.
mt_thresh	When the number of rows (variants) in the VCF is < mt_thresh, only use single-threading for reading in the VCF. This is because the overhead of parallelisation outweighs the speed benefits when VCFs are small.
nThread	Number of threads to use for parallel processes.
ntile	The number of tiles to generate.
verbose	Print messages.

Value

VCF file.

Source

```
path <- "https://gwas.mrcieu.ac.uk/files/ieu-a-298/ieu-a-298.vcf.gz" ##### Single-threaded
#### vcf <- MungeSumstats:::read_vcf_parallel(path = path) ##### Parallel ##### vcf2 <-
MungeSumstats:::read_vcf_parallel(path = path, nThread=11)
```

read_vcf_pval	<i>Read VCF: p-value column</i>
---------------	---------------------------------

Description

Parse p-value column in VCF file.

Usage

```
read_vcf_pval(sumstats_dt)
```

Arguments

sumstats_dt Summary stats data.table.

Value

Null output.

register_cores	<i>Register cores</i>
----------------	-----------------------

Description

Register a multi-threaded instances using **BiocParallel**.

Usage

```
register_cores(workers = 1, progressbar = TRUE)
```

Arguments

workers integer(1) Number of workers. Defaults to the maximum of 1 or the number of cores determined by detectCores minus 2 unless environment variables R_PARALLELLY_AVAILABLECORES_FALLBACK or BIOCPARALLEL_WORKER_NUMBER are set otherwise. For a SOCK cluster, workers can be a character() vector of host names.

progressbar logical(1) Enable progress bar (based on plyr:::progress_text).

Value

Null output.

remove_empty_cols	<i>Remove empty columns</i>
-------------------	-----------------------------

Description

Remove columns that are empty or contain all the same values in a data.table.

Usage

```
remove_empty_cols(sumstats_dt, sampled_rows = NULL, verbose = TRUE)
```

Arguments

sampled_rows	First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.
verbose	Print messages.

Value

Null output.

report_summary	<i>Report info on current state of the summary statistics</i>
----------------	---

Description

Prints report.

Usage

```
report_summary(sumstats_dt, orig_dims = NULL)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
-------------	---

Value

No return

select_api	<i>Toggle API address between development and release</i>
------------	---

Description

From ieugwasr.

Usage

```
select_api(where = "public", verbose = TRUE)
```

Arguments

where	Which API to use. Choice between "local", "release", "test". Default = "local"
-------	--

Value

No return

select_vcf_fields	Select VCF fields
-------------------	-------------------

Description

Select non-empty columns from each VCF field type.

Usage

```
select_vcf_fields(
  path,
  sampled_rows = 10000L,
  which = NULL,
  samples = NULL,
  nThread = 1,
  verbose = TRUE
)
```

Arguments

path	Path to local or remote VCF file.
sampled_rows	First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.
which	A GRanges describing the sequences and ranges to be queried. Variants whose POS lies in the interval(s) [start, end] are returned. If which is not specified all ranges are returned.
samples	Which samples to use: <ul style="list-style-type: none"> • 1 : Only the first sample will be used (<i>DEFAULT</i>). • NULL : All samples will be used. • c("<sample_id1>", "<sample_id2>", ...) : Only user-selected samples will be used (case-insensitive).
nThread	Number of threads to use for parallel processes.
verbose	Print messages.

Value

ScanVcfParam object.

sort_coords	<i>Sort sum stats</i>
-------------	-----------------------

Description

Sort summary statistics table by genomic coordinates.

Usage

```
sort_coords(
  sumstats_dt,
  sort_coordinates = TRUE,
  sort_method = c("data.table", "GenomicRanges")
)
```

Arguments

sumstats_dt	data.table obj of the summary statistics file for the GWAS.
sort_method	Method to sort coordinates by: <ul style="list-style-type: none"> • "data.table" (default) Uses <code>setorderv</code>, which is much faster than "GenomicRanges" but less robust to variations in some sum stats files. • "GenomicRanges" Uses <code>sort.GenomicRanges</code>, which is more robust to variations in sum stats files but much slower than the "data.table" method.
sort_coords	Whether to sort by coordinates.
make_ordered	Make CHR into an ordered factor to ensure they go from 1-22, X, Y.

Value

Sorted sumstats_dt

sort_coords_datatable	<i>Sort sum stats: data.table</i>
-----------------------	-----------------------------------

Description

Sort summary statistics table by genomic coordinates using a fast data.table-native strategy

Usage

```
sort_coords_datatable(
  sumstats_dt,
  chr_col = "CHR",
  start_col = "BP",
  end_col = start_col
)
```


Arguments

sumstats_dt [data.table](#) obj of the summary statistics file for the GWAS.
chr_col Chromosome column name.
start_col Genomic end position column name.

Value

Sorted sumstats_dt

sort_coord_genomicranges
Sort sum stats: GenomicRanges

Description

Sort summary statistics table by genomic coordinates using a slower (but in some cases more robust) GenomicRanges strategy

Usage

```
sort_coord_genomicranges(sumstats_dt)
```

Arguments

sumstats_dt [data.table](#) obj of the summary statistics file for the GWAS.

Value

Sorted sumstats_dt

standardise_header *Standardise the column headers in the Summary Statistics files*

Description

Use a reference data table of common column header names (stored in sumstatsColHeaders or user inputted mapping file) to convert them to a standard set, i.e. chromosome -> CHR. This function does not check that all the required column headers are present. The amended header is written directly back into the file

Usage

```
standardise_header(
  sumstats_dt,
  mapping_file = sumstatsColHeaders,
  uppercase_unmapped = TRUE,
  return_list = TRUE
)
```

Arguments

`sumstats_dt` data table obj of the summary statistics file for the GWAS.

`mapping_file` MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing from the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See `data(sumstatsColHeaders)` for default mapping and necessary format.

`uppercase_unmapped` For columns that could not be identified in the `mapping_file`, return them in the same format they were input as (without forcing them to uppercase).

`return_list` Return the `sumstats_dt` within a named list (default: TRUE).

Value

list containing `sumstats_dt`, the modified summary statistics data table object

Examples

```
sumstats_dt <- data.table::fread(system.file("extdata", "eduAttain0kbay.txt",
                                             package = "MungeSumstats"))
sumstats_dt2 <- standardise_header(sumstats_dt=sumstats_dt)
```

`sumstatsColHeaders` *Summary Statistics Column Headers*

Description

List of uncorrected column headers often found in GWAS Summary Statistics column headers. Note the effect allele will always be the A2 allele, this is the approach done for VCF(<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC>). This is enforced with the column header corrections here and also the check allele flipping test.

Usage

```
data("sumstatsColHeaders")
```

Format

dataframe with 2 columns

Source

```
The code to prepare the .Rda file from the marker file is: # Most the data in the below table
comes from the LDSC github wiki data("sumstatsColHeaders") # Make additions to sumstatsColHeaders
using github version of MungeSumstats-# shown is an example of adding columns for Standard
Error (SE) #se_cols <- data.frame("Uncorrected"=c("SE", "se", "STANDARD.ERROR", # "STANDARD_ERROR", "STAND
"Corrected"=rep("SE", 5)) #sumstatsColHeaders <- rbind(sumstatsColHeaders, se_cols)
#Once additions are made, order & save the new mapping dataset #now sort ordering -important
for logic that # uncorrected=corrected comes first sumstatsColHeaders$ordering <- sumstatsColHeaders$Unc
sumstatsColHeaders <- sumstatsColHeaders[order(sumstatsColHeaders$Corrected, sumstatsColHeaders$order
= TRUE), ] rownames(sumstatsColHeaders)<-1:nrow(sumstatsColHeaders) sumstatsColHeaders$ordering
<- NULL #manually move FRWQUENCY to above MAR - github issue 95 frequency <- sumstatsColHeaders[sumstatsCo
maf <- sumstatsColHeaders[sumstatsColHeaders$Uncorrected=="MAF", ] if(as.integer(rownames(frequency))>
sumstatsColHeaders[as.integer(rownames(frequency)), ] <- maf sumstatsColHeaders[as.integer(rownames(ma
<- frequency } usethis::use_data(sumstatsColHeaders, overwrite = TRUE, internal=TRUE)
save(sumstatsColHeaders, file="data/sumstatsColHeaders.rda") # You will need to restart
your r session for effects to take account
```

supported_suffixes *List supported file formats*

Description

List supported file formats

Usage

```
supported_suffixes(
  tabular = TRUE,
  tabular_compressed = TRUE,
  vcf = TRUE,
  vcf_compressed = TRUE
)
```

Arguments

```
tabular            Include tabular formats.
tabular_compressed            Include compressed tabular formats.

vcf                Include Variant Call Format.
vcf_compressed    Include compressed Variant Call Format.
```

Value

File formats

to_granges	<i>To GRanges</i>
------------	-------------------

Description

Convert a [data.table](#) to [GRanges](#).

Usage

```
to_granges(
  sumstats_dt,
  seqnames.field = "CHR",
  start.field = "BP",
  end.field = "BP",
  style = c("NCBI", "UCSC")
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
seqnames.field	A character vector of recognized names for the column in df that contains the chromosome name (a.k.a. sequence name) associated with each genomic range. Only the first name in seqnames.field that is found in colnames(df) is used. If no one is found, then an error is raised.
start.field	A character vector of recognized names for the column in df that contains the start positions of the genomic ranges. Only the first name in start.field that is found in colnames(df) is used. If no one is found, then an error is raised.
end.field	A character vector of recognized names for the column in df that contains the end positions of the genomic ranges. Only the first name in start.field that is found in colnames(df) is used. If no one is found, then an error is raised.
style	GRanges style to convert to, "NCBI" or "UCSC".

Value

GRanges object

to_vranges	<i>Convert to VRanges</i>
------------	---------------------------

Description

Convert to VRanges

Usage

```
to_vranges(sumstats_dt)
```

Arguments

sumstats_dt data table obj of the summary statistics file for the GWAS.

Value

VRanges object

unlist_dt	<i>Unlist a data.table</i>
-----------	----------------------------

Description

Identify columns that are lists and turn them into vectors.

Usage

```
unlist_dt(dt, verbose = TRUE)
```

Arguments

dt data.table
verbose Print messages.

Value

dt with list columns turned into vectors.

validate_parameters	<i>Ensure that the input parameters are logical</i>
---------------------	---

Description

Ensure that the input parameters are logical

Usage

```
validate_parameters(  
  path,  
  ref_genome,  
  convert_ref_genome,  
  convert_small_p,  
  es_is_beta,  
  compute_z,  
  compute_n,  
  convert_n_int,  
  analysis_trait,  
  INFO_filter,  
  FRQ_filter,  
  pos_se,  
  effect_columns_nonzero,  
  N_std,  
  N_dropNA,  
  rmv_chr,  
  on_ref_genome,  
  strand_ambig_filter,  
  allele_flip_check,  
  allele_flip_drop,  
  allele_flip_z,  
  allele_flip_frq,  
  bi_allelic_filter,  
  snp_ids_are_rs_ids,  
  remove_multi_rs_snp,  
  frq_is_maf,  
  indels,  
  drop_indels,  
  check_dups,  
  dbSNP,  
  write_vcf,  
  return_format,  
  ldsc_format,  
  save_format,  
  imputation_ind,  
  log_folder_ind,  
  log_mungesumstats_msgs,  
  mapping_file,  
  tabix_index,  
  chain_source  
)
```

Arguments

path	Filepath for the summary statistics file to be formatted. A dataframe or datatable of the summary statistics file can also be passed directly to MungeSumstats
------	--

	using the path parameter.
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
convert_ref_genome	name of the reference genome to convert to ("GRCh37" or "GRCh38"). This will only occur if the current genome build does not match. Default is not to convert the genome build (NULL).
convert_small_p	Binary, should non-negative p-values $\leq 5e-324$ be converted to 0? Small p-values pass the R limit and can cause errors with LDSC/MAGMA and should be converted. Default is TRUE.
es_is_beta	Binary, whether to map ES to BETA. We take BETA to be any BETA-like value (including Effect Size). If this is not the case for your sumstats, change this to FALSE. Default is TRUE.
compute_z	Whether to compute Z-score column. Default is FALSE. This can be computed from Beta and SE with (Beta/SE) or $P (Z:=\text{sign}(\text{BETA})*\text{sqrt}(\text{stats::qchisq}(P,1,\text{lower}=\text{FALSE})))$. Note that imputing the Z-score from P for every SNP will not be perfectly correct and may result in a loss of power. This should only be done as a last resort. Use 'BETA' to impute by BETA/SE and 'P' to impute by SNP p-value.
compute_n	Whether to impute N. Default of 0 won't impute, any other integer will be imputed as the N (sample size) for every SNP in the dataset. Note that imputing the sample size for every SNP is not correct and should only be done as a last resort. N can also be inputted with "ldsc", "sum", "giant" or "metal" by passing one of these for this field or a vector of multiple. Sum and an integer value creates an N column in the output whereas giant, metal or ldsc create an Neff or effective sample size. If multiples are passed, the formula used to derive it will be indicated.
convert_n_int	Binary, if N (the number of samples) is not an integer, should this be rounded? Default is TRUE.
analysis_trait	If multiple traits were studied, name of the trait for analysis from the GWAS. Default is NULL.
INFO_filter	numeric The minimum value permissible of the imputation information score (if present in sumstats file). Default 0.9.
FRQ_filter	numeric The minimum value permissible of the frequency(FRQ) of the SNP (i.e. Allele Frequency (AF)) (if present in sumstats file). By default no filtering is done, i.e. value of 0.
pos_se	Binary Should the standard Error (SE) column be checked to ensure it is greater than 0? Those that are, are removed (if present in sumstats file). Default TRUE.
effect_columns_nonzero	Binary should the effect columns in the data BETA,OR (odds ratio),LOG_ODDS,SIGNED_SUMSTAT be checked to ensure no SNP=0. Those that do are removed(if present in sumstats file). Default FALSE.
N_std	numeric The number of standard deviations above the mean a SNP's N is needed to be removed. Default is 5.

N_dropNA	Drop rows where N is missing. Default is TRUE.
rmv_chr	vector or character The chromosomes on which the SNPs should be removed. Use NULL if no filtering necessary. Default is X, Y and mitochondrial.
on_ref_genome	Binary Should a check take place that all SNPs are on the reference genome by SNP ID. Default is TRUE.
strand_ambig_filter	Binary Should SNPs with strand-ambiguous alleles be removed. Default is FALSE.
allele_flip_check	Binary Should the allele columns be checked against reference genome to infer if flipping is necessary. Default is TRUE.
allele_flip_drop	Binary Should the SNPs for which neither their A1 or A2 base pair values match a reference genome be dropped. Default is TRUE.
allele_flip_z	Binary should the Z-score be flipped along with effect and FRQ columns like Beta? It is assumed to be calculated off the effect size not the P-value and so will be flipped i.e. default TRUE.
allele_flip_frq	Binary should the frequency (FRQ) column be flipped along with effect and z-score columns like Beta? Default TRUE.
bi_allelic_filter	Binary Should non-biallelic SNPs be removed. Default is TRUE.
snp_ids_are_rs_ids	Binary Should the supplied SNP ID's be assumed to be RSIDs. If not, imputation using the SNP ID for other columns like base-pair position or chromosome will not be possible. If set to FALSE, the SNP RS ID will be imputed from the reference genome if possible. Default is TRUE.
remove_multi_rs_snp	Binary Sometimes summary statistics can have multiple RSIDs on one row (i.e. related to one SNP), for example "rs5772025_rs397784053". This can cause an error so by default, the first RS ID will be kept and the rest removed e.g. "rs5772025". If you want to just remove these SNPs entirely, set it to TRUE. Default is FALSE.
frq_is_maf	Conventionally the FRQ column is intended to show the minor/effect allele frequency (MAF) but sometimes the major allele frequency can be inferred as the FRQ column. This logical variable indicates that the FRQ column should be renamed to MAJOR_ALLELE_FRQ if the frequency values appear to relate to the major allele i.e. >0.5. By default this mapping won't occur i.e. is TRUE.
indels	Binary does your Sumstats file contain Indels? These don't exist in our reference file so they will be excluded from checks if this value is TRUE. Default is TRUE.
drop_indels	Binary, should any indels found in the sumstats be dropped? These can not be checked against a reference dataset and will have the same RS ID and position as SNPs which can affect downstream analysis. Default is False.
check_dups	whether to check for duplicates - if formatting QTL datasets this should be set to FALSE otherwise keep as TRUE. Default is TRUE.

dbSNP	version of dbSNP to be used for imputation (144 or 155).
write_vcf	Whether to write as VCF (TRUE) or tabular file (FALSE).
return_format	If return_data is TRUE. Object type to be returned ("data.table", "vranges", "granges").
ldsc_format	DEPRECATED, do not use. Use save_format="LDSC" instead.
save_format	Output format of sumstats. Options are NULL - standardised output format from MungeSumstats, LDSC - output format compatible with LDSC and openGWAS - output compatible with openGWAS VCFs. Default is NULL.
imputation_ind	Binary Should a column be added for each imputation step to show what SNPs have imputed values for differing fields. This includes a field denoting SNP allele flipping (flipped). On the flipped value, this denoted whether the alleles were switched based on MungeSumstats initial choice of A1, A2 from the input column headers and thus may not align with what the creator intended. Note these columns will be in the formatted summary statistics returned. Default is FALSE.
log_folder_ind	Binary Should log files be stored containing all filtered out SNPs (separate file per filter). The data is outputted in the same format specified for the resulting sumstats file. The only exception to this rule is if output is vcf, then log file saved as .tsv.gz. Default is FALSE.
log_mungesumstats_msgs	Binary Should a log be stored containing all messages and errors printed by MungeSumstats in a run. Default is FALSE
mapping_file	MungeSumstats has a pre-defined column-name mapping file which should cover the most common column headers and their interpretations. However, if a column header that is in your file is missing of the mapping we give is incorrect you can supply your own mapping file. Must be a 2 column dataframe with column names "Uncorrected" and "Corrected". See data(sumstatsColHeaders) for default mapping and necessary format.
tabix_index	Index the formatted summary statistics with tabix for fast querying.
chain_source	source of the chain file to use in liftover, if converting genome build ("ucsc" or "ensembl"). Note that the UCSC chain files require a license for commercial use. The Ensembl chain is used by default ("ensembl").

Value

No return

vcf2df*VCF to DF*

DescriptionFunction to convert a **VariantAnnotation** CollapsedVCF/ExpandedVCF object to a data.frame.

Usage

```
vcf2df(
  vcf,
  add_sample_names = TRUE,
  add_rowranges = TRUE,
  drop_empty_cols = TRUE,
  unique_cols = TRUE,
  unique_rows = TRUE,
  unlist_cols = TRUE,
  sampled_rows = NULL,
  verbose = TRUE
)
```

Arguments

vcf	Variant Call Format (VCF) file imported into R as a VariantAnnotation CollapsedVCF/ ExpandedVCF object.
add_sample_names	Append sample names to column names (e.g. "EZ" -> "EZ_ubm-a-2929").
add_rowranges	Include rowRanges from VCF as well.
drop_empty_cols	Drop columns that are filled entirely with: NA, ".", or "".
unique_cols	Only keep uniquely named columns.
unique_rows	Only keep unique rows.
unlist_cols	If any columns are lists instead of vectors, unlist them. Required to be TRUE when unique_rows=TRUE.
sampled_rows	First N rows to sample. Set NULL to use full sumstats_file. when determining whether cols are empty.
verbose	Print messages.

Value

data.frame version of VCF

Source

[Original code source](#)

vcfR:

```
if(!require("pinfsc50")) install.packages("pinfsc50") vcf_file <- system.file("extdata", "pinf_sc50.vcf.gz",
package = "pinfsc50") vcf <- read.vcfR( vcf_file, verbose = FALSE ) vcf_df_list <- vcfR::vcfR2tidy(vcf,
single_frame=TRUE) vcf_df <- data.table::data.table(vcf_df_list$dat)
```

Examples

```
#### VariantAnnotation ####
# path <- "https://github.com/brentp/vcfanno/raw/master/example/exac.vcf.gz"
path <- system.file("extdata", "ALSvcf.vcf",
                   package = "MungeSumstats")

vcf <- VariantAnnotation::readVcf(file = path)
vcf_df <- MungeSumstats::vcf2df(vcf = vcf)
```

write_sumstats	<i>Write sum stats file to disk</i>
----------------	-------------------------------------

Description

Write sum stats file to disk

Usage

```
write_sumstats(
  sumstats_dt,
  save_path,
  ref_genome = NULL,
  sep = "\t",
  write_vcf = FALSE,
  save_format = NULL,
  tabix_index = FALSE,
  nThread = 1,
  return_path = FALSE,
  save_path_check = FALSE
)
```

Arguments

sumstats_dt	data table obj of the summary statistics file for the GWAS.
save_path	File path to save formatted data. Defaults to <code>tempfile(fileext=".tsv.gz")</code> .
ref_genome	name of the reference genome used for the GWAS ("GRCh37" or "GRCh38"). Argument is case-insensitive. Default is NULL which infers the reference genome from the data.
sep	The separator between columns. Defaults to the character in the set <code>[, \t ; :]</code> that separates the sample of rows into the most number of lines with the same number of fields. Use NULL or "" to specify no separator; i.e. each line a single character column like <code>base::readLines</code> does.
write_vcf	Whether to write as VCF (TRUE) or tabular file (FALSE).
save_format	Output format of sumstats. Options are NULL - standardised output format from MungeSumstats, LDSC - output format compatible with LDSC and openGWAS - output compatible with openGWAS VCFs. Default is NULL.

tabix_index	Index the formatted summary statistics with <code>tabix</code> for fast querying.
nThread	The number of threads to use. Experiment to see what works best for your data on your hardware.
return_path	Return <code>save_path</code> . This will have been modified in some cases (e.g. after compressing and tabix-indexing a previously un-compressed file).
save_path_check	Ensure path name is valid (given the other arguments) before writing (default: FALSE).

Value

If `return_path=TRUE`, returns `save_path`. Else returns `NULL`.

Source

VariantAnnotation::writeVcf has some unexpected/silent file renaming behavior

Examples

```
path <- system.file("extdata", "eduAttainOkbay.txt",
  package = "MungeSumstats"
)
eduAttainOkbay <- read_sumstats(path = path)
write_sumstats(
  sumstats_dt = eduAttainOkbay,
  save_path = tempfile(fileext = ".tsv.gz")
)
```

Index

* datasets

sumstatsColHeaders, [106](#)

* downloaders

axel, [6](#)

downloader, [50](#)

* internal

api_query, [5](#)

axel, [6](#)

check_access_token, [7](#)

check_allele_flip, [7](#)

check_allele_merge, [9](#)

check_bi_allelic, [10](#)

check_chr, [11](#)

check_col_order, [12](#)

check_drop_indels, [12](#)

check_dup_bp, [13](#)

check_dup_col, [14](#)

check_dup_row, [15](#)

check_dup_snp, [16](#)

check_effect_columns_nonzero, [17](#)

check_empty_cols, [18](#)

check_four_step_col, [18](#)

check_frq, [19](#)

check_frq_maf, [20](#)

check_info_score, [20](#)

check_miss_data, [22](#)

check_multi_gwas, [23](#)

check_multi_rs_snp, [24](#)

check_n_int, [31](#)

check_n_num, [31](#)

check_no_allele, [25](#)

check_no_chr_bp, [26](#)

check_no_rs_snp, [27](#)

check_no_snp, [29](#)

check_numeric, [30](#)

check_on_ref_genome, [32](#)

check_pos_se, [33](#)

check_range_p_val, [35](#)

check_row_snp, [36](#)

check_save_path, [37](#)

check_signed_col, [38](#)

check_small_p_val, [39](#)

check_strand_ambiguous, [40](#)

check_tabular, [41](#)

check_two_step_col, [41](#)

check_vcf, [42](#)

check_vital_col, [42](#)

check_zscore, [43](#)

column_dictionary, [44](#)

compute_sample_size, [46](#)

compute_sample_size_n, [47](#)

compute_sample_size_neff, [48](#)

convert_sumstats, [49](#)

DF_to_dt, [50](#)

downloader, [50](#)

drop_duplicate_cols, [53](#)

drop_duplicate_rows, [53](#)

get_access_token, [62](#)

get_chain_file, [62](#)

get_genome_build, [63](#)

get_query_content, [65](#)

get_unique_name_log_file, [66](#)

get_vcf_sample_ids, [66](#)

granges_to_dt, [67](#)

gwasinfo, [67](#)

index_vcf, [76](#)

is_tabix, [77](#)

legacy_ids, [77](#)

logs_example, [81](#)

make_allele_upper, [82](#)

message_parallel, [83](#)

messenger, [82](#)

parse_dropped_chrom, [83](#)

parse_dropped_duplicates, [84](#)

parse_dropped_INFO, [84](#)

parse_dropped_nonA1A2, [85](#)

parse_dropped_nonBiallelic, [85](#)

parse_dropped_nonRef, [86](#)

- parse_flipped, 86
- parse_genome_build, 87
- parse_idStandard, 87
- parse_pval_large, 88
- parse_pval_neg, 89
- parse_pval_small, 89
- parse_report, 90
- parse_snps_freq_05, 90
- parse_snps_not_formatted, 91
- parse_time, 91
- preview_sumstats, 92
- read_vcf_genome, 97
- read_vcf_info, 98
- read_vcf_markername, 98
- read_vcf_parallel, 99
- read_vcf_pval, 100
- remove_empty_cols, 101
- report_summary, 102
- select_api, 102
- select_vcf_fields, 103
- sort_coord_genomicranges, 105
- sort_coords, 104
- sort_coords_datatable, 104
- supported_suffixes, 107
- to_granges, 108
- to_vranges, 108
- unlist_dt, 109
- validate_parameters, 109
- * **tabix**
 - index_tabular, 74
 - index_vcf, 76
- api_query, 5
- axel, 6, 51

- check_access_token, 7
- check_allele_flip, 7
- check_allele_merge, 9
- check_bi_allelic, 10
- check_chr, 11
- check_col_order, 12
- check_drop_indels, 12
- check_dup_bp, 13
- check_dup_col, 14
- check_dup_row, 15
- check_dup_snp, 16
- check_effect_columns_nonzero, 17
- check_empty_cols, 18
- check_four_step_col, 18
- check_freq, 19
- check_freq_maf, 20
- check_info_score, 20
- check_ldsc_format, 21
- check_miss_data, 22
- check_multi_gwas, 23
- check_multi_rs_snp, 24
- check_n_int, 31
- check_n_num, 31
- check_no_allele, 25
- check_no_chr_bp, 26
- check_no_rs_snp, 27
- check_no_snp, 29
- check_numeric, 30
- check_on_ref_genome, 32
- check_pos_se, 33
- check_range_p_val, 35
- check_row_snp, 36
- check_save_path, 37
- check_signed_col, 38
- check_small_p_val, 39
- check_strand_ambiguous, 40
- check_tabular, 41
- check_two_step_col, 41
- check_vcf, 42
- check_vital_col, 42
- check_zscore, 43
- CollapsedVCF, 114
- column_dictionary, 44
- compute_nsize, 45
- compute_sample_size, 46
- compute_sample_size_n, 47
- compute_sample_size_neff, 48
- convert_sumstats, 49

- data.table, 50, 67, 79, 88, 95, 96, 100, 104, 105, 108
- DataFrame, 50
- DF_to_dt, 50
- download.file, 50
- download_vcf, 51
- downloader, 6, 50
- drop_duplicate_cols, 53
- drop_duplicate_rows, 53

- ExpandedVCF, 114

- find_sumstats, 54
- format_sumstats, 30, 56, 70, 79, 81, 88

formatted_example, 55

get_access_token, 62

get_chain_file, 62

get_genome_build, 63

get_genome_builds, 64

get_query_content, 65

get_unique_name_log_file, 66

get_vcf_sample_ids, 66

GRanges, 67, 79, 96, 99, 103, 108

granges_to_dt, 67

gwasinfo, 67

hg19ToHg38, 68

hg38ToHg19, 68

ieu-a-298, 69

import_sumstats, 69, 79, 88

index_tabular, 74, 76

index_vcf, 75, 76

is_tabix, 77

legacy_ids, 77

liftover, 78

list_sumstats, 79

load_ref_genome_data, 80

load_snp_loc_data, 81

logs_example, 81

make_allele_upper, 82

mapGenomeBuilds, 98

message_parallel, 83

messenger, 82

parse_dropped_chrom, 83

parse_dropped_duplicates, 84

parse_dropped_INFO, 84

parse_dropped_nonA1A2, 85

parse_dropped_nonBiallelic, 85

parse_dropped_nonRef, 86

parse_flipped, 86

parse_genome_build, 87

parse_idStandard, 87

parse_logs, 83–88, 88, 89–91

parse_pval_large, 88

parse_pval_neg, 89

parse_pval_small, 89

parse_report, 90

parse_snps_freq_05, 90

parse_snps_not_formatted, 91

parse_time, 91

preview_sumstats, 92

raw_ALSvcf, 92

raw_eduAttainOkbay, 93

read_header, 93

read_sumstats, 94

read_vcf, 95, 96, 99

read_vcf_genome, 97

read_vcf_info, 98

read_vcf_markername, 98

read_vcf_parallel, 99

read_vcf_pval, 100

register_cores, 101

remove_empty_cols, 101

report_summary, 102

scanVcfHeader, 98

select_api, 102

select_vcf_fields, 103

setorderv, 104

sort.GenomicRanges, 104

sort_coord_genomicranges, 105

sort_coords, 104

sort_coords_datatable, 104

standardise_header, 55, 105

sumstatsColHeaders, 106

supported_suffixes, 107

to_granges, 108

to_vranges, 108

unlist_dt, 109

validate_parameters, 109

VCF, 95, 96, 100

vcf2df, 113

write_sumstats, 115