

Package ‘PowerExplorer’

March 20, 2019

Title Power Estimation Tool for RNA-Seq and proteomics data

Version 1.3.1

URL <https://gitlab.utu.fi/CompBioMedNGSTools/PowerExplorer>

Description Estimate and predict power among groups and multiple sample sizes with simulated data, the simulations are operated based on distribution parameters estimated from the provided input dataset.

biocViews ImmunoOncology, RNASeq, Proteomics, DifferentialExpression, MultipleComparison, Sequencing, Coverage, ChIPSeq

Depends R (>= 3.5.0), SummarizedExperiment

Imports DESeq2, ROTS, vsn, stats, utils, methods, gridExtra, MASS, data.table, ggplot2, Biobase, S4Vectors, BiocParallel

Suggests knitr, rmarkdown

VignetteBuilder knitr

License Artistic-2.0

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1.9000

git_url <https://git.bioconductor.org/packages/PowerExplorer>

git_branch master

git_last_commit 35a944d

git_last_commit_date 2019-01-04

Date/Publication 2019-03-19

Author Xu Qiao [aut, cre],
Laura Elo [cph]

Maintainer Xu Qiao <xu.qiao@utu.fi>

R topics documented:

| | |
|---------------------------------|---|
| estimatePower | 2 |
| exampleObject | 3 |
| exampleProteomicsData | 4 |
| exampleRNASeqData | 4 |
| listEstPwr | 5 |

| | |
|--|---|
| listPredPwr | 5 |
| plotEstPwr | 6 |
| plotPredPwr | 7 |
| PowerExplorerStorage-class | 7 |
| predictPower | 8 |
| show,PowerExplorerStorage-method | 9 |

Index 10

| | |
|---------------|--|
| estimatePower | <i>Estimate Power of the Actual Data</i> |
|---------------|--|

Description

Estimate power of comparison between each two groups based on the data simulated from estimated normal distributions of entries in the entire dataset

Usage

```
estimatePower(inputObject, groupVec, isLogTransformed = FALSE,
  dataType = c("RNASeq", "Proteomics"), minLFC = 0.5, alpha = 0.05,
  ST = 100, seed = 123, enableROTS = FALSE, paraROTS = list(B = 1000, K
  = NULL, paired = FALSE, a1 = NULL, a2 = NULL, progress = FALSE),
  showProcess = FALSE, saveResultData = FALSE, parallel = FALSE,
  BPPARAM = bpparam())
```

Arguments

| | |
|------------------|---|
| inputObject | a numeric raw data matrix or SummarizedExperiment object |
| groupVec | a vector indicating the grouping of samples |
| isLogTransformed | logical; set to TRUE, if the input data is log transformed. |
| dataType | "RNASeq" or "Proteomics" indicates the data type of the input data matrix. |
| minLFC | the threshold for log ₂ fold change, entries with lower LFC are not included in the power calculation, set to 0 if no threshold is needed. |
| alpha | controlled false positive rate. |
| ST | the number of simulations of abundance data generation and repeated times of statistical test for each entry (>=100 recommended). |
| seed | an integer seed for the random number generator. |
| enableROTS | logical; if TRUE, Reproducibility-Optimized Test Statistic (ROTS) will be used as the statistical model. used as the statistical model. |
| paraROTS | a list object containing additional parameters passed to ROTS (if enabled), see ROTS . |
| showProcess | logical; if TRUE, show the detailed information of each simulation, used for debugging only. |
| saveResultData | logical; if TRUE, save the simulated data into RData with name pattern "simulated_Data_numRep_X_numSim_XXX_XXXXX.RData" |
| parallel | logical; if FALSE parallelization is disabled; if TRUE, parallelize calculations using BiocParallel . |
| BPPARAM | an optional argument object passed bplapply to indicate the registered cores, if parallel=TRUE. |

Value

a list of power estimates grouped in comparisons between each two groups

See Also

[predictPower](#) predict power with increasing sample sizes

Examples

```
# Example 1: a random generated Proteomics dataset (10 DE, 100 non-DE)
# Note: Simulation times(ST) is specified as 10 for shorter example runtime,
# ST > 50 is recommended
data(exampleProteomicsData)
dataMatrix <- exampleProteomicsData$dataMatrix
groupVec <- exampleProteomicsData$groupVec

# Run estimation without LFC filtration
resObject <- estimatePower(dataMatrix, groupVec,
                           dataType="Proteomics",
                           isLogTransformed=FALSE,
                           minLFC=0, alpha=0.05,
                           ST=10, seed=123)
```

exampleObject

An Example Predicted Power Object For Tests

Description

This is an example PowerExplorerStorage resulted from an example run on a publically available RNA-Seq datase containing the gene expression in C57BL/6J and DBA/2J Mouse Striatum

Usage

```
data(exampleObject)
```

Format

An object of class PowerExplorerStorage with 12152 rows and 21 columns.

Examples

```
data(exampleObject)

show(exampleObject)
plotEstPwr(exampleObject)
```

exampleProteomicsData *Randomly Generated Proteomics Dataset*

Description

This is a randomly generated proteomics dataset with 130 protein entries (rows) and 15 samples (columns) in 3 sample groups A, B and C, the log₂ fold change (LFC) between group B and A is specified as 1, between C and B is also 1, thus the LFC is 2 between C and A.

Usage

```
data(exampleProteomicsData)
```

Format

An list contains "dataMatrix" and "groupVec"

Examples

```
data(exampleProteomicsData)
head(exampleProteomicsData$dataMatrix)
```

exampleRNASeqData *Randomly Generated RNASeq Dataset*

Description

This is a randomly generated RNASeq dataset with 130 gene entries (rows) and 15 samples (columns) in 3 sample groups A, B and C, the log₂ fold change (LFC) between group B and A is specified as 1, between C and B is also 1, thus the LFC is 2 between C and A.

Usage

```
data(exampleRNASeqData)
```

Format

An list contains "dataMatrix" and "groupVec"

Examples

```
data(exampleRNASeqData)
head(exampleRNASeqData$dataMatrix)
```

| | |
|------------|-----------------------------|
| listEstPwr | <i>List Estimated Power</i> |
|------------|-----------------------------|

Description

show a top-list of power in numerical order, or list the power selected genes/proteins.

Usage

```
listEstPwr(inputObject, decreasing = TRUE, top = 20, selected = NA)
```

Arguments

| | |
|-------------|---|
| inputObject | the input inputObject. |
| decreasing | logical; TRUE, decreasing order; FALSE, increasing order. |
| top | the number of genes/proteins in the top list |
| selected | default as NA; specify as a list of geneID or protein ID to show power of a list of interested records. |

Value

a top list of power / power of a list of interested genes or proteins

Examples

```
data(exampleObject)
# show 10 top genes with high power (decreasing order)
listEstPwr(exampleObject, decreasing = TRUE, top = 10)
# show a list of interested genes
listEstPwr(exampleObject,
            selected = c("ENSMUSG00000000303",
                        "ENSMUSG000000087272",
                        "ENSMUSG000000089921"))
```

| | |
|-------------|-----------------------------|
| listPredPwr | <i>List Predicted Power</i> |
|-------------|-----------------------------|

Description

show a top-list of predicted power in numerical order, or list the power selected genes/proteins.

Usage

```
listPredPwr(inputObject, decreasing = TRUE, top = 20, selected = NA)
```

Arguments

| | |
|-------------|---|
| inputObject | the input inputObject. |
| decreasing | logical; TRUE, decreasing order; FALSE, increasing order. |
| top | the number of genes/proteins in the top list |
| selected | default as NA; specify as a list of geneID or protein ID to show power of a list of interested records. |

Value

a top list of power / power of a list of interested genes or proteins for each sample size

Examples

```
data(exampleObject)
# show 10 top genes with high power (decreasing order)
listPredPwr(exampleObject, decreasing = TRUE, top = 10)

# show a list of interested genes
listPredPwr(exampleObject,
             selected = c("ENSMUSG00000000303",
                          "ENSMUSG000000087272",
                          "ENSMUSG000000089921"))
```

plotEstPwr

Plot A Summary of Estimated Power

Description

Produce a plot to summary the power estimated by function [estimatePower](#), the plot function is called in [estimatePower](#), but using it manually is possible

Usage

```
plotEstPwr(inputObject)
```

Arguments

| | |
|-------------|--|
| inputObject | a result container object PowerExplorerStorage returned from estimatePower . |
|-------------|--|

Value

plot(s) of the summarised information on the estimated power

Examples

```
data(exampleObject)
plotEstPwr(exampleObject)
```

plotPredPwr

Observe Predicted Power Within Different LFC Scales

Description

With a complete power list and LFC list returned from `predictPower`, power estimates can be observed dynamically within specified LFC ranges.

Usage

```
plotPredPwr(inputObject, minLFC, maxLFC, LFCscale = 1)
```

Arguments

| | |
|-------------|--|
| inputObject | a result container object <code>PowerExplorerStorage</code> |
| minLFC | default as 0, the left edge of the LFC range within which genes will be included in the graph. |
| maxLFC | default as NA (the maximum value in data will be used) the right edge of the LFC range within which genes will be included in the graph. |
| LFCscale | the size of each unit when segmenting predicted power by LFC |

Value

plot(s) of power density under multiple sample sizes

Examples

```
# load an example object containing
# predicted power under different sample sizes
data(exampleObject)
plotPredPwr(exampleObject)
plotPredPwr(exampleObject)
#It is possible to observe power trend in different scales and ranges of LFCs
plotPredPwr(exampleObject, minLFC=0, maxLFC=2, LFCscale=0.5)
```

PowerExplorerStorage-class

PowerExplorer Object

Description

An extended `SummarizedExperiment` object to contain input `dataMatrix`, grouping information, estimated power, predicted power, fold change estimates and other estimation parameters.

predictPower *Estimate Power Under Increasing Sample Sizes*

Description

Similar to [estimatePower](#), power estimations are performed under multiple increasing sample sizes

Usage

```
predictPower(inputObject, groupVec, isLogTransformed = FALSE,
             dataType = c("RNASeq", "Proteomics"), enableROTS = FALSE,
             paraROTS = list(B = 1000, K = NULL, paired = FALSE, a1 = NULL, a2 = NULL,
                             progress = FALSE), minLFC = 0.5, rangeSimNumRep = NA, alpha = 0.05,
             ST = 100, seed = 123, parallel = FALSE, BPPARAM = bpparam(),
             showProcess = FALSE, saveResultData = FALSE)
```

Arguments

| | |
|------------------|---|
| inputObject | a numeric raw Proteomics abundance data matrix, in which rows correspond to proteins and columns correspond to samples. |
| groupVec | a vector indicating the grouping of samples |
| isLogTransformed | logical; logical; set to TRUE, if the input data is log transformed. |
| dataType | "RNASeq" or "Proteomics" indicates the data type of the input data matrix. |
| enableROTS | logical; if TRUE, Reproducibility-Optimized Test Statistic (ROTS) will be used as the statistical model. |
| paraROTS | a list object containing additional parameters passed to ROTS (if enabled), see ROTS . |
| minLFC | LFC threshold |
| rangeSimNumRep | a vector of sample sizes under which power will be estimated |
| alpha | controlled false positive rate. |
| ST | the number of simulations of abundance data generation and repeated times of statistical test for each protein (≥ 100 recommended). |
| seed | an integer seed for the random number generator. |
| parallel | logical; if FALSE parallelization is disabled; if TRUE, parallelize calculations using BiocParallel . |
| BPPARAM | an optional argument object passed bplapply to indicate the registered cores, if parallel=TRUE. |
| showProcess | logical; if TRUE, show the detailed information of each simulation, used for debugging only. |
| saveResultData | logical; if TRUE, save the simulated data into RData with name pattern "simulated_Data_numRep_X_numSim_XXX_XXXXXX.RData". |

Value

a list of power predictions for each sample size, grouped in comparisons between each two groups

See Also

[estimatePower](#) estimate power based on actual data

Examples

```
# Example 1: a random generated Proteomics dataset (10 DE, 100 non-DE)
data(exampleProteomicsData)
dataMatrix <- exampleProteomicsData$dataMatrix
groupVec <- exampleProteomicsData$groupVec

# Run estimation
# Note: Simulation times(ST) is specified as 5 for shorter example runtime
#       For better performance, ST > 50 is recommended
predictedPower <- predictPower(dataMatrix, groupVec,
                               isLogTransformed=FALSE,
                               dataType="Proteomics",
                               minLFC=0,
                               rangeSimNumRep=c(5, 10, 15),
                               alpha=0.05, ST=5, seed=123)
```

show,PowerExplorerStorage-method

show method for PowerExplorerStorage

Description

show method for PowerExplorerStorage

Usage

```
## S4 method for signature 'PowerExplorerStorage'
show(object)
```

Arguments

object a PowerExplorerStorage object as input

Value

a summary of input PowerExplorerStorage object

Methods (by class)

- PowerExplorerStorage: method for PowerExplorerStorage objects

Examples

```
data(exampleObject)
show(exampleObject)
```

Index

*Topic **datasets**

- exampleObject, 3
- exampleProteomicsData, 4
- exampleRNASeqData, 4

BiocParallel, 2, 8
bplapply, 2, 8

estimatePower, 2, 6, 8, 9
exampleObject, 3
exampleProteomicsData, 4
exampleRNASeqData, 4

listEstPwr, 5
listPredPwr, 5

plotEstPwr, 6
plotPredPwr, 7
PowerExplorerStorage, 6, 7
PowerExplorerStorage
(PowerExplorerStorage-class), 7
PowerExplorerStorage-class, 7
predictPower, 3, 7, 8

ROTS, 2, 8

show, PowerExplorerStorage-method, 9