

Package ‘motifStack’

December 8, 2023

Type Package

Version 1.47.0

Title Plot stacked logos for single or multiple DNA, RNA and amino acid sequence

Author Jianhong Ou, Michael Brodsky, Scot Wolfe and Lihua Julie Zhu

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Depends R (>= 2.15.1), methods, grid

Imports ade4, Biostrings, ggplot2, grDevices, graphics, htmlwidgets, stats, stats4, utils, XML, TFBSTools

Suggests Cairo, grImport, grImport2, BiocGenerics, MotifDb, RColorBrewer, BiocStyle, knitr, RUnit, rmarkdown, JASPAR2020

biocViews SequenceMatching, Visualization, Sequencing, Microarray, Alignment, ChIPchip, ChIPSeq, MotifAnnotation, DataImport

Description The motifStack package is designed for graphic representation of multiple motifs with different similarity scores. It works with both DNA/RNA sequence motif and amino acid sequence motif. In addition, it provides the flexibility for users to customize the graphic parameters such as the font type and symbol colors.

License GPL (>= 2)

Lazyload yes

VignetteBuilder knitr

RoxygenNote 7.2.3

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/motifStack>

git_branch devel

git_last_commit b4bcd75

git_last_commit_date 2023-10-24

Repository Bioconductor 3.19

Date/Publication 2023-12-07

Table of contents:

| | |
|--------------------------------|----|
| motifStack-package | 3 |
| AAmotifAlignment | 3 |
| browseMotifs | 4 |
| browseMotifs-shiny | 5 |
| calF | 6 |
| call | 6 |
| clusterMotifs | 7 |
| colorset | 7 |
| compare2profiles | 8 |
| compareProfiles | 9 |
| DNAmotifAlignment | 9 |
| DNAmotifToRNAmotif | 10 |
| dpGlobal | 11 |
| dpLocal | 11 |
| GeomMotif | 12 |
| geom_motif | 13 |
| getALLRscoreFromCounts | 15 |
| getDistance | 15 |
| getRankedUniqueMotifs | 16 |
| getScore | 17 |
| highlightCol | 17 |
| importMatrix | 18 |
| marker-class | 19 |
| matalign | 19 |
| mergeMotifs | 20 |
| motifCircos | 21 |
| motifCloud | 24 |
| motifGrob | 26 |
| motifHelust | 27 |
| motifPiles | 28 |
| motifSig-class | 31 |
| motifSignature | 32 |
| motifStack | 33 |
| ouNode-class | 34 |
| pcm-class | 35 |
| pfm-class | 37 |
| pfm2pwm | 39 |
| plotAffinityLogo | 40 |
| plotMotifLogo | 41 |
| plotMotifLogoA | 42 |
| plotMotifLogoStack | 43 |
| plotMotifLogoStackWithTree | 44 |
| plotMotifOverMotif | 45 |
| plotMotifStackWithPhylog | 46 |
| plotMotifStackWithRadialPhylog | 47 |
| plotXaxis | 50 |

| | |
|----------------------------|----|
| plotYaxis | 51 |
| psam-class | 51 |
| pssm-class | 53 |
| readPCM | 54 |
| reorderUPGMAtree | 55 |
| traceBackGlobal | 56 |
| traceBackLocal | 56 |

| | |
|--------------|-----------|
| Index | 58 |
|--------------|-----------|

| | |
|--------------------|---|
| motifStack-package | <i>Plot stacked logos for single or multiple DNA, RNA and amino acid sequence</i> |
|--------------------|---|

Description

motifStack is a package that is able to draw amino acid sequence as easy as to draw DNA/RNA sequence. motifStack provides the flexibility for users to select the font type and symbol colors. motifStack is designed for graphical representation of multiple motifs.

Author(s)

Jianhong Ou and Lihua Julie Zhu

Maintainer: Jianhong Ou <jianhong.ou@umassmed.edu>

| | |
|------------------|------------------------|
| AAmotifAlignment | <i>align AA motifs</i> |
|------------------|------------------------|

Description

align AA motifs for plotting motifs stack

Usage

```
AAmotifAlignment(pcms, threshold = 0.4, minimalConsensus = 0)
```

Arguments

| | |
|------------------|---|
| pcms | a list of position frequency matrices, pfms must be a list of class pcm |
| threshold | information content cutoff threshold for useful postions |
| minimalConsensus | minimal length of consensus for alignment |

Value

a list of aligned motifs

Examples

```
pcms<-importMatrix(system.file("extdata", "prot.meme", package="motifStack"),
                  format="meme", to="pfm")
motifs<-AAMotifAlignment(pcms)
```

| | |
|--------------|----------------------|
| browseMotifs | <i>browse motifs</i> |
|--------------|----------------------|

Description

browse motifs in a web browser

Usage

```
browseMotifs(
  pfms,
  phylog,
  layout = c("tree", "cluster", "radialPhylog"),
  nodeRadius = 2.5,
  baseWidth = 12,
  baseHeight = 30,
  xaxis = TRUE,
  yaxis = TRUE,
  width = NULL,
  height = NULL,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| pfms | a list of pfm |
| phylog | layout type. see GraphvizLayouts |
| layout | layout type. Could be tree, cluster or radialPhylog. |
| nodeRadius | node radius, default 2.5px. |
| baseWidth, baseHeight | width and height of each alphabet of the motif logo. |
| xaxis, yaxis | plot x-axis or y-axis or not in the motifs. |
| width | width of the figure |
| height | height of the figure |
| ... | parameters not used |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

Examples

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
                          gsub("[^a-zA-Z0-9]", "_",
                              gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 10)
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  browseMotifs(pfms)
}

```

browseMotifs-shiny *Shiny bindings for browseMotifs*

Description

Output and render functions for using browseMotifs within Shiny applications and interactive Rmd documents.

Usage

```
browseMotifsOutput(outputId, width = "100%", height = "400px")
```

```
renderbrowseMotifs(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

| | |
|---------------|--|
| outputId | output variable to read from |
| width, height | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |
| expr | An expression that generates a browseMotifs |
| env | The environment in which to evaluate expr. |
| quoted | Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable. |

calF *calculate frequency*

Description

calculate frequency

Usage

```
calF(count, P = rep(1/length(count), length(count)), pseudo = 1)
```

Arguments

| | |
|--------|------------------------|
| count | position counts |
| P | background probability |
| pseudo | pseudocount |

Value

numeric(1)

calI *calculate I'*

Description

calculate I'

Usage

```
calI(freq1, freq2, P)
```

Arguments

| | |
|-------|--|
| freq1 | position frequency for matrix 1 position j |
| freq2 | position frequency for matrix 2 position j |
| P | background of profile1 |

Value

numeric(1)

| | |
|---------------|-----------------------|
| clusterMotifs | <i>cluster motifs</i> |
|---------------|-----------------------|

Description

A help function to do matalign and motifHclust in one function.

Usage

```
clusterMotifs(motifs, ...)
```

Arguments

| | |
|--------|--|
| motifs | A list of pcms of pfms. |
| ... | parameter to be passed to matalign function. |

Value

An object of hclust.

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){  
  fp <- system.file("extdata", package="motifStack")  
  fs <- dir(fp, "pcm$")  
  pcms <- importMatrix(file.path(fp, fs), format="pcm")  
  hc <- clusterMotifs(pcms)  
}
```

| | |
|----------|--|
| colorset | <i>retrieve color setting for logo</i> |
|----------|--|

Description

retrieve color setting for logo

Usage

```
colorset(alphabet = "DNA", colorScheme = "auto")
```

Arguments

| | |
|-------------|--|
| alphabet | character, 'DNA', 'RNA' or 'AA' |
| colorScheme | 'auto', 'charge', 'chemistry', 'classic' or 'hydrophobicity' for AA, 'auto', 'base-pairing', or 'blindnessSafe' for DNA ro RNA |

Value

A character vector of color scheme

Examples

```
col <- colorset("AA", "hydrophobicity")
```

| | |
|------------------|-----------------------------|
| compare2profiles | <i>compare two profiles</i> |
|------------------|-----------------------------|

Description

compare two pcm object

Usage

```
compare2profiles(  
  pcm1,  
  pcm2,  
  method = c("Smith-Waterman", "Needleman-Wunsch"),  
  pseudo = 1  
)
```

Arguments

| | |
|------------|--|
| pcm1, pcm2 | object of pcm |
| method | Alignment method. "Smith-Waterman" or "Needleman-Wunsch". Default is "Smith-Waterma" |
| pseudo | pseudocount |

Value

a list with names: motif1, motif2, alignmentScore, startPos1, startPos2, endPos1, endPos2, alignmentLength.

| | |
|-----------------|----------------------|
| compareProfiles | <i>comapre w pcm</i> |
|-----------------|----------------------|

Description

compare two pcm objects

Usage

```
compareProfiles(  
  pcm1,  
  pcm2,  
  method = c("Smith-Waterman", "Needleman-Wunsch"),  
  pseudo = 1,  
  revcomp = TRUE  
)
```

Arguments

| | |
|------------|--|
| pcm1, pcm2 | object of pcm |
| method | Alignment method. "Smith-Waterman" or "Needleman-Wunsch". Default is "Smith-Waterma" |
| pseudo | pseudocount |
| revcomp | Check reverseComplement or not. |

Value

a list with names: motif1, motif2, alignmentScore, startPos1, startPos2, endPos1, endPos2, alignmentLength.

| | |
|-------------------|-------------------------|
| DNAmotifAlignment | <i>align DNA motifs</i> |
|-------------------|-------------------------|

Description

align DNA motifs for plotting motifs stack

Usage

```
DNAmotifAlignment(  
  pfms,  
  threshold = 0.4,  
  minimalConsensus = 0,  
  rcpostfix = "(RC)",  
  revcomp = rep(TRUE, length(pfms))  
)
```

Arguments

| | |
|------------------|---|
| pfms | a list of position frequency matrices, pfms must be a list of class pfm or psam |
| threshold | information content cutoff threshold for useful postions |
| minimalConsensus | minimal length of consensus for alignment |
| rcpostfix | the postfix for reverse complements |
| revcomp | a logical vector to indicates whether the reverse complemet should be involved into alignment |

Value

a list of aligned motifs

Examples

```
pcms<-readPCM(file.path(find.package("motifStack"), "extdata"),"pcm$")
motifs<-lapply(pcms,pcm2pfm)
motifs<-DNAmotifAlignment(motifs)
```

DNAmotifToRNAmotif *convert DNA motif into RNA motif*

Description

convert DNA motif into RNA motif

Usage

```
DNAmotifToRNAmotif(pfm)
```

Arguments

pfm An object of "pcm" or "pfm"

Value

An object of "pcm" or "pfm" of RNA motif

Examples

```
motifs<-importMatrix(dir(file.path(find.package("motifStack"),
                               "extdata"),"pcm$", full.names = TRUE))
rnaMotifs <- DNAmotifToRNAmotif(motifs)
```

dpGlobal *Global alignment version*

Description

Global alignment version

Usage

dpGlobal(score, m, n)

Arguments

| | |
|-------|---------------------------|
| score | ALLR scores, m x n matrix |
| m, n | matrix width |

Value

score matrix

dpLocal *Dynamic programming function, local version*

Description

Dynamic programming function, local version

Usage

dpLocal(score, m, n)

Arguments

| | |
|-------|---------------------------|
| score | ALLR scores, m x n matrix |
| m, n | matrix width |

Value

score matrix

GeomMotif

GeomMotif object

Description

GeomMotif object is a ggproto object.

Usage

GeomMotif

Format

The format is: Classes 'GeomMotif', 'Geom', 'ggproto', 'gg' <ggproto object: Class GeomMotif, Geom, gg> aesthetics: function default_aes: uneval draw_group: function draw_key: function draw_layer: function draw_panel: function extra_params: na.rm handle_na: function non_missing_aes: optional_aes: parameters: function required_aes: xmin ymin xmax ymax motif setup_data: function use_defaults: function super: <ggproto object: Class Geom, gg>

See Also

geom_motif

Examples

```
pcm <- read.table(file.path(find.package("motifStack"),
                           "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- new("pcm", mat=as.matrix(pcm), name="bin_SOLEXA")

df <- data.frame(xmin=c(.25, .25), ymin=c(.25, .75), xmax=c(.75, .75), ymax=c(.5, 1))
df$motif <- list(pcm2pfm(motif), pcm2pfm(motif))

library(ggplot2)

ggplot(df, aes(xmin=xmin, ymin=ymin, xmax=xmax, ymax=ymax, motif=motif)) +
  geom_motif() + theme_bw() + ylim(0, 1) + xlim(0, 1)
```

 geom_motif

geom_motif

Description

geom_motif uses the locations of the four corners (xmin, xmax, ymin and ymax) to plot motifs.

Usage

```
geom_motif(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  ic.scale = TRUE,
  use.xy = FALSE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

Arguments

| | |
|-------------|---|
| mapping | Set of aesthetic mappings created by aes() or aes_(). If specified and inherit.aes = TRUE (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | The data to be displayed in this layer. |
| stat | The statistical transformation to use on the data for this layer, as a string. |
| position | Position adjustment, either as a string, or the result of a call to a position adjustment function. |
| ... | Other arguments passed on to layer(). |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| use.xy | logical If TRUE, the required aesthetics will be x, y, width, height, and motif. Otherwise, xmin, ymin, xmax, ymax and motif. |
| show.legend | Not used. |
| inherit.aes | If FALSE, overrides the default aesthetics, rather than combining with them. |

Value

a layer that contains GeomMotif object.

Aesthetics

geom_motif() understands the following aesthetics (required aesthetics are in bold):

- xmin
- xmax
- ymin
- ymax
- motif
- angle
- fontfamily
- fontface

OR

- x
- y
- width
- height
- motif
- angle
- fontfamily
- fontface

Author(s)

Jianhong Ou

Examples

```
pcm <- read.table(file.path(find.package("motifStack"),
                           "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- new("pcm", mat=as.matrix(pcm), name="bin_SOLEXA")

df <- data.frame(xmin=c(.25, .25), ymin=c(.25, .75), xmax=c(.75, .75), ymax=c(.5, 1))
df$motif <- list(pcm2pfm(motif), pcm2pfm(motif))

library(ggplot2)
ggplot(df, aes(xmin=xmin, ymin=ymin, xmax=xmax, ymax=ymax, motif=motif)) +
  geom_motif() + theme_bw() + ylim(0, 1) + xlim(0, 1)
```

getALLRscoreFromCounts
calculate ALLR from counts

Description

calculate ALLR from counts

Usage

getALLRscoreFromCounts(count1, count2, P1, P2, pseudo)

Arguments

count1, count2 count in position j for matrix 1 or 2
P1, P2 background for matrix 1 or 2
pseudo pseudocount

Value

numeric(1) of ALLR

getDistance *Calculate distances between two profiles*

Description

Calculate distances between two profiles

Usage

getDistance(hsp, count1, count2, P1, P2, pseudo)

Arguments

hsp output of traceBack function
count1, count2 motif profile 1 or 2
P1, P2 background of profile 1 or 2
pseudo pseudocount

Value

full distance and aligned distance.

getRankedUniqueMotifs *get the unique motif in each category grouped by distance*

Description

to get the unique motif in a given category, eg by species.

Usage

```
getRankedUniqueMotifs(phylog, attr)
```

Arguments

| | |
|--------|---------------------------------------|
| phylog | an object of class phylog |
| attr | attribute used for category of motifs |

Value

return a list:

| | |
|------------|--|
| uni.rank | unique motif ranks |
| uni.length | length of unique motif grouped by distance |
| uni.list | unique motif names grouped by distance |

Author(s)

Jianhong Ou

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  matrix.human <- query(MotifDb, "Hsapiens")
  pfms <- c(as.list(matrix.fly), as.list(matrix.human))
  pfms <- pfms[sample(seq_along(pfms), 100)]
  hc <- clusterMotifs(pfms)
  library(ade4)
  phylog <- ade4::hclust2phylog(hc)
  leaves <- names(phylog$leaves)
  attr <- gsub("^(.*)_*.*$", "\\1", leaves)
  getRankedUniqueMotifs(phylog, attr)
}
```

| | |
|----------|---|
| getScore | <i>Calculate pair_wise position score</i> |
|----------|---|

Description

Calculate pair_wise position score

Usage

```
getScore(pcm1, pcm2, pseudo = 1)
```

Arguments

| | |
|------------|---------------|
| pcm1, pcm2 | object of pcm |
| pseudo | pseudocount |

Value

A score matrix with nrow of ncol of pcm1 and ncol of ncol of pcm2.

| | |
|--------------|--|
| highlightCol | <i>add alpha transparency value to a color</i> |
|--------------|--|

Description

An alpha transparency value can be specified to a color, in order to get better color for background.

Usage

```
highlightCol(col, alpha = 0.5)
```

Arguments

| | |
|-------|--|
| col | vector of any of the three kinds of R color specifications, i.e., either a color name (as listed by colors()), a hexadecimal string of the form "#rrggbb" or "#rrggbbaa" (see rgb), or a positive integer i meaning palette()[i] . |
| alpha | a value in [0, 1] |

Value

a vector of colors in hexadecimal string of the form "#rrggbbaa".

Author(s)

Jianhong Ou

Examples

```
highlightCol(1:5, 0.3)
highlightCol(c("red", "green", "blue"), 0.3)
```

importMatrix

import motifs from local files

Description

Import the motifs into [pcm-class](#) or [pfm-class](#) from files exported from Transfac, CisBP, and JASPAR.

Usage

```
importMatrix(
  filenames,
  format = c("auto", "pfm", "cm", "pcm", "meme", "transfac", "jaspar", "scpd", "cisbp",
            "psam", "xmatrix"),
  to = c("auto", "pcm", "pfm", "pssm", "psam")
)
```

Arguments

| | |
|-----------|---|
| filenames | filename, an XMatrixList object, or an XMatrix object to be imported. |
| format | file format |
| to | import to pcm-class or pfm-class |

Value

a list of object [pcm-class](#) or [pfm-class](#)

Author(s)

Jianhong Ou

Examples

```
path <- system.file("extdata", package = "motifStack")
importMatrix(dir(path, "*.pcm", full.names = TRUE))
```

| | |
|--------------|---------------------|
| marker-class | <i>Class marker</i> |
|--------------|---------------------|

Description

An object of class "marker" represents a marker in a motif

Usage

```
## S4 method for signature 'marker'  
x$name
```

Arguments

| | |
|------|----------------------------|
| x | A marker object |
| name | slot name of marker object |

Objects from the Class

Objects can be created by calls of the form `new("marker", type, start, stop, label, gp)`.

Examples

```
new("marker", type="rect", start=c(2, 4), gp=gpar(lty=3))
```

| | |
|--------|-----------------------|
| malign | <i>Matrix Aligner</i> |
|--------|-----------------------|

Description

Matrix Aligner is modified from Malign-v4a. Malign-v4a is a program to compare two positional specific matrices. The author of Malign-v4a is Ting Wang and Gary Stormo.

Usage

```
malign(  
  pcms,  
  method = c("Smith-Waterman", "Needleman-Wunsch"),  
  pseudo = 1,  
  revcomp = TRUE,  
  ...  
)
```

Arguments

| | |
|---------|--|
| pcms | A list of pcm |
| method | Alignment method. "Smith-Waterman" or "Needleman-Wunsch". Default is "Smith-Waterma" |
| pseudo | pseudocount |
| revcomp | Check reverseComplement or not. |
| ... | Not use. |

Value

A data frame with alignment information. The column names are motif1, motif2, alignmentScore, startPos1, startPos2, endPos1, endPos2, alignmentLength.

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  fp <- system.file("extdata", package="motifStack")
  fs <- dir(fp, "pcm$")
  pcms <- importMatrix(file.path(fp, fs), format="pcm")
  matalign(pcms)
}
```

mergeMotifs

merge multiple motifs

Description

merge multiple motifs by calculate mean of each position

Usage

```
mergeMotifs(..., bgNoise = NA)
```

Arguments

| | |
|---------|---|
| ... | pcm or pfm objects |
| bgNoise | if it is not NA, test will using a background by Dirichlet(1)-distributed random frequencies with weight bg.noise. The value of bgNoise should be a number in the range of 0 to 1, eg. 0.05 |

Value

a [pfm](#) object

Author(s)

Jianhong Ou

Examples

```
pcms<-readPCM(file.path(find.package("motifStack"), "extdata"),"pcm$")
mergeMotifs(pcms)
```

| | |
|-------------|---|
| motifCircos | <i>plot sequence logo stacks with a radial phylogenetic tree and multiple color rings</i> |
|-------------|---|

Description

plot sequence logo stacks with a radial phylogenetic tree and multiple color rings. The difference from plotMotifStackWithRadialPhylog is that it has more color setting and one more group of pfms.

Usage

```
motifCircos(
  phylog,
  pfms = NULL,
  pfms2 = NULL,
  R = 2.5,
  r.tree = 1,
  col.tree.bg = NULL,
  col.tree.bg.alpha = 1,
  cnodes = 0,
  labels.nodes = names(phylog$nodes),
  clabel.nodes = 0,
  r.leaves = NA,
  cleaves = 1,
  labels.leaves = names(phylog$leaves),
  clabel.leaves = 1,
  col.leaves = rep("black", length(labels.leaves)),
  col.leaves.bg = NULL,
  col.leaves.bg.alpha = 1,
  r.pfms = NA,
  r.pfms2 = NA,
  r.rings = 0,
  col.rings = list(),
  col.inner.label.circle = NULL,
  inner.label.circle.width = 0.02,
  col.outer.label.circle = NULL,
  outer.label.circle.width = 0.02,
  draw.box = FALSE,
  clockwise = FALSE,
  init.angle = if (clockwise) 90 else 0,
  angle = 360,
  pfmNameSplitter = ";",
```

```

rcpostfix = "(RC)",
motifScale = c("linear", "logarithmic", "none"),
ic.scale = TRUE,
plotIndex = FALSE,
IndexCol = "black",
IndexCex = 0.8,
groupDistance = NA,
groupDistanceLineCol = "red",
plotAxis = FALSE
)

```

Arguments

| | |
|--------------------------|--|
| phylog | an object of class phylog |
| pfms | a list of objects of class pfm |
| pfms2 | a list of objects of class pfm |
| R | radius of canvas |
| r.tree | half width of the tree |
| col.tree.bg | a vector of colors for tree background |
| col.tree.bg.alpha | alpha value [0, 1] of colors for tree background |
| cnodes | a character size for plotting the points that represent the nodes, used with par("cex")*cnodes. If zero, no points are drawn |
| labels.nodes | a vector of strings of characters for the nodes labels |
| clabel.nodes | a character size for the nodes labels, used with par("cex")*clabel.nodes. If zero, no nodes labels are drawn |
| r.leaves | width of the leaves |
| cleaves | a character size for plotting the points that represent the leaves, used with par("cex")*cleaves. If zero, no points are drawn |
| labels.leaves | a vector of strings of characters for the leaves labels |
| clabel.leaves | a character size for the leaves labels, used with par("cex")*clabel.leaves |
| col.leaves | a vector of colors for leaves labels |
| col.leaves.bg | a vector of colors for background of leaves labels |
| col.leaves.bg.alpha | alpha value [0, 1] for the colors of background of leaves labels |
| r.pfms | width of the pfms |
| r.pfms2 | width of the pfms2 |
| r.rings | a vector of width of color rings |
| col.rings | a list of color rings |
| col.inner.label.circle | a vector of colors for inner circle of pfms |
| inner.label.circle.width | width for inner circle of pfms |

| | |
|---------------------------------------|--|
| <code>col.outer.label.circle</code> | a vector of colors for outer circle of pfms |
| <code>outer.label.circle.width</code> | width for outer circle of pfms |
| <code>draw.box</code> | if TRUE draws a box around the current plot with the function <code>box()</code> |
| <code>clockwise</code> | a logical value indicating if slices are drawn clockwise or counter clockwise |
| <code>init.angle</code> | number specifying the starting angle (in degrees) for the slices. Defaults to 0 (i.e., '3 o'clock') unless <code>clockwise</code> is true where <code>init.angle</code> defaults to 90 (degrees), (i.e., '12 o'clock') |
| <code>angle</code> | number specifying the angle (in degrees) for phylogenetic tree. Defaults 360 |
| <code>pfmNameSplitter</code> | splitter when name of pfms/pfms2 contain multiple node of labels.leaves |
| <code>rcpostfix</code> | the postfix for reverse complements |
| <code>motifScale</code> | the scale of logo size |
| <code>ic.scale</code> | logical. If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| <code>plotIndex</code> | logical. If TRUE, will plot index number in the motifLogo which can help user to describe the motifLogo |
| <code>IndexCol</code> | The color of the index number when <code>plotIndex</code> is TRUE. |
| <code>IndexCex</code> | The cex of the index number when <code>plotIndex</code> is TRUE. |
| <code>groupDistance</code> | show <code>groupDistance</code> on the draw |
| <code>groupDistanceLineCol</code> | <code>groupDistance</code> line color, default: red |
| <code>plotAxis</code> | logical. If TRUE, will plot distance axis. |

Value

none

Author(s)

Jianhong Ou

See Also

[plotMotifStackWithRadialPhylog](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
```

```

        gsub("[^a-zA-Z0-9]", "_",
            gsub("(_[0-9]+)$", "", names(motifs))))
motifs <- motifs[unique(names(motifs))]
pfms <- sample(motifs, 50)
hc <- clusterMotifs(pfms)
library(ade4)
phylog <- ade4::hclust2phylog(hc)
leaves <- names(phylog$leaves)
pfms <- pfms[leaves]
pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
pfms <- DNAmotifAlignment(pfms, minimalConsensus=3)
library(RColorBrewer)
color <- brewer.pal(12, "Set3")
motifCircos(phylog, pfms, cleaves = 0.5, clabel.leaves = 0.7,
            col.tree.bg=rep(color, each=5),
            col.leaves=rep(color, each=5),
            r.rings=c(0.02, 0.03, 0.04),
            col.rings=list(sample(colors(), 50),
                            sample(colors(), 50),
                            sample(colors(), 50)))
}

```

motifCloud

plot a DNA sequence logo cloud

Description

Plot a DNA sequence logo cloud

Usage

```

motifCloud(
  motifSig,
  rcpostfix = "(RC)",
  layout = c("rectangles", "cloud", "tree"),
  scale = c(6, 0.5),
  rot.per = 0.1,
  draw.box = TRUE,
  draw.freq = TRUE,
  box.col = "gray",
  freq.col = "gray",
  group.col = NULL,
  groups = NULL,
  draw.legend = FALSE,
  font = "sans",
  ic.scale = TRUE
)

```


Arguments

| | |
|-------------|---|
| motifSig | an object of class motifSig |
| rcpostfix | postfix for reverse-complement motif names, default: (RC) |
| layout | layout of the logo cloud, rectangles, cloud or tree |
| scale | A vector of length 2 indicating the range of the size of the sequence logo. |
| rot.per | proportion sequence logo with 90 degree rotation. Only work for "cloud" layout |
| draw.box | draw box for each sequence logo or not |
| draw.freq | label frequency of each signature or not |
| box.col | color of box for each sequence logo |
| freq.col | color of frequency label |
| group.col | color setting for groups |
| groups | a named vectors of motif groups |
| draw.legend | draw group color legend or not |
| font | font of logo |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |

Value

none

Examples

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
                           gsub("[^a-zA-Z0-9]", "_",
                                  gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 50)
  hc <- clusterMotifs(pfms)
  library(ade4)
  phylog <- ade4::hclust2phylog(hc)
  leaves <- names(phylog$leaves)
  pfms <- pfms[leaves]
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  motifSig <- motifSignature(pfms, phylog, cutoffPval=0.0001)
  motifCloud(motifSig)
}

```

 motifGrob

*Motif Grob***Description**

This function create a motif grob.

Usage

```
motifGrob(
  pfm,
  x = unit(0.5, "npc"),
  y = unit(0.5, "npc"),
  width = unit(1, "npc"),
  height = unit(1, "npc"),
  angle = 0,
  ic.scale = TRUE,
  default.units = "native",
  name = NULL,
  gp = gpar(fontfamily = "sans", fontface = "bold")
)
```

Arguments

| | |
|---------------|---|
| pfm | an object of pfm |
| x | A numeric vector or unit object specifying x-values. |
| y | A numeric vector or unit object specifying y-values. |
| width | A numeric vector or unit object specifying width. |
| height | A numeric vector or unit object specifying height. |
| angle | A numeric value indicating the angle of rotation of the motif. Positive values indicate the amount of rotation, in degrees, anticlockwise from the positive x-axis. |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| default.units | A string indicating the default units to use if x, y, width, or height are only given as numeric vectors. |
| name | A character value to uniquely identify the motifGrob once it has been pushed onto the grob tree. |
| gp | A gpar object, typically the output from a call to the function gpar. The list will be used as parameter of plotMotifLogoA. |

Value

An gTree object.

Author(s)

Jianhong Ou

Examples

```
pcm<-matrix(runif(40,0,100),nrow=4,ncol=10)
pfm<-pcm2pfm(pcm)
rownames(pfm)<-c("A","C","G","T")
motif <- new("pfm", mat=pfm, name="bin_SOLEXA")
motifGrob(motif)
```

motifHclust

Hierarchical Clustering motifs

Description

functions to perform clustering of output of matalign

Usage

```
motifHclust(align, ...)
```

Arguments

`align` output of matalign, used to generate distance matrix.
`...` parameter to pass to the [hclust](#).

Value

An object of `hclust`.

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  fp <- system.file("extdata", package="motifStack")
  fs <- dir(fp, "pcm$")
  pcms <- importMatrix(file.path(fp, fs), format="pcm")
  align <- matalign(pcms)
  hc <- motifHclust(align, method="average")
}
```

| | |
|------------|--|
| motifPiles | <i>plot sequence logo stacks with a linear phylogenetic tree and multiple color sets</i> |
|------------|--|

Description

plot sequence logo stacks with a linear phylogenetic tree and multiple color sets.

Usage

```
motifPiles(  
  phylog,  
  pfms = NULL,  
  pfms2 = NULL,  
  r.tree = 0.45,  
  col.tree = NULL,  
  cnodes = 0,  
  labels.nodes = names(phylog$nodes),  
  clabel.nodes = 0,  
  cleaves = 0.2,  
  labels.leaves = names(phylog$leaves),  
  clabel.leaves = 1,  
  col.leaves = rep("black", length(labels.leaves)),  
  col.leaves.bg = NULL,  
  col.leaves.bg.alpha = 1,  
  r.pfms = NA,  
  r.pfms2 = NA,  
  motifScale = c("logarithmic", "linear", "none"),  
  col.pfms = NULL,  
  col.pfms.width = 0.02,  
  col.pfms2 = NULL,  
  col.pfms2.width = 0.02,  
  r.anno = 0,  
  col.anno = list(),  
  pfmNameSplitter = ";",  
  rcpostfix = "(RC)",  
  ic.scale = TRUE,  
  plotIndex = FALSE,  
  IndexCol = "black",  
  IndexCex = 0.8,  
  groupDistance = NA,  
  groupDistanceLineCol = "red"  
)
```

Arguments

phylog an object of class phylog

| | |
|----------------------|--|
| pfms | a list of objects of class pfm |
| pfms2 | a list of objects of class pfm |
| r.tree | width of the tree |
| col.tree | a vector of colors for tree |
| cnodes | a character size for plotting the points that represent the nodes, used with <code>par("cex")*cnodes</code> . If zero, no points are drawn |
| labels.nodes | a vector of strings of characters for the nodes labels |
| clabel.nodes | a character size for the nodes labels, used with <code>par("cex")*clabel.nodes</code> . If zero, no nodes labels are drawn |
| cleaves | a character size for plotting the points that represent the leaves, used with <code>par("cex")*cleaves</code> . If zero, no points are drawn |
| labels.leaves | a vector of strings of characters for the leaves labels |
| clabel.leaves | a character size for the leaves labels, used with <code>par("cex")*clabel.leaves</code> |
| col.leaves | a vector of colors for leaves labels |
| col.leaves.bg | a vector of colors for background of leaves labels |
| col.leaves.bg.alpha | alpha value [0, 1] for the colors of background of leaves labels |
| r.pfms | width of the pfms |
| r.pfms2 | width of the pfms2 |
| motifScale | the scale of logo size |
| col.pfms | a vector of colors for inner pile of pfms |
| col.pfms.width | width for inner pile of pfms |
| col.pfms2 | a vector of colors for outer pile of pfms |
| col.pfms2.width | width for outer pile of pfms |
| r.anno | a vector of width of color sets |
| col.anno | a list of color sets |
| pfmNameSplitter | splitter when name of pfms/pfms2 contain multiple node of labels.leaves |
| rpostfix | the postfix for reverse complements |
| ic.scale | logical. If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| plotIndex | logical. If TRUE, will plot index number in the motifLogo which can help user to describe the motifLogo |
| IndexCol | The color of the index number when plotIndex is TRUE. |
| IndexCex | The cex of the index number when plotIndex is TRUE. |
| groupDistance | show groupDistance on the draw |
| groupDistanceLineCol | groupDistance line color, default: red |

Value

none

Author(s)

Jianhong Ou

See Also[motifCircos](#)**Examples**

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
                          gsub("[^a-zA-Z0-9]", "_",
                              gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 50)
  hc <- clusterMotifs(pfms)
  library(ade4)
  phylog <- ade4::hclust2phylog(hc)
  leaves <- names(phylog$leaves)
  pfms <- pfms[leaves]
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  pfms <- DNAmotifAlignment(pfms, minimalConsensus=3)
  library(RColorBrewer)
  color <- brewer.pal(12, "Set3")
  motifPiles(phylog, pfms, cleaves = 0.5, clabel.leaves = 0.7,
             col.leaves=rep(color, each=5),
             col.leaves.bg = sample(colors(), 50),
             col.tree=rep(color, each=5),
             r.anno=c(0.02, 0.03, 0.04),
             col.anno=list(sample(colors(), 50),
                          sample(colors(), 50),
                          sample(colors(), 50)))
}

```

| | |
|----------------|------------------|
| motifSig-class | Class "motifSig" |
|----------------|------------------|

Description

An object of class "motifSig" represents the output of function [motifSignature](#) methods for motifSig objects.

Usage

```
signatures(object)
```

```
frequence(object)
```

```
nodelist(object)
```

```
sigColor(object)
```

```
## S4 method for signature 'motifSig'
x$name
```

Arguments

| | |
|--------|------------------------------|
| object | An object of class motifSig. |
| x | A motifSig object |
| name | slot name of motifSig object |

Objects from the Class

Objects can be created by calls of the form `new("motifSig", signature, freq, nodelist, gpcol)`.

Methods

signatures signature(object = "motifSig") return the signatures of motifSig

frequence signature(object = "motifSig") return the frequency of motifSig

nodelist signature(object = "motifSig") return the nodelist of motifSig

sigColor signature(object = "motifSig") return the group color sets of motifSig

\$, \$<- Get or set the slot of [motifSig](#)

motifSignature *get signatures from motifs*

Description

extract signatures from multiple motifs by distance calculated from STAMP

Usage

```
motifSignature(  
  pfms,  
  phylog,  
  cutoffPval,  
  groupDistance,  
  rcpostfix = "(RC)",  
  min.freq = 2,  
  trim = 0.2,  
  families = list(),  
  sort = TRUE  
)
```

Arguments

| | |
|---------------|---|
| pfms | a list of objects of class pfm |
| phylog | an object of class phylog |
| cutoffPval | pvalue for motifs to merge. |
| groupDistance | maximal distance of motifs in the same group |
| rcpostfix | postfix for reverse-complement motif names, default: (RC) |
| min.freq | signatures with frequency below min.freq will not be plotted |
| trim | minimal information content for each position of signature |
| families | for each family, the motif number in one signature should only count as 1 |
| sort | sort the signatures by frequency or not. |

Value

an Object of class [motifSig](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){  
  library("MotifDb")  
  matrix.fly <- query(MotifDb, "Dmelanogaster")  
  motifs <- as.list(matrix.fly)  
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",  
                        names(motifs), fixed=TRUE)]
```



```

names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                    gsub("_FBgn[0-9]+$", "",
                        gsub("[^a-zA-Z0-9]", "_",
                            gsub("(_[0-9]+)$", "", names(motifs)))))
motifs <- motifs[unique(names(motifs))]
pfms <- sample(motifs, 50)
hc <- clusterMotifs(pfms)
library(ade4)
phylog <- ade4::hclust2phylog(hc)
leaves <- names(phylog$leaves)
pfms <- pfms[leaves]
pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
  new("pfm",mat=.ele, name=.name)})
motifSig <- motifSignature(pfms, phylog, cutoffPval=0.0001)
}

```

motifStack

plot a DNA sequence logo stack

Description

Plot a DNA sequence logo stack

Usage

```

motifStack(
  pfms,
  layout = c("stack", "treeview", "phylog", "radialPhylog"),
  reorder = TRUE,
  ...
)

```

Arguments

| | |
|---------|--|
| pfms | a list of objects of class pfm |
| layout | layout of the logo stack, stack, treeview or radialPhylog |
| reorder | logical(1). Default TRUE. Set to FALSE will do alignment but keep the order of the pfms. This parameter only work for stack layout. |
| ... | any parameters could to pass to plotMotifLogoStack , plotMotifLogoStackWithTree , plotMotifStackWithPhylog or plotMotifStackWithRadialPhylog |

Value

return a list contains pfms and phylog

Examples

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
                           gsub("[^a-zA-Z0-9]", "_",
                                   gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 50)
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  motifStack(pfms, "radialPhylog")

  ## AA motifs
  pcms<-importMatrix(system.file("extdata", "prot.meme",
                                package="motifStack"),
                    format="meme", to="pfm")
  motifStack(pcms[1:5])
  motifStack(pcms[1:5], reorder=FALSE)
}

```

ouNode-class

Class ouNode**Description**

An object of class "ouNode" represents a motif node in a cluster tree

Usage

```
## S4 method for signature 'ouNode'
x$name
```

Arguments

| | |
|------|----------------------------|
| x | A ouNode object |
| name | slot name of ouNode object |

Objects from the Class

Objects can be created by calls of the form `new("ouNode", left, right, parent, distl, distr, sizel, sizer)`.

Examples

```
new("ouNode", left="A", right="B", parent="Root", dist1=1, distr=2, size1=1, size2=1)
```

 pcm-class

 Class "pcm"

Description

An object of class "pcm" represents the position count matrix of a DNA/RNA/amino-acid sequence motif. The entry stores a matrix, which in row *i*, column *j* gives the counts of observing nucleotide/or amino acid *i* in position *j* of the motif.

methods for pcm objects.

Usage

```
## S4 method for signature 'pcm'
x$name

## S4 method for signature 'pcm,ANY'
plot(x, y = "missing", ...)

trimMotif(x, t)

matrixReverseComplement(x)

addBlank(x, n, b)

getIC(x, p)

pcm2pfm(x, background)

pcm2pssm(x, background)

## S4 method for signature 'pcm'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)

## S4 method for signature 'pcm'
format(x, ...)
```

Arguments

| | |
|-------------------|--|
| <code>x</code> | An object of class pcm. For getIC, if parameter <code>p</code> is followed, <code>x</code> should be an object of matrix. For pcm2pfm, <code>x</code> also could be an object of matrix. |
| <code>name</code> | slot name of pcm object. |
| <code>y</code> | Not use. |

... Further potential arguments passed to plotMotifLogo.
 t numeric value of information content threshold for trimming.
 n how many spaces should be added.
 b logical value to indicate where the space should be added.
 p p is the background frequency.
 background a "numeric" vector. The background frequency.
 row.names, optional
 see as.data.frame

Objects from the Class

Objects can be created by calls of the form `new("pcm", mat, name, alphabet, color, background)`.

Methods

addBlank signature(x="pcm", n="numeric", b="logical") add space into the position count matrix for alignment. b is a bool value, if TRUE, add space to the 3' end, else add space to the 5' end. n indicates how many spaces should be added.
coerce signature(from = "pcm", to = "matrix"): convert object pcm to matrix
getIC signature(x = "pcm",) Calculate information content profile for position frequency matrix.
matrixReverseComplement signature(x = "pcm") get the reverse complement of position frequency matrix.
plot signature(x = "pcm") Plots the sequence logo of the position count matrix.
trimMotif signature(x = "pcm", t= "numeric") trim motif by information content.
\$, \$<- Get or set the slot of `pcm-class`
as.data.frame convert `pcm-class` to a data.frame
format return the name_pcm of `pcm-class`

Examples

```
pcm <- read.table(file.path(find.package("motifStack"), "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- new("pcm", mat=as.matrix(pcm), name="bin_SOLEXA")
plot(motif)
pcm2pfm(pcm)
pcm2pssm(pcm)

pcm <- read.table(file.path(find.package("motifStack"), "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- new("pcm", mat=as.matrix(pcm), name="bin_SOLEXA")
getIC(motif)
matrixReverseComplement(motif)
as(motif, "matrix")
```

```

pcm2pfm(motif)
as.data.frame(motif)
format(motif)

```

pfm-class

Class "pfm"

Description

An object of class "pfm" represents the position frequency matrix of a DNA/RNA/amino-acid sequence motif. The entry stores a matrix, which in row *i*, column *j* gives the frequency of observing nucleotide/or amino acid *i* in position *j* of the motif.

methods for pfm objects.

Usage

```

## S4 method for signature 'pfm'
x$name

## S4 method for signature 'pfm,ANY'
plot(x, y = "missing", ...)

## S4 method for signature 'pfm,ANY'
getIC(x, p = "missing")

## S4 method for signature 'pfm,numeric'
trimMotif(x, t)

## S4 method for signature 'pfm'
matrixReverseComplement(x)

## S4 method for signature 'pfm,numeric,logical'
addBlank(x, n, b)

## S4 method for signature 'pfm'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)

## S4 method for signature 'pfm'
format(x, ...)

```

Arguments

| | |
|-------------------|---|
| <code>x</code> | An object of class pfm. For getIC, if parameter <code>p</code> is followed, <code>x</code> should be an object of matrix. |
| <code>name</code> | Slot name. |
| <code>y</code> | Not use. |

... Further potential arguments passed to plotMotifLogo.
 p p is the background frequency.
 t numeric value of information content threshold for trimming.
 n how many spaces should be added.
 b logical value to indicate where the space should be added.
 row.names, optional
 see as.data.frame

Objects from the Class

Objects can be created by calls of the form `new("pfm", mat, name, alphabet, color, background)`.

Methods

addBlank signature(x="pfm",n="numeric", b="logical") add space into the position frequency matrix for alignment. b is a bool value, if TRUE, add space to the 3' end, else add space to the 5' end. n indicates how many spaces should be added.

getIC signature(x = "pfm",) Calculate information content profile for position frequency matrix.

getIC signature(x = "matrix", p = "numeric") Calculate information content profile for matrix. p is the background frequency

matrixReverseComplement signature(x = "pfm") get the reverse complement of position frequency matrix.

plot signature(x = "pfm") Plots the sequence logo of the position frequency matrix.

trimMotif signature(x = "pfm", t= "numeric") trim motif by information content.

\$, \$<- Get or set the slot of [pfm-class](#)

as.data.frame convert [pfm-class](#) to a data.frame

format return the name_pfm of [pfm-class](#)

Examples

```
pcm <- read.table(file.path(find.package("motifStack"), "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- pcm2pfm(pcm)
motif <- new("pfm", mat=motif, name="bin_SOLEXA")
plot(motif)
```

```
pcm <- read.table(file.path(find.package("motifStack"), "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A", "C", "G", "T")
motif <- pcm2pfm(pcm)
motif <- new("pfm", mat=motif, name="bin_SOLEXA")
getIC(motif)
matrixReverseComplement(motif)
addBlank(motif, 1, FALSE)
```

```
addBlank(motif, 3, TRUE)
as(motif, "matrix")
as.data.frame(motif)
format(motif)
```

pfm2pwm

convert pfm object to PWM

Description

convert pfm object to PWM

Usage

```
pfm2pwm(x, N = 10000)
```

Arguments

x an object of [pfm](#) or [pcm](#) or matrix
N Total number of event counts used for pfm generation.

Value

A numeric matrix representing the Position Weight Matrix for PWM.

Author(s)

Jianhong Ou

See Also

[PWM](#)

Examples

```
library("MotifDb")
matrix.fly <- query(MotifDb, "Dmelanogaster")
pfm2pwm(matrix.fly[[1]])
```

plotAffinityLogo *plot affinity logo*

Description

plot affinity logo

Usage

```
plotAffinityLogo(  
  psam,  
  motifName,  
  font = "sans",  
  fontface = "bold",  
  colset = c("#00811B", "#2000C7", "#FFB32C", "#D00001"),  
  alpha = 0.5,  
  newpage = TRUE,  
  draw = TRUE  
)
```

Arguments

| | |
|-----------|--|
| psam | a position-specific affinity matrix |
| motifName | motif name |
| font | font of logo |
| fontface | fontface of logo |
| colset | color setting for each logo letter |
| alpha | Alpha channel for transparency of low affinity letters. |
| newpage | plot in a new canvas or not. |
| draw | Vector (logical(1)). TRUE to plot. FALSE, return a gList |

Value

none

References

Barrett C. Foat, Alexandre V. Morozov, Harmen J. Bussemaker; Statistical mechanical modeling of genome-wide transcription factor occupancy data by MatrixREDUCE, *Bioinformatics*, Volume 22, Issue 14, 15 July 2006, Pages e141-e149, <https://doi.org/10.1093/bioinformatics/btl223>

Examples

```
psam <- importMatrix(file.path(find.package("motifStack"), "extdata", "PSAM.mxr"),  
  format="psam")[[1]]  
plotAffinityLogo(psam)
```

plotMotifLogo *plot sequence logo*

Description

plot amino acid or DNA sequence logo

Usage

```
plotMotifLogo(  
  pfm,  
  motifName,  
  p = rep(0.25, 4),  
  font = "sans",  
  fontface = "bold",  
  colset = c("#00811B", "#2000C7", "#FFB32C", "#D00001"),  
  xaxis = TRUE,  
  yaxis = TRUE,  
  xlab = "position",  
  ylab = "bits",  
  xlcex = 1.2,  
  ylcex = 1.2,  
  ncex = 1.2,  
  ic.scale = TRUE,  
  newpage = TRUE,  
  margins = c(4.1, 4.1, 2.1, 0.1),  
  draw = TRUE  
)
```

Arguments

| | |
|-----------|---|
| pfm | a position frequency matrices |
| motifName | motif name |
| p | background possibility |
| font | font of logo |
| fontface | fontface of logo |
| colset | color setting for each logo letter |
| xaxis | draw x-axis or not. If a vector of character or numeric is provided, the function will try to plot the x-axis by setting the labels as the vectors. |
| yaxis | draw y-axis or not |
| xlab | x-label, do nothing if set xlab as NA |
| ylab | y-label, do nothing if set ylab as NA |
| xlcex | cex value for x-label |
| ylcex | cex value for y-label |

| | |
|----------|--|
| ncex | cex value for motif name |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. It will also can be set as FALSE followed by a numeric vectors. The format is c(FALSE, scale). If it is FALSE followed by a number (eg c(FALSE, 100)), the y axis labels will be re-scaled by 100. |
| newpage | logical If TRUE, plot it in a new page. |
| margins | A numeric vector interpreted in the same way as par(mar) in base graphics. |
| draw | Vector (logical(1)). TRUE to plot. FALSE, return a gList |

Value

none

Examples

```
pcm<-matrix(runif(40,0,100),nrow=4,ncol=10)
pfm<-pcm2pfm(pcm)
rownames(pfm)<-c("A","C","G","T")
plotMotifLogo(pfm)
```

plotMotifLogoA *plot sequence logo without plot.new*

Description

plot amino acid or DNA sequence logo in a given canvas

Usage

```
plotMotifLogoA(
  pfm,
  font = "sans",
  fontface = "bold",
  ic.scale = TRUE,
  draw = TRUE
)
```

Arguments

| | |
|----------|---|
| pfm | an object of pfm |
| font | font of logo |
| fontface | fontface of logo |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| draw | Vector (logical(1)). TRUE to plot. FALSE, return a gList |

Value

none

Examples

```
pcm<-matrix(runif(40,0,100),nrow=4,ncol=10)
pfm<-pcm2pfm(pcm)
rownames(pfm)<-c("A","C","G","T")
motif <- new("pfm", mat=pfm, name="bin_SOLEXA")
plotMotifLogoA(motif)
```

plotMotifLogoStack *plot sequence logos stack*

Description

plot sequence logos stack

Usage

```
plotMotifLogoStack(pfms, ...)
```

Arguments

pfms a list of position frequency matrices, pfms must be a list of class pfm
... other parameters can be passed to plotMotifLogo function

Value

none

Examples

```
pcm1<-matrix(c(0,50,0,50,
               100,0,0,0,
               0,100,0,0,
               0,0,100,0,
               0,0,0,100,
               50,50,0,0,
               0,0,50,50), nrow=4)
pcm2<-matrix(c(50,50,0,0,
               0,100,0,0,
               0,50,50,0,
               0,0,0,100,
               50,50,0,0,
               0,0,50,50), nrow=4)
rownames(pcm1)<-c("A","C","G","T")
rownames(pcm2)<-c("A","C","G","T")
```

```
pfms<-list(p1=new("pfm",mat=pcm2pfm(pcm1),name="m1"),
           p2=new("pfm",mat=pcm2pfm(pcm2),name="m2"))
pfms<-DNAMotifAlignment(pfms)
plotMotifLogoStack(pfms)
```

```
plotMotifLogoStackWithTree
```

plot sequence logos stack with hierarchical cluster tree

Description

plot sequence logos stack with hierarchical cluster tree

Usage

```
plotMotifLogoStackWithTree(pfms, hc, treewidth = 1/8, trueDist = FALSE, ...)
```

Arguments

| | |
|-----------|---|
| pfms | a list of position frequency matrices, pfms must be a list of class pfm |
| hc | an object of the type produced by stats::hclust |
| treewidth | the width to show tree |
| trueDist | logical flags to use hclust height or not. |
| ... | other parameters can be passed to plotMotifLogo function |

Value

none

Examples

```
#####Input#####
pcms<-readPCM(file.path(find.package("motifStack"), "extdata"),"pcm$")

#####Clustering#####
hc <- clusterMotifs(pcms)

##reorder the motifs for plotMotifLogoStack
motifs<-pcms[hc$order]
motifs <- lapply(motifs, pcm2pfm)
##do alignment
motifs<-DNAMotifAlignment(motifs)
##plot stacks
plotMotifLogoStack(motifs, ncex=1.0)
plotMotifLogoStackWithTree(motifs, hc=hc)
```

plotMotifOverMotif *plot motif over another motif*

Description

plot motif over another motif to emphasize the difference.

Usage

```
plotMotifOverMotif(  
  motif,  
  backgroundMotif,  
  bgNoise = NA,  
  font = "sans",  
  textgp = gpar()  
)
```

Arguments

| | |
|-----------------|---|
| motif | an object of pcm or pfm |
| backgroundMotif | an object of pcm or pfm |
| bgNoise | if it is not NA, test will using a background by Dirichlet(1)-distributed random frequencies with weight bg.noise. The value of bgNoise should be a number in the range of 0 to 1, eg. 0.05 |
| font | font for logo symbol |
| textgp | text parameter |

Value

none

Examples

```
pcms <- readPCM(file.path(find.package("motifStack"), "extdata"), "pcm$")  
len <- sapply(pcms, function(.ele) ncol(.ele$mat))  
pcms <- pcms[len==7]  
plotMotifOverMotif(pcms[[1]], pcms[[2]], bgNoise=0.05)
```

```
plotMotifStackWithPhylog
```

plot sequence logo stacks with a ape4-style phylogenetic tree

Description

plot sequence logo stacks with a ape4-style phylogenetic tree

Usage

```
plotMotifStackWithPhylog(
  phylog,
  pfms = NULL,
  f.phylog = 0.3,
  f.logo = NULL,
  cleaves = 1,
  cnodes = 0,
  labels.leaves = names(phylog$leaves),
  clabel.leaves = 1,
  labels.nodes = names(phylog$nodes),
  clabel.nodes = 0,
  font = "sans",
  ic.scale = TRUE
)
```

Arguments

| | |
|---------------|--|
| phylog | an object of class phylog |
| pfms | a list of objects of class pfm |
| f.phylog | a size coefficient for tree size (a parameter to draw the tree in proportion to leaves label) |
| f.logo | a size coefficient for the motif |
| cleaves | a character size for plotting the points that represent the leaves, used with <code>par("cex")*cleaves</code> . If zero, no points are drawn |
| cnodes | a character size for plotting the points that represent the nodes, used with <code>par("cex")*cnodes</code> . If zero, no points are drawn |
| labels.leaves | a vector of strings of characters for the leaves labels |
| clabel.leaves | a character size for the leaves labels, used with <code>par("cex")*clabel.leaves</code> |
| labels.nodes | a vector of strings of characters for the nodes labels |
| clabel.nodes | a character size for the nodes labels, used with <code>par("cex")*clabel.nodes</code> . If zero, no nodes labels are drawn |
| font | font of logo |
| ic.scale | logical If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |

Value

none

See Also[plot.phylog](#)**Examples**

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-", names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
    gsub("_FBgn[0-9]+$", "",
      gsub("[^a-zA-Z0-9]", "_",
        gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 50)
  hc <- clusterMotifs(pfms)
  library(ade4)
  phylog <- ade4::hclust2phylog(hc)
  leaves <- names(phylog$leaves)
  pfms <- pfms[leaves]
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  pfms <- DNAmotifAlignment(pfms, minimalConsensus=3)
  plotMotifStackWithPhylog(phylog, pfms, f.phylog=0.3,
    cleaves = 0.5, clabel.leaves = 0.7)
}

```

plotMotifStackWithRadialPhylog

plot sequence logo stacks with a radial phylogenetic tree

Description

plot sequence logo stacks with a radial phylogenetic tree

Usage

```

plotMotifStackWithRadialPhylog(
  phylog,
  pfms = NULL,
  circle = 0.75,
  circle.motif = NA,
  cleaves = 1,

```

```

cnodes = 0,
labels.leaves = names(phylog$leaves),
clabel.leaves = 1,
labels.nodes = names(phylog$nodes),
clabel.nodes = 0,
draw.box = FALSE,
col.leaves = rep("black", length(labels.leaves)),
col.leaves.bg = NULL,
col.leaves.bg.alpha = 1,
col.bg = NULL,
col.bg.alpha = 1,
col.inner.label.circle = NULL,
inner.label.circle.width = "default",
col.outer.label.circle = NULL,
outer.label.circle.width = "default",
clockwise = FALSE,
init.angle = if (clockwise) 90 else 0,
angle = 360,
pfmNameSplitter = ";",
rcpostfix = "(RC)",
motifScale = c("linear", "logarithmic"),
ic.scale = TRUE,
plotIndex = FALSE,
IndexCol = "black",
IndexCex = 0.8,
groupDistance = NA,
groupDistanceLineCol = "red",
plotAxis = FALSE,
font = "sans"
)

```

Arguments

| | |
|----------------------------|--|
| <code>phylog</code> | an object of class <code>phylog</code> |
| <code>pfms</code> | a list of objects of class <code>pfm</code> |
| <code>circle</code> | a size coefficient for the outer circle of the labels. Please note this is the position of <code>inner.label.cirle</code> . |
| <code>circle.motif</code> | a size coefficient for the motif circle |
| <code>cleaves</code> | a character size for plotting the points that represent the leaves, used with <code>par("cex")*cleaves</code> . If zero, no points are drawn |
| <code>cnodes</code> | a character size for plotting the points that represent the nodes, used with <code>par("cex")*cnodes</code> . If zero, no points are drawn |
| <code>labels.leaves</code> | a vector of strings of characters for the leaves labels |
| <code>clabel.leaves</code> | a character size for the leaves labels, used with <code>par("cex")*clabel.leaves</code> |
| <code>labels.nodes</code> | a vector of strings of characters for the nodes labels |
| <code>clabel.nodes</code> | a character size for the nodes labels, used with <code>par("cex")*clabel.nodes</code> . If zero, no nodes labels are drawn |

| | |
|--------------------------|--|
| draw.box | if TRUE draws a box around the current plot with the function box() |
| col.leaves | a vector of colors for leaves labels |
| col.leaves.bg | a vector of colors for background of leaves labels |
| col.leaves.bg.alpha | alpha value [0, 1] for the colors of backgroud of leaves labels |
| col.bg | a vector of colors for tree background |
| col.bg.alpha | a alpha value [0, 1] of colors for tree background |
| col.inner.label.circle | a vector of colors for inner circlce of pfms |
| inner.label.circle.width | width for inner circle of pfms |
| col.outer.label.circle | a vector of colors for outer circle of pfms |
| outer.label.circle.width | width for outer circle of pfms |
| clockwise | a logical value indicating if slices are drawn clockwise or counter clockwise |
| init.angle | number specifying the starting angle (in degrees) for the slices. Defaults to 0 (i.e., '3 o'clock') unless clockwise is true where init.angle defaults to 90 (degrees), (i.e., '12 o'clock') |
| angle | number specifying the angle (in degrees) for phylogenic tree. Defaults 360 |
| pfmNameSplitter | splitter when name of pfms contain multiple node of labels.leaves |
| rcpostfix | the postfix for reverse complements |
| motifScale | the scale of logo size |
| ic.scale | logical. If TRUE, the height of each column is proportional to its information content. Otherwise, all columns have the same height. |
| plotIndex | logical. If TRUE, will plot index number in the motifLogo which can help user to describe the motifLogo |
| IndexCol | The color of the index number when plotIndex is TRUE. |
| IndexCex | The cex of the index number when plotIndex is TRUE. |
| groupDistance | show groupDistance on the draw |
| groupDistanceLineCol | groupDistance line color, default: red |
| plotAxis | logical. If TRUE, will plot distance axis. |
| font | font of logo |

Value

none

See Also[plot.phylog](#)

Examples

```

if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-",
                        names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
                      gsub("_FBgn[0-9]+$", "",
                          gsub("[^a-zA-Z0-9]", "_",
                              gsub("(_[0-9]+)$", "", names(motifs))))))
  motifs <- motifs[unique(names(motifs))]
  pfms <- sample(motifs, 50)
  hc <- clusterMotifs(pfms)
  library(ade4)
  phylog <- ade4::hclust2phylog(hc)
  leaves <- names(phylog$leaves)
  pfms <- pfms[leaves]
  pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
    new("pfm",mat=.ele, name=.name)})
  pfms <- DNAmotifAlignment(pfms, minimalConsensus=3)
  library(RColorBrewer)
  color <- brewer.pal(12, "Set3")
  plotMotifStackWithRadialPhylog(phylog, pfms, circle=0.9,
    cleaves = 0.5, clabel.leaves = 0.7,
    col.bg=rep(color, each=5), col.leaves=rep(color, each=5))
}

```

plotXaxis

plot x-axis

Description

plot x-axis for the sequence logo

Usage

```
plotXaxis(pfm, p = rep(0.25, 4), label = NULL)
```

Arguments

| | |
|-------|-----------------------------|
| pfm | position frequency matrices |
| p | background possibility |
| label | x-axis labels |

Value

none

| | |
|-----------|--------------------|
| plotYaxis | <i>plot y-axis</i> |
|-----------|--------------------|

Description

plot y-axis for the sequence logo

Usage

```
plotYaxis(ymax, ic.scale)
```

Arguments

| | |
|----------|--|
| ymax | max value of y axis |
| ic.scale | Use IC scale or not. See plotMotifLogo for help. |

Value

none

| | |
|------------|---------------------|
| psam-class | <i>Class "psam"</i> |
|------------|---------------------|

Description

An object of class "psam" represents the position specific affinity matrix (PSAM) of a DNA/RNA/amino-acid sequence motif. The entry stores a matrix, which in row *i*, column *j* gives the affinity of observing nucleotide/or amino acid *i* in position *j* of the motif.

methods for psam objects.

Usage

```
## S4 method for signature 'psam'
x$name

## S4 method for signature 'psam,ANY'
plot(x, y = "missing", ...)

## S4 method for signature 'psam'
matrixReverseComplement(x)

## S4 method for signature 'psam,numeric,logical'
addBlank(x, n, b)

## S4 method for signature 'psam'
```

```
as.data.frame(x, row.names = NULL, optional = FALSE, ...)

## S4 method for signature 'psam'
format(x, ...)
```

Arguments

| | |
|---------------------|--|
| x | An object of class psam. |
| name | Slot name. |
| y | Not use. |
| ... | Further potential arguments passed to plotAffinityLogo. |
| n | how many spaces should be added. |
| b | logical value to indicate where the space should be added. |
| row.names, optional | see as.data.frame |

Objects from the Class

Objects can be created by calls of the form `new("psam", mat, name, alphabet, color)`.

Methods

addBlank signature(x="psam", n="numeric", b="logical") add space into the position specific affinity matrix for alignment. b is a bool value, if TRUE, add space to the 3' end, else add space to the 5' end. n indicates how many spaces should be added.

matrixReverseComplement signature(x = "psam") get the reverse complement of position specific affinity matrix.

plot signature(x = "psam") Plots the affinity logo of the position specific affinity matrix.

\$, \$<- Get or set the slot of [psam-class](#)

as.data.frame convert [psam-class](#) to a data.frame

format return the name_pfm of [psam-class](#)

Examples

```
motif <- importMatrix(file.path(find.package("motifStack"), "extdata", "PSAM.mxr"),
                      format="psam")[[1]]
plot(motif)

motif <- importMatrix(file.path(find.package("motifStack"), "extdata", "PSAM.mxr"),
                      format="psam")[[1]]
matrixReverseComplement(motif)
addBlank(motif, 1, FALSE)
addBlank(motif, 3, TRUE)
as(motif, "matrix")
as.data.frame(motif)
format(motif)
```

pssm-class *Class "pssm"*

Description

An object of class "pssm" represents the position specific score matrix of a DNA/RNA/amino-acid sequence motif. The entry stores a matrix, which in row *i*, column *j* gives the log-odds probability of nucleotide/or amino acid *i* in position *j* of the motif.

methods for pssm objects.

Usage

```
## S4 method for signature 'pssm'
x$name

## S4 method for signature 'pssm,ANY'
plot(x, y = "missing", ...)

## S4 method for signature 'pssm'
matrixReverseComplement(x)

## S4 method for signature 'pssm,numeric,logical'
addBlank(x, n, b)

## S4 method for signature 'pssm'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)

## S4 method for signature 'pssm'
format(x, ...)
```

Arguments

| | |
|----------------------------------|--|
| <code>x</code> | An object of class pssm. For getIC, if parameter <i>p</i> is followed, <i>x</i> should be an object of matrix. |
| <code>name</code> | Slot name. |
| <code>y</code> | Not use. |
| <code>...</code> | Further potential arguments passed to plotMotifLogo. |
| <code>n</code> | how many spaces should be added. |
| <code>b</code> | logical value to indicate where the space should be added. |
| <code>row.names, optional</code> | see as.data.frame |

Objects from the Class

Objects can be created by calls of the form `new("pssm", mat, name, alphabet, color, background)`.

Methods

addBlank signature(x="pssm",n="numeric", b="logical") add space into the position frequency matrix for alignment. b is a bool value, if TRUE, add space to the 3' end, else add space to the 5' end. n indicates how many spaces should be added.

matrixReverseComplement signature(x = "pssm") get the reverse complement of position frequency matrix.

plot signature(x = "pssm") Plots the sequence logo of the position frequency matrix.

\$, \$<- Get or set the slot of [pssm-class](#)

as.data.frame convert [pssm-class](#) to a data.frame

format return the name_pssm of [pssm-class](#)

Examples

```
pcm <- read.table(file.path(find.package("motifStack"),
                           "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A","C","G","T")
motif <- pcm2pssm(pcm)
motif <- new("pssm", mat=motif, name="bin_SOLEXA")
plot(motif)
```

```
pcm <- read.table(file.path(find.package("motifStack"),
                           "extdata", "bin_SOLEXA.pcm"))
pcm <- pcm[,3:ncol(pcm)]
rownames(pcm) <- c("A","C","G","T")
motif <- pcm2pssm(pcm)
motif <- new("pssm", mat=motif, name="bin_SOLEXA")
matrixReverseComplement(motif)
addBlank(motif, 1, FALSE)
addBlank(motif, 3, TRUE)
as(motif,"matrix")
as.data.frame(motif)
format(motif)
```

readPCM

read pcm from a path

Description

read position count matrix from a path

Usage

```
readPCM(path = ".", pattern = NULL)
```

Arguments

path a character vector of full path names
 pattern an optional regular expression

Value

A list of `pcm` objects

Examples

```
pcms<-readPCM(file.path(find.package("motifStack"), "extdata"),"pcm$")
```

reorderUPGMAtree *re-order UPGMA tree*

Description

re-order the UPGMA tree by adjacent motif distance

Usage

```
reorderUPGMAtree(phylog, motifs, rcpostfix = "(RC)")
```

Arguments

phylog an object of phylog
 motifs a list of objects of pfm
 rcpostfix the postfix for reverse complements

Value

an object of phylog

Author(s)

Jianhong Ou

Examples

```
if(interactive() || Sys.getenv("USER")==="jianhongou"){
  library("MotifDb")
  matrix.fly <- query(MotifDb, "Dmelanogaster")
  motifs <- as.list(matrix.fly)
  motifs <- motifs[grepl("Dmelanogaster-FlyFactorSurvey-", names(motifs), fixed=TRUE)]
  names(motifs) <- gsub("Dmelanogaster_FlyFactorSurvey_", "",
    gsub("_FBgn[0-9]+$", "",
      gsub("[^a-zA-Z0-9]", "_",
```

```

        gsub("[0-9]+", "", names(motifs))))))
motifs <- motifs[unique(names(motifs))]
pfms <- sample(motifs, 50)
hc <- clusterMotifs(pfms)
library(ade4)
phylog <- ade4::hclust2phylog(hc)
pfms <- mapply(pfms, names(pfms), FUN=function(.ele, .name){
  new("pfm",mat=.ele, name=.name)})
reorderUPGMAtree(phylog, pfms)
}

```

| | |
|-----------------|-------------------------|
| traceBackGlobal | <i>traceback global</i> |
|-----------------|-------------------------|

Description

traceback global

Usage

```
traceBackGlobal(dpScore, score, m, n)
```

Arguments

| | |
|---------|---------------------------|
| dpScore | Dynamic programming score |
| score | ALLR scores |
| m, n | matrix width |

Value

a data.frame

| | |
|----------------|------------------------|
| traceBackLocal | <i>traceback local</i> |
|----------------|------------------------|

Description

traceback local

Usage

```
traceBackLocal(dpScore, score, m, n)
```


Arguments

| | |
|---------|----------------------------------|
| dpScore | Dynamic programming score matrix |
| score | ALLR scores, m x n matrix |
| m, n | matrix width |

Value

a data.frame

Index

- * **classes**
 - marker-class, 19
 - motifSig-class, 31
 - ouNode-class, 34
 - pcm-class, 35
 - pfm-class, 37
 - psam-class, 51
 - pssm-class, 53
- * **datasets**
 - GeomMotif, 12
- * **misc**
 - getRankedUniqueMotifs, 16
 - highlightCol, 17
 - importMatrix, 18
 - mergeMotifs, 20
 - motifCircos, 21
 - motifPiles, 28
 - pfm2pwm, 39
 - reorderUPGMAtree, 55
- * **package**
 - motifStack-package, 3
- * **plot**
 - browseMotifs, 4
- \$.marker-method (marker-class), 19
- \$.motifSig-method (motifSig-class), 31
- \$.ouNode-method (ouNode-class), 34
- \$.pcm-method (pcm-class), 35
- \$.pfm-method (pfm-class), 37
- \$.psam-method (psam-class), 51
- \$.pssm-method (pssm-class), 53
- \$<-,marker-method (marker-class), 19
- \$<-,motifSig-method (motifSig-class), 31
- \$<-,ouNode-method (ouNode-class), 34
- \$<-,pcm-method (pcm-class), 35
- \$<-,pfm-method (pfm-class), 37
- \$<-,psam-method (psam-class), 51
- \$<-,pssm-method (pssm-class), 53
- _PACKAGE (motifStack-package), 3
- AAmotifAlignment, 3
- addBlank (pcm-class), 35
- addBlank,pcm,numeric,logical-method (pcm-class), 35
- addBlank,pfm,numeric,logical-method (pfm-class), 37
- addBlank,psam,numeric,logical-method (psam-class), 51
- addBlank,pssm,numeric,logical-method (pssm-class), 53
- as (pcm-class), 35
- as.data.frame,pfm-method (pfm-class), 37
- as.data.frame,psam-method (psam-class), 51
- as.data.frame,pssm-method (pssm-class), 53
- browseMotifs, 4
- browseMotifs-shiny, 5
- browseMotifsOutput (browseMotifs-shiny), 5
- calF, 6
- calI, 6
- clusterMotifs, 7
- coerce (pfm-class), 37
- coerce,pcm,matrix-method (pcm-class), 35
- coerce,pfm,matrix-method (pfm-class), 37
- coerce,psam,matrix-method (psam-class), 51
- coerce,pssm,matrix-method (pssm-class), 53
- colors, 17
- colorset, 7
- compare2profiles, 8
- compareProfiles, 9
- DNAmotifAlignment, 9
- DNAmotifToRNAmotif, 10
- dpGlobal, 11
- dpLocal, 11

- format, pcm-method (pcm-class), 35
- format, pfm-method (pfm-class), 37
- format, psam-method (psam-class), 51
- format, pssm-method (pssm-class), 53
- frequence (motifSig-class), 31
- frequence, motifSig-method (motifSig-class), 31

- geom_motif, 13
- GeomMotif, 12
- getALLRscoreFromCounts, 15
- getDistance, 15
- getIC (pcm-class), 35
- getIC, matrix, matrix-method (pfm-class), 37
- getIC, matrix, numeric-method (pfm-class), 37
- getIC, pcm, ANY-method (pcm-class), 35
- getIC, pfm, ANY-method (pfm-class), 37
- getRankedUniqueMotifs, 16
- getScore, 17
- GraphvizLayouts, 4

- hclust, 27
- highlightCol, 17

- importMatrix, 18

- marker (marker-class), 19
- marker-class, 19
- matalign, 7, 19
- matrixReverseComplement (pcm-class), 35
- matrixReverseComplement, pcm-method (pcm-class), 35
- matrixReverseComplement, pfm-method (pfm-class), 37
- matrixReverseComplement, psam-method (psam-class), 51
- matrixReverseComplement, pssm-method (pssm-class), 53
- mergeMotifs, 20
- motifCircos, 21, 30
- motifCloud, 24
- motifGrob, 26
- motifHclust, 27
- motifPiles, 28
- motifSig, 25, 31, 32
- motifSig (motifSig-class), 31
- motifSig-class, 31
- motifSignature, 31, 32
- motifStack, 33
- motifStack-package, 3

- nodelist (motifSig-class), 31
- nodelist, motifSig-method (motifSig-class), 31

- ouNode (ouNode-class), 34
- ouNode-class, 34

- palette, 17
- pcm, 20, 39, 45, 55
- pcm (pcm-class), 35
- pcm-class, 18, 35
- pcm2pfm (pcm-class), 35
- pcm2pfm, data.frame, ANY-method (pcm-class), 35
- pcm2pfm, data.frame, numeric-method (pcm-class), 35
- pcm2pfm, list, ANY-method (pcm-class), 35
- pcm2pfm, list, numeric-method (pcm-class), 35
- pcm2pfm, matrix, ANY-method (pcm-class), 35
- pcm2pfm, matrix, numeric-method (pcm-class), 35
- pcm2pfm, pcm, ANY-method (pcm-class), 35
- pcm2pssm (pcm-class), 35
- pcm2pssm, data.frame, ANY-method (pcm-class), 35
- pcm2pssm, data.frame, numeric-method (pcm-class), 35
- pcm2pssm, list, ANY-method (pcm-class), 35
- pcm2pssm, list, numeric-method (pcm-class), 35
- pcm2pssm, matrix, ANY-method (pcm-class), 35
- pcm2pssm, matrix, numeric-method (pcm-class), 35
- pcm2pssm, pcm, ANY-method (pcm-class), 35
- pfm, 4, 20, 33, 39, 45
- pfm (pfm-class), 37
- pfm-class, 18, 37
- pfm2pwm, 39
- plot (pcm-class), 35
- plot, pcm, ANY-method (pcm-class), 35
- plot, pfm, ANY-method (pfm-class), 37
- plot, psam, ANY-method (psam-class), 51

plot, pssm, ANY-method (pssm-class), 53
plot.phylog, 47, 49
plotAffinityLogo, 40
plotMotifLogo, 41
plotMotifLogoA, 42
plotMotifLogoStack, 33, 43
plotMotifLogoStackWithTree, 33, 44
plotMotifOverMotif, 45
plotMotifStackWithPhylog, 33, 46
plotMotifStackWithRadialPhylog, 23, 33,
47
plotXaxis, 50
plotYaxis, 51
psam (psam-class), 51
psam-class, 51
pssm (pssm-class), 53
pssm-class, 53
PWM, 39

readPCM, 54
renderbrowseMotifs
 (browseMotifs-shiny), 5
reorderUPGMAtree, 55
rgb, 17

sigColor (motifSig-class), 31
sigColor, motifSig-method
 (motifSig-class), 31
signatures (motifSig-class), 31
signatures, motifSig-method
 (motifSig-class), 31

traceBackGlobal, 56
traceBackLocal, 56
trimMotif (pcm-class), 35
trimMotif, pcm, numeric-method
 (pcm-class), 35
trimMotif, pfm, numeric-method
 (pfm-class), 37

XMatrix, 18
XMatrixList, 18