

Package ‘ALPS’

November 27, 2020

Title AnaLysis routines for ePigenomicS data

Version 1.4.0

Author Venu Thatikonda, Natalie Jäger

Maintainer Venu Thatikonda <thatikonda92@gmail.com>

Description

The package provides analysis and publication quality visualization routines for genome-wide epigenomics data such as histone modification or transcription factor ChIP-seq, ATAC-seq, DNase-seq etc.

The functions in the package can be used with any type of data that can be represented with bigwig files

at any resolution. The goal of the ALPS is to provide analysis tools for most downstream analysis without

leaving the R environment and most tools in the package require a minimal input that can be prepared with

basic R, unix or excel skills.

License MIT + file LICENSE

Encoding UTF-8

LazyData false

RoxygenNote 6.1.1

Depends R (>= 3.6)

Imports assertthat, BiocParallel, ChIPseeker, corrplot, data.table, dplyr, GenomicRanges, GGally, genefilter, gghalves, ggplot2, ggseqlogo, Gviz, magrittr, org.Hs.eg.db, plyr, reshape2, rtracklayer, stats, stringr, tibble, tidyr, TxDb.Hsapiens.UCSC.hg19.knownGene, TxDb.Hsapiens.UCSC.hg38.knownGene, utils

URL <https://github.com/itsvenu/ALPS>

BugReports <https://github.com/itsvenu/ALPS/issues>

Suggests knitr, rmarkdown, ComplexHeatmap, circlize, testthat

biocViews Epigenetics, Sequencing, ChIPSeq, ATACSeq, Visualization, Transcription, HistoneModification

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/ALPS>

git_branch RELEASE_3_12

git_last_commit efa0189

git_last_commit_date 2020-10-27

Date/Publication 2020-11-27

R topics documented:

get_genomic_annotatons	2
get_variable_regions	3
merge_GR	4
multiBigwig_summary	4
plot_browser_tracks	5
plot_correlation	6
plot_enrichments	7
plot_genomic_annotatons	9
plot_motif_logo	10
process_homer	10
process_jaspar	11
process_meme	11
process_pfm	12
process_transfac	12

Index **13**

get_genomic_annotatons

Annotate genomic regions

Description

annotate genomic regions by simultaneously merging overlapping regions and preparing consensus set of genomic regions from multiple files

Usage

```
get_genomic_annotatons(data_table, ref_gen = "hg38",
  tss_region = c(-1000, 1000), merge_level = "all")
```

Arguments

data_table	a data.frame of sample table, as is for multiBigwig_summary input table, default NULL
ref_gen	reference genome, either hg38 or hg19, default hg38
tss_region	bp \pm TSS to define promoter regions
merge_level	either all, group_level or none. all prepares a consensus set of peaks from all files present in data_table. group_level prepares consensus set of peaks from all samples present each group separately. none does not prepare any consensus peak set, annotates each peak file separately. Default all

Value

a data.frame of annotations and percentages

Examples

```
chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

get_genomic_annotations(data_table = chr21_data_table,
merge_level = 'group_level')
```

get_variable_regions *Get variable regions*

Description

given a data.frame of genomic regions enrichments, the function returns the number of variable regions across all samples. The resulting matrix can be directly used with PCAtools or ComplexHeatmap for further downstream explorative analysis e.g. unsupervised clustering

Usage

```
get_variable_regions(enrichments_df, log_transform = TRUE,
scale = TRUE, num_regions = 500)
```

Arguments

enrichments_df	a data.frame of enrichments at genomic regions. Output of multiBigwig_summary or a similar format is compatible
log_transform	logical, whether to log2 transform the counts, default TRUE
scale	logical, whether to scale the variable regions before returning the results, default TRUE
num_regions	number of variable regions to return, default 500

Value

a data.frame of scaled variable regions

Examples

```
mat <- matrix(sample.int(15, 9*100, TRUE), 9, 100) %>% as.data.frame()
mat <- mat %>%
tibble::rowid_to_column(var = 'start') %>%
dplyr::mutate(end = start + 1000) %>%
dplyr::mutate(chr = 'chr1') %>%
dplyr::select(chr, start, end, dplyr::everything())

get_variable_regions(enrichments_df = mat, num_regions = 50)
```

merge_GR *Merge genomic regions*

Description

merge overlapping genomic regions from multiple peak/bed files

Usage

```
merge_GR(x)
```

Arguments

x a character vector of bed file paths

Value

GRanges object

Examples

```
## load example data

chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt',
package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

x <- as.character(chr21_data_table$bed_path)

merge_GR(x = x)
```

multiBigwig_summary *Enrichments at genomics regions*

Description

multiBigwig_summary is a function to calculate enrichments from a set of given bigwig files and a set of genomics regions. This function is similar to deeptools multiBigwigSummary python package.

Usage

```
multiBigwig_summary(data_table, summary_type = "mean", parallel = TRUE)
```

Arguments

data_table	a dataframe that contains bw_path, sample_id. sample_id ids will be used in the final result matrix
summary_type	whether to calculate mean, median, min or max for each genomic region in within consensus peak-set from the bigwig files. Default is mean
parallel	logical. Whether to parallelize the calculation process, default is TRUE

Value

data.frame of enrichments within given genomic regions

Examples

```
## load example data

chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

enrichments <- multiBigwig_summary(data_table = chr21_data_table,
                                   summary_type = 'mean',
                                   parallel = FALSE)
```

plot_browser_tracks *UCSC Genome browser like plots*

Description

Function to plot genome browser like plots given a very minimal information such as a set of bigwig files and a genomics region. Tracks are arranged as they are in given input data.frame. Function uses highly customizable Gviz R/bioconductor package to plot browser like plots.

Usage

```
plot_browser_tracks(data_table, gene_range = NULL, ref_gen = "hg38",
                   cex.axis = 0.5, cex.title = 0.8, ...)
```

Arguments

data_table	a dataframe that contains bw_path, sample_id and color_code. Tracks are colored according to color_code. Default NULL
gene_range	genomic region for which browser-like plots needed in format chr:start-end. Default NULL
ref_gen	reference genome, to get gene annotations, currently supports hg19 and hg38. Default, hg38

cex.axis axis label size, default 0.5
 cex.title axis title size, default 0.8
 ... additional arguments to change the appearance of a plot. All arguments that can be passed to base R graphics are supported

Value

plot of genome browser tracks

Examples

```
## load example data

chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

gene_range = 'chr21:45643725-45942454'

plot_browser_tracks(data_table = chr21_data_table,
  gene_range = gene_range, ref_gen = 'hg38')
```

plot_correlation	<i>Correlations among replicates/groups</i>
------------------	---

Description

Function to calculate correlations of CHIP/ATAC-seq enrichment among replicates/samples or groups. The function is compatible with the output of [multiBigwig_summary](#) or any custom dataframe with the similar format.

Usage

```
plot_correlation(enrichments_df, log_transform = TRUE,
  method = "pearson", plot_type = "replicate_level", sample_metadata,
  ...)
```

Arguments

enrichments_df dataframe of enrichments, usually in the form of the output from function [multiBigwig_summary](#), default NULL
 log_transform logical, whether to log2 transform enrichments_df
 method method to calculate correlation coefficient, one of 'pearson' (default), 'spearman' or 'kendall'

`plot_type` whether to plot `replicate_level` correlations or `group_level` correlations. `replicate_level` plot represents the pairwise correlation values among all the samples/columns, where as the `group_level` plot is a paired plot of genomic regions after averaging of all samples in a group. Default `replicate_level`

`sample_metadata` a data.frame required if `plot_type = 'group_level'`. The data.frame must contain columns `sample_id` and `group`

... additional arguments either to `corrplot::corrplot` or `GGally::ggpairs` depending on arg `plot_type`

Value

corrplot or ggplot2 object

Examples

```
## load example data
## load example data

chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

enrichments <- multiBigwig_summary(data_table = chr21_data_table,
                                   summary_type = 'mean',
                                   parallel = TRUE)

## replicate_level correlation plot
plot_correlation(enrichments_df = enrichments,
                 log_transform = TRUE, plot_type = 'replicate_level',
                 sample_metadata = chr21_data_table)

## group_level correlation plot
plot_correlation(enrichments_df = enrichments,
                 log_transform = TRUE, plot_type = 'group_level',
                 sample_metadata = chr21_data_table)
```

plot_enrichments *Enrichment plots*

Description

Function to plot enrichments from ChIP-seq/ATAC-seq at genomics regions either as an individual groups or as paired condition e.g untreated-treated

Usage

```
plot_enrichments(enrichments_df = NULL, log_transform = TRUE,
  plot_type = "separate", sample_metadata, box_alpha = 0.8,
  violin_alpha = 0.8, x_order = NULL, overlap_order = NULL)
```

Arguments

enrichments_df	enrichments at genomics regions from all samples, as in the format of output from multiBigwig_summary
log_transform	logical. Should the data be log2 transformed? Default is TRUE
plot_type	either separate or overlap
sample_metadata	metadata associated with the columns present in enrichments_df, information in this table will be used depending on the option in plot_type
box_alpha	alpha/transparency to use for box plots, default 0.8
violin_alpha	alpha/transparency to use for violin plots, default 0.8
x_order	ordering of levels on x-axis in resulting plot, default NULL
overlap_order	ordering of overlaying if plot_type = 'overlap'. E.g. overlaying treatment data on top of untreated data, default NULL

Value

ggplot2 object

Examples

```
## load example data
chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)

## attach path to bw_path and bed_path
d_path <- dirname(chr21_data_table)

chr21_data_table <- read.delim(chr21_data_table, header = TRUE)
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)

enrichments <- multiBigwig_summary(data_table = chr21_data_table,
  summary_type = 'mean',
  parallel = TRUE)

## plot_type == 'separate'
plot_enrichments(enrichments_df = enrichments, log_transform = TRUE,
  plot_type = 'separate', sample_metadata = chr21_data_table)

## plot_type == 'overlap'
enrichments_4_overlapviolins <- system.file('extdata/overlap_violins', 'enrichments_4_overlapviolins.txt', package = 'ALPS', mustWork = TRUE)
enrichments_4_overlapviolins <- read.delim(enrichments_4_overlapviolins, header = TRUE)

## metadata associated with above enrichments
data_table_4_overlapviolins <- system.file('extdata/overlap_violins', 'data_table_4_overlapviolins.txt', package = 'ALPS', mustWork = TRUE)
data_table_4_overlapviolins <- read.delim(data_table_4_overlapviolins, header = TRUE)
```



```
plot_enrichments(enrichments_df = enrichemnts_4_overlapviolins, log_transform = FALSE,  
plot_type = 'overlap', sample_metadata = data_table_4_overlapviolins)
```

plot_genomic_annotatons

Plot genomic annotations

Description

plot the annotations of genomic regions either as stacked bar or heatmap. The function takes the output of [get_genomic_annotatons](#) directly or it is also compatible with a similar data.frame.

Usage

```
plot_genomic_annotatons(annotatons_df, plot_type = "bar", col = NULL)
```

Arguments

`annotatons_df` a data.frame of genomic annotations. It can either be of one sample or of multiple samples as a data.frame

`plot_type` either bar plot or heatmap, default bar

`col` vector of colors for each feature in `annotatons_df`. If provided these colors are used, if not a custom set of distinct colors will be used. Default NULL

Value

ggplot2 plot

Examples

```
## load example data  
  
chr21_data_table <- system.file('extdata/bw', 'ALPS_example_datatable.txt', package = 'ALPS', mustWork = TRUE)  
  
## attach path to bw_path and bed_path  
d_path <- dirname(chr21_data_table)  
  
chr21_data_table <- read.delim(chr21_data_table, header = TRUE)  
chr21_data_table$bw_path <- paste0(d_path, '/', chr21_data_table$bw_path)  
chr21_data_table$bed_path <- paste0(d_path, '/', chr21_data_table$bed_path)  
  
g_annotatons <- get_genomic_annotatons(data_table = chr21_data_table,  
merge_level = 'group_level')  
  
plot_genomic_annotatons(annotatons_df = g_annotatons, plot_type = 'heatmap')
```

plot_motif_logo	<i>Plot sequence motifs</i>
-----------------	-----------------------------

Description

Function to plot transcription factor motif logos in two different styles, bar plot or logo plot. It supports motif formats from different databases e.g. JASPAR, MEME, TRANSFAC, HOMER and PFM

Usage

```
plot_motif_logo(motif_path, database = NULL, plot_type = "bar")
```

Arguments

motif_path	path to motif file, default NULL
database	database name from which motif has taken, default NULL
plot_type	either bar or logo, default bar

Value

ggplot2 object

Examples

```
## examplr motif file paths
myc_meme <- system.file('extdata/motifs', 'MA0147.2.meme', package = 'ALPS', mustWork = TRUE)
myc_jaspar <- system.file('extdata/motifs', 'MA0147.2.jaspar', package = 'ALPS', mustWork = TRUE)
myc_transfac <- system.file('extdata/motifs', 'MA0147.2.transfac', package = 'ALPS', mustWork = TRUE)
myc_homer <- system.file('extdata/motifs', 'cmec.homer', package = 'ALPS', mustWork = TRUE)
myc_pfm <- system.file('extdata/motifs', 'MA0147.2.pfm', package = 'ALPS', mustWork = TRUE)

## plot motifs
plot_motif_logo(motif_path = myc_homer, database = 'homer', plot_type = 'logo')
```

process_homer	<i>Process homer format</i>
---------------	-----------------------------

Description

Process homer format

Usage

```
process_homer(x)
```

Arguments

x	path to homer format file
---	---------------------------

Value

data.frame

Examples

```
myc_homer <- system.file('extdata/motifs', 'myc.homer', package = 'ALPS', mustWork = TRUE)
myc_df <- process_homer(x = myc_homer)
```

process_jaspar	<i>Process jaspar format</i>
----------------	------------------------------

Description

Process jaspar format

Usage

```
process_jaspar(x)
```

Arguments

x path to jaspar format file

Value

data.frame

Examples

```
myc_jaspar <- system.file('extdata/motifs', 'MA0147.2.jaspar', package = 'ALPS', mustWork = TRUE)
myc_df <- process_jaspar(x = myc_jaspar)
```

process_meme	<i>Process meme format</i>
--------------	----------------------------

Description

Process meme format

Usage

```
process_meme(x)
```

Arguments

x path to meme format file

Value

data.frame

Examples

```
myc_meme <- system.file('extdata/motifs', 'MA0147.2.meme', package = 'ALPS', mustWork = TRUE)
myc_df <- process_meme(x = myc_meme)
```

process_pfm	<i>Process PFM format</i>
-------------	---------------------------

Description

Process PFM format

Usage

```
process_pfm(x)
```

Arguments

x path to PFM format file

Value

data.frame

Examples

```
myc_pfm <- system.file('extdata/motifs', 'MA0147.2.pfm', package = 'ALPS', mustWork = TRUE)
myc_df <- process_pfm(x = myc_pfm)
```

process_transfac	<i>Process transfac format</i>
------------------	--------------------------------

Description

Process transfac format

Usage

```
process_transfac(x)
```

Arguments

x path to transfac format file

Value

data.frame

Examples

```
myc_transfac <- system.file('extdata/motifs', 'MA0147.2.transfac', package = 'ALPS', mustWork = TRUE)
my_df <- process_transfac(x = myc_transfac)
```

Index

[get_genomic_annotations](#), [2](#), [9](#)
[get_variable_regions](#), [3](#)

[merge_GR](#), [4](#)
[multiBigwig_summary](#), [4](#), [6](#), [8](#)

[plot_browser_tracks](#), [5](#)
[plot_correlation](#), [6](#)
[plot_enrichments](#), [7](#)
[plot_genomic_annotations](#), [9](#)
[plot_motif_logo](#), [10](#)
[process_homer](#), [10](#)
[process_jaspar](#), [11](#)
[process_meme](#), [11](#)
[process_pfm](#), [12](#)
[process_transfac](#), [12](#)