

Package ‘ggsc’

April 15, 2024

Title Visualizing Single Cell Data

Version 1.0.2

Description Useful functions to visualize single cell and spatial data. It supports both 'SingleCellExperiment' and 'Seurat' objects. It also supports visualizing the data using grammar of graphics implemented in 'ggplot2'.

Imports Rcpp, RcppParallel, cli, dplyr, ggplot2, grDevices, grid, methods, rlang, scattermore, stats, Seurat, SingleCellExperiment, SummarizedExperiment, tidydr, tidyr, tibble, utils, yulab.utils

Suggests aplot, BiocParallel,forcats, ggforce, ggnewscale, igraph, knitr, ks, Matrix, prettydoc, rmarkdown, scran, scater, scuttle, shadowtext, sf, SeuratObject, SpatialExperiment, STexampleData, testthat (>= 3.0.0)

BugReports <https://github.com/YuLab-SMU/ggsc/issues>

URL <https://github.com/YuLab-SMU/ggsc>

biocViews DimensionReduction, GeneExpression, SingleCell, Software, Spatial, Transcriptomics, Visualization

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Config/testthat.edition 3

LinkingTo Rcpp, RcppArmadillo, RcppParallel

git_url <https://git.bioconductor.org/packages/ggsc>

git_branch RELEASE_3_18

git_last_commit 67f8871

git_last_commit_date 2023-10-31

Repository Bioconductor 3.18

Date/Publication 2024-04-15

Author Guangchuang Yu [aut, cre, cph]

(<<https://orcid.org/0000-0002-6485-8781>>),

Shuangbin Xu [aut] (<<https://orcid.org/0000-0003-3513-5362>>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

R topics documented:

ggsc-package	2
CalWkdeCpp	3
reexports	3
sc_dim	4
sc_dim_count	5
sc_dim_geom_ellipse	6
sc_dim_geom_feature	7
sc_dim_geom_label	8
sc_dim_geom_sub	9
sc_dim_sub	10
sc_feature	11
sc_geom_point	13
sc_spatial	14
sc_violin	16

Index

19

ggsc-package

ggsc: Visualizing Single Cell Data

Description

Useful functions to visualize single cell and spatial data. It supports both 'SingleCellExperiment' and 'Seurat' objects. It also supports visualizing the data using grammar of graphics implemented in 'ggplot2'.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> ([ORCID](#)) [copyright holder]

Authors:

- Shuangbin Xu <xshuangbin@163.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/YuLab-SMU/ggsc>
- Report bugs at <https://github.com/YuLab-SMU/ggsc/issues>

CalWkdeCpp*Two-Dimensional Weighted Kernel Density Estimation And Mapping
the Result To Original Dimension*

Description

Two-Dimensional Weighted Kernel Density Estimation And Mapping the Result To Original Dimension

Usage

```
CalWkdeCpp(x, w, l, h, adjust = 1, n = 400L)
```

Arguments

x	The 2-D coordinate matrix
w	The weighted sparse matrix, the number columns the same than the number rows than x.
l	The limits of the rectangle covered by the grid as c(xl, xu, yl, yu)
h	The vector of bandwidths for x and y directions, defaults to normal reference bandwidth (see bandwidth.nrd), A scalar value will be taken to apply to both directions (see ks::hpi).
adjust	numeric value to adjust to bandwidth, default is 1.
n	number of grid points in the two directions, default is 400.

reexports*Objects exported from other packages*

Description

These objects are imported from other packages. Follow the links below to see their documentation.

[ggplot2](#) [aes](#), [theme](#)

Value

Depending on the re-exported function

sc_dim	<i>sc_dim</i>	
--------	---------------	--

Description

`sc_dim`

Usage

```
sc_dim(
  object,
  dims = c(1, 2),
  reduction = NULL,
  cells = NULL,
  slot = "data",
  mapping = NULL,
  ...
)

## S4 method for signature 'Seurat'
sc_dim(
  object,
  dims = c(1, 2),
  reduction = NULL,
  cells = NULL,
  slot = "data",
  mapping = NULL,
  ...
)

## S4 method for signature 'SingleCellExperiment'
sc_dim(
  object,
  dims = c(1, 2),
  reduction = NULL,
  cells = NULL,
  slot = "data",
  mapping = NULL,
  ...
)
```

Arguments

<code>object</code>	Seurat object
<code>dims</code>	selected dimensions (must be a two-length vector) that are used in visualization
<code>reduction</code>	reduction method, default is <code>NULL</code> and will use the default setting store in the object

cells	selected cells to plot (default is all cells)
slot	slot to pull expression data from (e.g., 'count' or 'data')
mapping	aesthetic mapping
...	additional parameters pass to 'scattermore::geom_scattermore()'

Value

dimension reduction plot

See Also

[geom_scattermore](#);

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP', mapping = aes(colour = Cell_Cycle))
p2 <- sc_dim(sce, reduction = 'UMAP')
f1 <- p1 + sc_dim_geom_label()
f2 <- p2 +
  sc_dim_geom_label(
    geom = shadowtext::geom_shadowtext,
    color='black',
    bg.color='white'
  )
```

sc_dim_count *sc_dim_count*

Description

`sc_dim_count`

Usage

`sc_dim_count(sc_dim_plot)`

Arguments

`sc_dim_plot` dimension reduction plot of single cell data

Value

a bar plot to present the cell numbers of different clusters

See Also

[sc_dim\(\)](#)

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p <- sc_dim(sce, reduction = 'UMAP')
p1 <- sc_dim_count(p)
```

sc_dim_geom_ellipse *sc_dim_geom_ellipse*

Description

`sc_dim_geom_ellipse`

Usage

```
sc_dim_geom_ellipse(mapping = NULL, level = 0.95, ...)
```

Arguments

<code>mapping</code>	aesthetic mapping
<code>level</code>	the level at which to draw an ellipse
<code>...</code>	additional parameters pass to the <code>stat_ellipse</code>

Value

layer of ellipse

See Also

[stat_ellipse](#);

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP', mapping = aes(colour = Cell_Cycle))
p2 <- sc_dim(sce, reduction = 'UMAP')
f1 <- p1 + sc_dim_ellipse()
```

sc_dim_geom_feature *sc_dim_geom_feature*

Description

sc_dim_geom_feature

Usage

```
sc_dim_geom_feature(
  object,
  features,
  dims = c(1, 2),
  ncol = 3,
  ...,
  .fun = function(.data) dplyr::filter(.data, .data$value > 0)
)
```

Arguments

<code>object</code>	Seurat or SingleCellExperiment object
<code>features</code>	selected features (i.e., genes)
<code>dims</code>	selected dimensions (must be a two-length vector) that are used in visualization
<code>ncol</code>	number of facet columns if <code>'length(features) > 1'</code>
<code>...</code>	additional parameters pass to <code>'scattermore::geom_scattermore()'</code>
<code>.fun</code>	user defined function that will be applied to selected features (default is to filter out genes with no expression values)

Value

layer of points for selected features

See Also

[sc_feature\(\)](#)

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP')
set.seed(123)
genes <- rownames(sce) |> sample(6)
f1 <- p1 +
  sc_dim_geom_feature(
    object = sce,
    features = genes
  )
```

sc_dim_geom_label *sc_dim_geom_label*

Description

`sc_dim_geom_label`

Usage

```
sc_dim_geom_label(geom = ggplot2::geom_text, ...)
```

Arguments

<code>geom</code>	geometric layer (default: <code>geom_text</code>) to display the labels
<code>...</code>	additional parameters pass to the geom

Value

layer of labels

See Also

[sc_dim_geom_label\(\)](#)

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP', mapping = aes(colour = Cell_Cycle))
p2 <- sc_dim(sce, reduction = 'UMAP')
f1 <- p1 + sc_dim_geom_label()
```

`sc_dim_geom_sub` *sc_dim_geom_subset*

Description

`sc_dim_geom_subset`

Usage

```
sc_dim_geom_sub(mapping = NULL, subset, .column = "ident", ...)
```

Arguments

<code>mapping</code>	aesthetic mapping
<code>subset</code>	subset of clusters to be displayed
<code>.column</code>	which column represents cluster (e.g., 'ident')
<code>...</code>	additional parameters pass to <code>sc_geom_point</code>

Value

plot with a layer of specified clusters

See Also

[sc_dim_geom_sub](#)

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
```

```

clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP')
f1 <- p1 + sc_dim_geom_sub(subset = c(1, 2), .column = 'label')

```

sc_dim_sub*sc_dim_sub***Description**`sc_dim_sub`**Usage**`sc_dim_sub(subset, .column = "ident")`**Arguments**

<code>subset</code>	subset of clusters to be displayed
<code>.column</code>	which column represents cluster (e.g., 'ident')

Value

update plot with only subset displayed

See Also[sc_dim](#)**Examples**

```

library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
p1 <- sc_dim(sce, reduction = 'UMAP')
f1 <- p1 + sc_dim_sub(subset = c(1, 2), .column = 'label')

```

sc_feature	<i>sc_feature</i>
------------	-------------------

Description

`sc_feature`

Usage

```
sc_feature(
  object,
  features,
  dims = c(1, 2),
  reduction = NULL,
  cells = NULL,
  slot = "data",
  mapping = NULL,
  ncol = 3,
  density = FALSE,
  grid.n = 100,
  joint = FALSE,
  joint.fun = prod,
  common.legend = TRUE,
  ...
)

## S4 method for signature 'Seurat'
sc_feature(
  object,
  features,
  dims = c(1, 2),
  reduction = NULL,
  cells = NULL,
  slot = "data",
  mapping = NULL,
  ncol = 3,
  density = FALSE,
  grid.n = 100,
  joint = FALSE,
  joint.fun = prod,
  common.legend = TRUE,
  ...
)

## S4 method for signature 'SingleCellExperiment'
sc_feature(
  object,
```

```

features,
dims = c(1, 2),
reduction = NULL,
cells = NULL,
slot = "data",
mapping = NULL,
ncol = 3,
density = FALSE,
grid.n = 100,
joint = FALSE,
joint.fun = prod,
common.legend = TRUE,
...
)

```

Arguments

<code>object</code>	Seurat object
<code>features</code>	selected features (i.e., genes)
<code>dims</code>	selected dimensions (must be a two-length vector) that are used in visualization
<code>reduction</code>	reduction method, default is <code>NULL</code> and will use the default setting store in the object
<code>cells</code>	selected cells to plot (default is all cells)
<code>slot</code>	slot to pull expression data from (e.g., <code>'count'</code> or <code>'data'</code>)
<code>mapping</code>	aesthetic mapping
<code>ncol</code>	number of facet columns if <code>'length(features) > 1'</code>
<code>density</code>	whether plot the 2D weighted kernel density, default is <code>FALSE</code> .
<code>grid.n</code>	number of grid points in the two directions to estimate 2D weighted kernel density, default is 100.
<code>joint</code>	whether joint the multiple features with <code>joint.fun</code> , default is <code>FALSE</code> .
<code>joint.fun</code>	how to joint the multiple features if <code>joint=TRUE</code> , default is <code>prod</code> .
<code>common.legend</code>	whether to use <code>facet_wrap</code> to display the multiple features, default is <code>TRUE</code> .
<code>...</code>	additional parameters pass to <code>'scattermore::geom_scattermore()'</code>

Value

dimension reduction plot colored by selected features

Examples

```

library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)

```

```

clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runTSNE(sce, assay.type = 'logcounts')
set.seed(123)
genes <- rownames(sce) |> sample(6)
p1 <- sc_feature(sce, genes[1], slot='logcounts', reduction = 'TSNE')
p2 <- sc_feature(sce, genes, slot='logcounts', reduction = 'TSNE')
f1 <- sc_dim(sce, slot='logcounts', reduction = 'TSNE') +
  sc_dim_geom_feature(sce, genes[1], color='black')
f2 <- sc_dim(sce, alpha=.3, slot='logcounts', reduction = 'TSNE') +
  ggnewscale::new_scale_color() +
  sc_dim_geom_feature(sce, genes, mapping=aes(color=features)) +
  scale_color_viridis_d()
p1 + p2 + f1 + f2

```

sc_geom_point*sc_geom_point***Description**

`sc_geom_point`

Usage

```
sc_geom_point(mapping = NULL, ...)
```

Arguments

<code>mapping</code>	aesthetic mapping
<code>...</code>	additional parameters pass to 'scattermore::geom_scattermore()'

Value

layer of points

See Also

[sc_dim\(\)](#) and [sc_feature\(\)](#)

Examples

```

library(ggplot2)
ggplot(iris,
  aes(x= Sepal.Length, y = Petal.Width, color=Species)
) +
  sc_geom_point()

```

sc_spatial *sc_spatial*

Description

sc_spatial

Usage

```
sc_spatial(  
  object,  
  features = NULL,  
  sample.id = NULL,  
  image.id = NULL,  
  slot = "data",  
  image.plot = TRUE,  
  image.first.operation = "rotate",  
  image.rotate.degree = NULL,  
  image.mirror.axis = NULL,  
  remove.point = FALSE,  
  mapping = NULL,  
  ncol = 6,  
  density = FALSE,  
  grid.n = 100,  
  joint = FALSE,  
  joint.fun = prod,  
  common.legend = TRUE,  
  point.size = 5,  
  ...  
)  
  
## S4 method for signature 'Seurat'  
sc_spatial(  
  object,  
  features = NULL,  
  sample.id = NULL,  
  image.id = NULL,  
  slot = "data",  
  image.plot = TRUE,  
  image.first.operation = "rotate",  
  image.rotate.degree = NULL,  
  image.mirror.axis = NULL,  
  remove.point = FALSE,  
  mapping = NULL,  
  ncol = 6,  
  density = FALSE,  
  grid.n = 100,
```

```

joint = FALSE,
joint.fun = prod,
common.legend = TRUE,
point.size = 5,
...
)

## S4 method for signature 'SingleCellExperiment'
sc_spatial(
  object,
  features = NULL,
  sample.id = NULL,
  image.id = NULL,
  slot = "data",
  image.plot = TRUE,
  image.first.operation = "rotate",
  image.rotate.degree = NULL,
  image.mirror.axis = NULL,
  remove.point = FALSE,
  mapping = NULL,
  ncol = 6,
  density = FALSE,
  grid.n = 100,
  joint = FALSE,
  joint.fun = prod,
  common.legend = TRUE,
  point.size = 5,
  ...
)

```

Arguments

object	Seurat object
features	selected features to be visualized
sample.id	the index name of sample id, which only work with SingleCellExperiment or SpatialExperiment.
image.id	the index name of image id, which only work with SingleCellExperiment or SpatialExperiment.
slot	if plotting a feature, which data will be used (e.g., 'data', 'counts'), the assay name if object is SingleCellExperiment or SpatialExperiment.
image.plot	whether to display the issue image as background.
image.first.operation	character which the first operation to image, 'rotate' or 'mirror', default is 'rotate'.
image.rotate.degree	integer the degree to ratate image, default is NULL.

```

image.mirror.axis
  character the direction to mirror the image, default is 'h'.

remove.point
  whether to remove the spot points, it is nice if your just view the issue image,
  default is FALSE.

mapping
  aesthetic mapping, default is NULL.

ncol
  integer number of facet columns if 'length(features) > 1', default is 6.

density
  whether plot the 2D weighted kernel density, default is FALSE.

grid.n
  number of grid points in the two directions to estimate 2D weighted kernel den-
  sity, default is 100.

joint
  whether joint the multiple features with joint.fun, default is FALSE.

joint.fun
  how to joint the multiple features if joint = TRUE, default is prod.

common.legend
  whether to use facet_wrap to display the multiple features, default is TRUE.

point.size
  the size of point, default is 5.

...
  additional parameters.

```

Value

ggplot object

Examples

```

## Not run:
library(STexampleData)
# create ExperimentHub instance
eh <- ExperimentHub()
# query STexampleData datasets
myfiles <- query(eh, "STexampleData")
spe <- myfiles[["EH7538"]]
spe <- spe[, colData(spe)$in_tissue == 1]
set.seed(123)
genes <- rownames(spe) |> sample(6)
p <- sc_spatial(spe, features = genes,
                 image.rotate.degree = -90,
                 image.mirror.axis = NULL,
                 ncol = 3)

## End(Not run)

```

sc_violin

sc_violin

Description

sc_violin

Usage

```
sc_violin(  
  object,  
  features,  
  cells = NULL,  
  slot = "data",  
  .fun = NULL,  
  mapping = NULL,  
  ncol = 3,  
  ...  
)  
  
## S4 method for signature 'Seurat'  
sc_violin(  
  object,  
  features,  
  cells = NULL,  
  slot = "data",  
  .fun = NULL,  
  mapping = NULL,  
  ncol = 3,  
  ...  
)  
  
## S4 method for signature 'SingleCellExperiment'  
sc_violin(  
  object,  
  features,  
  cells = NULL,  
  slot = "data",  
  .fun = NULL,  
  mapping = NULL,  
  ncol = 3,  
  ...  
)
```

Arguments

object	Seurat object
features	selected features
cells	selected cells to plot (default is all cells)
slot	slot to pull expression data from (e.g., 'count' or 'data')
.fun	user defined function that will be applied to selected features (default is NULL and there is no data operation)
mapping	aesthetic mapping
ncol	number of facet columns if 'length(features) > 1'
...	additional parameters pass to 'ggplot2::geom_violin()'

Value

violin plot to visualize feature expression distribution

See Also

[geom_violin](#);

Examples

```
library(scuttle)
library(scater)
library(scran)
library(ggplot2)
sce <- mockSCE()
sce <- logNormCounts(sce)
clusters <- clusterCells(sce, assay.type = 'logcounts')
colLabels(sce) <- clusters
sce <- runUMAP(sce, assay.type = 'logcounts')
set.seed(123)
genes <- rownames(sce) |> sample(6)
sc_violin(sce, genes[1], slot = 'logcounts')
sc_violin(sce, genes[1], slot = 'logcounts',
  .fun=function(d) dplyr::filter(d, value > 0)
) +
  ggforce::geom_sina(size=.1)
sc_violin(sce, genes, slot = 'logcounts') +
  theme(axis.text.x = element_text(angle=45, hjust=1))
```

Index

* **internal**

- ggsc-package, 2
- reexports, 3
- aes, 3
- aes (reexports), 3
- CalWkdeCpp, 3
- geom_scattermore, 5
- geom_violin, 18
- ggsc (ggsc-package), 2
- ggsc-package, 2
- reexports, 3
- sc_dim, 4, 10
- sc_dim(), 6, 13
- sc_dim, Seurat (sc_dim), 4
- sc_dim, Seurat-method (sc_dim), 4
- sc_dim, SingleCellExperiment (sc_dim), 4
- sc_dim, SingleCellExperiment-method (sc_dim), 4
- sc_dim_count, 5
- sc_dim_geom_ellipse, 6
- sc_dim_geom_feature, 7
- sc_dim_geom_label, 8
- sc_dim_geom_label(), 8
- sc_dim_geom_sub, 9, 9
- sc_dim_sub, 10
- sc_feature, 11
- sc_feature(), 8, 13
- sc_feature, Seurat (sc_feature), 11
- sc_feature, Seurat-method (sc_feature), 11
- sc_feature, SingleCellExperiment (sc_feature), 11
- sc_feature, SingleCellExperiment-method (sc_feature), 11
- sc_geom_point, 13
- sc_spatial, 14
- sc_spatial, Seurat (sc_spatial), 14
- sc_spatial, Seurat-method (sc_spatial), 14
- sc_spatial, SingleCellExperiment (sc_spatial), 14
- sc_spatial, SingleCellExperiment-method (sc_spatial), 14
- sc_violin, 16
- sc_violin, Seurat (sc_violin), 16
- sc_violin, Seurat-method (sc_violin), 16
- sc_violin, SingleCellExperiment (sc_violin), 16
- sc_violin, SingleCellExperiment-method (sc_violin), 16
- stat_ellipse, 6
- theme, 3
- theme (reexports), 3