

Package ‘graphite’

May 14, 2025

Version 1.54.0

Date 2024-04-14

Title GRAPH Interaction from pathway Topological Environment

Description Graph objects from pathway topology derived from KEGG, Panther, PathBank, PharmGKB, Reactome SMPDB and WikiPathways databases.

License AGPL-3

URL <https://github.com/sales-lab/graphite>

BugReports <https://github.com/sales-lab/graphite/issues>

Depends R (>= 4.2), methods

Imports AnnotationDbi, graph (>= 1.67.1), httr, rappdirs, stats, utils, graphics, rlang, purrr

Suggests checkmate, a4Preproc, ALL, BiocStyle, codetools, hgu133plus2.db, hgu95av2.db, impute, knitr, org.Hs.eg.db, parallel, R.rsp, RCy3, rmarkdown, SPIA (>= 2.2), testthat, topologyGSA (>= 1.4.0)

Collate pathway.R fetch.R conversion.R plot.R utils.R graph.R spia.R tables.R topologygsa.R build.R

VignetteBuilder R.rsp

biocViews Pathways, ThirdPartyClient, GraphAndNetwork, Network, Reactome, KEGG, Metabolomics

git_url <https://git.bioconductor.org/packages/graphite>

git_branch RELEASE_3_21

git_last_commit 4461304

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-05-14

Author Gabriele Sales [cre],
Enrica Calura [aut],
Chiara Romualdi [aut]

Maintainer Gabriele Sales <gabriele.sales@unipd.it>

Contents

| | |
|-------------------------------|-----------|
| as.list.PathwayList | 2 |
| buildPathway | 3 |
| convertIdentifiers | 4 |
| cytoscapePlot | 5 |
| Pathway-class | 6 |
| pathwayDatabases | 7 |
| pathwayGraph | 8 |
| PathwayList-class | 8 |
| pathways | 9 |
| Pathways-class | 10 |
| prepareSPIA | 11 |
| runSPIA | 12 |
| runTopologyGSA | 13 |
| Index | 15 |

as.list.PathwayList *Conversion of PathwayLists into lists.*

Description

Converts a [PathwayList](#) into a list of [Pathways](#).

Usage

```
## S3 method for class 'PathwayList'
as.list(x, ...)
```

Arguments

x a [PathwayList](#) object
 ... extra arguments to as.list

Value

A list of pathways.

Author(s)

Gabriele Sales

See Also

[PathwayList](#)

Examples

```
as.list(pathways("hsapiens", "kegg"))
```

| | |
|--------------|--------------------------------|
| buildPathway | <i>Build a Pathway object.</i> |
|--------------|--------------------------------|

Description

This function creates a new object of type Pathway given a data frame describing its edges.

Usage

```
buildPathway(id, title, species, database, proteinEdges,  
             metaboliteEdges = NULL, mixedEdges = NULL,  
             timestamp = NULL)
```

Arguments

| | |
|-----------------|---|
| id | the pathway identifier. |
| title | the title of the pathway. |
| species | the species the pathway belongs to. |
| database | the name of the database the pathway derives from. |
| proteinEdges | a data.frame of edges between proteins (or genes). Must have the following columns: src_type, src, dest_type, dest, direction and type. Direction must be one of the two strings: "directed" or "undirected". |
| metaboliteEdges | interactions between metabolites. Can be NULL. Otherwise, it must have the same structure as proteinEdges. |
| mixedEdges | interactions between metabolites and proteins. Can be NULL. Otherwise, it must have the same structure as proteinEdges. |
| timestamp | when the pathway was annotated, by default the time buildPathway is called. |

Value

A new [Pathway](#) instance.

Examples

```
edges <- data.frame(src_type = "ENTREZID", src="672",  
                  dest_type = "ENTREZID", dest="7157",  
                  direction="undirected", type="binding")  
pathway <- buildPathway("#1", "example", "hsapiens", "database", edges)  
  
# Example with metabolites:  
edges <- data.frame(src_type = "ENTREZID", src="672",  
                  dest_type = "ENTREZID", dest="7157",  
                  direction="undirected", type="binding")
```

```
mixed <- data.frame(src_type = "CHEBI", src="77750",
                   dest_type = "ENTREZID", dest="7157",
                   direction="undirected", type="binding")
pathway <- buildPathway("#1", "example", "hsapiens", "database",
                       edges, mixedEdges = mixed)
```

convertIdentifiers *Convert the node identifiers of a pathway.*

Description

Converts the node identifiers of pathways.

If the option `Ncpus` is set to a value larger than 1 and the package `parallel` is installed, the conversion procedure will automatically use multiple cores.

Usage

```
convertIdentifiers(x, to)
```

Arguments

| | |
|-----------------|--|
| <code>x</code> | can be a list of pathways or a single pathway |
| <code>to</code> | a string describing the type of the identifier. Can assume the values "entrez", "symbol" or the name of one of the columns provided by an Annotation package (for example, "UNIPROT"). |

Value

A Pathway object.

See Also

[Pathway](#)

Examples

```
r <- pathways("hsapiens", "reactome")
convertIdentifiers(r$mTORC1-mediated signalling`, "symbol")
```

| | |
|---------------|--|
| cytoscapePlot | <i>Plot a pathway graph in Cytoscape</i> |
|---------------|--|

Description

Renders the topology of a pathway as a Cytoscape graph.

Usage

```
cytoscapePlot(pathway, ..., cy.ver = 3)
```

Arguments

| | |
|---------|--|
| pathway | a Pathway object. |
| ... | optional arguments forwarded to pathwayGraph . |
| cy.ver | select a Cytoscape version. Only version 3 is supported in this release. |

Details

Requires the RCy3 package.

Value

An invisible list with two items:

| | |
|-------|--|
| graph | the graphNEL object sent to Cytoscape. |
| suid | the RCy3 network SUID. |

See Also

[Pathway](#)
[pathwayGraph](#)

Examples

```
## Not run:  
r <- pathways()  
cytoscapePlot(convertIdentifiers(reactome$`Unwinding of DNA`, "symbol"))  
  
## End(Not run)
```

| | |
|---------------|------------------------|
| Pathway-class | <i>Class "Pathway"</i> |
|---------------|------------------------|

Description

A biological pathway.

Variants

A Pathway instance actually stores multiple variants of the same biological data.

This is the list of included variants:

- `proteins`: includes only interactions among proteins;
- `metabolites`: includes only interactions among metabolites;
- `mixed`: includes all available interactions.

Methods

`pathwayId(p)`: Returns the native ID of the pathway.

`pathwayTitle(p)`: Returns the title of the pathway.

`pathwayDatabase(p)`: Returns the name of the database the pathway was derived from.

`pathwaySpecies(p)`: Returns the name of the species in which the pathway was annotated.

`pathwayTimestamp(p)`: Returns the date of pathway data retrieval.

`pathwayURL(p)`: Returns the URL of the pathway in its original database, if available.

`convertIdentifiers(p, to)`: Returns a new pathway using a different type of node identifiers.

`edges(p, which = c("proteins", "metabolites", "mixed"), stringsAsFactors = TRUE)`: Returns a data.frame describing the edges of this pathway.

The option which selects the desired pathway variant (see section "Variants" above).

If `stringsAsFactors` is TRUE, strings are converted to factors.

`nodes(p, which = c("proteins", "metabolites", "mixed"))`: Returns the names of the nodes belonging to this pathway.

The option which selects the desired pathway variant (see section "Variants" above).

`plot(p)`: Shows the pathway topology in Cytoscape.

`runClipper(p, expr, classes, method, ...)`: Runs a clipper analysis over the pathway.

`runTopologyGSA(p, test, exp1, exp2, alpha, ...)`: Runs a topologyGSA analysis over the pathway.

Author(s)

Gabriele Sales

See Also

[pathways](#)

Examples

```
reactome <- pathways("hsapiens", "reactome")
pathway <- reactome[[1]]

pathwayTitle(pathway)
pathwaySpecies(pathway)
nodes(pathway)
edges(pathway)
```

| | |
|------------------|--|
| pathwayDatabases | <i>List the available pathway databases.</i> |
|------------------|--|

Description

Obtains the list of pathway databases available through graphi te.

Usage

```
pathwayDatabases()
```

Value

Returns a data . frame with two columns: species and database.

Author(s)

Gabriele Sales

See Also

[pathways](#)

Examples

```
pathwayDatabases()
```

| | |
|--------------|---|
| pathwayGraph | <i>Graph representing the topology of a pathway</i> |
|--------------|---|

Description

Builds a graphNEL object representing the topology of a pathway.

Usage

```
pathwayGraph(pathway, which = "proteins", edge.types = NULL)
```

Arguments

| | |
|------------|--|
| pathway | a Pathway object. |
| which | the pathway variant you want. See Pathway documentation for a list of the supported variants. |
| edge.types | keep only the edges matching the type names in this vector. |

Value

A graphNEL object.

See Also

[Pathway](#)
[graphNEL](#)

Examples

```
r <- pathways("hsapiens", "reactome")
pathwayGraph(r$`mTORC1-mediated signalling`, edge.types="Binding")
```

| | |
|-------------------|----------------------------|
| PathwayList-class | <i>Class "PathwayList"</i> |
|-------------------|----------------------------|

Description

A collection of pathways from a single database.

Extends

Class "[Pathways](#)", directly.

Methods

`l[i]` returns a selection of the pathways contained in the pathway list.

`l[[i]]` gives access to one of the pathways contained in the pathway list.

`l$title` loads a pathways by its title.

`convertIdentifiers(l, to)` returns a new list of pathways using a different type of node identifiers.

`length(l)` returns the number of pathways contained in the list.

`names(l)` returns the titles of the pathways contained in the list.

`prepareSPIA(l, pathwaySetName, print.names=FALSE)` prepares the pathways for a SPIA analysis.

`runClipper(l, expr, classes, method, maxNodes=150, ...)` runs a clipper analysis over all the pathways in the list.

`runTopologyGSA(l, test, exp1, exp2, alpha, maxNodes=150, ...)` runs a topologyGSA analysis over all the pathways in the list.

Author(s)

Gabriele Sales

See Also

[pathways](#)

pathways

Retrieve a list of pathways.

Description

Retrieve a list of pathways from a database for a given species.

graphite currently supports the following databases:

- [KEGG](#)
- [PANTHER](#)
- [PathBank](#)
- [PharmGKB](#)
- [Reactome](#)
- [SMPDB](#)
- [WikiPathways](#)

Call the [pathwayDatabase](#) function for more details.

Usage

```
pathways(species, database)
```

Arguments

species one of the supported species
database the name of the pathway database

Value

A PathwayList object.

See Also

[PathwayList](#), [pathwayDatabases](#)

Examples

```
pathways("hsapiens", "reactome")
```

| | |
|----------------|-------------------------|
| Pathways-class | <i>Class "Pathways"</i> |
|----------------|-------------------------|

Description

A virtual class acting as a common parent to all other classes representing pathway databases.

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

No methods defined with class "Pathways" in the signature.

Author(s)

Gabriele Sales

See Also

[PathwayList](#)

| | |
|-------------|---|
| prepareSPIA | <i>Prepare pathway dataset needed by runSPIA.</i> |
|-------------|---|

Description

Prepare pathway dataset needed by runSPIA. See [runSPIA](#) and [spia](#) for more details.

Usage

```
prepareSPIA(db, pathwaySetName, print.names = FALSE)
```

Arguments

`db` a [PathwayList](#) object or a list of [Pathways](#).
`pathwaySetName` name of the output pathway set.
`print.names` print pathway names as the conversion advances.

Value

This function has no return value.

References

Tarca AL, Draghici S, Khatri P, Hassan SS, Mittal P, Kim JS, Kim CJ, Kusanovic JP, Romero R. A novel signaling pathway impact analysis. *Bioinformatics*. 2009 Jan 1;25(1):75-82.

Adi L. Tarca, Sorin Draghici, Purvesh Khatri, et. al, A Signaling Pathway Impact Analysis for Microarray Experiments, 2008, *Bioinformatics*, 2009, 25(1):75-82.

Draghici, S., Khatri, P., Tarca, A.L., Amin, K., Done, A., Voichita, C., Georgescu, C., Romero, R.: A systems biology approach for pathway level analysis. *Genome Research*, 17, 2007.

See Also

[runSPIA](#)

[spia](#)

[PathwayList](#)

runSPIA

*Run SPIA analysis***Description**

Run a topological analysis on an expression dataset using SPIA.

Usage

```
runSPIA(de, all, pathwaySetName, ...)
```

Arguments

| | |
|----------------|---|
| de | A named vector containing log2 fold-changes of the differentially expressed genes. The names of this numeric vector are Entrez gene IDs. |
| all | A vector with the Entrez IDs in the reference set. If the data was obtained from a microarray experiment, this set will contain all genes present on the specific array used for the experiment. This vector should contain all names of the 'de' argument. |
| pathwaySetName | The name of a pathway set created with prepareSPIA . |
| ... | Additional options to pass to spia . |

Details

The spia option "organism" is internally used. It is an error use it in the additional options.

Value

The same of spia, without KEGG links. A data frame containing the ranked pathways and various statistics: pSize is the number of genes on the pathway; NDE is the number of DE genes per pathway; tA is the observed total perturbation accumulation in the pathway; pNDE is the probability to observe at least NDE genes on the pathway using a hypergeometric model; pPERT is the probability to observe a total accumulation more extreme than tA only by chance; pG is the p-value obtained by combining pNDE and pPERT; pGFdr and pGFWER are the False Discovery Rate and respectively Bonferroni adjusted global p-values; and the Status gives the direction in which the pathway is perturbed (activated or inhibited).

References

Tarca AL, Draghici S, Khatri P, Hassan SS, Mittal P, Kim JS, Kim CJ, Kusanovic JP, Romero R. A novel signaling pathway impact analysis. *Bioinformatics*. 2009 Jan 1;25(1):75-82.

Adi L. Tarca, Sorin Draghici, Purvesh Khatri, et. al, A Signaling Pathway Impact Analysis for Microarray Experiments, 2008, *Bioinformatics*, 2009, 25(1):75-82.

Draghici, S., Khatri, P., Tarca, A.L., Amin, K., Done, A., Voichita, C., Georgescu, C., Romero, R.: A systems biology approach for pathway level analysis. *Genome Research*, 17, 2007.

See Also[spia](#)**Examples**

```

if (require(SPIA) && require(hgu133plus2.db)) {
  data(colorectalcancer)

  top$ENTREZ <- mapIds(hgu133plus2.db, top$ID, "ENTREZID", "PROBEID", multiVals = "first")
  top <- top[!is.na(top$ENTREZ) & !duplicated(top$ENTREZ), ]
  top$ENTREZ <- paste("ENTREZID", top$ENTREZ, sep = ":")
  tg1 <- top[top$adj.P.Val < 0.05, ]

  DE_Colorectal = tg1$logFC
  names(DE_Colorectal) <- tg1$ENTREZ
  ALL_Colorectal <- top$ENTREZ

  kegg <- pathways("hsapiens", "kegg")[1:20]
  kegg <- convertIdentifiers(kegg, "ENTREZID")
  prepareSPIA(kegg, "keggEx")
  runSPIA(de = DE_Colorectal, all = ALL_Colorectal, "keggEx")

  unlink("keggExSPIA.RData")
}

```

| | |
|----------------|---|
| runTopologyGSA | <i>Run a topological analysis on an expression dataset using topologyGSA.</i> |
|----------------|---|

Description

Use graphical models to test the pathway components highlighting those involved in its deregulation.

If the option `Ncpus` is set to a value larger than 1 and the package `parallel` is installed, the conversion procedure will automatically use multiple cores.

Usage

```
runTopologyGSA(x, test, exp1, exp2, alpha, ...)
```

Arguments

| | |
|--------------------|--|
| <code>x</code> | a PathwayList , a list of Pathways or a single Pathway object. |
| <code>test</code> | Either "var" and "mean". Determine the type of test used by topologyGSA. |
| <code>exp1</code> | Experiment matrix of the first class, genes in columns. |
| <code>exp2</code> | Experiment matrix of the second class, genes in columns. |
| <code>alpha</code> | Significance level of the test. |

... Additional parameters forwarded to topologyGSA.
When invoked on a [PathwayList](#), can use the named option "maxNodes" to limit the analysis to those pathways having up to this given number of nodes.

Details

This function produces a warning and returns NULL when the number of genes in common between the expression matrices and the pathway is less than 3.

Value

See documentation of [pathway.var.test](#) and [pathway.mean.test](#).

References

Massa MS, Chiogna M, Romualdi C. Gene set analysis exploiting the topology of a pathway. BMC System Biol. 2010 Sep 1;4:121.

Examples

```
if (require(topologyGSA)) {  
  data(examples)  
  colnames(y1) <- paste("SYMBOL", colnames(y1), sep = ":")  
  colnames(y2) <- paste("SYMBOL", colnames(y2), sep = ":")  
  
  k <- pathways("hsapiens", "kegg")  
  p <- convertIdentifiers(k[["Fc epsilon RI signaling pathway"]], "SYMBOL")  
  runTopologyGSA(p, "var", y1, y2, 0.05)  
}
```

Index

- * **analysis**
 - runSPIA, [12](#)
 - runTopologyGSA, [13](#)
- * **classes**
 - Pathway-class, [6](#)
 - PathwayList-class, [8](#)
 - Pathways-class, [10](#)
- * **spia**
 - runSPIA, [12](#)
- * **topologyGSEA**
 - runTopologyGSA, [13](#)
- * **topology**
 - runSPIA, [12](#)
 - runTopologyGSA, [13](#)
- [,PathwayList-method
 - (PathwayList-class), [8](#)
- [[,PathwayList-method
 - (PathwayList-class), [8](#)
- \$,PathwayList-method
 - (PathwayList-class), [8](#)
- as.list.PathwayList, [2](#)
- buildPathway, [3](#)
- convertIdentifiers, [4](#)
- convertIdentifiers,Pathway-method
 - (Pathway-class), [6](#)
- convertIdentifiers,PathwayList-method
 - (PathwayList-class), [8](#)
- cytoscapePlot, [5](#)
- edges,Pathway-method (Pathway-class), [6](#)
- graphNEL, [5, 8](#)
- length,PathwayList-method
 - (PathwayList-class), [8](#)
- names,PathwayList-method
 - (PathwayList-class), [8](#)
- nodes,Pathway-method (Pathway-class), [6](#)
- Pathway, [2–5, 8, 11, 13](#)
- Pathway-class, [6](#)
- pathway.mean.test, [14](#)
- pathway.var.test, [14](#)
- pathwayDatabase, [9](#)
- pathwayDatabase (Pathway-class), [6](#)
- pathwayDatabases, [7, 10](#)
- pathwayGraph, [5, 8](#)
- pathwayId (Pathway-class), [6](#)
- PathwayList, [2, 10, 11, 13, 14](#)
- PathwayList-class, [8](#)
- Pathways, [8](#)
- pathways, [6, 7, 9, 9](#)
- Pathways-class, [10](#)
- pathwaySpecies (Pathway-class), [6](#)
- pathwayTimestamp (Pathway-class), [6](#)
- pathwayTitle (Pathway-class), [6](#)
- pathwayURL (Pathway-class), [6](#)
- plot,Pathway, ANY-method
 - (Pathway-class), [6](#)
- prepareSPIA, [11, 12](#)
- prepareSPIA, list-method (prepareSPIA), [11](#)
- prepareSPIA,PathwayList-method
 - (PathwayList-class), [8](#)
- runClipper,Pathway-method
 - (Pathway-class), [6](#)
- runClipper,PathwayList-method
 - (PathwayList-class), [8](#)
- runSPIA, [11, 12](#)
- runTopologyGSA, [13](#)
- runTopologyGSA, list-method
 - (runTopologyGSA), [13](#)
- runTopologyGSA,Pathway-method
 - (Pathway-class), [6](#)
- runTopologyGSA,PathwayList-method
 - (PathwayList-class), [8](#)

`runTopologyGSAMulti` (`runTopologyGSA`), [13](#)

`spia`, [11–13](#)